

```
No.      Time      Source      Destination      Protocol Length Info
 1227 09:05:40.152171 d1:b6:4f:00:16:b6 MS-NLB-PhysServer-32_08:00:00:13:02 802.11 111 Association Request, SN=3775, FN=4,
Flags=.pm...F.C
Frame 1227: 111 bytes on wire (888 bits), 111 bytes captured (888 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: .pm...F.C
Data (51 bytes)
0000 00 aa aa 03 00 00 00 08 00 45 20 00 28 ca 0e 00 .....E.(...
0010 00 29 06 09 3b 40 e9 bb 68 c0 a8 01 6d 00 50 09 ..);@.h...m.P.
0020 f2 aa de 4d 70 fc 84 7a 6f 50 10 19 20 5e c8 00 ...Mp..zoP.. ^..
0030 00 00 00
...
No.      Time      Source      Destination      Protocol Length Info
 1750 09:05:56.723535 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1607, FN=0, Flags=.....C,
SSID="linksys_SES_24086"
Frame 1750: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: .....C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1751 09:05:56.725675 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1607, FN=0, Flags=...R...C,
SSID="linksys_SES_24086"
Frame 1751: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: ....R...C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1824 09:06:00.862401 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1613, FN=0, Flags=.....C,
SSID="linksys_SES_24086"
Frame 1824: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: .....C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1825 09:06:00.863400 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1613, FN=0, Flags=...R...C,
SSID="linksys_SES_24086"
Frame 1825: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: ....R...C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1827 09:06:00.866025 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1613, FN=0, Flags=.....C,
SSID="linksys_SES_24086"
Frame 1827: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: .....C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1926 09:06:04.976156 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1620, FN=0, Flags=.....C,
SSID="linksys_SES_24086"
Frame 1926: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: .....C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1927 09:06:04.977402 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1620, FN=0, Flags=...R...C,
SSID="linksys_SES_24086"
Frame 1927: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: ....R...C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1932 09:06:04.983652 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1620, FN=0, Flags=...R...C,
SSID="linksys_SES_24086"
Frame 1932: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: ....R...C
IEEE 802.11 Wireless Management
No.      Time      Source      Destination      Protocol Length Info
 1933 09:06:04.988402 Intel_d1:b6:4f CiscoLinksys_f5:ba:bb 802.11 107 Association Request, SN=1620, FN=0, Flags=...R...C,
SSID="linksys_SES_24086"
Frame 1933: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24
```

802.11 radio information
IEEE 802.11 Association Request, Flags:R...C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
1934	09:06:04.996656	Intel_d1:b6:4f	CiscoLinksys_f5:ba:bb	802.11	107	Association Request, SN=1620, FN=0, Flags=....R...C, SSID="linksys_SES_24086"

Frame 1934: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Request, Flags:R...C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
1935	09:06:05.008673	Intel_d1:b6:4f	CiscoLinksys_f5:ba:bb	802.11	107	Association Request, SN=1620, FN=0, Flags=....R...C, SSID="linksys_SES_24086"

Frame 1935: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Request, Flags:R...C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
1937	09:06:05.011653	Intel_d1:b6:4f	CiscoLinksys_f5:ba:bb	802.11	107	Association Request, SN=1620, FN=0, Flags=.....C, SSID="linksys_SES_24086"

Frame 1937: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Request, Flags:C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
2126	09:06:09.249402	Intel_d1:b6:4f	CiscoLinksys_f5:ba:bb	802.11	107	Association Request, SN=1645, FN=0, Flags=.....C, SSID="linksys_SES_24086"

Frame 2126: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Request, Flags:C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
2127	09:06:09.250651	Intel_d1:b6:4f	CiscoLinksys_f5:ba:bb	802.11	107	Association Request, SN=1645, FN=0, Flags=....R...C, SSID="linksys_SES_24086"

Frame 2127: 107 bytes on wire (856 bits), 107 bytes captured (856 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Request, Flags:R...C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
2162	09:06:10.242367	Intel_d1:b6:4f	CiscoLinksys_f7:1d:51	802.11	89	Association Request, SN=1648, FN=0, Flags=.....C, SSID="30 Munroe St"

Frame 2162: 89 bytes on wire (712 bits), 89 bytes captured (712 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Request, Flags:C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
2166	09:06:10.264558	CiscoLinksys_f7:1d:51	Intel_d1:b6:4f	802.11	94	Association Response, SN=3728, FN=0, Flags=.....C

Frame 2166: 94 bytes on wire (752 bits), 94 bytes captured (752 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Response, Flags:C
IEEE 802.11 Wireless Management

No.	Time	Source	Destination	Protocol	Length	Info
2307	09:06:17.252406	CiscoLinksys_f5:ba:7b	f9:ff:ff:ff:ff:ff	802.11	132	Fragmented IEEE 802.11 frame

Frame 2307: 132 bytes on wire (1056 bits), 132 bytes captured (1056 bits)
Radiotap Header v0, Length 24

802.11 radio information
IEEE 802.11 Association Request, Flags: ...P.M.TC
Data (80 bytes)

0000	86 91 35 73 dc 05 00 66 27 b5 11 30 ab d3 6c 59	..5s...f'..0..1Y
0010	75 0d 70 49 68 5f 93 29 53 61 f8 a2 e9 08 2d cd	u.pIh_)Sa....-
0020	62 07 85 4b fa 9b 0c 06 35 1f 00 b2 61 36 bb 35	b..K....5...a6.5
0030	2b 6b 2e c2 6c f4 dd eb 78 56 94 0e c3 1c f3 00	+k..l...xV.....
0040	c4 9a cc 44 03 56 a6 ec d8 74 54 45 f4 67 73 84	...D.V...tTE.gs.