	8		7	6	5		4	3	DWG NO DC2223005 SH 1	1	
	NOTES: UNLESS OT	OTES: UNLESS OTHERWISE SPECIFIED			NORTHROP GRUMMAN P	RIVATE/PROPRI	ETARY LEVEL I		REVISIONS REV DESCRIPTION	DATE APPROVED	
	1. THIS DRAWING SHALL BE INTERPRETED IAW ASME Y14.100 - 2017. AFTER FINISHING AND PLATING.			.100 - 2017. AFTER			130, USING INK, FN	601, WITH .12 HIGH	1 ENGINEERING DEVELOPMENT	20130307 ON FILE	E
				CHARACTERS. LOCA	TE APPROXIMAT	ELY WHERE SHOWN.		2 SH 1, DEL NOTE 11. RJO UPDATED SCREW HEAD TYPE AND	20170425 ON FILE	=	
	 MATERIAL: SEE SEPARATE PARTS LIST. PART TO BE MANUFACTURED USING THIS DRAWING AND SPECIFIED CAD/CAM DATA FILE. PART IS MODELED AT NOMINAL SIZE. 				11. DELETED				3 ADDED GASKET, SH 2. ADDED FLA NOTE 14. OVERALL GENERAL		E
D					12 INSTALL FIND NO 501 AND 502 AFTER FINISH.		DRAWING REVIEW. MS		D		
					13. ABBREVIATIONS NOT IAW ASME Y14.38: JET: JOINT ENTERPRISE TERMINAL				PROTOTYPE RELEASE ONLY UNCONTROLLED COPY		
	4. ALL FEATURE SIZES, TOLERANCES AND LOCATIONS SHALL BE IAW THIS DRAWING AND THE CAD/CAM DATA FILE. DIMENSIONAL VALUES OF GEOMETRY DERIVED FROM THE CAD/CAM DATA FILE REPRESENT A BASIC DIMENSION UPON WHICH A TOLERANCE IS APPLIED. UNLESS OTHERWISE SPECIFIED ON THE DRAWING, THE FOLLOWING TOLERANCES				14 INSTALL EMI GASKET, FN 602 AS INDICATED INTO COVER GROOVES FN 1. STRETCHING OF GASKET IS NOT PERMISSABLE. MITER CUT JOINED END.				USER MUST VERIFY CURRENT REVISION PRIOR TO USE		
	SHALL APPLY: A. PROFILE TOLERANCE FOR ALL UNSPECIFIED SURFACES TO BE:			JRFACES TO BE:	MAXIMUM ALLOWABLE GAP IS .020 INCH.						
	<u> </u>	10 A B C									
		N TOLERANCE FOR ALL UNSPECIFIED 10 M A B M C M		D HOLES TO BE:	APPROVED SOURCE(S) OF SUPPLY 8						
			ARE CRITICAL TO FUNCT	ΓΙΟΝ.	CAD/CAM DATA FILE	PART NUMBER	NATIVE CAD FILE	VENDOR			
				G TAKE PRECEDENCE OVER SUPPLIED	DC2223005-1_3.IGS	D00000005 4	D00000005 0 -i	PROCURE ONLY FROM SUPPLIER			
	CAD/CAM DATA		SHOWN ON THIS DRAWING	A TAKE PRECEDENCE OVER SUPPLIED	DC2223005-1_3.STP	DC2223005 - 1	DC2223005_3.zip	WITH SAP QMSV, 2 OR BETTER			
	7. INSPECTION RE		ADDITOADIE OAD /OAR	DATA FILE TO INCOPERT DART	UNSPECIFIED FEATURE CONTROL					С	
O	A. USE THIS DRAWING AND APPLICABLE CAD/CAM DATA FILE TO INSPECT PART. B. MINIMUM INSPECTION REQUIREMENTS: 1. ALL DIMENSIONS AND TOLERANCES SHOWN ON THIS DRAWING. 2. QUALITY OF FINISH IAW APPLICABLE FINISH SPECIFICATION. 3. RADIUS .050, .094, AND .125 MAY BE VERIFIED IN LIEU OF INSPECTION. 4. ALL TAPPED HOLES SHALL BE GAGED PRIOR TO INSERT INSTALLATION.			DATA FILE TO INSPECT PART.	FILLET RADII HOLE TOLERANCES		R .000 TO R.015 MODELED AS SHARP PER DRAWING TITLE BLOCK MODELED AS NOMINAL				
					THREADE	THREADED HOLES CLASS 3B THREAD		MODELED AT NOMINAL			
					SHARP EDGES RADIUS	.005 TO .015 R .000015	MODELED AS SHARP MODELED AS SHARP				
	5. AFTE	R FINISH, ALL	BLIND TAPPED HOLES S	SHALL BE INSPECTED FOR DEBRIS.							
				AINED ALONG DATUM A ONLY.							
			` '	JPPLY IS NOT TO BE CONSTRUED AS A Y AS A SOURCE OF SUPPLY FOR THE ITEM							
	DESCRIBED ON	THIS DRAWING									
	9 FINISH:	I CONVEDCION	DED TAW MIL DIL 5541								
	B. APPLY P	RIMER COATING	•	TYPE I, CLASS C, AND ΕΡΟΧΥ							
	TOP COAT IAW MIL-PRF-22750, WHITE COLOR NO. 17925, IAW FED-STD-595, ON INDICATED SURFACES. PRIMER AND TOPCOAT APPLICATION SHALL FOLLOW MANUFACTURER' RECOMMENDED PROCEDURES. PRIMER SHALL HAVE A DRY FILM THICKNESS OF .0009 MAX. TOPCOAT SHALL HAVE A DRY FILM THICKNESS OF .00170023.				S		0				
В											В
	TOLOGAT	DITI TILM THIORNESS (JI 10017 - 100231	SHOWN FOR REFERENCE ONLY							
	NORTHROP GRUMMAN PRIVATE/PROPRIETARY LEVEL I THE DATA IN THIS DOCUMENT IS OWNED BY AND IS PROPRIETARY TO NORTHROP GRUMMAN SYSTEMS COI				ORPORATION ACTING		SCALE: NONE		CRITICAL TO FUNCTION DRAWING		
	THROUGH ITS NORTHROP GRUMMAN MISSION SYSTEMS SECTOR, AIRBOURNE C4ISR SYSTEMS DIVISION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DATA IS EXPRESSLY PROHIBITED EXCEPT AS THE NORTHROP GRUMMAN INFORMATION SYSTEMS SECTOR OF THE NORTHROP GRUMMAN SYSTEMS CORPORATION MAY OTHERWISE AGREE TO IN WRITING.								ONLY CRITICAL FEATURES ARE DEF		
						j			APPLICABLE CAD/CAM DATA FILE N	NUST BE USED FOR	
	LIMITED RIGHTS:	THE GOVERNME	ENT'S RIGHTS TO USE,	MODIFY, REPRODUCE, RELEASE, PERFORM,	OR DISCLOSE THESE TE	ECHNICAL			COMPLETE PART DEFINITION AND F	INAL ACCEPTANCE.	
	DATA ARE RESTRICTED BY PARAGRAPH (B) (3) OF THE RIGHTS IN TECHNICAL DATA-NONCOMMERCIAL ITEMS CLAUSE AS IDENTIFIED IN CONTRACT H94003-04-D-0005-41. ANY REPRODUCTION OF TECHNICAL DATA OR PORTIONS THEREOF MARKED WITH THIS LEGEND							SEE SEPARA	ATE PARTS LIST		
	MUST ALSO CONTAIN THIS MARKING. ANY PERSON, OTHER THAN THE GOVERNMENT, WHO HAS BEEN PROMUST PROMPTLY NOTIFY THE ABOVE NAMED CONTRACTOR.										
Α	DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO THE DEPARTMENT OF DEFENSE (DOD) AN				AND DOD CONTRACTORS	C ONLY:	CAG	E PART OR IDENTIFYING NO. NOMENCLATURE DESCRIPTION	E OR ON MATERIAL	SPEC REF FIN	1D
	CRITICAL TECHNOLOGY, 14 JUL 2011. OTHER REQUESTS SHALL BE REFERRED TO ACC/AFC2IC/C2DT.					ONLT,			PARTS LIST D NOT SCALE DRAWING		
	WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT						1. DIMENSIONS ARE IN INCHES. 2. SURFACE TEXTURE SHALL BE 3. DIMENSIONS APPLY AFTER PLATING ON ALL HOLE DIAMETERS			<u>GRUMMAN</u>	Δ
	(TITLE 22, U.S.C., SEC 2751, ET SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C. APP. 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN					•	OR CONVERSION COATING. 4. REMOVE BURRS AND SHARP EDGES. 5. PARENTHETICAL DATA IS FOR DEFERENCE ONLY. UNDER .0140 +.0020 .501 THRU .750 +.008 001 001 001 001 001 001 001 001 001 001 001 001 001 001 001 001 001 001 001				
	ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.						FOR REFERENCE ONLY. 6. ALL SHEETS ARE THE SAME REVISION STATUS.	.126 THRU .250 +.005 1.001 THRU 2.000 +.012 R D E	COVER,	BATTERY	
	HANDLING AND DESTRUCTION NOTICE: COMPLY WITH DISTRIBUTION STATEMENT AND DESTROY BY ANY METHOD THAT WILL PREVEN DISCLOSURE OF CONTENTS OR RECONSTRUCTION OF THE DOCUMENT.						ON DECIMAL ON ANGULAR DIMENSIONS: ON ANGULAR ON ANGULAR ON A C C E S S - J A C C E S S - J A C C E S S - J				
						.XX ± .03 LOCATIN FORMED .X ± .1			REV	V	
				RIGHTS RESERVED. THIS MATERIAL MAY B GHT LICENSE SET FORTH UNDER DEFARS 25		995).	USED ON CI NO. NEXT A	ASSY FINISH 9 HEAT TREAT	HIRD ANGLE	2223005 3	
	8		7	6	5		4	3 CRIR	ROJECTION SCALE 2/1 2	SHEET 1 OF 2	

