

Control structures

Stat 580

References

- Part of this slide set is based on *Essential C* by Nick Parlante:

Stanford CS Education Library This is document #101, Essential C, in the Stanford CS Education Library. This and other educational materials are available for free at <http://cslibrary.stanford.edu/>. This article is free to be used, reproduced, excerpted, retransmitted, or sold so long as this notice is clearly reproduced at its beginning.

(for copyright reason, this notice is reproduced here.)

if statement

Four common forms:

```
if (<expression>) <statement>    /* simple form with no {} or else clause */
```

```
if (<expression>) {                /* simple form with {}'s to group statements */  
    <statement>  
    <statement>  
}
```

```
if (<expression>) {                /* full then/else form */  
    <statement>  
} else {  
    <statement>  
}
```

```
if (<expression>) {                /* full then/else form */  
    <statement>  
} else if (<expression>) {  
    <statement>  
} else {  
    <statement>  
}
```

Example

```
double x, y, min;  
x = 1.3;  
y = 2.1;  
  
/* if-else */  
if (x < y) {  
    min = x;  
} else {  
    min = y;  
}  
printf("%f\n", min); /* 1.300000 */
```

Conditional expression

The conditional expression can be used as a shorthand for some if-else statements.

```
<expression1> ? <expression2> : <expression3>
```

- expression, not a statement
- If <expression1> is true, this expression returns <expression2>. Otherwise, it returns <expression3>.

```
/* conditional operator */  
min = (x<y) ? x : y;  
printf("%f\n", min);
```

switch statement

- useful when there are many cases (if ... else if ... else if ... else ...)

```
switch (<expression>) {  
    case <const-expression-1>:  
        <statement>  
        break;  
    case <const-expression-2>:  
        <statement>  
        break;  
    case <const-expression-3>:  
        <statement>  
        break;  
    default: /* optional */  
        <statement>  
}
```

- The switch expression is evaluated, and then the flow of control jumps to the matching const-expression case.
- The case expressions are typically int or char constants.
- break is important!

Example 1

```
int n=4;

switch(n) {
    case 3:
        printf("value is 3\n");
        break;
    case 4:
        printf("value is 4\n");
        break;
    case 5:
        printf("value is 5\n");
        break;
    default:
        printf("value is not in any of the cases: %d\n", n);
}
```

Example 2

```
int n=4;

switch(n) {
    case 3:
        printf("value is 3\n");
        break;
    case 4:
    case 5:
        printf("value is 4 or 5\n");
        break;
    default:
        printf("value is not in any of the cases: %d\n", n);
}
```


Example 2

```
int n=4;

switch(n) { /* n is an integer or a character */
  case 3: /* error if duplicated */
    printf("value is 3\n");
    break; /* problematic if break is removed */
  case 4:
  case 5: /* same statement for case 4 or 5 */
    printf("value is 4 or 5\n");
    break;
  default:
    printf("value is not in any of the cases: %d\n", n);
}
```

while loop

```
while (<expression>) {  
    <statement>  
}
```

- while the <expression> is true, the loop continues
- <expression> is evaluated before every loop
- may lead to infinite-loop

Example:

```
j=5;  
  
while (j--) /* is it an infinite loop? */  
    printf("%d\n",j);
```

do-while loop

```
do {  
    <statement>  
} while (<expression>)
```

- do-while is a variation of while loop, which ensures the loop body is executed at least once.

What are the outputs of the following two loops?

```
j=5;  
while (j--)  
    printf("%d\n", j);
```

```
j=5;  
do  
    printf("%d\n", j);  
while (j--);
```

for loop

```
for (<initialization>; <continuation>; <action>) {  
    <statement>  
}
```

- The loop header contains three parts:
 - an initialization
 - a continuation condition
 - an action
- The initialization is executed once before the body of the loop is entered.
- The loop continues to run as long as the continuation condition remains true (like a while).
- After every execution of the loop, the action is executed.

Example

```
int x, y;  
  
for (x=0; x<10; x++){  
    printf("%d\n", x);  
}
```

We can have multiple variables in <initialization> and <action>:

```
for (x=1, y=5; (x+y<10)&&(y<=5); x++, y++) { /* multiple variables */  
    printf("(%d, %d)\n", x, y);  
}
```

break

```
while (<expression>) {  
    <statement>  
    <statement>  
    if (<"break condition">)  
        break;  
    <statement>  
    <statement>  
}  
/* control jumps down here on the break */
```

- The break statement will move control outside a loop or switch statement.
- It's preferable to use a straight while with a single test at the top if possible.
- It *does not* work with if (does not break if), while it usually occurs together with if.

continue

- The continue statement causes control to jump to the bottom of the loop, skipping over any code below the continue.

```
while (<expression>) {  
    ...  
    if (<condition>)  
        continue;  
    ...  
    ...  
    /* control jumps here on the continue */  
}
```