DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL 1 0W-16	60 Months		60 °C		None	
MOBIL 1 0W-20	60 Months		60 °C		None	
MOBIL 1 0W-30	60 Months		60 °C		None	
MOBIL 1 0W-40	60 Months		60 °C		None	
MOBIL 1 10W-30	60 Months		60 °C		None	
MOBIL 1 10W-60	60 Months		60 °C		None	
MOBIL 1 15W-50	60 Months		60 °C		None	
MOBIL 1 5W-20	60 Months		60 °C		None	
MOBIL 1 5W-30	60 Months		60 °C		None	
MOBIL 1 5W-40	60 Months		60 °C		None	
MOBIL 1 5W-50	60 Months		60 °C		None	
MOBIL 1 RACING 4T 10W-40	60 Months		60 °C		None	
MOBIL 1 RACING 4T 15W-50	60 Months		60 °C		None	
MOBIL ALMO 527	120 Months		40 °C		None	
MOBIL ALMO 529	120 Months		40 °C		None	
MOBIL ALMO 530	120 Months		40 °C		None	
MOBIL ALMO 532	120 Months		40 °C		None	
MOBIL ANTIFREEZE	**24 Months;36 Months**	**24 mo applies to AC000043, AC000079, and AC000080;36 mo applies to AC000004**			**Blending, Handling, and Storage temperatures are Ambient**	**x**

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL ANTIFREEZE ADVANCED	60 Months				Maximum Blending and Handling Tempertures are Ambient	
MOBIL ANTIFREEZE EXTRA	60 Months				Blending, Handling, and Storage temperatures are Ambient	
MOBIL ANTIFREEZE HEAVY DUTY	60 Months				Max Blending, Handling, and Storage temperatures are Ambient	
MOBIL ATF 220	60 Months		50 °C		None	
MOBIL COOLANT READY MIXED - 36°C	60 Months				Maximum Blending, Handling and Storage Tempertures are Ambient	
MOBIL DELVAC MX 15W-40	60 Months		60 °C		Do not overheat.	
MOBIL DELVAC MX 20W-50	**60 Months**		**60 °C**		**Do not overheat.**	**x**
MOBIL DELVAC MX ESP 15W-40	**60 Months**				None	**x**
MOBIL DELVAC SUPER 1300 15W-	60 Months		60 °C		None	
MOBIL DELVAC SUPER 1400 15W-	**60 Months**		**60 °C**		**Do not overheat.**	**x**
MOBIL DELVAC SUPER 1400 20W-	60 Months		60 °C		Do not overheat.	
MOBIL DELVAC SYNTHETIC GEAR	60 Months		50 °C		None	
MOBIL DELVAC SYNTHETIC GEAR	60 Months		44 °C		None	
MOBIL DELVAC SYNTHETIC GEAR	60 Months		44 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL DTE 10 EXCEL 100	120 Months		45 °C		None	
MOBIL DTE 10 EXCEL 15	120 Months		45 °C		None	
MOBIL DTE 10 EXCEL 150	120 Months		45 °C		None	
MOBIL DTE 10 EXCEL 22	120 Months		45 °C		None	
MOBIL DTE 10 EXCEL 32	120 Months		45 °C		None	
MOBIL DTE 10 EXCEL 46	120 Months		45 °C		None	
MOBIL DTE 10 EXCEL 68	120 Months		45 °C		None	
MOBIL DTE 21	120 Months		45 °C		None	
MOBIL DTE 22	120 Months		45 °C		None	
MOBIL DTE 24	120 Months		45 °C		None	
MOBIL DTE 25	120 Months		45 °C		None	
MOBIL DTE 26	120 Months		45 °C		None	
MOBIL DTE 27	120 Months		45 °C		None	
MOBIL DTE 28	120 Months		45 °C		None	
MOBIL DTE 732	120 Months		40 °C		None	
MOBIL DTE 732 M	60 Months		40 °C		None	
MOBIL DTE 746	120 Months		40 °C		None	
MOBIL DTE 768	120 Months		40 °C		None	
MOBIL DTE 832	120 Months		40 °C		None	
MOBIL DTE 846	120 Months		40 °C		None	
MOBIL DTE 932 GT	60 Months		40 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL DTE OIL EXTRA HEAVY	120 Months		45 °C		None	
MOBIL DTE OIL HEAVY MEDIUM	120 Months		40 °C		None	
MOBIL DTE OIL LIGHT	120 Months		40 °C		None	
MOBIL DTE OIL MEDIUM	120 Months		40 °C		None	
MOBIL EAL 224H	24 Months		35 °C		None	
MOBIL EAL ARCTIC 100	36 Months		40 °C		None	
MOBIL EAL ARCTIC 15	36 Months		40 °C		None	
MOBIL EAL ARCTIC 22	36 Months		40 °C		None	
MOBIL EAL ARCTIC 22 CC	36 Months		40 °C		None	
MOBIL EAL ARCTIC 220	36 Months		40 °C		None	
MOBIL EAL ARCTIC 32	36 Months		40 °C		None	
MOBIL EAL ARCTIC 46	36 Months		40 °C		None	
MOBIL EAL ARCTIC 68	36 Months		40 °C		None	
MOBIL EXTRA 4T 10W-40	60 Months		45 °C		None	
MOBIL GARGOYLE ARCTIC 68 NH	**60 Months**		**45 °C**		None	**x**
MOBIL GARGOYLE ARCTIC SHC 224	120 Months		45 °C		None	
MOBIL GARGOYLE ARCTIC SHC 226	120 Months		45 °C		None	
MOBIL GARGOYLE ARCTIC SHC 226E	120 Months		45 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL GARGOYLE ARCTIC SHC 228	120 Months		45 °C		None	
MOBIL GARGOYLE ARCTIC SHC 230	120 Months		45 °C		None	
MOBIL GARGOYLE ARCTIC SHC 234	120 Months		45 °C		None	
MOBIL GARGOYLE ARCTIC SHC NH 68	120 Months		35 °C		None	
MOBIL GLYGOYLE 100	60 Months		40 °C		None	
MOBIL GLYGOYLE 1000	60 Months		40 °C		None	
MOBIL GLYGOYLE 11	120 Months		40 °C		None	
MOBIL GLYGOYLE 150	60 Months		40 °C		None	
MOBIL GLYGOYLE 22	120 Months		40 °C		None	
MOBIL GLYGOYLE 220	60 Months		40 °C		None	
MOBIL GLYGOYLE 30	120 Months		40 °C		None	
MOBIL GLYGOYLE 320	60 Months		40 °C		None	
MOBIL GLYGOYLE 460	60 Months		40 °C		None	
MOBIL GLYGOYLE 68	60 Months		40 °C		None	
MOBIL GLYGOYLE 680	60 Months		40 °C		None	
MOBIL HYDRAULIC 10W	60 Months		60 °C		None	
MOBIL PEGASUS 605	36 Months		45 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL PEGASUS 610	36 Months		45 °C		None	
MOBIL PEGASUS 805	36 Months		45 °C		None	
MOBIL POLYREE EM	60 Months		45 °C		(a) Max Blending Temperature refers to potential top temperature duringthe cooking of the soap. (b) Max Handling Temperature refers to themovement of finished grease from processing unit into the storagecontainer. (c) Max Storage Temperature refers to the storage of thefinished grease in tank or when warehoused. (d) Temperatures can varybased on plant capabilities and mode of manufacturing.	
MOBIL POLYREX EM	60 Months		45 °C			
MOBIL POLYREX EM 103	60 Months		45 °C			
MOBIL PYROTEC HFD 46	24 Months	Store Indoors	50 °C		None	
MOBIL RARUS 424	120 Months		45 °C		None	
MOBIL RARUS 425	120 Months		45 °C		None	
MOBIL RARUS 426	120 Months		45 °C		None	
MOBIL RARUS 427	120 Months		45 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL RARUS 429	120 Months		45 °C		None	
MOBIL RARUS 827	120 Months		45 °C		None	
MOBIL RARUS 829	120 Months		45 °C		None	
MOBIL RARUS SHC 1024	120 Months		45 °C		None	
MOBIL RARUS SHC 1025	120 Months		45 °C		None	
MOBIL RARUS SHC 1026	120 Months		45 °C		None	
MOBIL SHC 522	120 Months		45 °C		None	
MOBIL SHC 524	120 Months		45 °C		None	
MOBIL SHC 525	120 Months		45 °C		None	
MOBIL SHC 526	120 Months		45 °C		None	
MOBIL SHC 527	120 Months		45 °C		None	
MOBIL SHC 624	60 Months	Shelf life recertification should include top / middle / bottom sampling to ensure homogeneity	40 °C		None	
MOBIL SHC 625	60 Months		40 °C		None	
MOBIL SHC 626	60 Months		40 °C		None	
MOBIL SHC 627	60 Months		40 °C		None	
MOBIL SHC 629	60 Months		40 °C		None	
MOBIL SHC 630	60 Months		40 °C		None	
MOBIL SHC 632	60 Months		40 °C		None	
MOBIL SHC 634	60 Months		40 °C		None	
MOBIL SHC 636	60 Months		40 °C		None	
MOBIL SHC 639	60 Months		40 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SHC 824	120 Months		40 °C		None	
MOBIL SHC 825	120 Months		40 °C		None	
MOBIL SHC CHAIN 240	36 Months		40 °C		None	
MOBIL SHC CIBUS 100	60 Months		45 °C		None	
MOBIL SHC CIBUS 150	60 Months		45 °C		None	
MOBIL SHC CIBUS 220	60 Months		45 °C		None	
MOBIL SHC CIBUS 32	60 Months		45 °C		None	
MOBIL SHC CIBUS 32 HT	60 Months		45 °C		None	
MOBIL SHC CIBUS 320	60 Months		45 °C		None	
MOBIL SHC CIBUS 46	60 Months		45 °C		None	
MOBIL SHC CIBUS 460	60 Months		45 °C		None	
MOBIL SHC CIBUS 68	60 Months		45 °C		None	
MOBIL SHC GEAR 1000	48 Months	Recertification for after shelf life blends should at least include BRT section and AM-S 1393 or Flender Foam tests.	40 °C		None	
MOBIL SHC GEAR 150	48 Months		40 °C		None	
MOBIL SHC GEAR 1500	60 Months		40 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SHC GEAR 220	48 Months	Recertification for after shelf life blends should at least include BRT section and AM-S 1393 or Flender Foam tests.	40 °C		None	
MOBIL SHC GEAR 22M	60 Months		45 °C		Maximum handling temperature of 120C is not to exceed 24 hours	
MOBIL SHC GEAR 320	48 Months	Recertification for after shelf life blends should at least include BRT section and AM-S 1393 or Flender Foam tests.	40 °C		None	
MOBIL SHC GEAR 320 WT	60 Months		45 °C		None	
MOBIL SHC GEAR 3200	60 Months		40 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SHC GEAR 460	48 Months	Recertification for after shelf life blends should at least include BRT section and AM-S 1393 or Flender Foam tests.	40 °C		None	
MOBIL SHC GEAR 46M	60 Months		45 °C		Maximum handling temperature of 120C is not to exceed 24 hours	
MOBIL SHC GEAR 680	48 Months	Recertification for after shelf life blends should at least include BRT section and AM-S 1393 or Flender Foam tests.	40 °C		None	
MOBIL SHC GEAR 6800	60 Months		40 °C		None	
MOBIL SHC POLYREX 102 EM	**60 Months**		**45 °C**		None	**x**
MOBIL SHC POLYREX 103 EM	**60 Months**		**45 °C**		None	**x**

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SHC POLYREX 221	60 Months		45 °C		(a) Max Blending Temperature refers to potential top temperature duringthe cooking of the soap. (b) Max Handling Temperature refers to themovement of finished grease from processing unit into the storagecontainer. (c) Max Storage Temperature refers to the storage of thefinished grease in tank or when warehoused. (d) Temperatures can varybased on plant capabilities and mode of manufacturing.	
MOBIL SHC POLYREX 222	60 Months		45 °C			
MOBIL SHC POLYREX 462	60 Months		45 °C			
MOBIL SHC RARUS 32	60 Months		40 °C		None	
MOBIL SHC RARUS 46	60 Months		40 °C		None	
MOBIL SHC RARUS 68	60 Months		40 °C		None	
MOBIL SPECIAL 10W-30	60 Months		60 °C		None	
MOBIL SPECIAL 10W-40	60 Months		45 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SPECIAL 15W-40	60 Months		45 °C		None	
MOBIL SPECIAL 15W-50	60 Months		45 °C		None	
MOBIL SPECIAL 20W-50	60 Months		45 °C		None	
MOBIL SPECIAL 25W-50	60 Months		60 °C		None	
MOBIL SPECIAL 4T 10W-40	60 Months		60 °C		None	
MOBIL SPECIAL 4T 20W-40	60 Months		50 °C		None	
MOBIL SPECIAL 4T 20W-50	60 Months		45 °C		None	
MOBIL SPECIAL 5W-30	60 Months		60 °C		None	
MOBIL SUPER + 4T 20W-50	60 Months		45 °C		None	
MOBIL SUPER 0W-20	60 Months	None	45 °C		None	
MOBIL SUPER 1000 10W-30	60 Months		60 °C		None	
MOBIL SUPER 1000 10W-40	60 Months		45 °C		None	
MOBIL SUPER 1000 15W-50	60 Months		45 °C		None	
MOBIL SUPER 1000 20W-50	60 Months		45 °C		None	
MOBIL SUPER 1000 5W-20	60 Months		45 °C		None	
MOBIL SUPER 1000 5W-30	60 Months		45 °C		None	
MOBIL SUPER 1000 DIESEL 10W-	60 Months		50 °C		None	
MOBIL SUPER 1000 DIESEL 15W-40	**60 Months**		**60 °C**		**Do not overheat.**	**x**
MOBIL SUPER 1000 DIESEL G 15W-40	**60 Months**		**60 °C**		**Do not overheat.**	**x**

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SUPER 1000 X1 10W-30	60 Months		60 °C		None	
MOBIL SUPER 1000 X1 15W-40	60 Months		45 °C		None	
MOBIL SUPER 1000 X1 20W-50	60 Months		45 °C		None	
MOBIL SUPER 1000 X1 DIESEL	60 Months		45 °C		None	
MOBIL SUPER 1000 X2 15W-40	60 Months		45 °C		None	
MOBIL SUPER 1000 X2 20W-50	60 Months		45 °C		None	
MOBIL SUPER 1000 X2 TM 15W-40	60 Months		45 °C		None	
MOBIL SUPER 1000 X3 15W-40	60 Months		45 °C		None	
MOBIL SUPER 1000 X3 5W-30	60 Months		60 °C		None	
MOBIL SUPER 1000 X3 TURBO	60 Months		45 °C		None	
MOBIL SUPER 1000 X4 20W-50	60 Months		45 °C		None	
MOBIL SUPER 1000 XE DIESEL 5W-	60 Months		45 °C		None	
MOBIL SUPER 10W-30	60 Months		60 °C		None	
MOBIL SUPER 10W-40	60 Months		45 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SUPER 2000 10W-30	60 Months		45 °C		None	
MOBIL SUPER 2000 5W-20	60 Months		45 °C		None	
MOBIL SUPER 2000 5W-30	60 Months		45 °C		None	
MOBIL SUPER 2000 5W-40	60 Months		45 °C		None	
MOBIL SUPER 2000 X2 10W-40	60 Months		45 °C		None	
MOBIL SUPER 2000 X3 10W-40	60 Months		45 °C		None	
MOBIL SUPER 4T 10W-30	60 Months		60 °C		None	
MOBIL SUPER 4T 15W-40	60 Months		60 °C		None	
MOBIL SUPER 4T 20W-40	60 Months		60 °C		None	
MOBIL SUPER 4T 20W-50	60 Months		45 °C		None	
MOBIL SUPER 4T 25W-50	60 Months		60 °C		None	
MOBIL SUPER MOTO 4T 10W-30					None	**x**
MOBIL SUPER MOTO 4T 15W-50	60 Months		45 °C		None	
MOBIL SUPER MOTO 4T 20W-50	60 Months		45 °C		None	
MOBIL SUPER MOTO 4T 25W-50	60 Months		60 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SUPER MOTO 4T MX 10W-30	**24 Months;60 Months**	**24 mo applies to RN005729AC;60 mo applies to RN005954AC and RN006204AC**	**45 °C**		None	**x**
MOBIL SUPER MOTO 4T MX 10W-	60 Months		60 °C		None	
MOBIL SUPER MOTO 4T MX 15W-	60 Months		45 °C		None	
MOBIL SUPER MOTO GREASE	60 Months		45 °C		(a) Max Blending Temperature refers to potential top temperature duringthe cooking of the soap. (b) Max Handling Temperature refers to themovement of finished grease from processing unit into the storagecontainer. (c) Max Storage Temperature refers to the storage of thefinished grease in tank or when warehoused. (d) Temperatures can varybased on plant capabilities and mode of manufacturing.	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL SYNTHETIC OVEN LUBE	120 Months		45 °C		None	
MOBIL VACTRA OIL NO. 1	120 Months		45 °C		None	
MOBIL VACTRA OIL NO. 2	120 Months		45 °C		None	
MOBIL VACTRA OIL NO. 3	120 Months		45 °C		None	
MOBIL VACTRA OIL NO. 4	120 Months		45 °C		None	
MOBIL VACUOLINE 1405	120 Months		40 °C		None	
MOBIL VACUOLINE 1409	120 Months		40 °C		None	
MOBIL VACUOLINE 525	120 Months		40 °C		None	
MOBIL VACUOLINE 528	120 Months		45 °C		None	
MOBIL VACUOLINE 533	120 Months		40 °C		None	
MOBIL VACUOLINE 537	120 Months		45 °C		None	
MOBIL VACUOLINE 546	120 Months		45 °C		None	
MOBIL VACUOLINE 548	120 Months		40 °C		None	
MOBIL VACUUM PUMP OIL	120 Months		40 °C		None	
MOBIL VACUUM PUMP OIL 100	120 Months		40 °C		None	
MOBIL VELOCITE DX	120 Months		40 °C		None	
MOBIL VELOCITE E	120 Months		40 °C		None	
MOBIL VELOCITE HP 24	120 Months		45 °C		None	
MOBIL VELOCITE HP 32	120 Months		45 °C		None	
MOBIL VELOCITE HP 46	120 Months		45 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBIL VELOCITE HP 68	120 Months		45 °C		None	
MOBIL VELOCITE OIL CX	120 Months		45 °C		None	
MOBIL VELOCITE OIL NO. 10	120 Months		45 °C		None	
MOBIL VELOCITE OIL NO. 3	120 Months		45 °C		None	
MOBIL VELOCITE OIL NO. 4	120 Months		45 °C		None	
MOBIL VELOCITE OIL NO. 6	120 Months		45 °C		None	
MOBIL VELOCITE OIL NO. 8	120 Months		45 °C		None	
MOBILARMA 245	60 Months		30 °C		None	
MOBILARMA 247	120 Months		30 °C		None	
MOBILARMA 798	60 Months		45 °C		None	
MOBILCUT 100	12 Months	No shelf life extension allowed for EAME	35 °C	5 °C	Protect from Freezing.	
MOBILCUT 140	**12 Months;9 Months**	**No shelf life extension allowed for EAME;9 mo Shelf Life limited to RJ000865, 12 mo Shelf Life may be utilized for other formulations of Mobilcut 140**	**35 °C**	**5 °C**	**Protect from Freezing.**	**x**

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBILCUT 240	12 Months	No shelf life extension allowed for EAME	25 °C	5 °C	Protect from Freezing. Max Temperature for 12 month storage. Maximum Storage Temperature is 10-25 C	
MOBILECT 39	36 Months	In metal drums stored indoor. Product must be degassed and preconditioned to remove water before use.	35 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBILECT 44	36 Months	In metal drums stored indoor. Product must be degassed and preconditioned to remove water before use.	35 °C		Nynas guarantees specification at a max of 1 year if product is storedat a ambient temperature in a dry place protected from sunlight. Forresearch purposes, recertify material after 1 year before using... Thetemperatures indicated are for guidance only and may vary according tothe use of the material. When using this material near (within 20 deg.C) or above the flash point, special precautions must be taken.	
MOBILFLUID 424	60 Months		45 °C		None	
MOBILGEAR 600 XP 100	120 Months		45 °C		Please see Blending/Manufacturing Instructions for more information on maximum blending temperature limit	
MOBILGEAR 600 XP 150	120 Months		45 °C			
MOBILGEAR 600 XP 220	120 Months		45 °C			
MOBILGEAR 600 XP 320	120 Months		45 °C			
MOBILGEAR 600 XP 460	120 Months		45 °C			
MOBILGEAR 600 XP 68	120 Months		45 °C			

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBILGEAR 600 XP 680	120 Months		45 °C			
MOBILGREASE FM 101	36 Months		45 °C		(a) Max Blending Temperature refers to potential top temperature duringthe cooking of the soap. (b) Max Handling Temperature refers to themovement of finished grease from processing unit into the storagecontainer. (c) Max Storage Temperature refers to the storage of thefinished grease in tank or when warehoused. (d) Temperatures can varybased on plant capabilities and mode of manufacturing.	
MOBILGREASE FM 222	36 Months		45 °C			
MOBILGREASE XHP 221	60 Months		45 °C			
MOBILGREASE XHP 222	60 Months		45 °C			
MOBILGREASE XHP 222 SPECIAL	60 Months		45 °C			
MOBILGREASE XHP 223	60 Months		45 °C			
MOBILGREASE XHP 461	60 Months		45 °C			
MOBILGREASE XHP 462	60 Months		45 °C			
MOBILGREASE XHP 462 MOLY	60 Months		45 °C			
MOBILITH SHC 007	60 Months		45 °C			
MOBILITH SHC 100	60 Months		45 °C			
MOBILITH SHC 1000 SPECIAL	60 Months		45 °C			
MOBILITH SHC 1500	60 Months		45 °C			
MOBILITH SHC 220	60 Months		45 °C			
MOBILITH SHC 221	60 Months		45 °C			
MOBILITH SHC 460	60 Months		45 °C			
MOBILTAC 375 NC	**24 Months**		**40 °C**		None	**x**

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBILTEMP SHC 100	24 Months		45 °C		(a) Max Blending Temperature refers to potential top temperature duringthe cooking of the soap. (b) Max Handling Temperature refers to themovement of finished grease from processing unit into the storagecontainer. (c) Max Storage Temperature refers to the storage of thefinished grease in tank or when warehoused. (d) Temperatures can varybased on plant capabilities and mode of manufacturing.	
MOBILTEMP SHC 32	72 Months		45 °C			
MOBILTEMP SHC 460 SPECIAL	24 Months		45 °C			
MOBILTHERM 605	120 Months		40 °C		Bulk oil temperature in closed systems: 10 C - 315 C (50 F - 600 F).Bulk oil temperature in open systems: 10 C - 185 C (50 F - 365 F).	
MOBILTRANS HD 10W	60 Months		50 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBILTRANS HD 30	60 Months		50 °C	-30 °C	Handling at product pour point temperatures and below is not recommended.	
MOBILTRANS HD 50	60 Months		50 °C	-30 °C	Handling at product pour point temperatures and below is not recommended.	
MOBILTRANS HD 60	60 Months		50 °C		None	
MOBILUBE HD 75W-90	60 Months		50 °C		None	
MOBILUBE HD 80W-140	60 Months		45 °C		None	
MOBILUBE HD 80W-90	60 Months		50 °C	-30 °C	This product can be stored down to -30C. Handling at product pour point temperatures and below is not recommended.	
MOBILUBE HD 85W-140	60 Months		50 °C	-30 °C	This product can be stored down to -30C. Handling at product pour point temperatures and below is not recommended.	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
MOBILUX EP 0	60 Months		45 °C		(a) Max Blending Temperature refers to potential top temperature duringthe cooking of the soap. (b) Max Handling Temperature refers to themovement of finished grease from processing unit into the storagecontainer. (c) Max Storage Temperature refers to the storage of thefinished grease in tank or when warehoused. (d) Temperatures can varybased on plant capabilities and mode of manufacturing.	
MOBILUX EP 004	60 Months		45 °C			
MOBILUX EP 023	60 Months		45 °C			
MOBILUX EP 1	60 Months		45 °C			
MOBILUX EP 111	60 Months		45 °C			
MOBILUX EP 2	60 Months		45 °C			
MOBILUX EP 3	60 Months		45 °C			
NUTO H 100	120 Months		45 °C		None	
NUTO H 150	120 Months		45 °C		None	
NUTO H 32	120 Months		45 °C		None	
NUTO H 46	120 Months		45 °C		None	
NUTO H 68	120 Months		45 °C		None	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
NYVAC FR 200D	24 Months	CN3590 recommended shelf life is 12 months.	40 °C		No negative impact of storing the water glycol below 0C for example downto -17.8C for two months. There should be no phase separation of thefluid which would remain homogeneous. Do not store any partially fulldrums at temperatures below 0C where the moisture in the head space aircould be a factor. If Nyvac FR 200D is stored at a lower temperatures(below 0C) for two months the drums should be placed in an area at atemperature of 20-40C to warm up to that ambient temperature prior touse. Do not use drum heating bands, steam and canvas or a hot room toaccelerate warming of drums that have been stored at temperatures lessthan 0C for months.	

DPIM Product Technical Data List

ExxonMobil Confidential Information

V9: Nov, 2016

This list should be used for reference. In case of any questions please refer to ExxonMobil for further advice.
Products listed may not be available in all countries. Any products or product data not contained in this list should be referred to ExxonMobil for further advice.
Shelf Life Estimate applicable unless otherwise specified on the product label.
Changes vs. previous version are marked in bold and the corresponding line items are marked with a "x" in column H.

Product Name	Shelf Life Estimate	Shelf Life Comments	Maximum Storage Temperature	Minimum Storage Temperature	Storage Temperature Comments	Filter by Changes
UNIREX N 2	60 Months		45 °C		(a) Max Blending Temperature refers to potential top temperature duringthe cooking of the soap. (b) Max Handling Temperature refers to themovement of finished grease from processing unit into the storagecontainer. (c) Max Storage Temperature refers to the storage of thefinished grease in tank or when warehoused. (d) Temperatures can varybased on plant capabilities and mode of manufacturing.	
UNIREX N 3	60 Months		45 °C			