



The Dow Chemical Company

Date: September 11, 2018

Re: Discontinuation of Molykote™ 1292 Long Life Bearing Grease

Dear valued customer,

This notification is to inform you about our decision to no longer produce Molykote™ 1292 Long Life Bearing Grease as part of our ongoing commitment to safety, sustainability and the environment. Remaining inventories will be allocated to existing open orders on a pro-rated basis.

We understand this discontinued product notification could impact your process and have identified possible alternative products that are readily available: Molykote™ G-9000 Grease and Molykote™ 3451 Chemical Resistant Grease.

Molykote™ G-9000 Grease is a phenyl-fluoro siloxane copolymer based grease developed as a long life, high temperature bearing grease. Molykote™ G-9000 Grease can be used in a variety of applications where benefits of extended performance at elevated temperatures is required, with bearings being the primary application target. Molykote™ 3451 Chemical Resistant Grease uses the same fluoro siloxane base oil as the discontinued Molykote™ 1292 Long Life Bearing Grease, however uses a different thickening system. Molykote™ 3451 Chemical Resistant Grease can also be used in a variety of applications especially where chemical resistance is important.

Conditions and methods of use of our products are beyond our control, therefore, upon your request, we will provide you a sample of alternative material so you may test to determine which alternative products are effective and satisfactory for your intended end-use. Our technical support team would be happy to answer any questions about these products during the conversion of your application to an alternative Molykote™ product.

Discontinued materials:

- 1292 GRSE,TUB,100G-CTN\10
- 1292 GRSE,TUB,150G-12CTN
- 1292 GRSE EC,CAN,1KG-10CTN
- 1292 GRSE,KG,4.5KG-4CTN
- 1292 GRSE,KG,5KG-PAIL
- 1292 GRSE,KG,20.4KG-PAIL
- 1292 GRSE,KG,25KG-PAIL
- 1292 GRSE,KG,58.9KG-DRUM



WORLDWIDE PARTNER



Alternative materials:

- G-9000 TUB,100G-CTN\10
- G-9000 GREASE,CRT,0.540KG-10CTN
- G-9000 GREASE,KG,1KG-CAN-10CTN
- G-9000 GREASE,KG,5KG-PAIL
- G-9000 GREASE,KG,25KG-PAIL
- 3451 GRSE,TUB,85G-12CTN
- 3451 GRSE NO2,TUB,100G-CTN
- 3451 GRSE,CRT,550G-10CTN
- 3451 GRSE EC,CAN,1KG-10CTN
- 3451 GRSE,KG,4.5KG-PAIL
- 3451 GRSE,KG,18.0KG-PAIL
- 3451 GRSE,KG,18.1KG-PAIL
- 3451 GRSE,TUB,50G-20CTN
- 3451 GRSE,KG,25KG-PAIL
- 3451 CHM/RES BRNG GRSE EU,KG,180KG-DRU

We value you as our customer and continuously strive to provide consistent product quality, supply, and service. Please contact your local Molykote™ team for help ordering replacement offerings.

In the Americas:

Email: tech.info@dowcorning.com

Phone: 1800 248 2841

In Europe:

Email: eutech.info@dowcorning.com

Phone: 49611237512

In Korea:

Email: korea.info@dowcorning.com

Phone: 82 2 6411 7600

In China:

Email: china.info@dowcorning.com

Phone: 86 21 38997919

In India:

Email: india.info@dowcorning.com

Phone: 49 611 237 507

In Japan:

Email: info.tech2@dowcorning.com

Phone: 0120 77 6278

In South America:

Email: latech.infor@dowcorning.com

Phone: 0800 721 0520

In ASEAN/ANZ

Email: aseananz.infor@dowcorning.com

Phone: 0018004412572



**Product Test Comparison Table**

Test	Standard	Units	Molykote™ 1292	Molykote™ G-9000	Molykote™ 3451
Color			white	white	white
Worked Penetration Range	ISO 2137	mm/10	280 - 340	265 - 295	265-295
Base Oil viscosity		mm ² s ⁻¹	620 (40°C)	650 (40°C)	620 (40°C)
Density (20°C)	ISO 2811	g/cm ³	1.28	1.42	1.50
Dropping Point	ASTM D566 IP 392-02	°C	> 250	> 280	>280
4-Ball Testing:	DIN 51350				
Weld load		N	3400	> 1800	3200
Wear scar		mm	1.33	< 1.1	0.74
Low temperature torque (-30°C)	ASTM D1478				
Initial		Nm	118x10 ⁻³	286x10 ⁻³	126x10 ⁻³
Running (20min)		Nm	41x10 ⁻³	106x10 ⁻³	72x10 ⁻³
SKF EMCOR (7 days, dist. water)	DIN 51802	degree	3	0	2-3
Bearing Test: FAG FE-9 (3000 rpm, 1500 N, 200°C)	DIN 51821	F(50), h	35	> 300	
Contact Molykote™ Technical Service for product conversion support					

ASTM: American Society for Testing and Materials

ISO: International Standardization Organization

DIN: Deutsche Industrie Norm

Typical Properties: The data set forth above represent typical properties of Molykote™ materials and are not intended for use as lot acceptance requirements or specifications, and do not imply any fitness for a particular purpose or application performance guarantee.