

STABURAGS® NBU 8 EP

Rolling bearing and high-pressure grease



Description:

STABURAGS NBU 8 EP is a lubricating grease based on mineral oil and barium complex soap. It has been used successfully for many years as a long-term grease for bearings subject to high specific loads. Its good wear protection properties are enhanced by the barium complex thickener. STABURAGS NBU 8 EP protects reliably against corrosion and is resistant to water. It meets the requirements of DIN 51 807, dated May 1970: SKF-R2F test, test run B, 140 °C, and it achieves about 4000 operating hours in the SKF-ROF test at 120 °C.

Application:

STABURAGS NBU 8 EP has proven efficient as a rolling bearing and high pressure grease protecting against wear. It is used in traction motors, journal bearings, electric motors, pumps, and tapered roller bearings.

Application notes:

The product is applied by brush, spatula or conventional metering systems.

Minimum shelf life:

The minimum shelf life is approx. 60 months if the product is stored in the original closed container in a dry place.

Pack sizes:

400 g cartridge
1 kg can
25 kg bucket

STABURAGS NBU 8 EP

- Good corrosion protection
- Good resistance to ambient media
- Good wear protection / EP properties
- Protects against tribo-corrosion
- High-pressure grease

Product data:

Base	mineral oil / barium complex
Colour	light brown
Service temperature range*, °C, approx.	– 20 to 140
Density, DIN 51 757, at 20 °C, g/cm ³ , approx.	0.99
Drop point, DIN ISO 2176, °C	> 220
Worked penetration, DIN ISO 2137, at 25 °C, 0.1 mm	265 to 295
Consistency, NLGI grade, DIN 51 818	2
Base oil viscosity, DIN 51 561 at 40 °C, mm ² /s, approx. at 100 °C, mm ² /s, approx.	95 12
Speed factor**, (n x d _m), approx.	500,000
Apparent viscosity, Klüber viscosity grade***	M

* Service temperatures are guide values which depend on the lubricant's composition, the intended use and the application method. Lubricants change their consistency, apparent dynamic viscosity or viscosity depending on the mechano-dynamical loads, time, pressure and temperature. These changes in product characteristics may affect the function of a component.

** Speed factors are guide values which depend on the type and size of the rolling bearing type and the local operating conditions, which is why they have to be confirmed in tests carried out by the user in each individual case.

*** Klüber viscosity grades: EL = extra light lubricating grease; L = light lubricating grease; M = medium lubricating grease; S = heavy lubricating grease; ES = extra heavy lubricating grease

The data in this product information is based on our general experience and knowledge at the time of printing and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. We recommend contacting our Technical Consulting Staff to discuss your specific application. If required and possible we will be pleased to provide a sample for testing. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this product information at any time without notice.



Klüber Lubrication, a member of the Freudenberg group

Publisher and Copyright:
Klüber Lubrication München KG

Reprints, total or in part, are permitted if source
is indicated and voucher copy is forwarded.

Klüber Lubrication München KG
Geisenhausenerstraße 7, 81379 München, Deutschland
☎ +49 89 7876-0, Telefax +49 89 7876-333, www.klueber.com