

Moodle LMS 3.9 Database schema / Zoola Analytics

Table / View	Children	Parents	Columns	Rows	Type	Comments
analytics_indicator_calc	0	1	9	-1	Table	Stored indicator calculations
analytics_models	6	0	13	-1	Table	Analytic models.
analytics_models_log	0	1	12	-1	Table	Analytic models changes during evaluation.
analytics_predict_samples	0	1	8	-1	Table	Samples already used for predictions.
analytics_prediction_actions	0	2	5	-1	Table	Register of user actions over predictions.
analytics_predictions	1	2	11	-1	Table	Predictions
analytics_train_samples	0	1	6	-1	Table	Samples used for training
analytics_used_analysables	0	1	6	-1	Table	List of analysables used by each model
analytics_used_files	0	2	5	-1	Table	Files that have already been used for training and prediction.
assign	10	0	30	-1	Table	This table saves information about an instance of mod_assign in a course.
assign_grades	5	2	8	-1	Table	Grading information about a single assignment submission.
assign_overrides	0	3	8	-1	Table	The overrides to assign settings.
assign_plugin_config	0	1	6	-1	Table	Config data for an instance of a plugin in an assignment.
assign_submission	2	2	9	-1	Table	This table keeps information about student interactions with the mod/assign. This is limited to metadata about a student submission but does not include the submission itself which is stored by plugins.
assign_user_flags	0	2	8	-1	Table	List of flags that can be set for a single user in a single assignment.
assign_user_mapping	0	2	3	-1	Table	Map an assignment specific id number to a user
assignfeedback_comments	0	2	5	-1	Table	Text feedback for submitted assignments
assignfeedback_editpdf_annot	0	1	11	-1	Table	stores annotations added to pdfs submitted by students
assignfeedback_editpdf_cmnt	0	1	9	-1	Table	Stores comments added to pdfs
assignfeedback_editpdf_queue	0	0	4	-1	Table	Queue for processing.
assignfeedback_editpdf_quick	0	1	5	-1	Table	Stores teacher specified quicklist comments
assignfeedback_editpdf_rot	0	1	6	-1	Table	Stores rotation information of a page.
assignfeedback_file	0	2	4	-1	Table	Stores info about the number of files submitted by a student.
assignment	1	0	19	-1	Table	Defines assignments
assignment_submissions	0	2	14	-1	Table	Info about submitted assignments
assignment_upgrade	0	0	6	-1	Table	Info about upgraded assignments
assignsubmission_file	0	2	4	-1	Table	Info about file submissions for assignments
assignsubmission_onlinetext	0	2	5	-1	Table	Info about onlinetext submission

Table / View	Children	Parents	Columns	Rows	Type	Comments
auth_oauth2_linked_login	0	3	10	-1	Table	Accounts linked to a users Moodle account.
backup_controllers	1	1	17	-1	Table	To store the backup_controllers as they are used
backup_courses	0	1	6	-1	Table	To store every course backup status
backup_logs	0	1	5	-1	Table	To store all the logs from backup and restore operations (by db logger)
badge	7	3	26	-1	Table	Defines badge
badge_alignment	0	1	7	-1	Table	Defines alignment for badges
badge_backpack	2	2	7	-1	Table	Defines settings for connecting external backpack
badge_backpack_oauth2	0	4	11	-1	Table	Default comment for the table, please edit me
badge_criteria	2	1	6	-1	Table	Defines criteria for issuing badges
badge_criteria_met	0	3	5	-1	Table	Defines criteria that were met for an issued badge
badge_criteria_param	0	1	4	-1	Table	Defines parameters for badges criteria
badge_endorsement	0	1	8	-1	Table	Defines endorsement for badge
badge_external	0	1	5	-1	Table	Setting for external badges display
badge_external_backpack	2	1	7	-1	Table	Defines settings for site level backpacks that a user can connect to.
badge_external_identifier	0	1	5	-1	Table	Setting for external badges mappings
badge_issued	1	2	8	-1	Table	Defines issued badges
badge_manual_award	0	4	6	-1	Table	Track manual award criteria for badges
badge_related	0	2	3	-1	Table	Defines badge related for badges
block	1	0	5	-1	Table	contains all installed blocks
block_instances	5	2	12	-1	Table	This table stores block instances. The type of block this is is given by the blockname column. The places this block instance appears is controlled by the parentcontextid, showinsubcontexts, pagetypepattern and subpagepattern fields. Where the block appears on the page (by default) is controlled by the defaultposition and defaultweight columns. The block's own configuration is stored serialized in configdata.
block_positions	0	2	8	-1	Table	Stores the position of a sticky block_instance on a another page than the one where it was added.
block_recent_activity	0	2	7	-1	Table	Recent activity block
block_recentlyaccesseditems	0	3	5	-1	Table	Most recently accessed items accessed by a user
block_rss_client	0	1	9	-1	Table	Remote news feed information. Contains the news feed id, the userid of the user who added the feed, the title of the feed itself and a description of the feed contents along with the url used to access the remote feed. Preferredtitle is a field for future use - intended to allow for custom titles rather than those found in the feed
block_zoola_module_name	0	1	5	-1	Table	Module names

Table / View	Children	Parents	Columns	Rows	Type	Comments
block_zoola_notifications	0	1	2	-1	Table	Zoola notifications
block_zoola_reports	0	1	5	-1	Table	Reports configured in this block instance
block_zoola_reports_cohort	0	2	3	-1	Table	Cohorts that can access this block instance
block_zoola_reports_eventcfg	1	0	14	-1	Table	Event schedules configuration
block_zoola_reports_schedule	0	3	5	-1	Table	Reports scheduled from an event
block_zoola_reports_schreps	1	2	23	-1	Table	Manually scheduled reports
block_zoola_reports_user	0	2	3	-1	Table	Users that can access this block instance
block_zoola_schedule_rcp	0	2	3	-1	Table	Scheduled reports recipients
blog_association	0	2	3	-1	Table	Associations of blog entries with courses and module instances
blog_external	0	1	9	-1	Table	External blog links used for RSS copying of blog entries to Moodle user blogs
book	1	0	11	-1	Table	Defines book
book_chapters	0	1	11	-1	Table	Defines book_chapters
cache_filters	0	0	6	-1	Table	For keeping information about cached data
cache_flags	0	0	6	-1	Table	Cache of time-sensitive flags
capabilities	1	0	6	-1	Table	this defines all capabilities
chat	3	0	10	-1	Table	Each of these is a chat room
chat_messages	0	2	7	-1	Table	Stores all the actual chat messages
chat_messages_current	0	2	7	-1	Table	Stores current session
chat_users	0	2	12	-1	Table	Keeps track of which users are in which chat rooms
choice	2	0	18	-1	Table	Available choices are stored here
choice_answers	0	3	5	-1	Table	choices performed by users
choice_options	1	1	5	-1	Table	available options to choice
cohort	4	1	11	-1	Table	Each record represents one cohort (aka site-wide group).
cohort_members	0	2	4	-1	Table	Link a user to a cohort.
comments	0	2	9	-1	Table	moodle comments module
competency	9	2	17	-1	Table	This table contains the master record of each competency in a framework
competency_coursecomp	0	2	8	-1	Table	Link a competency to a course.
competency_coursecompsetting	0	1	6	-1	Table	This table contains the course specific settings for competencies.
competency_evidence	0	2	14	-1	Table	The evidence linked to a user competency
competency_framework	1	2	13	-1	Table	List of competency frameworks.
competency_modulecomp	0	2	8	-1	Table	Link a competency to a module.

Table / View	Children	Parents	Columns	Rows	Type	Comments
competency_plan	0	2	13	-1	Table	Learning plans
competency_plancomp	0	1	7	-1	Table	Plan competencies
competency_relatedcomp	0	1	6	-1	Table	Related competencies
competency_template	3	1	10	-1	Table	Learning plan templates.
competency_templatecohort	0	2	6	-1	Table	Default comment for the table, please edit me
competency_templatecomp	0	2	7	-1	Table	Link a competency to a learning plan template.
competency_usercomp	1	2	10	-1	Table	User competencies
competency_usercompcourse	0	3	9	-1	Table	User competencies in a course
competency_usercompplan	0	2	10	-1	Table	User competencies plans
competency_userevidence	0	1	9	-1	Table	The evidence of prior learning
competency_userevidencecomp	0	2	6	-1	Table	Relationship between user evidence and competencies
config	0	0	3	-1	Table	Moodle configuration variables
config_log	0	1	7	-1	Table	Changes done in server configuration through admin UI
config_plugins	0	0	4	-1	Table	Moodle modules and plugins configuration variables
contentbank_content	0	3	10	-1	Table	This table stores content data in the content bank.
context	39	0	6	-1	Table	one of these must be set
context_temp	0	0	4	-1	Table	Used by build_context_path() in upgrade and cron to keep context depths and paths in sync.
course	66	1	32	-1	Table	Central course table
course_categories	4	1	14	-1	Table	Course categories
course_completion_aggr_methd	0	1	5	-1	Table	Course completion aggregation methods for criteria
course_completion_crit_compl	0	3	7	-1	Table	Course completion user records
course_completion_criteria	1	3	10	-1	Table	Course completion criteria
course_completion_defaults	0	2	8	-1	Table	Default settings for activities completion
course_completions	0	2	7	-1	Table	Course completion records
course_format_options	0	1	6	-1	Table	Stores format-specific options for the course or course section
course_modules	5	3	21	-1	Table	course_modules table retrofitted from MySQL
course_modules_completion	0	2	7	-1	Table	Stores the completion state (completed or not completed, etc) of each user on each activity.
course_published	0	1	8	-1	Table	Information about how and when an local courses were published to hubs
course_request	0	0	9	-1	Table	course requests
course_sections	0	1	10	-1	Table	to define the sections for each course

Table / View	Children	Parents	Columns	Rows	Type	Comments
customfield_category	1	1	11	-1	Table	core_customfield category table
customfield_data	0	2	12	-1	Table	core_customfield data table
customfield_field	1	1	11	-1	Table	core_customfield field table
data	2	0	37	-1	Table	all database activities
data_content	0	2	8	-1	Table	the content introduced in each record/fields
data_fields	1	1	16	-1	Table	every field available
data_records	1	2	7	-1	Table	every record introduced
editor_atto_autosave	0	2	9	-1	Table	Draft text that is auto-saved every 5 seconds while an editor is open.
enrol	3	2	35	-1	Table	Instances of enrolment plugins used in courses, fields marked as custom have a plugin defined meaning, core does not touch them. Create a new linked table if you need even more custom fields.
enrol_flatfile	0	3	8	-1	Table	enrol_flatfile table retrofitted from MySQL
enrol_lti_lti2_consumer	5	0	19	-1	Table	LTI consumers interacting with moodle
enrol_lti_lti2_context	1	1	7	-1	Table	Information about a specific LTI contexts from the consumers
enrol_lti_lti2_nonce	0	1	4	-1	Table	Nonce used for authentication between moodle and a consumer
enrol_lti_lti2_resource_link	2	3	9	-1	Table	Link from the consumer to the tool
enrol_lti_lti2_share_key	0	1	5	-1	Table	Resource link share key
enrol_lti_lti2_tool_proxy	0	1	6	-1	Table	A tool proxy between moodle and a consumer
enrol_lti_lti2_user_result	0	1	6	-1	Table	Results for each user for each resource link
enrol_lti_tool_consumer_map	0	2	3	-1	Table	Table that maps the published tool to tool consumers.
enrol_lti_tools	2	2	19	-1	Table	List of tools provided to the remote system
enrol_lti_users	0	2	12	-1	Table	User access log and gradeback data
enrol_paypal	0	3	21	-1	Table	Holds all known information about PayPal transactions
event	0	4	24	-1	Table	For everything with a time associated to it
event_subscriptions	1	2	10	-1	Table	Tracks subscriptions to remote calendars.
events_handlers	1	0	8	-1	Table	This table is for storing which components requests what type of event, and the location of the responsible handlers. For example, the assignment registers 'grade_updated' event with a function assignment_grade_handler() that should be called event time an 'grade_updated' event is triggered by grade_update() function.
events_queue	1	1	5	-1	Table	This table is for storing queued events. It stores only one copy of the eventdata here, and entries from this table are being references by the event_queue_handlers table.
events_queue_handlers	0	2	6	-1	Table	This is the list of queued handlers for processing. The event object is retrieved from the events_queue table. When no further reference is made to the event_queues table, the

Table / View	Children	Parents	Columns	Rows	Type	Comments
						corresponding entry in the events_queue table should be deleted. Entry should get deleted after a successful event processing by the specified handler.
external_functions	0	0	8	-1	Table	list of all external functions
external_services	3	0	11	-1	Table	built in and custom external services
external_services_functions	0	1	3	-1	Table	lists functions available in each service group
external_services_users	0	2	6	-1	Table	users allowed to use services with restricted users flag
external_tokens	0	4	13	-1	Table	Security tokens for accessing of external services
favourite	0	2	9	-1	Table	Stores the relationship between an arbitrary item (itemtype, itemid), and a context area (component, contextid) for a specific user. Used by the favourites subsystem.
feedback	4	0	17	-1	Table	all feedbacks
feedback_completed	0	3	7	-1	Table	filled out feedback
feedback_completedtmp	0	3	8	-1	Table	filled out feedback
feedback_item	2	2	13	-1	Table	feedback_items
feedback_sitecourse_map	0	2	3	-1	Table	feedback sitecourse map
feedback_template	1	0	4	-1	Table	templates of feedbackstructures
feedback_value	0	1	6	-1	Table	values of the completeds
feedback_valuetmp	0	1	6	-1	Table	values of the completedstmp
file_conversion	0	2	11	-1	Table	Table to track file conversions.
files	3	3	20	-1	Table	description of files, content is stored in sha1 file pool
files_reference	1	1	5	-1	Table	Store files references
filter_active	0	1	5	-1	Table	Stores information about which filters are active in which contexts. Also the filter sort order. See get_active_filters in lib/filterlib.php for how this data is used.
filter_config	0	1	5	-1	Table	Stores per-context configuration settings for filters which have them.
folder	0	0	10	-1	Table	each record is one folder resource
forum	8	0	29	-1	Table	Forums contain and structure discussion
forum_digests	0	2	4	-1	Table	Keeps track of user mail delivery preferences for each forum
forum_discussion_subs	0	3	5	-1	Table	Users may choose to subscribe and unsubscribe from specific discussions.
forum_discussions	4	2	14	-1	Table	Forums are composed of discussions
forum_grades	0	2	7	-1	Table	Grading data for forum instances
forum_posts	3	3	18	-1	Table	All posts are stored in this table
forum_queue	0	3	5	-1	Table	For keeping track of posts that will be mailed in digest form
forum_read	0	4	7	-1	Table	Tracks each users read posts

Table / View	Children	Parents	Columns	Rows	Type	Comments
forum_subscriptions	0	2	3	-1	Table	Keeps track of who is subscribed to what forum
forum_track_prefs	0	2	3	-1	Table	Tracks each users untracked forums
glossary	2	0	28	-1	Table	all glossaries
glossary_alias	0	1	3	-1	Table	entries alias
glossary_categories	1	1	4	-1	Table	all categories for glossary entries
glossary_entries	2	2	16	-1	Table	all glossary entries
glossary_entries_categories	0	2	3	-1	Table	categories of each glossary entry
glossary_formats	0	0	10	-1	Table	Setting of the display formats
grade_categories	5	2	14	-1	Table	This table keeps information about categories, used for grouping items.
grade_categories_history	0	4	18	-1	Table	History of grade_categories
grade_grades	1	4	23	-1	Table	grade_grades This table keeps individual grades for each user and each item, exactly as imported or submitted by modules. The rawgrademax/min and rawscaleid are stored here to record the values at the time the grade was stored, because teachers might change this for an activity! All the results are normalised/resampled for the final grade value.
grade_grades_history	0	6	24	-1	Table	History table
grade_import_newitem	1	1	4	-1	Table	temporary table for storing new grade_item names from grade import
grade_import_values	0	4	9	-1	Table	Temporary table for importing grades
grade_items	4	4	31	-1	Table	This table keeps information about gradeable items (ie columns). If an activity (eg an assignment or quiz) has multiple grade_items associated with it (eg several outcomes or numerical grades), then there will be a corresponding multiple number of rows in this table.
grade_items_history	0	6	34	-1	Table	History of grade_items
grade_letters	0	1	4	-1	Table	Repository for grade letters, for courses and other moodle entities that use grades.
grade_outcomes	4	3	10	-1	Table	This table describes the outcomes used in the system. An outcome is a statement tied to a rubric scale from low to high, such as "Not met, Borderline, Met" (stored as 0,1 or 2)
grade_outcomes_courses	0	2	3	-1	Table	stores what outcomes are used in what courses.
grade_outcomes_history	0	4	12	-1	Table	History table
grade_settings	0	1	4	-1	Table	gradebook settings
grading_areas	1	1	5	-1	Table	Identifies gradable areas where advanced grading can happen. For each area, the current active plugin can be set.
grading_definitions	4	3	14	-1	Table	Contains the basic information about an advanced grading form defined in the given gradable area

Table / View	Children	Parents	Columns	Rows	Type	Comments
grading_instances	2	2	9	-1	Table	Grading form instance is an assessment record for one gradable item assessed by one rater
gradingform_guide_comments	0	1	5	-1	Table	frequently used comments used in marking guide
gradingform_guide_criteria	1	1	9	-1	Table	Stores the rows of the criteria grid.
gradingform_guide_fillings	0	2	6	-1	Table	Stores the data of how the guide is filled by a particular rater
gradingform_rubric_criteria	2	1	5	-1	Table	Stores the rows of the rubric grid.
gradingform_rubric_fillings	0	2	6	-1	Table	Stores the data of how the rubric is filled by a particular rater
gradingform_rubric_levels	0	1	5	-1	Table	Stores the columns of the rubric grid.
groupings	2	1	9	-1	Table	A grouping is a collection of groups. WAS: groups_groupings
groupings_groups	0	2	4	-1	Table	Link a grouping to a group (note, groups can be in multiple groupings ONLY in a course). WAS: groups_groupings_groups
groups	5	1	11	-1	Table	Each record represents a group.
groups_members	0	2	6	-1	Table	Link a user to a group.
h5p	1	1	9	-1	Table	Stores H5P content information
h5p_contents_libraries	0	2	6	-1	Table	Store which library is used in which content.
h5p_libraries	5	0	16	-1	Table	Stores information about libraries used by H5P content.
h5p_libraries_cachedassets	0	1	3	-1	Table	H5P cached library assets
h5p_library_dependencies	0	2	4	-1	Table	Stores H5P library dependencies
h5pactivity	1	1	12	-1	Table	Stores the h5pactivity activity module instances.
h5pactivity_attempts	1	2	12	-1	Table	Users attempts inside H5P activities
h5pactivity_attempts_results	0	1	14	-1	Table	H5Pactivities_attempts tracking info
imscp	0	0	9	-1	Table	each record is one imscp resource
label	0	0	6	-1	Table	Defines labels
lesson	7	0	42	-1	Table	Defines lesson
lesson_answers	1	2	13	-1	Table	Defines lesson_answers
lesson_attempts	0	4	9	-1	Table	Defines lesson_attempts
lesson_branch	0	3	8	-1	Table	branches for each lesson/user
lesson_grades	0	2	6	-1	Table	Defines lesson_grades
lesson_overrides	0	3	11	-1	Table	The overrides to lesson settings.
lesson_pages	3	1	13	-1	Table	Defines lesson_pages
lesson_timer	0	2	7	-1	Table	lesson timer for each lesson
license	0	0	8	-1	Table	store licenses used by moodle

Table / View	Children	Parents	Columns	Rows	Type	Comments
local_activityvisibility	0	3	7	-1	Table	Default comment for local_activityvisibility, please edit me
local_activityvisibility_que	0	2	4	-1	Table	The update queue
local_id_course	2	2	4	-1	Table	Total time spent within a course
local_id_course_day	0	1	6	-1	Table	Time spent on a course at day level
local_id_import_logs_status	0	1	7	-1	Table	Current status of the import logs task
local_id_lastactivity	0	3	5	-1	Table	Last activity that user has performed
local_id_module	1	2	4	-1	Table	Time spent on a module
local_id_module_day	0	1	5	-1	Table	Time spent on a module at day level
lock_db	0	0	4	-1	Table	Stores active and inactive lock types for db locking method.
log	0	1	10	-1	Table	Every action is logged as far as possible
log_display	0	0	6	-1	Table	For a particular module/action, specifies a moodle table/field
log_queries	0	0	9	-1	Table	Logged database queries.
logstore_standard_log	0	4	21	-1	Table	Standard log table
lti	3	1	26	-1	Table	This table contains Basic LTI activities instances
lti_access_tokens	0	1	7	-1	Table	Security tokens for accessing of LTI services
lti_submission	0	2	9	-1	Table	Keeps track of individual submissions for LTI activities.
lti_tool_proxies	1	0	13	-1	Table	LTI tool proxy registrations
lti_tool_settings	0	4	8	-1	Table	LTI tool setting values
lti_types	3	0	18	-1	Table	Basic LTI pre-configured activities
lti_types_config	0	0	4	-1	Table	Basic LTI types configuration
ltiservice_gradebookservices	0	2	9	-1	Table	This file records the grade items created by the LTI Gradebook Services service
message	1	0	17	-1	Table	Stores all unread messages
message_airnotifier_devices	0	1	3	-1	Table	Store information about the devices registered in Airnotifier for PUSH notifications
message_contact_requests	0	2	4	-1	Table	Maintains list of contact requests between users
message_contacts	0	3	4	-1	Table	Maintains lists of contacts between users
message_conversation_actions	0	2	5	-1	Table	Stores all per-user actions on individual conversations
message_conversation_members	0	2	4	-1	Table	Stores all members in a conversations
message_conversations	4	1	11	-1	Table	Stores all message conversations
message_email_messages	0	3	4	-1	Table	Keeps track of what emails to send in an email digest
message_popup	0	1	3	-1	Table	Keep state of notifications for the popup message processor
message_popup_notifications	0	1	2	-1	Table	List of notifications to display in the message output popup

Table / View	Children	Parents	Columns	Rows	Type	Comments
message_processors	0	0	3	-1	Table	List of message output plugins
message_providers	0	0	4	-1	Table	This table stores the message providers (modules and core systems)
message_read	0	2	17	-1	Table	Stores all messages that have been read
message_user_actions	0	2	5	-1	Table	Stores all per-user actions on individual messages
message_users_blocked	0	2	4	-1	Table	Maintains lists of blocked users
messageinbound_datakeys	0	1	6	-1	Table	Inbound Message data item secret keys.
messageinbound_handlers	1	0	6	-1	Table	Inbound Message Handler definitions.
messageinbound_messagelist	0	1	5	-1	Table	A list of message IDs for existing replies
messages	2	2	11	-1	Table	Stores all messages
mnet_application	1	0	6	-1	Table	Information about applications on remote hosts
mnet_host	1	1	15	-1	Table	Information about the local and remote hosts for RPC
mnet_host2service	0	0	5	-1	Table	Information about the services for a given host
mnet_log	0	1	13	-1	Table	Store session data from users migrating to other sites
mnet_remote_rpc	0	0	6	-1	Table	This table describes functions that might be called remotely (we have less information about them than local functions)
mnet_remote_service2rpc	0	0	3	-1	Table	Group functions or methods under a service
mnet_rpc	0	0	11	-1	Table	Functions or methods that we may publish or subscribe to
mnet_service	0	0	5	-1	Table	A service is a group of functions
mnet_service2rpc	0	0	3	-1	Table	Group functions or methods under a service
mnet_session	0	1	9	-1	Table	Store session data from users migrating to other sites
mnet_sso_access_control	0	0	4	-1	Table	Users by host permitted (or not) to login from a remote provider
mnetservice_enrol_courses	0	1	14	-1	Table	Caches the information fetched via XML-RPC about courses on remote hosts that are offered for our users
mnetservice_enrol_enrolments	0	2	7	-1	Table	Caches the information about enrolments of our local users in courses on remote hosts
modules	2	0	6	-1	Table	modules available in the site
my_pages	0	1	5	-1	Table	Extra user pages for the My Moodle system
notifications	1	1	15	-1	Table	Stores all notifications
oauth2_access_token	0	0	8	-1	Table	Stores access tokens for system accounts in order to be able to use a single token across multiple sessions
oauth2_endpoint	0	1	7	-1	Table	Describes the named endpoint for an oauth2 service.
oauth2_issuer	5	0	20	-1	Table	Details for an oauth 2 connect identity issuer.
oauth2_system_account	0	0	9	-1	Table	Stored details used to get an access token as a system user for this oauth2 service.

Table / View	Children	Parents	Columns	Rows	Type	Comments
oauth2_user_field_mapping	0	1	7	-1	Table	Mapping of oauth user fields to moodle fields.
page	2	0	13	-1	Table	Each record is one page and its config data
portfolio_instance	4	0	4	-1	Table	base table (not including config data) for instances of portfolio plugins.
portfolio_instance_config	0	1	4	-1	Table	config for portfolio plugin instances
portfolio_instance_user	0	2	5	-1	Table	user data for portfolio instances.
portfolio_log	0	2	11	-1	Table	log of portfolio transfers (used to later check for duplicates)
portfolio_mahara_queue	0	1	3	-1	Table	maps mahara tokens to transfer ids
portfolio_tempdata	1	2	6	-1	Table	stores temporary data for portfolio exports. the id of this table is used for the itemid for the temporary files area. cron can clean up stale records (and associated file data) after expirytime.
post	1	4	19	-1	Table	Generic post table to hold data blog entries etc in different modules
profiling	0	0	11	-1	Table	Stores the results of all the profiling runs
qtype_ddimageortext	0	1	10	-1	Table	Defines drag and drop (text or images onto a background image) questions
qtype_ddimageortext_drags	0	1	6	-1	Table	Images to drag. Actual file names are not stored here we use the file names as found in the file storage area.
qtype_ddimageortext_drops	0	1	7	-1	Table	Drop boxes
qtype_ddmarker	0	1	11	-1	Table	Defines drag and drop (text or images onto a background image) questions
qtype_ddmarker_drags	0	1	6	-1	Table	Labels for markers to drag.
qtype_ddmarker_drops	0	1	6	-1	Table	drop regions
qtype_essay_options	0	1	12	-1	Table	Extra options for essay questions.
qtype_match_options	0	1	10	-1	Table	Defines the question-type specific options for matching questions
qtype_match_subquestions	0	1	5	-1	Table	The subquestions that make up a matching question
qtype_multichoice_options	0	1	14	-1	Table	Options for multiple choice questions
qtype_randomsamatch_options	0	1	11	-1	Table	Info about a random short-answer matching question
qtype_shortanswer_options	0	1	3	-1	Table	Options for short answer questions
question	29	4	20	-1	Table	The questions themselves
question_answers	0	1	7	-1	Table	Answers, with a fractional grade (0-1) and feedback
question_attempt_step_data	0	1	4	-1	Table	Each question_attempt_step has an associative array of the data that was submitted by the user in the POST request. It can also contain extra data from the question type or behaviour to avoid re-computation. The convention is that names belonging to the behaviour start with -, and cached values added to the submitted data start with _ or _-
question_attempt_steps	1	2	7	-1	Table	Stores one step in in a question attempt. As well as the data here, the step will have some data in the question_attempt_step_data table.

Table / View	Children	Parents	Columns	Rows	Type	Comments
question_attempts	3	2	14	-1	Table	Each row here corresponds to an attempt at one question, as part of a question_usage. A question_attempt will have some question_attempt_steps
question_calculated	0	1	7	-1	Table	Options for questions of type calculated
question_calculated_options	0	1	13	-1	Table	Options for questions of type calculated
question_categories	4	2	9	-1	Table	Categories are for grouping questions
question_dataset_definitions	1	1	6	-1	Table	Organises and stores properties for dataset items
question_dataset_items	0	0	4	-1	Table	Individual dataset items
question_datasets	0	2	3	-1	Table	Many-many relation between questions and dataset definitions
question_ddwtos	0	1	10	-1	Table	Defines drag and drop (words into sentences) questions
question_gapselect	0	1	10	-1	Table	Defines select missing words questions
question_hints	0	1	7	-1	Table	Stores the the part of the question definition that gives different feedback after each try in interactive and similar behaviours.
question_multianswer	0	1	3	-1	Table	Options for multianswer questions
question_numerical	0	1	4	-1	Table	Options for numerical questions.
question_numerical_options	0	1	6	-1	Table	Options for questions of type numerical This table is also used by the calculated question type
question_numerical_units	0	1	4	-1	Table	Optional unit options for numerical questions. This table is also used by the calculated question type.
question_response_analysis	1	1	10	-1	Table	Analysis of student responses given to questions.
question_response_count	0	1	4	-1	Table	Count for each responses for each try at a question.
question_statistics	0	1	18	-1	Table	Statistics for individual questions used in an activity.
question_truefalse	0	1	4	-1	Table	Options for True-False questions
question_usages	1	1	4	-1	Table	This table's main purpose it to assign a unique id to each attempt at a set of questions by some part of Moodle. A question usage is made up of a number of question_attempts.
questionnaire	1	2	20	-1	Table	Main questionnaire table.
questionnaire_dependency	0	2	7	-1	Table	Holds the combined dependencies per question to navigate in the test
questionnaire_fb_sections	1	1	7	-1	Table	questionnaire_fb_sections table retrofitted from MySQL
questionnaire_feedback	0	1	7	-1	Table	questionnaire_feedback table retrofitted from MySQL
questionnaire_quest_choice	0	1	4	-1	Table	questionnaire_quest_choice table retrofitted from MySQL
questionnaire_question	2	1	12	-1	Table	questionnaire_question table retrofitted from MySQL
questionnaire_question_type	0	0	5	-1	Table	questionnaire_question_type table retrofitted from MySQL
questionnaire_resp_multiple	0	0	4	-1	Table	questionnaire_resp_multiple table retrofitted from MySQL

Table / View	Children	Parents	Columns	Rows	Type	Comments
questionnaire_resp_single	0	0	4	-1	Table	questionnaire_resp_single table retrofitted from MySQL
questionnaire_response	0	2	6	-1	Table	questionnaire_response table retrofitted from MySQL
questionnaire_response_bool	0	0	4	-1	Table	questionnaire_response_bool table retrofitted from MySQL
questionnaire_response_date	0	0	4	-1	Table	questionnaire_response_date table retrofitted from MySQL
questionnaire_response_other	0	0	5	-1	Table	questionnaire_response_other table retrofitted from MySQL
questionnaire_response_rank	0	0	5	-1	Table	questionnaire_response_rank table retrofitted from MySQL
questionnaire_response_text	0	0	4	-1	Table	questionnaire_response_text table retrofitted from MySQL
questionnaire_survey	3	1	17	-1	Table	questionnaire_survey table retrofitted from MySQL
quiz	7	0	41	-1	Table	The settings for each quiz.
quiz_attempts	0	2	15	-1	Table	Stores users attempts at quizzes.
quiz_feedback	0	1	6	-1	Table	Feedback given to students based on which grade band their overall score lies.
quiz_grades	0	2	5	-1	Table	Stores the overall grade for each user on the quiz, based on their various attempts and the quiz.grademethod setting.
quiz_overrides	0	3	9	-1	Table	The overrides to quiz settings on a per-user and per-group basis.
quiz_overview_regrades	0	2	7	-1	Table	This table records which question attempts need regrading and the grade they will be regraded to.
quiz_reports	0	0	4	-1	Table	Lists all the installed quiz reports and their display order and so on. No need to worry about deleting old records. Only records with an equivalent directory are displayed.
quiz_sections	0	1	5	-1	Table	Stores sections of a quiz with section name (heading), from slot-number N and whether the question order should be shuffled.
quiz_slot_tags	0	2	4	-1	Table	Stores data about the tags that a question must have so that it can be selected for a quiz slot (when having a random question by tags on that slot).
quiz_slots	1	3	9	-1	Table	Stores the question used in a quiz, with the order, and for each question, which page it appears on, and the maximum mark (weight).
quiz_statistics	0	0	19	-1	Table	table to cache results from analysis done in statistics report for quizzes.
quizaccess_seb_quizsettings	0	2	29	-1	Table	Stores the quiz level Safe Exam Browser configuration.
quizaccess_seb_template	0	1	9	-1	Table	Templates for Safe Exam Browser configuration.
rating	0	3	10	-1	Table	moodle ratings
registration_hubs	0	0	7	-1	Table	hub where the site is registered on with their associated token
repository	0	0	4	-1	Table	This table contains one entry for every configured external repository instance.
repository_instance_config	0	0	4	-1	Table	The config for instances
repository_instances	1	2	10	-1	Table	This table contains one entry for every configured external repository instance.
repository_onedrive_access	0	1	6	-1	Table	List of temporary access grants.

Table / View	Children	Parents	Columns	Rows	Type	Comments
resource	1	0	13	-1	Table	Each record is one resource and its config data
resource_old	0	0	16	-1	Table	backup of all old resource instances from 1.9
role	24	0	6	-1	Table	moodle roles
role_allow_assign	0	2	3	-1	Table	this defines what role can assign what role
role_allow_override	0	2	3	-1	Table	this defines what role can override what role
role_allow_switch	0	2	3	-1	Table	This table stores which which other roles a user is allowed to switch to if they have one role.
role_allow_view	0	2	3	-1	Table	This table stores which which other roles a user is allowed to view to if they have one role.
role_assignments	0	3	9	-1	Table	assigning roles in different context
role_capabilities	0	4	7	-1	Table	permission has to be signed, overriding a capability for a particular role in a particular context
role_context_levels	0	1	3	-1	Table	Lists which roles can be assigned at which context levels. The assignment is allowed in the corresponding row is present in this table.
role_names	0	2	4	-1	Table	role names in native strings
scale	10	2	8	-1	Table	Defines grading scales
scale_history	0	4	11	-1	Table	History table
scorm	3	0	42	-1	Table	each table is one SCORM module and its configuration
scorm_aicc_session	0	2	12	-1	Table	Used by AICC HACP to store session information
scorm_scoes	8	1	10	-1	Table	each SCO part of the SCORM module
scorm_scoes_data	0	1	4	-1	Table	Contains variable data get from packages
scorm_scoes_track	0	3	8	-1	Table	to track SCOes
scorm_seq_mapinfo	0	2	8	-1	Table	SCORM2004 objective mapinfo description
scorm_seq_objective	1	1	6	-1	Table	SCORM2004 objective description
scorm_seq_rolluprule	1	1	7	-1	Table	SCORM2004 sequencing rule
scorm_seq_rolluprulecond	0	2	5	-1	Table	SCORM2004 sequencing rule
scorm_seq_rulecond	0	2	7	-1	Table	SCORM2004 rule condition
scorm_seq_ruleconds	1	1	5	-1	Table	SCORM2004 rule conditions
search_index_requests	0	1	7	-1	Table	Records requests for (re)indexing of specific contexts. Entries will be removed from this table when indexing of that context is complete. (This table is not used for normal time-based indexing of new content.)
search_simpledb_index	0	3	14	-1	Table	search_simpledb table containing the index data.
sessions	0	1	9	-1	Table	Database based session storage - now recommended

Table / View	Children	Parents	Columns	Rows	Type	Comments
stats_daily	0	2	7	-1	Table	to accumulate daily stats
stats_monthly	0	2	7	-1	Table	To accumulate monthly stats
stats_user_daily	0	3	8	-1	Table	To accumulate daily stats per course/user
stats_user_monthly	0	3	8	-1	Table	To accumulate monthly stats per course/user
stats_user_weekly	0	3	8	-1	Table	To accumulate weekly stats per course/user
stats_weekly	0	2	7	-1	Table	To accumulate weekly stats
survey	3	0	11	-1	Table	Each record is one SURVEY module with its configuration
survey_analysis	0	2	4	-1	Table	text about each survey submission
survey_answers	0	3	7	-1	Table	the answers to each questions filled by the users
survey_questions	1	0	7	-1	Table	the questions conforming one survey
tag	3	2	10	-1	Table	Tag table - this generic table will replace the old "tags" table.
tag_area	0	1	9	-1	Table	Defines various tag areas, one area is identified by component and itemtype
tag_coll	2	0	7	-1	Table	Defines different set of tags
tag_correlation	0	1	3	-1	Table	The rationale for the 'tag_correlation' table is performance. It works as a cache for a potentially heavy load query done at the 'tag_instance' table. So, the 'tag_correlation' table stores redundant information derived from the 'tag_instance' table
tag_instance	0	2	10	-1	Table	tag_instance table holds the information of associations between tags and other items
task_adhoc	1	1	8	-1	Table	List of adhoc tasks waiting to run.
task_log	0	1	11	-1	Table	The log table for all tasks
task_scheduled	0	0	14	-1	Table	List of scheduled tasks to be run by cron.
tool_cohortroles	0	3	7	-1	Table	Mapping of users to cohort role assignments.
tool_customlang	0	1	11	-1	Table	Contains the working checkout of all strings and their customization
tool_customlang_components	1	0	3	-1	Table	Contains the list of all installed plugins that provide their own language pack
tool_dataprivacy_category	2	0	7	-1	Table	Data categories
tool_dataprivacy_ctxexpired	0	1	9	-1	Table	Default comment for the table, please edit me
tool_dataprivacy_ctxinstance	0	3	7	-1	Table	Default comment for the table, please edit me
tool_dataprivacy_ctxlevel	0	2	7	-1	Table	Default comment for the table, please edit me
tool_dataprivacy_purpose	3	0	11	-1	Table	Data purposes
tool_dataprivacy_purposerole	0	2	10	-1	Table	Data purpose overrides for a specific role
tool_dataprivacy_request	0	4	15	-1	Table	Table for data requests
tool_monitor_events	0	3	8	-1	Table	A table that keeps a log of events related to subscriptions
tool_monitor_history	0	2	4	-1	Table	Table to store history of message notifications sent

Table / View	Children	Parents	Columns	Rows	Type	Comments
tool_monitor_rules	1	2	14	-1	Table	Table to store rules
tool_monitor_subscriptions	1	3	8	-1	Table	Table to store user subscriptions to various rules
tool_policy	1	1	3	-1	Table	Contains the list of policy documents defined on the site.
tool_policy_acceptances	0	3	9	-1	Table	Tracks users accepting the policy versions
tool_policy_versions	2	2	16	-1	Table	Holds versions of the policy documents
tool_recyclebin_category	0	1	5	-1	Table	A list of items in the category recycle bin
tool_recyclebin_course	0	1	6	-1	Table	A list of items in the course recycle bin
tool_usertours_steps	0	1	8	-1	Table	Steps in an tour
tool_usertours_tours	1	0	7	-1	Table	List of tours
upgrade_log	0	1	10	-1	Table	Upgrade logging
url	0	0	10	-1	Table	each record is one url resource
user	185	0	54	-1	Table	One record for each person
user_devices	0	1	11	-1	Table	This table stores user's mobile devices information in order to send PUSH notifications
user_enrolments	0	3	9	-1	Table	Users participating in courses (aka enrolled users) - everybody who is participating/ visible in course, that means both teachers and students
user_info_category	1	0	3	-1	Table	Customisable fields categories
user_info_data	0	2	5	-1	Table	Data for the customisable user fields
user_info_field	1	1	20	-1	Table	Customisable user profile fields
user_lastaccess	0	2	4	-1	Table	To keep track of course page access times, used in online participants block, and participants list
user_password_history	0	1	4	-1	Table	A rotating log of hashes of previously used passwords for each user.
user_password_resets	0	1	5	-1	Table	table tracking password reset confirmation tokens
user_preferences	0	1	4	-1	Table	Allows modules to store arbitrary user preferences
user_private_key	0	1	8	-1	Table	access keys used in cookieless scripts - rss, etc.
wiki	1	0	13	-1	Table	Stores Wiki activity configuration
wiki_links	0	2	5	-1	Table	Page wiki links
wiki_locks	0	2	5	-1	Table	Manages page locks
wiki_pages	2	2	10	-1	Table	Stores wiki pages
wiki_subwikis	2	2	4	-1	Table	Stores subwiki instances
wiki_synonyms	0	1	4	-1	Table	Stores wiki pages synonyms
wiki_versions	0	2	7	-1	Table	Stores wiki page history
workshop	10	1	37	-1	Table	This table keeps information about the module instances and their settings

Table / View	Children	Parents	Columns	Rows	Type	Comments
workshop_aggregations	0	2	5	-1	Table	Aggregated grades for assessment are stored here. The aggregated grade for submission is stored in workshop_submissions
workshop_assessments	1	3	15	-1	Table	Info about the made assessment and automatically calculated grade for it. The proposed grade can be overridden by teacher.
workshop_grades	0	1	7	-1	Table	How the reviewers filled-up the grading forms, given grades and comments
workshop_submissions	1	3	19	-1	Table	Info about the submission and the aggregation of the grade for submission, grade for assessment and final grade. Both grade for submission and grade for assessment can be overridden by teacher. Final grade is always the sum of them. All grades are stored as of 0-100.
workshopallocation_scheduled	0	1	9	-1	Table	Stores the allocation settings for the scheduled allocator
workshopeval_best_settings	0	1	3	-1	Table	Settings for the grading evaluation subplugin Comparison with the best assessment.
workshopform_accumulative	0	1	7	-1	Table	The assessment dimensions definitions of Accumulative grading strategy forms
workshopform_comments	0	1	5	-1	Table	The assessment dimensions definitions of Comments strategy forms
workshopform_numerrors	0	1	9	-1	Table	The assessment dimensions definitions of Number of errors grading strategy forms
workshopform_numerrors_map	0	1	4	-1	Table	This maps the number of errors to a percentual grade for submission
workshopform_rubric	1	1	5	-1	Table	The assessment dimensions definitions of Rubric grading strategy forms
workshopform_rubric_config	0	1	3	-1	Table	Configuration table for the Rubric grading strategy
workshopform_rubric_levels	0	1	5	-1	Table	The definition of rubric rating scales