

Date Submitted: 11/11/2019**Task 01:**Youtube Link: https://www.youtube.com/watch?v=d_Cy3cZYUo0**Modified Schematic (if applicable):** N/A**Modified Code:**

```
//-----
// BIOS header files
//-----
#include <xdc/std.h>           //mandatory - have to include first, for BIOS types
#include <ti/sysbios/BIOS.h>   //mandatory - if you call APIs like BIOS_start()
#include <xdc/runtime/Log.h>    //needed for any Log_info() call
#include <xdc/cfg/global.h>     //header file for statically defined objects/handles

//-----
// TivaWare Header Files
//-----
#include <stdint.h>
#include <stdbool.h>

#include "inc/hw_types.h"
#include "inc/hw_memmap.h"
#include "driverlib/sysctl.h"
#include "driverlib/gpio.h"
#include "inc/hw_ints.h"
#include "driverlib/interrupt.h"
#include "driverlib/timer.h"

//-----
// Prototypes
//-----
void hardware_init(void);
void ledToggle(void);

//-----
// Globals
//-----
volatile int16_t i16ToggleCount = 0;

//-----
// main()
//-----
void main(void)
```

```

{
    hardware_init();                // init hardware via Xware

    BIOS_start();
}

//-----
// hardware_init()
//
// inits GPIO pins for toggling the LED
//-----
void hardware_init(void)
{
    uint32_t ui32Period;

    //Set CPU Clock to 40MHz. 400MHz PLL/2 = 200 DIV 5 = 40MHz
    SysCtlClockSet(SYSCTL_SYSDIV_5|SYSCTL_USE_PLL|SYSCTL_XTAL_16MHZ|SYSCTL_OSC_MAI
N);

    // ADD Tiva-C GPIO setup - enables port, sets pins 1-3 (RGB) pins for output
    SysCtlPeripheralEnable(SYSCTL_PERIPH_GPIOF);
    GPIOPinTypeGPIOOutput(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3);

    // Turn on the LED
    GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, 4);

    // Timer 2 setup code
    SysCtlPeripheralEnable(SYSCTL_PERIPH_TIMER2);                // enable Timer 2
    periph clks
    TimerConfigure(TIMER2_BASE, TIMER_CFG_PERIODIC);                // cfg Timer 2 mode
- periodic

    ui32Period = (SysCtlClockGet() /2);                            //
period = CPU clk div 2 (500ms)
    TimerLoadSet(TIMER2_BASE, TIMER_A, ui32Period);                // set Timer
2 period

    TimerIntEnable(TIMER2_BASE, TIMER_TIMA_TIMEOUT);                // enables Timer 2
to interrupt CPU

    TimerEnable(TIMER2_BASE, TIMER_A);                            //
enable Timer 2
}

//-----
// ledToggle()
//
// toggles LED on Tiva-C LaunchPad
//-----
void ledToggle(void)

```

```
{
    TimerIntClear(TIMER2_BASE, TIMER_TIMA_TIMEOUT);           // must clear timer
    flag FROM timer

    // LED values - 2=RED, 4=BLUE, 8=GREEN
    if(GPIOPinRead(GPIO_PORTF_BASE, GPIO_PIN_2))
    {
        GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, 0);
    }
    else
    {
        GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_2, 4);
    }

    i16ToggleCount += 1;
    // keep track of #toggles

    Log_info1("LED TOGGLED [%u] TIMES", i16ToggleCount);       // send toggle
    count to UIA
}
```

Task 02:

Youtube Link:

Modified Schematic (if applicable): N/A

Modified Code:
