

**Date Submitted:** 11/18/2019**Task 01:**Youtube Link: <https://www.youtube.com/watch?v=d0STdqgm4dk>

Modified Schematic (if applicable): N/A

**Modified Code:**

```

/* TI-RTOS Header files */
#include <xdc/std.h>
#include <ti/sysbios/BIOS.h>
#include <ti/sysbios/knl/Task.h>
#include <ti/drivers/GPIO.h>
/* Example/Board Header files */
#include "Board.h"
void myDelay(int count);
/* Could be anything, like computing primes */
#define FakeBlockingSlowWork() myDelay(12000000)
#define FakeBlockingFastWork() myDelay(2000000)
Task_Struct workTask;
/* Make sure we have nice 8-byte alignment on the stack to avoid wasting memory */
#pragma DATA_ALIGN(workTaskStack, 8)
#define STACKSIZE 1024
static uint8_t workTaskStack[STACKSIZE];

void doUrgentWork(void)
{
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_OFF);
    FakeBlockingFastWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_ON);
}

void doWork(void)
{
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_OFF);
    FakeBlockingSlowWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_ON);
}

Void workTaskFunc(UArg arg0, UArg arg1)
{
    while (1)
    {
        /* Do work */
        doWork();
        /* Wait a while, because doWork should be a periodic thing, not continuous.*/
        myDelay(24000000);
    }
}

```

**Grading scheme:** 30% Coding, 30% Documentation, 40% Execution/Video.

```

/*
* ===== main =====
*
*/
int main(void)
{
    Board_initGeneral();
    GPIO_init();
    /* Set up the led task */
    Task_Params workTaskParams;
    Task_Params_init(&workTaskParams);
    workTaskParams.stackSize = STACKSIZE;
    workTaskParams.priority = 2;
    workTaskParams.stack = &workTaskStack;
    Task_construct(&workTask, workTaskFunc, &workTaskParams, NULL);
    /* Start kernel. */
    BIOS_start();
    return (0);
}
/*
* ===== myDelay =====
* Assembly function to delay. Decrements the count until it is zero
* The exact duration depends on the processor speed.
*/
__asm(".sect \".text:myDelay\"\n"
".clink\n"
".thumbfunc myDelay\n"
".thumb\n"
".global myDelay\n"
"myDelay:\n"
" subs r0, #1\n"
" bne.n myDelay\n"
" bx lr\n");

```

---

**Task 02:**

Youtube Link: N/A same as task 1

Modified Schematic (if applicable): N/A

**Modified Code:**

```

/* TI-RTOS Header files */
#include <xdc/std.h>
#include <ti/sysbios/BIOS.h>
#include <ti/sysbios/knl/Task.h>
#include <ti/drivers/GPIO.h>
/* Example/Board Header files */
#include "Board.h"
void myDelay(int count);
/* Could be anything, like computing primes */
#define FakeBlockingSlowWork() myDelay(12000000)
#define FakeBlockingFastWork() myDelay(2000000)
Task_Struct workTask;
/* Make sure we have nice 8-byte alignment on the stack to avoid wasting memory */
#pragma DATA_ALIGN(workTaskStack, 8)
#define STACKSIZE 1024
static uint8_t workTaskStack[STACKSIZE];

void doUrgentWork(void)
{
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_OFF);
    FakeBlockingFastWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_ON);
}

void doWork(void)
{
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_OFF);
    FakeBlockingSlowWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_ON);
}

Void workTaskFunc(UArg arg0, UArg arg1)
{
    while (1)
    {
        /* Do work */
        doWork();
        /* Wait a while, because doWork should be a periodic thing, not continuous.*/
        myDelay(24000000);
    }
}
/*
 * ===== main =====
 */

```

```

*/
int main(void)
{
    Board_initGeneral();
    GPIO_init();
    /* Set up the led task */
    Task_Params workTaskParams;
    Task_Params_init(&workTaskParams);
    workTaskParams.stackSize = STACKSIZE;
    workTaskParams.priority = 2;
    workTaskParams.stack = &workTaskStack;
    Task_construct(&workTask, workTaskFunc, &workTaskParams, NULL);
    /* Start kernel. */
    BIOS_start();
    return (0);
}
/*
 * ===== myDelay =====
 * Assembly function to delay. Decrements the count until it is zero
 * The exact duration depends on the processor speed.
 */
__asm(" .sect \".text:myDelay\"\n"
      ".clink\n"
      ".thumbfunc myDelay\n"
      ".thumb\n"
      ".global myDelay\n"
      "myDelay:\n"
      " subs r0, #1\n"
      " bne.n myDelay\n"
      " bx lr\n");

```

---

### Task 03:

Youtube Link: N/A same as task 1

Modified Schematic (if applicable): N/A

#### Modified Code:

```

/* TI-RTOS Header files */
#include <xdc/std.h>
#include <ti/sysbios/BIOS.h>
#include <ti/sysbios/knl/Task.h>
#include <ti/drivers/GPIO.h>
#include <ti/sysbios/knl/Clock.h>
/* Example/Board Header files */
#include "Board.h"
void myDelay(int count);
/* Could be anything, like computing primes */
#define FakeBlockingSlowWork() myDelay(12000000)
#define FakeBlockingFastWork() myDelay(2000000)
Task_Struct workTask;

```

```

/* Make sure we have nice 8-byte alignment on the stack to avoid wasting memory */
#pragma DATA_ALIGN(workTaskStack, 8)
#define STACKSIZE 1024
static uint8_t workTaskStack[STACKSIZE];

void doUrgentWork(void)
{
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_OFF);
    FakeBlockingFastWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_ON);
}

void doWork(void)
{
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_OFF);
    FakeBlockingSlowWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_ON);
}

Void workTaskFunc(UArg arg0, UArg arg1)
{
    int numTicks = Clock_tickPeriod;
    while (1)
    {
        /* Do work */
        doWork();
        /* Wait a while, because doWork should be a periodic thing, not continuous.*/
        //myDelay(24000000);
        Task_sleep(numTicks*50);
    }
}

/*
 * ===== main =====
 */
int main(void)
{
    Board_initGeneral();
    GPIO_init();
    /* Set up the led task */
    Task_Params workTaskParams;
    Task_Params_init(&workTaskParams);
    workTaskParams.stackSize = STACKSIZE;
    workTaskParams.priority = 2;
    workTaskParams.stack = &workTaskStack;
    Task_construct(&workTask, workTaskFunc, &workTaskParams, NULL);
    /* Start kernel. */
    BIOS_start();
    return (0);
}

/*
 * ===== myDelay =====
 * Assembly function to delay. Decrements the count until it is zero
 * The exact duration depends on the processor speed.
 */

```

```
__asm(" .sect \".text:myDelay\"\n"
".clink\n"
".thumbfunc myDelay\n"
".thumb\n"
".global myDelay\n"
"myDelay:\n"
" subs r0, #1\n"
" bne.n myDelay\n"
" bx lr\n");
```

---

### Task 04:

Youtube Link: <https://www.youtube.com/watch?v=cpQ5woVzQTU>

Modified Schematic (if applicable): N/A

#### Modified Code:

```
/* TI-RTOS Header files */
#include <xdc/std.h>
#include <ti/sysbios/BIOS.h>
#include <ti/sysbios/knl/Task.h>
#include <ti/drivers/GPIO.h>
#include <ti/sysbios/knl/Clock.h>
/* Example/Board Header files */
#include "Board.h"

void myDelay(int count);
/* Could be anything, like computing primes */
#define FakeBlockingSlowWork() myDelay(12000000)
#define FakeBlockingFastWork() myDelay(2000000)

Task_Struct workTask;
Task_Struct urgentWorkTask;
/* Make sure we have nice 8-byte alignment on the stack to avoid wasting memory */
#pragma DATA_ALIGN(workTaskStack, 8)
#define STACKSIZE 1024
static uint8_t workTaskStack[STACKSIZE];
static uint8_t urgentWorkTaskStack[STACKSIZE];

void doUrgentWork(void)
{
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_OFF);
    FakeBlockingFastWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED1, Board_GPIO_LED_ON);
}

void doWork(void)
{
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_OFF);
    FakeBlockingSlowWork(); /* Pretend to do something useful but time-consuming */
    GPIO_write(Board_GPIO_LED0, Board_GPIO_LED_ON);
}

Void workTaskFunc(UArg arg0, UArg arg1)
{
    //int numTicks = Clock_tickPeriod;
```

```

while (1)
{
    /* Do work */
    doWork();
    /* Wait a while, because doWork should be a periodic thing, not continuous.*/
    //myDelay(24000000);
    Task_sleep(500*(1000 / Clock_tickPeriod));
}
}

Void urgentWorkTaskFunc(UArg arg0, UArg arg1)
{
    //int numTicks = Clock_tickPeriod;
    while (1)
    {
        /* Do work */
        doUrgentWork();
        /* Wait a while, because doWork should be a periodic thing, not continuous.*/
        //myDelay(24000000);
        Task_sleep(50*(1000 / Clock_tickPeriod));
    }
}
/*
* ===== main =====
*
*/
int main(void)
{
    Board_initGeneral();
    GPIO_init();
    /* Set up the led task */
    Task_Params workTaskParams;
    Task_Params_init(&workTaskParams);
    workTaskParams.stackSize = STACKSIZE;
    workTaskParams.priority = 2;
    workTaskParams.stack = &workTaskStack;
    Task_construct(&workTask, workTaskFunc, &workTaskParams, NULL);

    workTaskParams.priority = 3;
    workTaskParams.stack = &urgentWorkTaskStack;
    Task_construct(&urgentWorkTask, urgentWorkTaskFunc, &workTaskParams, NULL);
    /* Start kernel. */
    BIOS_start();
    return (0);
}
__asm( ".sect \".text:myDelay\"\n"
".clink\n"
".thumbfunc myDelay\n"
".thumb\n"
".global myDelay\n"
"myDelay:\n"
" subs r0, #1\n"
" bne.n myDelay\n"
" bx lr\n");

```

---