

Functions

- void init_comhand(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Will initiate the command handler function. Calls sys_req(READ) to get buffer user input from polling, executing code based on what the buffer reads.
- void comhand_version(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Will print the current project version to the user.
- void comhand_shutdown(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Will prompt the user for shutdown. If the user inputs 'yes', the system will initiate the shutdown procedure.
- void comhand_help(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Will print all currently implemented help files. Shows the user *all* commands the OS can run.
- void comhand_rtc(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Will print and display the current time of the real time clock to the user.
- void comhand_setTime(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Will prompt the user for input, asking them to enter a formatted (HH:MM:SS) text input that shows the
- getTime()
 - **Parameters:** N/A
 - **Returns:** char*
 - **Description:** will get time from ports, convert from BCD to decimal, and return as a char*

- getDate()
 - Parameters: N/A
 - Returns: char*
 - Description: gets the date from ports, converts it from bcd to int to char* and formats in it MM/DD/YY format
- int serial_poll(device dev, char* buffer, size_t len)
 - **Parameters:** device dev: the device to be read from. char* buffer: user-provided buffer. size_t len: the size of the buffer.
 - **Returns:** int the number of bytes read from the device, or a negative number on error
 - **Description:** Data is read one character at a time from the device's base register (same address as the device) using the inb() macro. When data is available, the least significant bit in the Line Status Register (device + LSR) is set
- setTime(char* newTime)
 - **Parameters:** char* newTime (containing new time to write)
 - **Returns:** N/A
 - **Description:** Takes parameter of char* and writes to the ports to set the new time
- setDate(char* newDate)
 - **Parameters:** char* newDate, the new date in MM/DD/YY format
 - **Returns:** N/A
 - **Description:** takes the date contained in newDate and writes to ports
- formatTime(int timeToFormat, char* stringPtr)
 - **Parameters:** int timeToFormat containing the time as an int read from the port. char* stringPtr as the pointer to the string to output the string to
 - **Returns:** N/A
 - **Description:** A helper function to getTime() that will take the output the int value from the ports and the pointer to the string to output, and will correctly format the time so that it shows up as ##.

- `char* toupper(char* string)`
 - **Parameters:** `char* string` (string to convert to uppercase)
 - **Returns:** New string, with each alphabetical character being uppercase.
 - **Description:** This function will turn whatever string is set as a parameter into an uppercase version of the same string. Returns a new string in memory that is fully uppercase.
- `int isdigit(int c)`
 - **Parameters:** `int c`, the character to check
 - **Returns:** 1 if `c` is a digit, 0 otherwise
 - **Description:** checks if `c` is a numeric ASCII character
- `char* itoa(int i, char* dest)`
 - **Parameters:** `int i`: the number to convert to ASCII, `char* dest`: location to store the resulting `char*` in
 - **Returns:** ASCII representation of `i`
 - **Description:** converts an integer to ASCII and stores the result in the memory address specified, as well as returning a reference to it.
- `char* formatCore(char* format, ...)`
 - **Parameters:** `char* format`: string containing the desired string with placeholders for the rest of the arguments. `Va_list`: a variable length list of any elements that are to be inserted into the string.
 - **Returns:** the resulting string.
 - **Description:** takes the format string and replaces the placeholders with the specified elements
 - Use `%s` to insert a `char*`
 - Use `%c` to insert a `char`
 - Use `%d` or `%i` to insert an integer
 - Use `%f` to insert a float
 - Use `%x` to display an integer in hexadecimal
 - Use `%o` to display an integer in octal
 - Place a number between the `%` and the specified data type to specify the length of the string that is placed in the spot of the placeholder, if the padding size is shorter than the length of the string, the original length will be preserved. If a `'.'` is placed before the padding number, it will be padded with zeros as necessary.

- For floats, the number after a decimal point determines the precision of the display, if this is not specified the precision is 6.

- `Int sprintf(char* dest, char* format, ...)`
 - **Parameters:** `dest`: `char*` to store the result in. `format`: string containing placeholder for values, see `formatCore` for more details. `va_list`: a variable argument list of the elements to be inserted.
 - **Returns:** the length of the resulting string.
 - **Description:** wrapper that takes the result of `formatCore` and stores it in a `char*`. See `formatCore` description
- `Void printf(char* format, ...)`
 - **Parameters:** `format`: string containing placeholder for values, see `formatCore` for more details. `va_list`: a variable argument list of the elements to be inserted.
 - **Returns:** N/A
 - **Description:** wrapper that takes the result of `formatCore` and prints it to the console. See `formatCore` description for formatting details.
- `Void puts(char* buf)`
 - **Parameters:** `char* buf`: a string.
 - **Returns:** N/A
 - **Description:** Prints the `buf` to the console.
- `Void comhand_pcbCreate(void)`
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Assists the user in creating a new PCB with specific parameters.
- `Void comhand_pcbDelete(void)`
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Assists the user in deleting a specific PCB.
- `Void comhand_pcbBlock(void)`
 - **Parameters:** N/A
 - **Returns:** N/A

- **Description:** Assists the user in changing a specific PCB to the [BLOCKED] state
- Void comhand_pcbUnblock(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Assists the user in changing a specific PCB to the [READY] state
- Void comhand_pcbSuspend(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Assists the user in changing a specific PCB to the [SUSPENDED] state
- Void comhand_pcbResume(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Assists the user in changing a specific PCB to the [NOT SUSPENDED] state
- Void comhand_pcbPriority(void)
 - **Parameters:** N/A
 - **Returns:** N/A
 - **Description:** Assists the user in changing a specific PCB's priority.
- Void comhand_pcbShow(int entry)
 - **Parameters:** int entry : Tells the function which type of show to perform.
 - **Returns:** N/A
 - **Description:** Shows either a specific PCB, all ready PCBs, all blocked PCBs, or all PCBs.
- Void comhand_pcbShowHelper(pcb* target)
 - **Parameters:** pcb* target the pcb to display
 - **Returns:** N/A
 - **Description:** Assists the comhand_pcbShow function in the print statements of PCBs.
- Void comhand_pcbprintPcbList(list* li)
 - **Parameters:** list* li the list to print
 - **Returns:** N/A
 - **Description:** iterates through the given pcb list, displaying them with comhand_pcbShowHelper

- list* getList(int entry)
 - **Parameters:** int entry : Specifies which list to return.
 - **Returns:** the user-specified list
 - **Description:** Returns a list specified by the int entry parameter.
- pcb* pcb_allocate(void)
 - **Parameters:** N/A
 - **Returns:** a pcb* to a new pointer, or NULL on error;
 - **Description:** allocates memory for a pcb and initialized the name char*, stack, and stackPtr
- int pcb_free(pcb* target)
 - **Parameters:** pcb* target the pcb* to free
 - **Returns:** 0 on success, non-zero on error
 - **Description:** frees the memory associated to the target pcb
- pcb* pcb_setup(const char* name, int class, int priority)
 - **Parameters:** const char* name the name for the new pcb
 - Int class USER or SYSTEM
 - Int priority the priority level of the new PCB, 0-9 from highest to lowest priority
 - **Returns:** the created PCB
 - **Description:** allocates a PCB with pcb_allocate and initializes it with the given values
- pcb* pcb_find(const char* name)
 - **Parameters:** const char* name, the name of the pcb to search for
 - **Returns:** the specified pcb, or NULL if not found
 - **Description:** searches through each list of Pcb's to locate a pcb with the specified name
- void pcb_insert(pcb* newPCB)
 - **Parameters:** pcb* newPCB the pcb to add to the queue
 - **Returns:** N/A
 - **Description:** adds the given PCB to its proper queue
- int pcb_remove(pcb* target)
 - **Parameters:** pcb* target the pcb to remove
 - **Returns:** 0 on success, non-zero on error
 - **Description:** removes the given pcb from its' queue without freeing associated memory
- int pcb_createcheck(char* procName)
 - **Parameters:** char* name for a new Pcb

- **Returns:** a negative number if name is taken, 1 if the name is available
- **Description:** searches for an existing PCB with the given name
- list* createList(void)
 - **Parameters:** N/A
 - **Returns:** list* pointer to new list
 - **Description:** creates and allocated memory for the linked list, and returns pointer
- node* createNode(void* data)
 - **Parameters:** void* data pointer for data to store in node
 - **Returns:** node pointer to node created
 - **Description:** creates and allocated memory for node and stores void pointer in parameter to data, and returns pointer to created node
- node* get(list* listPtr, int index)
 - **Parameters:** list* listPtr which is the pointer to the list, int index which is the index within the list
 - **Returns:** node pointer at index in list, NULL if DNE
 - **Description:** takes pointer to list and index as an int and will return the node pointer of node at index, or NULL if node DNE at index
- node* getHead(list* listPtr)
 - **Parameters:** list* listPtr pointer to list
 - **Returns:** node pointer of head of list
 - **Description:** returns node pointer of head of linked list within parameter
- node* add(list* listPtr, node* nodePtr)
 - **Parameters:** list* listPtr which is the pointer to list, node* nodePtr which is the pointer to the node to add
 - **Returns:** node pointer that was added to the list
 - **Description:** takes node pointer and adds to list in parameter and returns pointer to added node
- node* addToHead(list* listPtr, node* nodePtr)
 - **Parameters:** list* listPtr which is the pointer to the list, node* nodePtr which is the pointer to the node to add
 - **Returns:** node pointer that was added to the head of the list
 - **Description:** adds node pointer to the head of the list in the parameter and returns the pointer to the node added
- node* remove(list* listPtr, node* nodePtr)

- **Parameters:** list* listPtr which is the pointer to the list, node* nodePtr which is the node to remove from the list
- **Returns:** node pointer of node removed from the list
- **Description:** finds and removes node from the list in the parameter, and returns the removed node
- node* removeHead(list* listPtr)
 - **Parameters:** list* listPtr which is the pointer to the list
 - **Returns:** node pointer of removed head from the list
 - **Description:** removes head of list in parameter, sets head to the next node in the list, and returns pointer to removed node
- int contains(list* listPtr, node* nodePtr)
 - **Parameters:** list* listPtr which is the pointer to the list, node* nodePtr which is the pointer to the node to find
 - **Returns:** int which is the nodes location in the list (headPtr == 0), of -1 if node DNE in list
 - **Description:** Finds location of node in list found in parameter, and returns int index of node, or -1 if node DNE in list
- void* getData(node*)
 - **Parameters:** node pointer
 - **Returns:** void pointer to data in node
 - **Description:** gets and returns the void pointer (data) within the node pointer

New data types

- Pcb : struct
 - char* name: name for the pcb
 - Int class: USER or SYSTEM
 - Int priority: priority value from 0-9, 0 being the highest priority
 - Int executionState: READY, RUNNING, or BLOCKED
 - Int dispatchingState: SUSPENDED or NOT_SUSPENDED
 - Char[] stack: 1024 byte array
 - char*stackPtr: pointer to the last few bytes of the stack
- list : struct
 - node * headPtr: pointer to the head node of the list
- node : struct
 - node* prevPtr: pointer to the previous node in the list
 - node* nextPtr: pointer to the next node in the list

- `void* data`: void pointer to the data stored in the node