



502070

WEB APPLICATION DEVELOPMENT USING NODEJS

LESSON 02 – EXPRESSJS

OUTLINE

1. Initial Steps
2. Views and Layouts
3. Static Files and Views
4. Dynamic Content in Views
5. Examples

OUTLINE

1. Initial Steps
2. Views and Layouts
3. Static Files and Views
4. Dynamic Content in Views
5. Examples

RECALL

```
var http = require('http');
var url = require('url');
var fs = require('fs');

http.createServer(function (req, res) {
  var q = url.parse(req.url, true);
  var filename = "." + q.pathname;
  fs.readFile(filename, function(err, data) {
    if (err) {
      res.writeHead(404, {'Content-Type': 'text/html'});
      return res.end("404 Not Found");
    }
    res.writeHead(200, {'Content-Type': 'text/html'});
    res.write(data);
    return res.end();
  });
}).listen(8080);
```

ExpressJS - Initial Steps

- Start by creating a new directory
- npm manages project dependencies—as well as metadata about the project—in a file called package.json
- The easiest way to create this file is to run **npm init**
- The first step will be installing Express. Run the following npm command:

```
npm install express
```

ExpressJS - Initial Steps

- Now create the *app.js* file:

```
const express = require('express')
const app = express()
const port = 3000
// custom 404 page
app.use((req, res) => {
  res.type('text/plain')
  res.status(404)
  res.send('404 - Not Found')
})
```

ExpressJS - Initial Steps

```
// custom 500 page  
app.use((err, req, res, next) => {  
  console.error(err.message)  
  res.type('text/plain')  
  res.status(500)  
  res.send('500 - Server Error')  
})  
  
app.listen(port, () => console.log(  
  'Express started on http://localhost:${port}; ' +  
  'press Ctrl-C to terminate. '))
```

ExpressJS - Initial Steps

- Let's add some routes for the home page and an About page.

```
app.get('/', (req, res) => {  
  res.type('text/plain')  
  res.send('Web Travel');  
})  
  
app.get('/about', (req, res) => {  
  res.type('text/plain')  
  res.send('About Web Travel')  
})
```


OUTLINE

1. Initial Steps
2. Views and Layouts
3. Static Files and Views
4. Dynamic Content in Views
5. Examples

ExpressJS – Views and Layouts

- Essentially, a view is what gets delivered to the user. In the case of a website, that usually means HTML.
- A view differs from a static resource (like an image or CSS file) in that a view doesn't necessarily have to be static.
- Express supports many different view engines that provide different levels of abstraction.
- In this course we will use **Handlebars**.

ExpressJS – Views and Layouts

- To provide Handlebars support, we'll use Eric Ferraiuolo's express-handlebars package:

```
npm install express-handlebars
```

ExpressJS – Views and Layouts

- Then in our *app.js* file, modify the first few lines:

```
const express = require('express')
const hbs = require('express-handlebars')
const app = express()
// configure Handlebars view engine
app.engine('handlebars', hbs.engine({
  defaultLayout: 'main',
}))
app.set('view engine', 'handlebars')
```

ExpressJS – Views and Layouts

- Now create a directory called *views* that has a subdirectory called *layouts*.
- Let's create a layout for our site. Create a file called *views/layouts/main.handlebars*:

```
<!doctype html>
<html>
<head>
<title>Web Travel</title>
</head>
<body>
{{{body}}}
</body>
</html>
```

ExpressJS – Views and Layouts

- Now let's create view pages for our home page, *views/home.handlebars*:

```
<h1>Welcome to Web Travel</h1>
```

- Then our About page, *views/about.handlebars*:

```
<h1>About Web Travel</h1>
```

- Then our Not Found page, *views/404.handlebars*:

```
<h1>404 - Not Found</h1>
```

- And finally our Server Error page, *views/500.handlebars*:

```
<h1>500 - Server Error</h1>
```

ExpressJS – Views and Layouts

- Now that we have some views set up, we have to replace our old routes with new ones that use these views:

```
app.get('/', (req, res) => res.render('home'))
app.get('/about', (req, res) => res.render('about'))
// custom 404 page
app.use((req, res) => {
  res.status(404)
  res.render('404')
})
// custom 500 page
app.use((err, req, res, next) => {
  console.error(err.message)
  res.status(500)
  res.render('500')
})
```

OUTLINE

1. Initial Steps
2. Views and Layouts
3. Static Files and Views
4. Dynamic Content in Views
5. Examples

ExpressJS – Static Files and Views

- Express relies on *middleware* to handle static files and views.
- *Middleware* is a concept that will be covered in more detail later.
- The *static* middleware allows you to designate one or more directories as containing static resources that are simply to be delivered to the client without any special handling.
- This is where you would put things such as images, CSS files, and client-side JavaScript files.

ExpressJS – Static Files and Views

- In your project directory, create a subdirectory called *public*.
- Then, in *app.js* before you declare any routes, you'll add the static middleware:

```
app.use(express.static(__dirname + '/public'))
```

- The static middleware has the same effect as creating a route for each static file you want to deliver that renders a file and returns it to the client.
- So let's create an *img* subdirectory inside *public* and put our *logo.png* file in there.

ExpressJS – Static Files and Views

- Now we can simply reference `/img/logo.png` (note, we do not specify *public*; that directory is invisible to the client), and the *static* middleware will serve that file.
- Now let's modify our layout so that our logo appears on every page:

```
<body>
```

```
<header>
```

```

```

```
</header>
```

```
{{{body}}}
```

```
</body>
```

- Remember that middleware is processed in order, and static middleware—which is usually declared first or at least very early—will override other routes.

OUTLINE

1. Initial Steps
2. Views and Layouts
3. Static Files and Views
4. Dynamic Content in Views
5. Examples

ExpressJS – Dynamic Content in Views

- The real power of views is that they can contain dynamic information.
- Let's say that on the About page, we want to deliver a “virtual fortune cookie.”
- In our *app.js* file, we define an array of fortune cookies:

```
const fortunes = [  
  "Conquer your fears or they will conquer you.",  
  "Rivers need springs.",  
  "Do not fear what you don't know.",  
  "You will have a pleasant surprise.",  
  "Whenever possible, keep it simple.",  
]
```

ExpressJS – Dynamic Content in Views

- Modify the view (*/views/about.handlebars*) to display a fortune:

```
<h1>About Web Travel</h1>
```

```
{{#if fortune}}
```

```
<p>Your fortune for the day:</p>
```

```
<blockquote>{{fortune}}</blockquote>
```

```
{{/if}}
```

ExpressJS – Dynamic Content in Views

- Now modify the route /about to deliver the random fortune cookie:

```
app.get('/about', (req, res) => {  
    const randomFortune =  
    fortunes[Math.floor(Math.random() * fortunes.length)]  
    res.render('about', { fortune: randomFortune })  
})
```

Exercises

- Create route to show a table n rows and m columns, each cell contains value of $i+j$, where i is row, j is column. (Note: n, m is set in code)

Helpers in view

Loop in view

```
<ul class="people_list">
  {{#each people}}
    <li>{{this}}</li>
  {{/each}}
</ul>
```

Example input

```
{ people: [ "Yehuda Katz", "Alan Johnson", "Charles
Jolley", ]}
```

else section which will display only when the list is empty.

```
{{#each paragraphs}}
<p>{{this}}</p>
{{else}} <p class="empty">No content</p>
{{/each}}
```

Helpers in view

Access properties with #with

```
{{#with person}}  
{{firstname}} {{lastname}}  
{{/with}}
```

Example input:

```
{ person: { firstname: "Yehuda", lastname: "Katz", } }
```

Define references

```
{{#with city as | city |}}  
  {{#with city.location as | loc |}}  
    {{city.name}} {{loc.north}} {{loc.east}}  
  {{/with}}  
{{/with}}
```

Exercises

- Create route to show a table n rows and m columns, each cell contains value of $i+j$, where i is row, j is column. (Note: n, m is set in code; generate HTML in template)

Get data in request

- **Express 4.0 to 4.15**

```
var bodyParser = require('body-parser')
app.use( bodyParser.json() ); // to support JSON-encoded bodies
app.use(bodyParser.urlencoded({ // to support URL-encoded bodies
  extended: true }));
```

- **Express 4.16+**

```
app.use(express.json()); // to support JSON-encoded bodies
app.use(express.urlencoded()); // to support URL-encoded bodies
```

OUTLINE

1. Initial Steps
2. Views and Layouts
3. Static Files and Views
4. Dynamic Content in Views
5. Examples

ExpressJS – Examples

- Example 1. Basic usage

```
// basic usage  
app.get('/about', (req, res) => {  
    res.render('about')  
})
```

- Example 2. Response codes other than 200

```
app.get('/error', (req, res) => {  
    res.status(500)  
    res.render('error')  
})  
  
// or on one line...  
app.get('/error', (req, res) => res.status(500).render('error'))
```

ExpressJS – Examples

- Example 3. Passing a context to a view

```
app.get('/greeting', (req, res) => {  
  res.render('greeting', {  
    message: 'Hello esteemed programmer!',  
    cookies: req.cookies  
  })  
})
```

- Example 4. Rendering a view without a layout

```
// the following layout doesn't have a layout file, so  
// views/no-layout.handlebars must include all necessary HTML  
app.get('/no-layout', (req, res) =>  
  res.render('no-layout', { layout: null })  
)
```

ExpressJS – Examples

- Example 5. Rendering a view with a custom layout

```
// the layout file views/layouts/custom.handlebars will be used  
app.get('/custom-layout', (req, res) =>  
    res.render('custom-layout', { layout: 'custom' })  
)
```

- Example 6. Rendering plain text output

```
app.get('/text', (req, res) => {  
    res.type('text/plain')  
    res.send('this is a test')  
})
```


ExpressJS – Examples

- Example 7. Adding an error handler

```
// this should appear AFTER all of your routes
// note that even if you don't need the "next" function, it must be
// included for Express to recognize this as an error handler
app.use((err, req, res, next) => {
  console.error('** SERVER ERROR: ' + err.message)
  res.status(500).render('08-error', { message: "you shouldn't have clicked that!" })
})
```

- Example 8. Adding a 404 handler

```
// this should appear AFTER all of your routes
app.use((req, res) =>
  res.status(404).render('404')
)
```

ExpressJS – Examples

- Example 9. Simple GET endpoint returning only JSON

```
const tours = [  
  { id: 0, name: 'Hood River', price: 99.99 },  
  { id: 1, name: 'Oregon Coast', price: 149.95 },  
]  
  
app.get('/api/tours', (req, res) => res.json(tours))
```

ExpressJS – Examples

- Example 10. GET endpoint that returns JSON, XML, or text

```
app.get('/api/tours', (req, res) => {  
  const toursXml = '<?xml version="1.0"?><tours>' +  
    tours.map(p =>  
      '<tour price="${p.price}" id="${p.id}">${p.name}</tour>'  
    ).join('') + '</tours>'  
  const toursText = tours.map(p =>  
    `${p.id}: ${p.name} (${p.price})`  
  ).join('\n')  
  res.format({  
    'application/json': () => res.json(tours),  
    'application/xml': () => res.type('application/xml').send(toursXml),  
    'text/xml': () => res.type('text/xml').send(toursXml),  
    'text/plain': () => res.type('text/plain').send(toursText),  
  })  
})
```

ExpressJS – Examples

- Example 11. PUT endpoint for updating

```
app.put('/api/tour/:id', (req, res) => {  
    const p = tours.find(p => p.id === parseInt(req.params.id))  
    if(!p) return res.status(404).json({ error: 'No such tour exists' })  
    if(req.body.name) p.name = req.body.name  
    if(req.body.price) p.price = req.body.price  
    res.json({ success: true })  
})
```

ExpressJS – Examples

- Example 12. DELETE endpoint for deleting

```
app.delete('/api/tour/:id', (req, res) => {  
    const idx = tours.findIndex(tour => tour.id === parseInt(req.params.id))  
    if(idx < 0) return res.json({ error: 'No such tour exists.' })  
    tours.splice(idx, 1)  
    res.json({ success: true })  
})
```

Exercises

- Add API allow search tour and add new tour.