



Comment	Description	Designator	Footprint	LibRef	Quantity	Value
CP2102		*1	QFN50P500X500X9 0_HS-29N	CP2102	1	
XTAL		*2	XTAL SMD 4PIN	XTAL	1	
ATAL			DIODE SMA (DO-	ATAL	'	
Diode		*3	214AC)	Diode	1	
L D400/		*4	DPAK228P972X230-			
LD1086	Available in 1.8V,	*4	3N	LD1086	1	
	2.5V, 2.85V, 3.3V,					
	5V, and					
184447	Adjustable	0.0044	0.0.7.000 414	11111111		111017
LM1117	Versions Switch button 4	ASM1	SOT223-4N	LM1117	1	LM317
SW	pin	BTN1, RST1	Tact SW 4 pin	Tact SW - 4Pin	2	Button chip 4 pin
	γ	DITTI, NOT	ruot ott i piii	1400.000 11 111		button omp 1 pm
		C1, C2, C3, C4, C5,				
		C6, C7, C8, C9,				
		C10, C11, C12, C13, C14, C15,				
		C15, C14, C15, C16, C17, C18,				100nF, 10uF,
Cap Non-Pol SMD	Capacitor	C19, C20, C21, C22	CAP-SM-0603	Cap Non-Pol SMD	22	100pF
	Polarized					
Cap Pol SMD	Capacitor (Radial)	C23	CAP ALU SIZE B	Cap Pol SMD	1	100uF
Cap Non-Pol SMD	Capacitor	C24, C25, C26, C27	CAP-SM-0805	Cap Non-Pol SMD	4	100nF, 10uF
		D1, D2, D3, D4,				
LED SMD	LED	D5, D6, D7	LED_0603_Blue	LED SMD	7	
Hole	Hole 3mm	H1, H2, H3, H4	LO KHOAN 3MM	Hole	4	
	Micro USB 2.0					
	Type AB Receptacle WR-					
	COM, Horizontal,					
629105150921	SMT	J1	629105150921	629105150921	1	
Jack DC	Jack DC input	JDC1	DC-IN	Jack DC	1	Jac DC
Header 4	Header, 4-Pin	P1, P3, P4, P6	JP4	Header 4	4	
Header 8	Header, 8-Pin	P2	JP8	Header 8	1	
	Header, 3-Pin,					
Header 3X2	Dual row	P5	JP3x2	Header 3X2	1	
Header 3	Header, 3-Pin	P7, P9	JP3	Header 3	2	
Haadan 4V2	Header, 4-Pin,	D0	ID4::2	Lloodor AVO	_	
Header 4X2	Dual row NPN Bipolar	P8	JP4x2	Header 4X2	1	
C1815	Transistor	Q1, Q2, Q3	SOT23B	C1815	3	
		R1, R2, R3, R4, R5,	<u> </u>			
		R6, R7, R8, R9,				
RESISTOR SMD	Resistor	R10, R11, R12	RES-SM-0603	RESISTOR SMD	12	4.7K, 10K, 1K
STM33E40E		STM1	CQFP50P1150X115 0X160-64N	STM33E40E	1	
STM32F405		311/11	UA 10U-04IN	STM32F405	ı	