

# ACT Series

## 10~200kVA 3-phase Tower UPS

Internal 7/9Ah modular battery strips



### Power range

10~200kVA



### Operation

3P/3P, 3P/1P, 1P/1P, Online double conversion



### Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



### Characteristics

- 7 inch touch LCD with IoT functions.
- High power density, small volume.
- High reliability and environmental adaptability.
- Optional full metal battery strips, with internal batteries

capable of configuring up to 20 pcs battery strips.



Full metal battery strips(Optional)

| Model                |                                     | TT010EB-80P                                                                               | TT020EB-80P | TT030EB-80P | TT040EB-160P  |
|----------------------|-------------------------------------|-------------------------------------------------------------------------------------------|-------------|-------------|---------------|
|                      |                                     | TT010EL                                                                                   | TT020EL     | TT030EL     | TT040EL       |
| Rate Power           |                                     | 10kVA                                                                                     | 20kVA       | 30kVA       | 40kVA         |
| Main input           | Input                               | 3P5W (3P+N+PE)                                                                            |             |             |               |
|                      | Rate Voltage                        | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |             |             |               |
|                      | Rate Freq.                          | 50/60Hz                                                                                   |             |             |               |
|                      | Input PF                            | >0.99                                                                                     |             |             |               |
|                      | Current distortion                  | THDi<2%                                                                                   |             |             |               |
|                      | Voltage range                       | 304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%              |             |             |               |
|                      | Freq. range                         | 40-70Hz                                                                                   |             |             |               |
| Battery              | Rate voltage                        | ±120VDC                                                                                   | ±240VDC     |             |               |
|                      | Model                               | UPS with internal batteries,12VDC/7~9Ah                                                   |             |             |               |
|                      |                                     | UPS for external batteries,Settable                                                       |             |             |               |
|                      | Internal BAT                        | Battery strips                                                                            |             |             |               |
|                      | Quantity                            | Depend on external battery, 40PCS(default, 30-50 PCS, selceted)                           |             |             |               |
|                      | External BAT                        |                                                                                           |             |             |               |
|                      | Charging capacity                   | Max. 50%*Pout                                                                             |             |             | Max. 20%*Pout |
| Charging accuracy    |                                     | ±1%                                                                                       |             |             |               |
| Bypass               | Rate voltage                        | 380/400/415VAC(L-L)220/230/240VAC(L-N)                                                    |             |             |               |
|                      | Voltage range                       | Range: -40%- +25% , Settable, default -20% ~ +15%                                         |             |             |               |
|                      | Frequency range                     | 50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz                                                       |             |             |               |
| Inverter             | Rate voltage                        | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |             |             |               |
|                      | Rate Freq.                          | 50/60Hz                                                                                   |             |             |               |
|                      | Output PF                           | 1                                                                                         |             |             |               |
|                      | Voltage accuracy                    | ±1.0%                                                                                     |             |             |               |
|                      | Output THDu                         | <1% ( linear load ) ,<5% (non-linear load)                                                |             |             |               |
|                      | Overload                            | 110%,1 hour ; 125%,10 mins; 150%,1 min; >150%,200ms                                       |             |             |               |
|                      | Frequency accuracy                  | 0.1%                                                                                      |             |             |               |
|                      | Synchronize window                  | Settable , ±0.5Hz±5Hz, default ±3Hz                                                       |             |             |               |
|                      | Slew rate                           | Settable , 0.5Hz/S-3Hz/S, default 0.5Hz/S                                                 |             |             |               |
|                      | Crest factor                        | 3:1                                                                                       |             |             |               |
|                      | Phase Accuracy                      | 120°±0.5°                                                                                 |             |             |               |
| System               | Efficiency                          | Up to 97%                                                                                 |             |             | Up to 96.8%   |
|                      | Display                             | LED + 7 inch touch LCD                                                                    |             |             |               |
|                      | Certification- Safety               | IEC62040-1, IEC60950-1                                                                    |             |             |               |
|                      | Certification- EMS                  | IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge) |             |             |               |
|                      | IP degree                           | IP20                                                                                      |             |             |               |
|                      | Configuration                       | USB, RS232, RS485, Dry contact, Air filter, Cold start                                    |             |             |               |
|                      | Option                              | SNMP card, AS400 card, Parallel kit                                                       |             |             |               |
| Environment          |                                     | 0-40℃ ( operation ) ; -25℃~70℃ ( storage ) ; 0-95% (Humidity, non-condensing )            |             |             |               |
| Dimension (W*D*H) mm | Internal BAT                        | 400*861*783                                                                               |             |             | 500*800*1350  |
|                      | External BAT                        | 250*745*556                                                                               |             |             | 250*728*650   |
| Weight(kg)           | Internal BAT (No include batteries) | 67                                                                                        | 68          | 70          | 87            |
|                      | External BAT                        | 30.8                                                                                      | 31.8        | 32.35       | 66            |

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

| Model                 |                                     | TT060EB-160P                                                                              | TT100EB-200P                                                    | /       |         |              |  |
|-----------------------|-------------------------------------|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------|---------|---------|--------------|--|
|                       |                                     | TT060EL                                                                                   | TT100EL                                                         | TT120EL | TT150EL | TT200EL      |  |
| Rate Power            |                                     | 60kVA                                                                                     | 100kVA                                                          | 120kVA  | 150kVA  | 200kVA       |  |
| Main input            | Input                               | 3P5W (3P+N+PE)                                                                            |                                                                 |         |         |              |  |
|                       | Rate Voltage                        | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |                                                                 |         |         |              |  |
|                       | Rate Freq.                          | 50/60Hz                                                                                   |                                                                 |         |         |              |  |
|                       | Input PF                            | >0.99                                                                                     |                                                                 |         |         |              |  |
|                       | Current distortion                  | THDi<2%                                                                                   |                                                                 |         |         |              |  |
|                       | Voltage range                       | 304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%              |                                                                 |         |         |              |  |
|                       | Freq. range                         | 40-70Hz                                                                                   |                                                                 |         |         |              |  |
| Battery               | Rate voltage                        | ±240VDC                                                                                   |                                                                 |         |         |              |  |
|                       | Model                               | Internal BAT                                                                              | UPS with internal batteries,12VDC/7~9Ah                         |         |         |              |  |
|                       |                                     | External BAT                                                                              | UPS for external batteries,Settable                             |         |         |              |  |
|                       | Quantity                            | Internal BAT                                                                              | Battery strips                                                  |         |         |              |  |
|                       |                                     | External BAT                                                                              | Depend on external battery, 40PCS(default, 30-50 PCS, selceted) |         |         |              |  |
|                       | Charging capacity                   | Max. 20%*Pout                                                                             |                                                                 |         |         |              |  |
|                       | Charging accuracy                   | ±1%                                                                                       |                                                                 |         |         |              |  |
| Bypass                | Rate voltage                        | 380/400/415VAC(L-L)220/230/240VAC(L-N)                                                    |                                                                 |         |         |              |  |
|                       | Voltage range                       | Range: -40%- +25% , Settable, default -20% ~ +15%                                         |                                                                 |         |         |              |  |
|                       | Frequency range                     | 50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz                                                       |                                                                 |         |         |              |  |
| Inverter              | Rate voltage                        | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |                                                                 |         |         |              |  |
|                       | Rate Freq.                          | 50/60Hz                                                                                   |                                                                 |         |         |              |  |
|                       | Output PF                           | 1                                                                                         |                                                                 |         |         |              |  |
|                       | Voltage accuracy                    | ±1.0%                                                                                     |                                                                 |         |         |              |  |
|                       | Output THDu                         | <1%(linear load),<5%(non-linear load)                                                     |                                                                 |         |         |              |  |
|                       | Overload                            | 110%,1 hour ; 125%,10 mins; 150%,1 min; >150%,200ms                                       |                                                                 |         |         |              |  |
|                       | Frequency accuracy                  | 0.1%                                                                                      |                                                                 |         |         |              |  |
|                       | Synchronize window                  | Settable, ±0.5Hz±5Hz, default ±3Hz                                                        |                                                                 |         |         |              |  |
|                       | Slew rate                           | Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S                                                  |                                                                 |         |         |              |  |
|                       | Crest factor                        | 3:1                                                                                       |                                                                 |         |         |              |  |
|                       | Phase Accuracy                      | 120°±0.5°                                                                                 |                                                                 |         |         |              |  |
|                       | System                              | Efficiency                                                                                | Up to 96.8%                                                     |         |         |              |  |
|                       |                                     | Display                                                                                   | LED + 7 inch touch LCD                                          |         |         |              |  |
| Certification- Safety |                                     | IEC62040-1, IEC60950-1                                                                    |                                                                 |         |         |              |  |
| Certification- EMS    |                                     | IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge) |                                                                 |         |         |              |  |
| IP degree             |                                     | IP20                                                                                      |                                                                 |         |         |              |  |
| Configuration         |                                     | USB, RS232, RS485, Dry contact, Air filter,Cold start                                     |                                                                 |         |         |              |  |
| Option                |                                     | SNMP card, AS400 card, Parallel kit                                                       |                                                                 |         |         |              |  |
| Environment           |                                     | 0-40℃ ( operation ) ; -25℃~70℃ ( storage ) ; 0-95% (Humidity, non-condensing )            |                                                                 |         |         |              |  |
| Dimension (W*D*H) mm  | Internal BAT                        | 500*800*1350                                                                              | 500*950*1750                                                    | /       |         |              |  |
|                       | External BAT                        | 250*728*650                                                                               | 380*950*900                                                     |         |         | 500*900*1300 |  |
| Weight(kg)            | Internal BAT (No include batteries) | 87                                                                                        | 113                                                             | /       |         |              |  |
|                       | External BAT                        | 72                                                                                        | 91                                                              | 100     | 143     |              |  |

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

# ACT Series

## 10~200kVA 3 phases Tower UPS



### Power range

10~200kVA



### Operation

3P/3P, 3P/1P, 1P/1P, Online double conversion



### Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



### Characteristics

- 7 inch colorful touch LCD with IoT functions.
- THDi<2%.
- 3-level topology design, online efficiency up to 97%.
- 3-Phase UPS with internal batteries minimal support for 20 PCS batteries.
- Supports recording and exporting logs, and can store up to 10,000 pcs event logs.

| Model                 |                                                                                | TT010EB-20                                                                                | TT010EB-40                              | TT010EB-80  | TT020EB-40  | TT020EB-80  | TT030EB-80  |
|-----------------------|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-----------------------------------------|-------------|-------------|-------------|-------------|
|                       |                                                                                | TT010EL                                                                                   |                                         |             | TT020EL     |             | TT030EL     |
| Rate Power            |                                                                                | 10kVA                                                                                     |                                         |             | 20kVA       |             | 30kVA       |
| Main input            | Input                                                                          | 3P5W (3P+N+PE)                                                                            |                                         |             |             |             |             |
|                       | Rate Voltage                                                                   | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |                                         |             |             |             |             |
|                       | Rate Freq.                                                                     | 50/60Hz                                                                                   |                                         |             |             |             |             |
|                       | Input PF                                                                       | >0.99                                                                                     |                                         |             |             |             |             |
|                       | Current distortion                                                             | THDi<2%                                                                                   |                                         |             |             |             |             |
|                       | Voltage range                                                                  | 304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%              |                                         |             |             |             |             |
|                       | Freq. range                                                                    | 40-70Hz                                                                                   |                                         |             |             |             |             |
| Battery               | Rate voltage                                                                   | ±120VDC                                                                                   | ±240VDC                                 |             |             |             |             |
|                       | Model                                                                          | Internal BAT                                                                              | UPS with internal batteries,12VDC/7~9Ah |             |             |             |             |
|                       |                                                                                | External BAT                                                                              | UPS for external batteries,Settable     |             |             |             |             |
|                       | Quantity                                                                       | Internal BAT                                                                              | 20PCS                                   | 40PCS       | 80PCS       | 40PCS       | 80PCS       |
|                       |                                                                                | External BAT                                                                              | Depend on external battery              |             |             |             |             |
|                       | Charging capacity                                                              | Internal BAT                                                                              | Max. 50%*Pout                           |             |             |             |             |
|                       |                                                                                | External BAT                                                                              |                                         |             |             |             |             |
|                       | Charging accuracy                                                              | ±1%                                                                                       |                                         |             |             |             |             |
| Bypass                | Rate voltage                                                                   | 380/400/415VAC(L-L)220/230/240VAC(L-N)                                                    |                                         |             |             |             |             |
|                       | Voltage range                                                                  | Range: -40%- +25% , Settable, default -20% ~ +15%                                         |                                         |             |             |             |             |
|                       | Frequency range                                                                | 50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz                                                       |                                         |             |             |             |             |
| Inverter              | Rate voltage                                                                   | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |                                         |             |             |             |             |
|                       | Rate Freq.                                                                     | 50/60Hz                                                                                   |                                         |             |             |             |             |
|                       | Output PF                                                                      | 1                                                                                         |                                         |             |             |             |             |
|                       | Voltage accuracy                                                               | ±1.0%                                                                                     |                                         |             |             |             |             |
|                       | Output THDu                                                                    | <1% ( linear load ) ,<5% ( non-linear load according to IEC 62040-3 )                     |                                         |             |             |             |             |
|                       | Overload                                                                       | 110%,1 hour; 125%,10 mins; 150%,1 min; >150%,200ms                                        |                                         |             |             |             |             |
|                       | Frequency accuracy                                                             | 0.1%                                                                                      |                                         |             |             |             |             |
|                       | Synchronize window                                                             | Settable, ±0.5Hz-±5Hz, default ±3Hz                                                       |                                         |             |             |             |             |
|                       | Slew rate                                                                      | Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S                                                  |                                         |             |             |             |             |
|                       | Crest factor                                                                   | 3:1                                                                                       |                                         |             |             |             |             |
|                       | Phase Accuracy                                                                 | 120°±0.5°                                                                                 |                                         |             |             |             |             |
|                       | System                                                                         | Efficiency                                                                                | Up to 97%                               |             |             |             |             |
| Display               |                                                                                | LED + 7 inch touch LCD                                                                    |                                         |             |             |             |             |
| Certification- Safety |                                                                                | IEC62040-1, IEC60950-1                                                                    |                                         |             |             |             |             |
| Certification- EMS    |                                                                                | IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge) |                                         |             |             |             |             |
| Certification- Perf.  |                                                                                | IEC62040-3                                                                                |                                         |             |             |             |             |
| IP degree             |                                                                                | IP20                                                                                      |                                         |             |             |             |             |
| Configuration         |                                                                                | USB, RS232, RS485, Dry contact, Air filter,Cold start                                     |                                         |             |             |             |             |
| Option                |                                                                                | SNMP card, AS400 card, Parallel kit                                                       |                                         |             |             |             |             |
| Environment           | 0-40℃ ( operation ) ; -25℃~70℃ ( storage ) ; 0-95% (Humidity, non-condensing ) |                                                                                           |                                         |             |             |             |             |
| Dimension (W*D*H) mm  | Internal BAT                                                                   | 250*645*556                                                                               | 250*694*724                             | 400*770*854 | 250*694*724 | 400*770*854 | 400*770*854 |
|                       | External BAT                                                                   | 250*745*556                                                                               |                                         |             |             |             |             |
| Weight(kg)            | Internal BAT                                                                   | 90                                                                                        | 139                                     | 245         | 140         | 248         | 250         |
|                       | External BAT                                                                   | 30.8                                                                                      |                                         |             | 31.8        |             | 32.35       |

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

| Model                |                                                                                | TT040EB-80                                                                                | /       |         |             |         |              |
|----------------------|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|---------|---------|-------------|---------|--------------|
|                      |                                                                                | TT040EL                                                                                   | TT060EL | TT100EL | TT120EL     | TT150EL | TT200EL      |
| Rate Power           |                                                                                | 40kVA                                                                                     | 60kVA   | 100kVA  | 120kVA      | 150kVA  | 200kVA       |
| Main input           | Input                                                                          | 3P5W (3P+N+PE)                                                                            |         |         |             |         |              |
|                      | Rate Voltage                                                                   | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |         |         |             |         |              |
|                      | Rate Freq.                                                                     | 50/60Hz                                                                                   |         |         |             |         |              |
|                      | Input PF                                                                       | >0.99                                                                                     |         |         |             |         |              |
|                      | Current distortion                                                             | THDi<2%                                                                                   |         |         |             |         |              |
|                      | Voltage range                                                                  | 304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%              |         |         |             |         |              |
|                      | Freq. range                                                                    | 40-70Hz                                                                                   |         |         |             |         |              |
| Battery              | Rate voltage                                                                   | ±240VDC                                                                                   |         |         |             |         |              |
|                      | Model                                                                          | UPS with internal batteries,12VDC/7~9Ah                                                   |         |         |             |         |              |
|                      |                                                                                | UPS for external batteries,Settable                                                       |         |         |             |         |              |
|                      | Internal BAT                                                                   | 80PCS                                                                                     | /       |         |             |         |              |
|                      | Quantity                                                                       |                                                                                           |         |         |             |         |              |
|                      | External BAT                                                                   | Depend on external battery, 40PCS(default, 30-50 PCS, selceted)                           |         |         |             |         |              |
|                      | Charging capacity                                                              | Max. 20%*Pout                                                                             |         |         |             |         |              |
| Charging accuracy    | ±1%                                                                            |                                                                                           |         |         |             |         |              |
| Bypass               | Rate voltage                                                                   | 380/400/415VAC(L-L)220/230/240VAC(L-N)                                                    |         |         |             |         |              |
|                      | Voltage range                                                                  | Range: -40%- +25% , Settable, default -20% ~ +15%                                         |         |         |             |         |              |
|                      | Frequency range                                                                | 50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz                                                       |         |         |             |         |              |
| Inverter             | Rate voltage                                                                   | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |         |         |             |         |              |
|                      | Rate Freq.                                                                     | 50/60Hz                                                                                   |         |         |             |         |              |
|                      | Output PF                                                                      | 1                                                                                         |         |         |             |         |              |
|                      | Voltage accuracy                                                               | ±1.0%                                                                                     |         |         |             |         |              |
|                      | Output THDu                                                                    | <1%(linear load),<5%(non-linear load)                                                     |         |         |             |         |              |
|                      | Overload                                                                       | 110%,1 hour ; 125%,10 mins; 150%,1 min; >150%,200ms                                       |         |         |             |         |              |
|                      | Frequency accuracy                                                             | 0.1%                                                                                      |         |         |             |         |              |
|                      | Synchronize window                                                             | Settable , ±0.5Hz±5Hz, default ±3Hz                                                       |         |         |             |         |              |
|                      | Slew rate                                                                      | Settable , 0.5Hz/S-3Hz/S, default 0.5Hz/S                                                 |         |         |             |         |              |
|                      | Crest factor                                                                   | 3:1                                                                                       |         |         |             |         |              |
|                      | Phase Accuracy                                                                 | 120°±0.5°                                                                                 |         |         |             |         |              |
| System               | Efficiency                                                                     | Max. 97%                                                                                  |         |         |             |         |              |
|                      | Display                                                                        | LED + 7 inch touch LCD                                                                    |         |         |             |         |              |
|                      | Certification- Safety                                                          | IEC62040-1, IEC60950-1                                                                    |         |         |             |         |              |
|                      | Certification- EMS                                                             | IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge) |         |         |             |         |              |
|                      | IP degree                                                                      | IP20                                                                                      |         |         |             |         |              |
|                      | Configuration                                                                  | USB, RS232, RS485, Dry contact,Air filter,Cold start                                      |         |         |             |         |              |
| Option               | SNMP card, AS400 card, Parallel kit                                            |                                                                                           |         |         |             |         |              |
| Environment          | 0-40℃ ( operation ) ; -25℃~70℃ ( storage ) ; 0-95% (Humidity, non-condensing ) |                                                                                           |         |         |             |         |              |
| Dimension (W*D*H) mm | Internal BAT                                                                   | 400*800*950                                                                               | /       |         |             |         |              |
|                      | External BAT                                                                   | 250*728*650                                                                               |         |         | 350*950*900 |         | 500*900*1300 |
| Weight(kg)           | Internal BAT                                                                   | 270                                                                                       | /       |         |             |         |              |
|                      | External BAT                                                                   | 66                                                                                        | 72      | 91      | 100         | 143     |              |

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

# ACT Series

## 10~60kVA 3 phases Rack UPS



### Power range

10~60kVA



### Operation

3P/3P,3P/1P,1P/1P,Online double conversion



### Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



### Characteristics

- Mounted in 19 inch rack, or install as tower UPS.
- 7 inch touch LCD with IoT functions.
- Flexible configuration as 3/3,3/1,1/1.
- High power density, small volume, 30kW in 3U.
- High reliability and environmental adaptability.



| Model                |                       | TT010ELR                                                                                  | TT015ELR                                    | TT020ELR | TT030ELR | TT040ELR         | TT060ELR |
|----------------------|-----------------------|-------------------------------------------------------------------------------------------|---------------------------------------------|----------|----------|------------------|----------|
| Rate Power           |                       | 10kVA                                                                                     | 15kVA                                       | 20kVA    | 30kVA    | 40kVA            | 60kVA    |
| Main input           | Input                 | 3P5W (3P+N+PE)                                                                            |                                             |          |          |                  |          |
|                      | Rate Voltage          | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |                                             |          |          |                  |          |
|                      | Rate Freq.            | 50/60Hz                                                                                   |                                             |          |          |                  |          |
|                      | Input PF              | >0.99                                                                                     |                                             |          |          |                  |          |
|                      | Current distortion    | THDi<2%                                                                                   |                                             |          |          | THDi<2%          |          |
|                      | Voltage range         | 304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%              |                                             |          |          |                  |          |
|                      | Freq. range           | 40-70Hz                                                                                   |                                             |          |          |                  |          |
| Battery              | Rate voltage          | ±120VDC(default 20 PCS, 20-50 PCS, selceted)                                              | ±240VDC(default 40 PCS,30-50 PCS, selceted) |          |          |                  |          |
|                      | Charging capacity     | Max. 50%*Pout                                                                             |                                             |          |          | Max. 20%*Pout    |          |
|                      | Charging accuracy     | ±1%                                                                                       |                                             |          |          |                  |          |
| Bypass               | Rate voltage          | 380/400/415VAC(L-L)220/230/240VAC(L-N)                                                    |                                             |          |          |                  |          |
|                      | Voltage range         | Range: -40%- +25% , Settable, default -20% ~ +15%                                         |                                             |          |          |                  |          |
|                      | Frequency range       | 50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz                                                       |                                             |          |          |                  |          |
| Inverter             | Rate voltage          | 380/400/415VAC(L-L); 220/230/240VAC(L-N)                                                  |                                             |          |          |                  |          |
|                      | Rate Freq.            | 50/60Hz                                                                                   |                                             |          |          |                  |          |
|                      | Output PF             | 1                                                                                         |                                             |          |          |                  |          |
|                      | Voltage accuracy      | ±1.0%                                                                                     |                                             |          |          |                  |          |
|                      | Output THDu           | <1% ( linear load ) , <5% ( non-linear load according to IEC 62040-3 )                    |                                             |          |          |                  |          |
|                      | Overload              | 110%,1 hour; 125%,10 mins; 150%,1 min; >150%,200ms                                        |                                             |          |          |                  |          |
|                      | Frequency accuracy    | 0.1%                                                                                      |                                             |          |          |                  |          |
|                      | Synchronize window    | Settable, ±0.5Hz-±5Hz, default ±3Hz                                                       |                                             |          |          |                  |          |
|                      | Slew rate             | Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S                                                  |                                             |          |          |                  |          |
|                      | Crest factor          | 3:1                                                                                       |                                             |          |          |                  |          |
|                      | Phase Accuracy        | 120°±0.5°                                                                                 |                                             |          |          |                  |          |
| System               | Efficiency            | Up to 97%                                                                                 |                                             |          |          | Up to 96.8%      |          |
|                      | Display               | LED + 7 inch touch LCD                                                                    |                                             |          |          |                  |          |
|                      | Certification- Safety | IEC62040-1, IEC60950-1                                                                    |                                             |          |          |                  |          |
|                      | Certification- EMS    | IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge) |                                             |          |          |                  |          |
|                      | IP degree             | IP20                                                                                      |                                             |          |          |                  |          |
|                      | Configuration         | USB, RS232, RS485, Dry contact, Cold start*                                               |                                             |          |          |                  |          |
|                      | Option                | SNMP card, AS400 card, Parallel kit, Air filter                                           |                                             |          |          |                  |          |
|                      | Environment           | 0-40℃ ( operation ) ; -25℃~70℃ ( storage ) ; 0-95% (Humidity, non-condensing )            |                                             |          |          |                  |          |
| Dimension (W*D*H) mm |                       | 440*775*130 (3U)                                                                          |                                             |          |          | 440*810*175 (4U) |          |
| Weight(kg)           |                       | 21.4                                                                                      | 22.4                                        |          | 22.7     | 60               |          |

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.