



COSMOS RF

T E C H N O L O G I E S

ACS Series

1~3kVA online Tower UPS



Power range

1~3kVA



Operation

1P/1P, online double conversion



Applications

Government, Finance, IT,
Education, Transportation,
Broadcasting, Medical,
Energy, etc.



Characteristics

- High efficiency up to 96%.
- Output PF=1, high load adaptability.
- Wide input voltage range of 110~300Vac.
- Max charging current up to 12A.



Model		SS001B	SS001L	SS01.5B	SS01.5L	SS002B	SS002L	SS003B	SS003L
Rate Power		1kVA/1kW	1kVA/1kW	1.5kVA/1.5kW	1.5kVA/1.5kW	2kVA/2kW	2kVA/2kW	3kVA/3kW	3kVA/3kW
Cold start		Default output 50/60Hz							
Input voltage range		110~300VAC;100% load@176VAC~276VAC, 100%~50% power derating@110VAC~176VAC, 50% load@276VAC~300VAC							
Input power factor		≥0.99							
Frequency range		50/60±5Hz(default),±3Hz/±10Hz(settable)							
Output power factor		1.0							
Output	Rate voltage	220/230/240VAC, 200/208VAC(PF=0.9)							
	Load response	≤5% (0% - 100% -0% step load)							
	Recovery time	≤40ms (0% - 100% -0% step load)							
	Output THDu	≤2% , Linear load ; ≤ 5% non-linear load according to IEC62040-3							
	Crest factor	3:1							
Transfer time	Main to BAT	0							
	INV to BYP	4ms							
Efficiency (normal mode)		Max 96%							
Noise (1 meter)		43dB@<60%load, 47dB@>60%load				<50dB@<60%load, <55dB@>60%load		<50dB@<60%load, <55dB@>60%load	
Normal		102%~110%: 30mins, 110%~125%:10mins, 125%~150%: 30 seconds							
OverloadBattery mode		102%~110%: 1min, 110%~125%: 10 seconds, 125%~150%:5 seconds							
Bypass mode		<130%: long time, 130%~150%:10mins, 150%~180%:5 seconds							
Battery	Quantity	3(12VDC*7Ah)	Depend on external battery	3(12VDC*7Ah)	Depend on external battery	6(12VDC*7Ah)	Depend on external battery	8(12VDC*7Ah)	Depend on external battery
	Max charging	1A	1-12A(optional)	1A	1-12A(optional)	1A	1-12A(optional)	1A	1-12A(optional)
	Rate voltage	36VDC		36VDC		72VDC		96VDC	
Standard		EPO, RS232							
Option		SNMP card,AS400, USB, RS485, Air filter							
Dimension ,W*D*H(mm)		144*355*226				190*400*328	144*398*223	190*400*328	144*398*223
Weight (kg)		10,5	4,5	10,5	10,5	20,5	6	25	6

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.