

ACT Series

10~200kVA 3-phase Tower UPS

Internal 7/9Ah modular battery strips



Power range

10~200kVA



Operation

3P/3P, Online double conversion



Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



Characteristics

- 7 inch touch LCD with IoT functions.
- High power density, small volume.
- High reliability and environmental adaptability.
- Optional full metal battery strips, with internal batteries capable of configuring up to 16 pcs battery strips.



Full metal battery strips(Optional)

Model		TT010EB-80P	TT015EB-80P	TT030EB-80P	TT040B-120P
		TT010EL	TT015EL	TT030EL	TT040L
Rate Power		10kVA	15kVA	30kVA	40kVA
Main input	Input	3P5W (3P+N+PE)			
	Rate Voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)			
	Rate Freq.	50/60Hz			
	Input PF	>0.99			
	Current distortion	THDi<2%			THDi<3%
	Voltage range	304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%			
	Freq. range	40-70Hz			
Battery	Rate voltage	±240VDC(default 40 PCS,30-50 PCS, selceted)			
	Model	UPS with internal batteries,12VDC/7~9Ah			
		UPS for external batteries,Settable			
	Internal BAT	Battery strips			
	Quantity	Depend on external battery, 40PCS(default, 30-50 PCS, selceted)			
	External BAT				
	Charging capacity	Max. 50%*Pout			Max. 20%*Pout
Bypass	Internal BAT				
	External BAT				
	Charging accuracy	±1%			
	Rate voltage	380/400/415VAC(L-L)220/230/240VAC(L-N)			
	Voltage range	Range: -40%- +25% , Settable, default -20% ~ +15%			
	Frequency range	50/60Hz, Settable : ±1Hz, ±3Hz, ±5Hz			
Inverter	Rate voltage	380/400/415 VAC(L-L); 220/230/240 VAC(L-N)			
	Rate Freq.	50/60Hz			
	Output PF	1			
	Voltage accuracy	±1.0%			
	Output THDu	<1% (linear load) , <5% (non-linear load)			
	Overload	110%,1 hour ; 125%,10 mins; 150%,1 min; >150%,200ms			
	Frequency accuracy	0.1%			
	Synchronize window	Settable, ±0.5Hz-±5Hz, default ±3Hz			
	Slew rate	Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S			
	Crest factor	3:1			
	Phase Accuracy	120°±0.5°			
	Efficiency	Up to 97%			Up to 96%
	Display	LED + 7 inch touch LCD			
System	Certification- Safety	IEC62040-1, IEC60950-1			
	Certification- EMS	IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge)			
	Configuration	USB, RS232, RS485, Dry contact, Air filter, Cold start,Ethernet			USB, RS232, RS485, Dry contact, Air filter, Cold start
	Option	SNMP card, AS400 card, Parallel kit			SNMP card, AS400 card, Parallel kit
	Environment	0-40℃ (operation) ; -25℃~70℃ (storage) ; 0-95% (Humidity, non-condensing)			
Dimension (W*D*H) mm	Internal BAT	400*790*783			500*864*922
	External BAT	250*745*556			250*782*650
Weight(kg)	Internal BAT (No include batteries)	67	68	70	78
	External BAT	30.8	31.8	32.35	66

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

Model		TT060B-160P	TT100EB-200P		/	
		TT060L	TT080EL	TT100EL	TT180EL	TT200EL
Rate Power		60kVA	100kVA		200kVA	
Main input	Input	3P5W (3P+N+PE)				
	Rate Voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)				
	Rate Freq.	50/60Hz				
	Input PF	>0.99				
	Current distortion	THDi<3%	THDi<2%			
	Voltage range	304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%				
	Freq. range	40-70Hz				
	Rate voltage	±240VDC				
Battery	Model	UPS with internal batteries,12VDC/7~9Ah				
		UPS for external batteries,Settable				
	Internal BAT	Battery strips			/	
	Quantity	Depend on external battery, 40PCS(default, 30-50 PCS, selceted)				
	External BAT					
	Charging capacity	Max. 20%*Pout	/			
	Internal BAT		Max. 15%*Pout			
	External BAT					
Charging accuracy	±1%					
Bypass	Rate voltage	380/400/415VAC(L-L)220/230/240VAC(L-N)				
	Voltage range	Range: -40%- +25% , Settable, default -20% ~ +15%				
	Frequency range	50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz				
Inverter	Rate voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)				
	Rate Freq.	50/60Hz				
	Output PF	1				
	Voltage accuracy		±1.0%			
	Output THDu	<1% (linear load) <5% (non-linear load)	<1%(linear load),<3%(non-linear load)			
	Overload	110%,1 hour ; 125%,10 mins; 150%,1 min; >150%,200ms				
	Frequency accuracy	0.1%				
	Synchronize window	Settable , ±0.5Hz±5Hz, default ±3Hz				
	Slew rate	Settable , 0.5Hz/S-3Hz/S, default 0.5Hz/S				
	Crest factor	3:1				
	Phase Accuracy	120°±0.5°				
	System	Efficiency	Up to 96%	Up to 97%		
Display		LED + 7 inch touch LCD				
Certification- Safety		IEC62040-1, IEC60950-1				
Certification- EMS		IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge)				
Configuration		USB, RS232, RS485, Dry contact, Air filter, Cold start	USB, RS232, RS485, Dry contact, Air filter,Cold start			
Option		SNMP card, AS400 card, Parallel kit	SNMP card, AS400 card, Parallel kit			
Environment		0-40℃ (operation) ; -25℃~70℃ (storage) ; 0-95% (Humidity, non-condensing)				
Dimension (W*D*H) mm	Internal BAT	500*865*1250	500*950*1700			
	External BAT	250*782*650	380*950*900		500*900*1200	
Weight(kg)	Internal BAT (No include batteries)	87	113			
	External BAT	72	91		143	

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

ACT Series

10~40kVA 3 phases Tower UPS



Power range

10~40 kVA



Operation

3P/3P, Online double conversion



Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



Characteristics

- 7 inch touch LCD with IoT functions.
- High power density, small volume.
- High reliability and environmental adaptability.
- UPS with internal batteries minimal support for 20 PCS batteries.
- Standard configuration for mains input/output, bypass, maintenance bypass, battery breaker.

Model		TT010EB-20	TT010EB-40	TT010EB-80	
		TT010EL			
Rate Power		10kVA			
Main input	Input	3P5W (3P+N+PE)			
	Rate Voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)			
	Rate Freq.	50/60Hz			
	Input PF	>0.99			
	Current distortion	THDi<2%			
	Voltage range	304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%			
	Freq. range	40-70Hz			
	Rate voltage	±120VDC(default 20 PCS,20-50 PCS, selceted)	±240VDC(default 40 PCS,30-50 PCS, selceted)		
Battery	Model	Internal BAT UPS with internal batteries,12VDC/7~9Ah			
		External BAT UPS for external batteries,Settable			
	Quantity	Internal BAT	20PCS	40PCS	80PCS
		External BAT	20PCS(default, 20-50PCS optional)		
	Charging capacity	Internal BAT	Max. 50%*Pout		
		External BAT			
Charging accuracy		±1%			
Bypass	Rate voltage	380/400/415VAC(L-L)220/230/240VAC(L-N)			
	Voltage range	Range: -40%- +25% , Settable, default -20% ~ +15%			
	Frequency range	50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz			
Inverter	Rate voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)			
	Rate Freq.	50/60Hz			
	Output PF	1			
	Voltage accuracy	±1.0%			
	Output THDu	<1% (linear load) ,<5% (non-linear load according to IEC 62040-3)			
	Overload	110%,1 hour; 125%,10 mins; 150%,1 min; >150%,200ms			
	Frequency accuracy	0.1%			
	Synchronize window	Settable, ±0.5Hz-±5Hz, default ±3Hz			
	Slew rate	Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S			
	Crest factor	3:1			
	Phase Accuracy	120°±0.5°			
	System	Efficiency	Up to 97%		
Display		LED + 7 inch touch LCD			
Certification- Safety		IEC62040-1, IEC60950-1			
Certification- EMS		IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge)			
Configuration		USB, RS232, RS485, Dry contact, Air filter, Cold start,Enternet port			
Option		SNMP card, AS400 card, Parallel kit			
Environment		0-40℃ (operation) ; -25℃~70℃ (storage) ; 0-95% (Humidity, non-condensing)			
Dimension (W*D*H) mm	Internal BAT	250*645*556	250*694*724	400*770*854	
	External BAT	250*745*556			
Weight(kg)	Internal BAT	90	139	245	
	External BAT	30.8			

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

Model		TT020EB-40	TT020EB-80	TT030EB-80	TT040B-80
		TT020EL		TT030EL	TT040L
Rate Power		20kVA		30kVA	40kVA
Main input	Input	3P5W (3P+N+PE)			
	Rate Voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)			
	Rate Freq.	50/60Hz			
	Input PF	>0.99			
	Current distortion	THDi<2%			THDi<3%
	Voltage range	304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%			
	Freq. range	40-70Hz			
	Rate voltage	±240VDC(default 40 PCS)			
Battery	Model	Internal BAT	UPS with internal batteries,12VDC/7~9Ah		
		External BAT	UPS for external batteries,Settable		
	Quantity	Internal BAT	40PCS	80PCS	
		External BAT	40PCS(default, 30-50PCS optional)		
	Charging capacity	Internal BAT	Max. 50%*Pout		Max. 20%*Pout
		External BAT			
Charging accuracy		±1%			
Bypass	Rate voltage	380/400/415VAC(L-L)220/230/240VAC(L-N)			
	Voltage range	Range: -40%- +25% , Settable, default -20% ~ +15%			
	Frequency range	50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz			
Inverter	Rate voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)			
	Rate Freq.	50/60Hz			
	Output PF	1			
	Voltage accuracy	±1.0%			
	Output THDu	<1% (linear load) ,<5% (non-linear load according to IEC 62040-3)			
	Overload	110%,1 hour; 125%,10 mins; 150%,1 min; >150%,200ms			
	Frequency accuracy	0.1%			
	Synchronize window	Settable, ±0.5Hz-±5Hz, default ±3Hz			
	Slew rate	Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S			
	Crest factor	3:1			
	Phase Accuracy	120°±0.5°			
	System	Efficiency	Up to 97%		
Display		LED + 7 inch touch LCD			
Certification- Safety		IEC62040-1, IEC60950-1			
Certification- EMS		IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge)			
Configuration		USB, RS232, RS485, Dry contact, Air filter, Cold start,Enternet port			USB, RS232, RS485, Dry contact, Cold start
Option		SNMP card, AS400 card, Parallel kit			SNMP card, AS400 card, Parallel kit,Air filter
Environment		0-40℃ (operation) ; -25℃~70℃ (storage) ; 0-95% (Humidity, non-condensing)			
Dimension (W*D*H) mm	Internal BAT	250*694*724	400*770*854		350*823*1200
	External BAT	250*745*556			250*782*650
Weight(kg)	Internal BAT	140	248	250	262
	External BAT	31.8		32.35	49

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

ACT Series

10~60kVA 3 phases Rack UPS



Power range

10~60kVA



Operation

3P/3P,3P/1P,1P/1P,Online double conversion



Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



Characteristics

- Mounted in 19 inch rack, or install as tower UPS.
- 7 inch touch LCD with IoT functions.
- Flexible configuration as 3/3,3/1,1/1.
- High power density, small volume, 30kW in 3U.
- High reliability and environmental adaptability.



Model		TT010ELR	TT015ELR	TT020ELR	TT030ELR	TT040LR	TT060LR
Rate Power		10kVA	15kVA	20kVA	30kVA	40kVA	60kVA
Main input	Input	3P5W (3P+N+PE)					
	Rate Voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)					
	Rate Freq.	50/60Hz					
	Input PF	>0.99					
	Current distortion	THDi<2%				THDi<3%	
	Voltage range	304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%					
	Freq. range	40-70Hz					
Battery	Rate voltage	±120VDC(default 20 PCS, 20-50 PCS, selceted)	±240VDC(default 40 PCS,30-50 PCS, selceted)				
	Charging capacity	Max. 50%*Pout				Max. 20%*Pout	
	Charging accuracy	±1%					
Bypass	Rate voltage	380/400/415VAC(L-L)220/230/240VAC(L-N)					
	Voltage range	Range: -40%- +25% , Settable, default -20% ~ +15%					
	Frequency range	50/60Hz, Settable: ±1Hz, ±3Hz, ±5Hz					
Inverter	Rate voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)					
	Rate Freq.	50/60Hz					
	Output PF	1					
	Voltage accuracy	±1.0%					
	Output THDu	<1% (linear load) ,<5% (non-linear load according to IEC 62040-3)					
	Overload	110%,1 hour; 125%,10 mins; 150%,1 min; >150%,200ms					
	Frequency accuracy	0.1%					
	Synchronize window	Settable, ±0.5Hz-±5Hz, default ±3Hz					
	Slew rate	Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S					
	Crest factor	3:1					
	Phase Accuracy	120°±0.5°					
System	Efficiency	Up to 97%				Up to 96%	
	Display	LED + 7 inch touch LCD					
	Certification- Safety	IEC62040-1, IEC60950-1					
	Certification- EMS	IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge)					
	IP degree	IP20					
	Configuration	USB, RS232, RS485, Dry contact, Cold start,Ethernet port				USB, RS232, RS485, Dry contact	
	Option	SNMP card, AS400 card, Parallel kit, Air filter				SNMP card, AS400 card, Parallel kit, Air filter,Cold start	
	Environment	0-40℃ (operation) ; -25℃~70℃ (storage) ; 0-95% (Humidity, non-condensing)					
Dimension (W*D*H) mm		440*620*130 (3U)				440*788*174 (4U)	440*807*218 (5U)
Weight(kg)		21.4	22.4		22.7	38	60

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.