

CSE 301 – DATABASE

Lecture 9

Chapter 3: Relational Model


Modification of Database

- The content of the database may be modified using the following operations:
 - ✓ Insertion
 - ✓ Deletion
 - ✓ Updating
- All the operations are expressed using the assignment operator (\leftarrow).
- E.g., $\mathbf{R_{new} \leftarrow \text{operations on } (R_{old})}$

Deletion

- ❑ A delete request is expressed similarly to a query, except instead of displaying tuples to the user, the selected tuples are removed from the database.
- ❑ In deletion, **tuples are deleted from the relation**
- ❑ Can delete only whole tuples; cannot delete values only particular attributes
- ❑ A deletion is expressed in relational algebra by: $R \leftarrow R - E$
 - ✓ Where R is a relation and E is a relational algebra expression.

Examples of Deletion



Examples of Deletion

- Delete all account records in the Perryridge branch.

$\text{account} \leftarrow \text{account} - \sigma_{\text{branch-name} = \text{"Perryridge"}}(\text{account})$

- Delete all loan records with amount in the range of 0 to 50

$\text{loan} \leftarrow \text{loan} - \sigma_{\text{amount} \geq 0 \text{ and } \text{amount} \leq 50}(\text{loan})$

- Delete all accounts at branches located in Needham.

$r_1 \leftarrow \sigma_{\text{branch-city} = \text{"Needham"}}(\text{account} \bowtie \text{branch})$

$r_2 \leftarrow \Pi_{\text{account-number}, \text{branch-name}, \text{balance}}(r_1)$

$r_3 \leftarrow \Pi_{\text{customer-name}, \text{account-number}}(r_2 \bowtie \text{depositor})$

$\text{account} \leftarrow \text{account} - r_2$

$\text{depositor} \leftarrow \text{depositor} - r_3$

Insertion

- ❑ *Similar to deletion*, but **use union operator (U)** instead of **minus (-)** operator.
- ❑ In **insertion**, tuples are added to the relation
- ❑ To insert data into a relation, we either:
 - ✓ **Specify a tuple to be inserted**, or
 - ✓ **Write a query whose result is asset of tuples to be inserted**
- ❑ An insertion is expressed in relational algebra by: $R \leftarrow R \cup E$, where R is a relation and E is a relational algebra expression.
- ❑ The *insertion of a single tuple* is expressed by letting E be a constant relation containing one tuple.

Examples of Insertion

$R \leftarrow R \cup \{(2, 4, 20)\}$

| A | B | C |
|---|---|----|
| 1 | 1 | 10 |
| 1 | 2 | 10 |
| 2 | 3 | 10 |



| A | B | C |
|---|---|----|
| 1 | 1 | 10 |
| 1 | 2 | 10 |
| 2 | 3 | 10 |
| 2 | 4 | 20 |

Examples of Insertion

- Insert information in the database specifying that **Smith** has **\$1200** in account **A-973** at the **Perryridge** branch.

$account \leftarrow account \cup \{(A-973, \text{"Perryridge"}, 1200)\}$

$depositor \leftarrow depositor \cup \{(\text{"Smith"}, A-973)\}$

We may want to insert tuples on the basis of result of a query.

- Provide as a gift for **all loan customers** in the **Perryridge** branch, a **\$200 savings account**. Let the loan number serve as the account number for the new savings account.

$r_1 \leftarrow (\sigma_{branch-name = \text{"Perryridge"}}(borrower \bowtie loan))$

$account \leftarrow account \cup \Pi_{loan-number, branch-name, 200}(r_1)$

$depositor \leftarrow depositor \cup \Pi_{customer-name, loan-number}(r_1)$

Updating

- ❑ *Updating* is a mechanism to change a value in a tuple without changing all values in the tuple.
- ❑ Use the generalized projection operator to do this task.

$$R \leftarrow \Pi_{F_1, F_2, \dots, F_n}(R)$$

- ❑ Each F_i can be either :
 - The **attribute** of R , or
 - An **expression**, involving only *constants and the attributes* of R , which gives the new value for the attribute.

Note: The schema of expression resulting from the generalized projection expression must match the original schema of R .

Examples of Updating

$$R \leftarrow \Pi_{A, 2*B, C}(R)$$

| A | B | C |
|---|---|----|
| 1 | 1 | 10 |
| 1 | 2 | 10 |
| 2 | 4 | 20 |



| A | B | C |
|---|---|----|
| 1 | 2 | 10 |
| 1 | 4 | 10 |
| 2 | 8 | 20 |

$$R \leftarrow \Pi_{A, 2*B, C}(\sigma_{A=1}(R))$$

| A | B | C |
|---|---|----|
| 1 | 2 | 10 |
| 1 | 4 | 10 |

Examples of Updating

- Make interest payments by increasing all balances by 5 percent.

$\text{account} \leftarrow \Pi_{\text{account-number}, \text{branch-name}, \text{balance} * 1.05} (\text{account})$

- Pay all accounts with balances over \$10,000 a 6 percent interest and pay all others 5 percent

$$\text{account} \leftarrow \Pi_{\text{account-number}, \text{branch-name}, \text{balance} * 1.06} (\sigma_{\text{balance} > 10000} (\text{account})) \cup \Pi_{\text{account-number}, \text{branch-name}, \text{balance} * 1.05} (\sigma_{\text{balance} \leq 10000} (\text{account}))$$

Views

- ❑ In some cases, it is not desirable for all users to see the entire logical model i.e. all the actual relations stored in the database.
- ❑ Consider “a person who needs to know a customer’s loan number but has no need to see the amount.” the person should see a relation described, in the relational algebra, by

$$\Pi_{\text{customer-name, loan-number}} (\text{borrower} \bowtie \text{loan})$$

- ❑ Any relation that is made visible to a user as a “virtual Relation” is called a VIEW
 - ❑ It provides *Limited access to DB*
 - ❑ It presents the *Tailored schema*.

Views

- ❑ “**Views**” are Virtual Relations or Virtual tables, through which a selective portion of the data from one or more relations or tables can be seen.
- ❑ Views do not contain data of their own.
- ❑ Views do not exist physically.
- ❑ Uses of View:
 - ✓ It helps in query processing like simplify commands for the user, store complex queries, etc.
 - ✓ To restrict access to the database
 - ✓ To hide data complexity

Views

- ❑ Data modifications like insert, update, delete operations on views affects the actual relations in the database, upon which view is based. (Same in SQL)
- ❑ Views are stored in data dictionary in the table called USER_VIEWS.

Views

- A **view** is defined using the **create view** statement:

create view v as <query expression>

where **<query expression>** is any legal relational algebra query expression, and **v** represents the **view name**

Example: In SQL, **create view v as**
select column-list
from table-name [**where** condition];

Once a **view** is defined, the **view name** can be used to refer to the **virtual relation** that the view generates.

Example: In SQL, **select * from v ;**

View definition is not the same as creating a new relation by evaluating the query expression.

- ❖ Rather, a **view definition** causes the saving of an expression to be substituted into queries using the view.

- ❑ It means wherever **view v** is used, it is actually replaced by the equivalent **query expression** at run time

Examples of Views

- Creating a **view** (*loan-customer*) consisting all loan customers and their loan number

create view *loan-customer* **as**

$\Pi_{\text{customer-name, loan-number}} (\text{borrower} \bowtie \text{loan})$

- We can find all loan customers and their loan number
loan-customer

- **Note:** So wherever **view** *loan-customer* is used, it is actually replaced by the equivalent **query expression** at run time. This query is evaluated and the entire answer is resulted.

Examples of Views

- Creating a **view** (*all-customer*) consisting of branches and their customers

create view *all-customer* as

$$\Pi_{branch-name, customer-name} (depositor \bowtie account) \\ \cup \Pi_{branch-name, customer-name} (borrower \bowtie loan)$$

- We can find all customers of the Perryridge branch

$$\Pi_{customer-name} (\sigma_{branch-name = "Perryridge"} (all-customer))$$

- **Note:** So wherever **view** *all-customer* is used, it is actually replaced by the equivalent **query expression** at run time. This query is evaluated and the entire answer is resulted.

Examples of Views in SQL

- Creating a view *loan-customer*: from multiple tables

```
create view loan-customer as
```

```
select customer-name, loan-number
```

```
from borrower natural inner join loan;
```

- We can find all loan customers and their loan number

```
select *
```

```
from loan-customer
```

Examples of Views in SQL

- Creating a view *student-view*: from single tables

create view *student-view* as

select *name, age*

from *Students*;

| roll-no | name | age | address |
|---------|-------|-----|---------|
| 1 | Rohan | 20 | Delhi |
| 2 | Sohan | 21 | Mumbai |
| 3 | Mohan | 22 | Pune |

- To see the *student-view*

select *

from *student-view*;

| name | age |
|-------|-----|
| Rohan | 20 |
| Sohan | 21 |
| Mohan | 22 |

Drop View

- A view can be deleted using the **Drop View** statement.

```
drop view viewname
```

- Example: **drop view** *student-view*

Views : Summary

“Views does not stored **physically.**”

- When we define a view, the **database system stores the definition of the view itself, rather than the result of evaluation of the relational-algebra expression** that defines the view.
- Wherever a view relation appears in a query, it is **replaced by the stored query expression.**
- Thus, whenever we evaluate the query, the view relation gets **recomputed.**
- If the original table used in view changes, it does not affects the view relation because it is evaluated every time

Types of Views

□ ***Read-only View :***

- Used only to read data.
- In SQL, it allows only SELECT operations.

□ ***Updateable View :***

- Used to read and update the data.
- In SQL, it allows SELECT as well as INSERT , UPDATE and DELETE operations.

Materialized Views

For some views, there is a term called **materialization**. So some views are materialized. This depends on the query engine etc., the database engine.

- **Certain database systems allow view relations to be stored**, but they make sure that, if the actual relations used in the view definition change, the view is kept up to date. Such views are called **materialized views**.
 - ❑ The **process of keeping the view up to date** is called **view maintenance**.
 - ❑ Applications that use a view frequently in multiple queries benefited from the use of **materialized views** because then query expression is not going to be evaluated at run time
 - ❑ Of course, the benefits to queries from the materialization of a view must be weighed against the storage costs and the added overhead for updates.