

UHF RFID Reader



Android









Bluetooth



UHF





2D Barcode



IRIS



NFC/HF





This device is an Android rugged mobile computer. It features quad-core processor, 8000mAh battery and superb UHF RFID capability. It can be equipped with R2000 linearly or circularly polarized antenna. That it can read tags in bulk from long distance enables it to be deployed in asset management, retail, warehousing, fleet management and etc.





Specification

Dimensions	164.2 x 80.0 x 24.3mm / 6.46 x 3.15 x 0.96in
Weight	654g / 23.07oz
Display	5.2" IPS FHD 1920x1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Li-ion, rechargeable, 8000mAh
	Standby: over 500 hours
	Continuous use: over 12 hours (depending on user environment)
	Charging time: 3-4 hours (with standard adaptor and USB cable)
Expansion Slot	1 slot for SIM card, 1 slot for SIM or TF card
Interfaces	USB 2.0 Type-C, OTG
Audio	Speaker, 2 microphones
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
Sensors	Gravity sensor, light sensor, proximity sensor, vibration motor
Performance	
CPU	Cortex-A53 Quad-core 1.3GHz
RAM+ROM	2GB+16GB
Expansion	Supports up to 32 GB Micro SD card
User Environn	nent
Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.5m/4.9ft drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5m/1.6ft falls at room temperature
Sealing	Host IP65
ESD	±8KV air discharge, ±4KV conductive discharge
Developing En	nvironment
Operating System	Android 6.0
SDK	Software Development Kit
Language	Java
Tool	Eclipse / Android Studio
Communication	on
WLAN	IEEE802.11 a/b/g/n, 2.4G/5G dual-band, internal antenna
	2G: 850/900/1800/1900MHz
WWAN(Europe)	3G: 850/900/1900/2100MHz
	4G: B1, B3, B5, B7, B8, B20, B40

WWAN(America)	2G: 850/900/1800/1900MHz
	3G: 850/900/1700/1900MHz
WWAN (China)	4G: B2, B4, B7, B12, B17
	2G: 900/1800MHz
	3G: 900/1900/2000/2100MHz
	4G: B1, B3, B5, B38, B39, B40, B41
WWAN (Others)	Depending on the country's ISP
Bluetooth	Bluetooth 4.0, BLE
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Data Collection

Camera

Camera 13MP Autofocus with flash

RFID (Optional)

UHF	
Frequency	865MHz-868MHz / 920-925MHz / 902-928MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Linear polarization(1.8dBi); circular polarization (4dBi)
Power	1W (30dBm, +5dBm to +30dBm adjustable)
R/W range	>6m (linear polarization); >10m (circular polarization, open outdoors); >20m (circular polarization, indoors)
Reading rate	>200 tags/s (circular polarization)

^{*} Ranges and rates depend on tags and environment

Barcode Scanning (Optional)

1D Linear Scanner	Honeywell N4313
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scanner	Zebra: SE4710 / SE4750 / SE4750MR; Honeywell: N6603
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

Iris (optional)

Rate	<150ms
Range	20-40cm
FAR	1/1000000

HF/ NFC (optional)

The trace (optional)	
Frequency	13.56MHz
*HF RFID is alternative to NFC.	

Accessories







AC Adaptor

