


NOTES

- सभी माप मिलीमीटर में तथा ऊँचाई मीटर में दिए गए हैं।
ALL DIMENSIONS ARE IN MILLIMETERS AND LEVELS IN METERS.
- UNLESS SPECIFIED OTHERWISE M25/A40 GRADE CONCRETE SHALL BE USED AS PER SECTION B.9 OF TECHNICAL SPECIFICATION.
- UNLESS SPECIFIED OTHERWISE REINFORCEMENT SHALL BE H.Y.S.D STEEL BARS GRADE FE 500 CONFORMING TO IS:1786 AS PER SECTION B.11 OF TECHNICAL SPECIFICATION.
- STANDARD LAP LENGTH AND ANCHORAGE LENGTH/DEVELOPMENT LENGTH SHALL BE 50 TIMES THE DIAMETER OF BARS UNLESS OTHERWISE SPECIFIED.
- LAPS AND SPLICES PROVIDED IN REINFORCING BARS SHALL BE AS FAR AS POSSIBLE STAGGERED.
- CLEAR COVER TO REINFORCEMENT SHALL BE 50 MM UNLESS OTHERWISE SPECIFIED.

REFERENCE DRAWINGS:-

- NHDB-3BC4-41-DD-0001.
- NHDB-3BC4-41-DD-1001.

SCALE:



एन एच पी सी लिमिटेड
(भारत सरकार का उद्यम)
NHPC Limited
(A GOVT. OF INDIA ENTERPRISE)

दिबांग बहुउद्देशीय परियोजना
DIBANG MULTIPURPOSE PROJECT

HEAD RACE TUNNEL
ADIT TO HRT PORTAL
CONCRETE AND REINFORCEMENT DETAILS

19.09.2024	00	ISSUED FOR CONSTRUCTION	BY CH. APP.	DATE	SEP 2024	DRG. NO.	NHDB 3BC4 41 DD	2001	00
DATE	NO.	REVISION OR ISSUES	BY	CH. APP.	DATE	DRG. NO.	NHDB 3BC4 41 DD	2001	00
DESIGN MEMO NO.	डिजाइन मेमो संख्या								