Synchronization

Concurrent Processes

- Concurrent processes can:
 - Compete for shared resources
 - Cooperate with each other in sharing the global resources
- OS deals with competing processes
 - carefully allocating resources
 - properly isolating processes from each other
- OS deals with cooperating processes
 - providing mechanisms to share resources

Processes: Competing

- Processes that do not work together cannot affect the execution of each other, but they can compete for devices and other resources
- Example: Independent processes running on a computer
- Properties: Deterministic; reproducible
 - Can stop and restart without side effects
 - Can proceed at arbitrary rate

Processes: Cooperating

- Processes that are aware of each other, and directly (by exchanging messages) or indirectly (by sharing a common object) work together, may affect the execution of each other
- Example: Transaction processes in an airline reservation system

Properties:

- Share a common object or exchange messages
- Non-deterministic; May be irreproducible
- Subject to race conditions coming up!

Why Cooperation?

- Cooperation clearly presents challenges why do we want it?
- We may want to share resources:
 - Sharing a global task queue
- We may want to do things faster:
 - Read next block while processing current one; divide a job into pieces and execute concurrently
- We may want to solve problems modularly UNIX example:

```
cat infile | tr ' '\012' | tr '[A-Z]' '[a-z]' | sort | uniq -c
```

Problem with Original application..

- Hard to understand or executing programs
- Instructions of the prog B = B * 2 arbitrarily
- A = 1B = 2A = B + 1
 - For cooperating processes, the order of (some) instructions are irrelevant
 - However, certain instruction combinations must be avoided, for example:

Process A	Process B	concurrent access
A = 1;	B = 2;	does not matter
A = B + 1;	B = B * 2;	important!

Race Conditions

- When two or more processes are reading or writing some shared data and final result depends on who runs precisely when is a race condition
- How to avoid race conditions?
 - Prohibit more than one process from reading and writing shared data at the same time
 - Essentially we need mutual exclusion
- Mutual exclusion:
 - When one process is reading or writing a shared data, other processes should be prevented from doing the same
 - Providing mutual exclusion in OS is a major design issue

An Example

Correct balance = \$100 (\$50 withdrawal and \$50 deposit)

A & B are updating a drawing and B depositing.

Initial halance = \$100 Process A

R1 <- \$100

balance <- R1 = \$50

Process B

Possible values for balance are \$50, \$150, and \$100!

An Example....

Suppose we have the following code for the account transactions

authenticate user open account load R1, balance load R2, amount (-ve for withdrawal) add R1, R2 store R1, balance close account display account info

An Example....

Suppose we have the following code for the account transactions

> authenticate user open account

load R1, balance Critical section

load R2, amount (-ve for withdrawal)

add R1, R2

store R1, balance

close account

display account info

Critical Section

- Part of the program that accesses shared data
- If we arrange the program runs such that no two programs are in their critical sections at the same time, race conditions can be avoided processes

Critical Section

- For multiple programs to cooperate correctly and efficiently:
 - No two processes may be simultaneously in their critical sections
 - No assumptions be made about speeds or number of CPUs
 - No process running outside its critical section may block other processes
 - No process should have to wait forever to enter its critical section

Critical Sections

- Critical region execution should be atomic i.e., its runs "all or none"
- Should not be interrupted in the middle
- For efficiency, we need to minimize the length of the critical sections
- Most inefficient scenario
 - Whole program is a critical section no multiprogramming!

Road to a Solution

Simplest solution:

- Disable all interrupts
- This should work in a single processor situation
- Because interrupts cause out-of-order execution due to interrupt servicing
- With interrupts disabled, a process will run until it yields the resource voluntarily

Not practical:

- OS won't allow a user process to disable all interrupts – OS operation will be hindered too!
- Does not work on multiprocessors

Road to a Solution

- Idea: To come up with a software solution
- Use "lock" variables to prevent two processes entering the critical section at the same time – all along we are talking about a single critical section
- Use variable lock
- # If lock == 0 set lock =1 and enter_region
- If lock == 1 wait until lock becomes 0
- Does not work, Why??

Strict Alternation

- Two processes take turns in entering the critical section
- Global variable turn set either to 0 or 1

```
Process 0
                            Process 1
while (TRUE) { while (TRUE) {
   while (turn !=0);
                            while (turn !=1);
                            critical section();
   critical section();
   turn = 1;
                            turn = 0;
   non critical();
                            non critical();
```

Strict Alternation


- What is the problem with strict alternation?
- We can have starvation, why??
- What are the other drawbacks?
 - Continuously testing a variable until some value appears is called busy waiting
 - Busy waiting wastes CPU time should be used when the expected wait is short
 - A lock that uses busy waiting is called spin lock

Example

Kernel level multi-threads are used for concurrent processing in a data-parallel application. The application has a critical section. If a single thread of execution is used the critical section takes 2 seconds and other parts take 6 seconds. We have a large dataset so we use 2 threads. What is the run time? We have an even larger dataset so we use 8 threads. What is the run time?

Assume single CPU and ideal time sharing (no overhead). All threads starting at the same time.

Locks – An Illutration



Mutual Exclusion: First Attempt

The simplest mutual exclusion strategy is taking turns as considered earlier

```
/* process 0 */
.
.
while (turn != 0);
/* critical section */
turn = 1;
.
.
```

```
/* process 1 */
.
.
.
while (turn != 1);
/* critical section */
turn = 0;
.
```

Mutual Exclusion: Second Attempt

- First attempt problem single key shared by the two processes
- Each have their own key to the critical section
- Solution does not work! Why??

```
/* process 0 */
.
.
while (flag[1]);
flag[0] = true;
/* critical section */
flag[0] = false;
.
.
```

```
/* process 1 */
.
.
while (flag[0]);
flag[1] = true;
/* critical section */
flag[1] = false;
.
.
```

Mutual Exclusion: Third Attempt

- This works, i.e., provides mutual exclusion
- Has deadlock why?

```
/* process 0 */
.
flag[0] = true;
while (flag[1]);
/* critical section */
flag[0] = false;
.
.
```

```
/* process 1 */
.
.
flag[1] = true;
while (flag[0]);
/* critical section */
flag[1] = false;
.
.
```

Mutual Exclusion: Fourth Attempt

- This works
- Has livelock why?

```
/* process 0 */
flag[0] = true;
while (flag[1])
        flag[0] = false;
        /* random delay */
        flag[0] = true;
/* critical section */
flag[0] = false;
```

```
/* process 1 */
flag[1] = true;
while (flag[0])
        flag[1] = false;
        /* random delay */
        flag[1] = true;
/* critical section */
flag[1] = false;
```

Peterson's Algorithm

Can Hardware Help?

- Dekker's and Peterson's algorithms are pure software solutions
- Can hardware provide any help?
 - make the solution more efficient
 - make it scalable to more processes?
- Yes!
- Current microprocessors have hardware instructions supporting mutual exclusion

Test and Lock

- TSL RX, LOCK is a typical CPU instruction providing support for mutual exclusion
 - read the contents of memory location LOCK into register RX and stores a non-zero value at memory location LOCK
 - operation of reading and writing are indivisible atomic

```
enter_section:
    TSL REGISTER, LOCK
    // copy lock to reg and set lock to 1
    CMP REGISTER, #0
    // was lock zero??
    JNE enter_section
    // if non zero, lock was set
    RET
```

```
leave_region:
MOVE LOCK, #0
RET
```

Properties of Machine Instruction Approach

Advantages:

- applicable to any number of processes
- can be used with single processor or multiple processors that share a single memory
- simple and easy to verify
- can be used to support multiple critical sections, i.e., define a separate variable for each critical section

Properties of Machine Instruction Approach

- Disadvantages:
 - Busy waiting is employed process waiting to get into a critical section consumes CPU time
 - Starvation is possible selection of entering process is arbitrary when multiple processes are contending to enter

Busy Waiting Approaches

- Mutual exclusion schemes discussed so far are based on busy waiting
- Busy waiting not desirable:
- Suppose a computer runs two processes H: high priority and L: low priority
 - scheduler always runs H when it is in ready state
 - at a certain time L is in its critical section and H become runnable
 - H begins busy waiting to enter the critical section
 - L is never scheduled to leave the critical section
 - there is a deadlock
 - this situation is sometimes referred to as the priority inversion problem

Sleep/Wakeup Approach

- Alternative to busy waiting that is inefficient and deadlock prone is to use a sleep/wakeup approach
- Implemented by the Semaphores

Fundamental principle:

- two or more processes can cooperate by sending simple messages
- a process can be forced to stop at a specific place until it receives a specific message
- complex coordination can be satisfied by appropriately structuring these messages
- for messaging a special variable called semaphore s
 is used
- to transmit a message via a semaphore a process executes signal(s)
- to receive a message via a semaphore a process executes wait(s)

- Operations defined on a semaphore:
 - can be initialized to a nonnegative value set semaphore
 - wait decrements the semaphore value if value becomes negative, process executing wait is blocked
 - signal increments the semaphore value if value is not positive, a process blocked by a wait operation is unblocked

A definition of semaphore primitives...

```
struct semaphore {
    int count;
    queueType queue;
}
```

```
void wait(semaphore s)
{
    s.count--;
    if (s.count < 0)
        {
        place this process in s.queue;
        block this process
    }
}</pre>
```

```
void signal(semaphore s)
{
    s.count++;
    if (s.count <= 0)
    {
        remove a process P
        from s.queue;
        place process P on
        ready list;
    }
}</pre>
```

- Wait and Signal primitives are assumed to be atomic
 - they cannot be interrupted and treated as an indivisible step
- A queue is used to hold the processes waiting on a semaphore
- How are the processes removed from this queue?
 - FIFO: process blocked longest should be released next – strong semaphore
 - Order not specified weak semaphore

Type of sema

- Semaphores are usually ways:
- These are initial values.
 A semaphore can have negative value at any time .. many threads or processes waiting on it
- binary—is a semaphore with of 0 or 1
 - Or a value of FALSE RUE if you prefer
 - Initialized to 1 for mutex applications
- counting—is a semaphore with an integer value ranging between 0 and an arbitrarily large number initial value might represent the number of units of the critical resources that are available also known as a general semaphore

Producer-Consumer: Semaphores

```
semaphore mutex = 1;
semaphore empty = N;
semaphore full = 0;
producer() {
  int item;
  while(TRUE) {
      item = produce_item();
      wait(&empty);
      wait(&mutex);
      insert_item(item);
      signal(&mutex);
      signal(&full);
```

```
// protects the critical section
// counts the empty slots
// counts full buffer slots
consumer() {
  int item;
   while(TRUE) {
       wait(&full);
       wait(&mutex);
       item = remove_item();
       signal(&mutex);
       signal(&empty);
       consume_item(item);
```

Producer-Consumer: Semaphores

- One binary semaphore mutex to ensure only one process is manipulating the buffers at a time
- Empty and Full counting semaphores, to count the number of empty or full buffer slots respectively
 - Empty initialized to N, so waiting on empty means waiting if there are no empty slots (buffer full!)
 - Full initialized to 0, so waiting on full means waiting if there are no full slots (buffer empty!)

Primitives Revisited

The synchronization primitives discussed so far are all of the form:


```
entry protocol
     < access data >
exit protocol
```

- Semaphores give us some abstraction: implementation of the protocol to access shared data is transparent to the user
- More abstraction would be of additional benefit (as it often is!)

- A monitor is a high-level (programming language) abstraction that combines (and hides) the following:
 - shared data
 - operations on the data
 - synchronization using condition variables


- Mutual exclusion --- not the only thing we need for concurrency
- Abstraction provided by monitors allows us to deal with many different issues in concurrency
 - block processes when a resource is busy
- With a monitor data type, we define a set of variables that define the state of an instance of the type, and a set of procedures that define the externally available operations on the type

- Monitors are more than just objects
- A monitor ensures that only one process at a time can be active within the monitor – so you don't need to code this explicitly



- Just this on its own though isn't enough need the additional synchronization mechanisms
- Monitors use condition variables to provide user-tailored synchronization and manage each with a separate queue for each condition
- The only operations available on these variables are WAIT and SIGNAL
 - wait suspends process that executes it until someone else does a signal (different from semaphore wait!)
 - signal resumes one suspended process. no effect if nobody's waiting (different from semaphore free/signal)!

Monitor Abstraction



How Monitors Work

- Remember only one process can be active in the monitor at once. Some will be waiting to get in, others will be waiting on conditions in the monitor

 Hoare's Monitor
- If P executes x.signal (signal for condition x), and there's a process Q suspended on x, both can't be active at once. 2 possibilities;
 - ♦ P waits on some condition till Q leaves monitor

Hansen's Monitor

- Q waits on some condition till P leaves monitor
- P executes signal as the last operation, it leaves monitor automatically, resuming Q

Problems with synch Primitives

- Starvation: the situation in which some processes are making progress toward completion but some others are locked out of the resource(s)
- Deadlock: the situation in which two or more processes are locked out of the resource(s) that are held by each other

Problems with synch Primitives

- The most important deficiency of the primitives discussed so far is that they were all designed on the concept of one or more CPUs accessing a 'common' memory
 - Hence, these primitives are not applicable to distributed systems. Solution? Message passing...

Synch Primitives—Summary

