

Scan Report

February 1, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Web_Hao”. The scan started at Sun Feb 1 05:12:13 2026 UTC and ended at Sun Feb 1 06:04:09 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.168.2.10	2
2.1.1	Medium 80/tcp	2
2.1.2	Low general/tcp	4
2.1.3	Low 22/tcp	5

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.2.10	0	0	2	2	0	0
Total: 1	0	0	2	2	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 4 results selected by the filtering described above. Before filtering there were 54 results.

2 Results per Host

2.1 192.168.2.10

Host scan start Sun Feb 1 05:13:21 2026 UTC

Host scan end Sun Feb 1 06:04:03 2026 UTC

Service (Port)	Threat Level
80/tcp	Medium
general/tcp	Low
22/tcp	Low

2.1.1 Medium 80/tcp

Medium (CVSS: 5.0)

NVT: Missing 'HttpOnly' Cookie Attribute (HTTP)

Summary

The remote HTTP web server / application is missing to set the 'HttpOnly' cookie attribute for one or more sent HTTP cookie.

Quality of Detection (QoD): 70%

... continues on next page ...

...continued from previous page ...
Vulnerability Detection Result The cookie(s): Set-Cookie: PHPSESSID=***replaced***; path=/ is/are missing the "HttpOnly" cookie attribute.
Solution: Solution type: Mitigation - Set the 'HttpOnly' cookie attribute for any session cookie - Evaluate / do an own assessment of the security impact on the web server / application and create an override for this result if there is none (this can't be checked automatically by this VT)
Affected Software/OS Any web application with session handling in cookies.
Vulnerability Insight The flaw exists if a session cookie is not using the 'HttpOnly' cookie attribute. This allows a cookie to be accessed by JavaScript which could lead to session hijacking attacks.
Vulnerability Detection Method Checks all cookies sent by the remote HTTP web server / application for a missing 'HttpOnly' cookie attribute. Details: Missing 'HttpOnly' Cookie Attribute (HTTP) OID:1.3.6.1.4.1.25623.1.0.105925 Version used: 2024-01-12T16:12:12Z
References url: https://www.rfc-editor.org/rfc/rfc6265#section-5.2.6 url: https://owasp.org/www-community/HttpOnly url: https://wiki.owasp.org/index.php/Testing_for_cookies_attributes_(OTG-SESS-0↪02)
Medium (CVSS: 4.8) NVT: Cleartext Transmission of Sensitive Information via HTTP
Summary The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following input fields were identified (URL:input name): http://192.168.2.10/:password http://192.168.2.10/index.php:password
... continues on next page ...

...continued from previous page ...
Impact An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.
Solution: Solution type: Workaround Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.
Affected Software/OS Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.
Vulnerability Detection Method Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection. The script is currently checking the following: - HTTP Basic Authentication (Basic Auth) - HTTP Forms (e.g. Login) with input field of type 'password' Details: Cleartext Transmission of Sensitive Information via HTTP OID:1.3.6.1.4.1.25623.1.0.108440 Version used: 2023-09-07T05:05:21Z
References url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure url: https://cwe.mitre.org/data/definitions/319.html

[\[return to 192.168.2.10 \]](#)

2.1.2 Low general/tcp

Low (CVSS: 2.6) NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result ... continues on next page ...

...continued from previous page ...
It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 4175300707 Packet 2: 4175301803
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090

[\[return to 192.168.2.10 \]](#)

2.1.3 Low 22/tcp

Low (CVSS: 2.6) NVT: Weak MAC Algorithm(s) Supported (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↪)
Summary The remote SSH server is configured to allow / support weak MAC algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak client-to-server MAC algorithm ↪(s): umac-64-etm@openssh.com umac-64@openssh.com The remote SSH server supports the following weak server-to-client MAC algorithm ↪(s): umac-64-etm@openssh.com umac-64@openssh.com
Solution: Solution type: Mitigation Disable the reported weak MAC algorithm(s).
Vulnerability Detection Method Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak MAC algorithms are defined as the following: - MD5 based algorithms - 96-bit based algorithms - 64-bit based algorithms - 'none' algorithm Details: Weak MAC Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.105610 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565)
References
... continues on next page ...

...continued from previous page ...

url: <https://www.rfc-editor.org/rfc/rfc6668>

url: <https://www.rfc-editor.org/rfc/rfc4253#section-6.4>

[[return to 192.168.2.10](#)]

This file was automatically generated.