

Lab 10: Structural Bioinformatics 1

Nicholas Chiu

1. PDB Statistics

```
## PDB Statistics
csv <- "C:\\Users\\iWumb\\OneDrive\\Desktop\\UCSD\\Winter 24\\BIMM143\\BIMM143 R\\class10\\
df <- read.csv(csv, header=TRUE, stringsAsFactors=FALSE)

df
```

	Molecular.Type	X.ray	EM	NMR	Multiple.methods	Neutron	Other
1	Protein (only)	161,793	12,645	12,343	202	74	32
2	Protein/Oligosaccharide	9,358	2,177	34	8	2	0
3	Protein/NA	8,405	3,933	286	7	0	0
4	Nucleic acid (only)	2,760	125	1,478	14	3	1
5	Other	164	9	33	0	0	0
6	Oligosaccharide (only)	11	0	6	1	0	4
	Total						
1	187,089						
2	11,579						
3	12,631						
4	4,381						
5	206						
6	22						

```
totals <- 187089 + 11579 + 12631 + 4381 + 206 + 22

xrayEM <- 161793+12645+9358+2177+8405+3933+2760+125+164+9+11

# proportion solved by xray or EM
xrayEM / totals
```

```
[1] 0.9327121
```

```
proteins <- 187089 + 11579 + 12631  
  
# proportion of protein  
proteins/totals
```

```
[1] 0.9786529
```


Q1: 93.3% of structures in the PDB are solved by x-ray and EM

Q2: 0.979 of structures in the PDB are protein

Q3: There are 455 HIV proteases in the current PDB

2. Visualizing the HIV-1 protease structure

Q4: We only see one atom per water molecule because only the oxygen is important to show in the diagram.



Q5: HOH 308



Q6:

Q7: Optional

3. Introduction to Bio3D in R

```
library(bio3d)

# Reading PDB file data into R
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

pdb

```
Call: read.pdb(file = "1hsg")
```

```
Total Models#: 1
```

```
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)
```

```
Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 172 (residues: 128)
```

```
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```

```
Protein sequence:
```

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLTTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLTTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

attributes(pdb)

```
$names
```

```
[1] "atom" "xyz" "seqres" "helix" "sheet" "calpha" "remark" "call"
```

```
$class
```

```
[1] "pdb" "sse"
```

head(pdb\$atom)

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87

```

6 ATOM      6      CG <NA>  PRO      A      1      <NA> 29.296 37.591 7.162 1 38.40
  segid elesy charge
1  <NA>      N  <NA>
2  <NA>      C  <NA>
3  <NA>      C  <NA>
4  <NA>      O  <NA>
5  <NA>      C  <NA>
6  <NA>      C  <NA>

```

```

# Predicting functional motions of a single structure
adk <- read.pdb("6s36")

```

Note: Accessing on-line PDB file
PDB has ALT records, taking A only, rm.alt=TRUE

```
adk
```

```
Call: read.pdb(file = "6s36")
```

```

Total Models#: 1
  Total Atoms#: 1898,  XYZs#: 5694  Chains#: 1  (values: A)

  Protein Atoms#: 1654  (residues/Calpha atoms#: 214)
  Nucleic acid Atoms#: 0  (residues/phosphate atoms#: 0)

  Non-protein/nucleic Atoms#: 244  (residues: 244)
  Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]

```

```

Protein sequence:
MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLV
DELVIALVKERIAQEDCRNGFLDGFPRTPQADAMKEAGINVDYVLEFDVPDELIVDKI
VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQM TAPLIG
YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG

```

```

+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call

```

```
m <- nma(adk)
```

```
Building Hessian...      Done in 0.03 seconds.  
Diagonalizing Hessian... Done in 0.53 seconds.
```

```
m
```

```
Call:
```

```
  nma.pdb(pdb = adk)
```

```
Class:
```

```
  VibrationalModes (nma)
```

```
Number of modes:
```

```
  642 (6 trivial)
```

```
Frequencies:
```

```
  Mode 7:  0.005
```

```
  Mode 8:  0.007
```

```
  Mode 9:  0.009
```


```
  Mode 10: 0.011
```

```
  Mode 11: 0.013
```

```
  Mode 12: 0.015
```

```
+ attr: modes, frequencies, force.constants, fluctuations,  
      U, L, xyz, mass, temp, triv.modes, natoms, call
```

```
plot(m)
```



```
mktrj(m, file="adk_m7.pdb")
```

4. Comparative structure analysis of Adenylate Kinase

```
## Search and retrieve ADK structures
```

```
library(bio3d)
```

```
aa <- get.seq("1ake_A")
```

Warning in get.seq("1ake_A"): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

```
aa
```

```

      1          .          .          .          .          60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLV

```


Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6S36.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6RZE.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3HPR.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb exists. Skipping download

			0%
=====			8%
=====			15%
=====			23%
=====			31%
=====			38%
=====			46%
=====			54%
=====			62%
=====			69%
=====			77%
=====			85%
=====			92%
=====			100%

Align and superpose structures

Align related PDBs

`pdbbs <- pdbaln(files, fit = TRUE, exefile="msa")`

Reading PDB files:

`pdbbs/split_chain/1AKE_A.pdb`

`pdbbs/split_chain/6S36_A.pdb`

`pdbbs/split_chain/6RZE_A.pdb`

`pdbbs/split_chain/3HPR_A.pdb`

`pdbbs/split_chain/1E4V_A.pdb`

```

pdbs/split_chain/5EJE_A.pdb
pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
...

```

Extracting sequences

```

pdb/seq: 1   name: pdbs/split_chain/1AKE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbs/split_chain/6S36_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbs/split_chain/6RZE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 4   name: pdbs/split_chain/3HPR_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 6   name: pdbs/split_chain/5EJE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 8   name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 9   name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 10  name: pdbs/split_chain/6HAM_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 11  name: pdbs/split_chain/4K46_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 13  name: pdbs/split_chain/4PZL_A.pdb

```

```

# Vector containing PDB codes for figure axis
ids <- basename.pdb(pdb$ids)

# Draw schematic alignment

## Rendering plot causes margin too large error. Commented out for submission

#par(mar = c(1, 1, 1, 1))
#plot(pdb, labels=ids)

## Annotate collected PDB structures

anno <- pdb.annotate(ids)
unique(anno$source)

```

```

[1] "Escherichia coli"
[2] "Escherichia coli K-12"
[3] "Escherichia coli 0139:H28 str. E24377A"
[4] "Escherichia coli str. K-12 substr. MDS42"
[5] "Photobacterium profundum"
[6] "Burkholderia pseudomallei 1710b"
[7] "Francisella tularensis subsp. tularensis SCHU S4"

```

```
anno
```

	structureId	chainId	macromoleculeType	chainLength	experimentalTechnique
1AKE_A	1AKE	A	Protein	214	X-ray
6S36_A	6S36	A	Protein	214	X-ray
6RZE_A	6RZE	A	Protein	214	X-ray
3HPR_A	3HPR	A	Protein	214	X-ray
1E4V_A	1E4V	A	Protein	214	X-ray
5EJE_A	5EJE	A	Protein	214	X-ray
1E4Y_A	1E4Y	A	Protein	214	X-ray
3X2S_A	3X2S	A	Protein	214	X-ray
6HAP_A	6HAP	A	Protein	214	X-ray
6HAM_A	6HAM	A	Protein	214	X-ray
4K46_A	4K46	A	Protein	214	X-ray
3GMT_A	3GMT	A	Protein	230	X-ray
4PZL_A	4PZL	A	Protein	242	X-ray
	resolution	scopDomain			pfam

1AKE_A	2.00	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)
6S36_A	1.60	<NA>	Adenylate kinase, active site lid (ADK_lid)
6RZE_A	1.69	<NA>	Adenylate kinase, active site lid (ADK_lid)
3HPR_A	2.00	<NA>	Adenylate kinase (ADK)
1E4V_A	1.85	Adenylate kinase	Adenylate kinase (ADK)
5EJE_A	1.90	<NA>	Adenylate kinase, active site lid (ADK_lid)
1E4Y_A	1.85	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)
3X2S_A	2.80	<NA>	Adenylate kinase, active site lid (ADK_lid)
6HAP_A	2.70	<NA>	Adenylate kinase (ADK)
6HAM_A	2.55	<NA>	Adenylate kinase, active site lid (ADK_lid)
4K46_A	2.01	<NA>	Adenylate kinase, active site lid (ADK_lid)
3GMT_A	2.10	<NA>	Adenylate kinase, active site lid (ADK_lid)
4PZL_A	2.10	<NA>	Adenylate kinase, active site lid (ADK_lid)

ligandId

1AKE_A	AP5
6S36_A	CL (3),NA,MG (2)
6RZE_A	NA (3),CL (2)
3HPR_A	AP5
1E4V_A	AP5
5EJE_A	AP5,CO
1E4Y_A	AP5
3X2S_A	JPY (2),AP5,MG
6HAP_A	AP5
6HAM_A	AP5
4K46_A	ADP,AMP,P04
3GMT_A	SO4 (2)
4PZL_A	CA,FMT,GOL

ligandName

1AKE_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
6S36_A	CHLORIDE ION (3),SODIUM ION,MAGNESIUM ION (2)
6RZE_A	SODIUM ION (3),CHLORIDE ION (2)
3HPR_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
1E4V_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
5EJE_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE,COBALT (II) ION
1E4Y_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
3X2S_A	N-(pyren-1-ylmethyl)acetamide (2),BIS(ADENOSINE)-5'-PENTAPHOSPHATE,MAGNESIUM ION
6HAP_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
6HAM_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
4K46_A	ADENOSINE-5'-DIPHOSPHATE,ADENOSINE MONOPHOSPHATE,PHOSPHATE ION
3GMT_A	SULFATE ION (2)
4PZL_A	CALCIUM ION,FORMIC ACID,GLYCEROL

source

1AKE_A	Escherichia coli
--------	------------------

6S36_A	Escherichia coli
6RZE_A	Escherichia coli
3HPR_A	Escherichia coli K-12
1E4V_A	Escherichia coli
5EJE_A	Escherichia coli 0139:H28 str. E24377A
1E4Y_A	Escherichia coli
3X2S_A	Escherichia coli str. K-12 substr. MDS42
6HAP_A	Escherichia coli 0139:H28 str. E24377A
6HAM_A	Escherichia coli K-12
4K46_A	Photobacterium profundum
3GMT_A	Burkholderia pseudomallei 1710b
4PZL_A	Francisella tularensis subsp. tularensis SCHU S4

1AKE_A STRUCTURE OF THE COMPLEX BETWEEN ADENYLATE KINASE FROM ESCHERICHIA COLI AND THE INHIB

6S36_A
6RZE_A
3HPR_A
1E4V_A
5EJE_A
1E4Y_A
3X2S_A
6HAP_A
6HAM_A
4K46_A
3GMT_A
4PZL_A

Cryst

The crys

		citation	rObserved	rFree
1AKE_A	Muller, C.W., et al.	J Mol Biol (1992)	0.19600	NA
6S36_A	Rogne, P., et al.	Biochemistry (2019)	0.16320	0.23560
6RZE_A	Rogne, P., et al.	Biochemistry (2019)	0.18650	0.23500
3HPR_A	Schrank, T.P., et al.	Proc Natl Acad Sci U S A (2009)	0.21000	0.24320
1E4V_A	Muller, C.W., et al.	Proteins (1993)	0.19600	NA
5EJE_A	Kovermann, M., et al.	Proc Natl Acad Sci U S A (2017)	0.18890	0.23580
1E4Y_A	Muller, C.W., et al.	Proteins (1993)	0.17800	NA
3X2S_A	Fujii, A., et al.	Bioconj Chem (2015)	0.20700	0.25600
6HAP_A	Kantaev, R., et al.	J Phys Chem B (2018)	0.22630	0.27760
6HAM_A	Kantaev, R., et al.	J Phys Chem B (2018)	0.20511	0.24325
4K46_A	Cho, Y.-J., et al.	To be published	0.17000	0.22290
3GMT_A	Buchko, G.W., et al.	Biochem Biophys Res Commun (2010)	0.23800	0.29500
4PZL_A	Tan, K., et al.	To be published	0.19360	0.23680

rWork spaceGroup

1AKE_A	0.19600	P 21 2 21
6S36_A	0.15940	C 1 2 1

```





6RZE_A 0.18190    C 1 2 1
3HPR_A 0.20620    P 21 21 2
1E4V_A 0.19600    P 21 2 21
5EJE_A 0.18630    P 21 2 21
1E4Y_A 0.17800    P 1 21 1
3X2S_A 0.20700    P 21 21 21
6HAP_A 0.22370    I 2 2 2
6HAM_A 0.20311      P 43
4K46_A 0.16730    P 21 21 21
3GMT_A 0.23500    P 1 21 1
4PZL_A 0.19130      P 32

```

```

## PCA
# Perform PCA
pc.xray <- pca(pdbbs)
plot(pc.xray)

```



```

# Calculate RMSD
rd <- rmsd(pdbbs)

```

Warning in rmsd(pdbbs): No indices provided, using the 204 non NA positions


```
# Structure-based clustering
hc.rd <- hclust(dist(rd))
grps.rd <- cutree(hc.rd, k=3)

plot(pc.xray, 1:2, col="grey50", bg=grps.rd, pch=21, cex=1)
```

