В							Resistance
	lattery	Holder Battery; Coin Battery; 1 Cell; Tab; 0.787 in. Dia.	BT1	PCB- 65mdyjamygte6kia jklb-1	CMP- fda93507aa51226e -3	1	
0.1μF C	Cap	CAP CER 0.1UF 50V X7R 0603	C1, C2, C3, C4, C5, C6, C8, C10, C15, C16	PCB- mhhqftc5ilnrg4qi8 ds6-1	CMP- 1af8d38ac64bc53f -4	10	
1uF C	04	0603 0.1 uF 16 V ± 10 % Tolerance X7R SMT Multilayer Ceramic Capacitor	C7, C9, C11, C17	0603C_B	CMP-123646-11	4	
2.2uF C	ageo CO603KRX7R7BB	0603 0.1 uF 16 V ± 10 % Tolerance X7R SMT Multilayer Ceramic Capacitor	C12, C13	0603C_B	CMP-123646-11	2	
	Sameboy artridge slot	Gameboy cartridge slot	CN1	PCB- uwgfzvbds2v1ko1 1221f-1	Gameboy cartridge slot-1	1	
Fi	CI 20021121- 10010C1LF	Conn Unshrouded Header HDR 10 POS 1.27mm Solder ST SMD T/R	CN2	PCB- ch0b5fvyy24ict2e1 x4o-1	CMP- c6d60ecf2c091911 -2	1	
		Single Port 5 Contact Horizontal Micro B USB 2.0 Connector	CN3	PCB- edlm2od7brxgpj7 8b9fm-1	CMP- 2509ed477c75face -11	1	
SI	BR80520LT3G	Schottky Power Rectifier, 2-Pin SOD-123, Pb-Free, Tape and Reel	D1, D2, D3, D4	ONSC-SOD-123-2- 425-04_V	CMP-822511-2, SBR80520LT3G-2, SBR80520LT3G-2, SBR80520LT3G-2	4	
		PTC Resettable Fuse 0.05A(hold) 0.15A(trip) 60VDC 10A 0.4W 1.5s 3.60hm SMD Solder Pad 3.5 X 1.8 X 0.85mm T/R	F1, F2	PCB- g6xbbgrf1j6f6hdc s2hx-1	Bel Fuse 0ZCJ0005FF2E-1	2	
F	ai Tech CM1608KF- 01T03	Magnetic beads, 600R, 350mA, 0603, FCM1608KF- 601T03, Tai-tech	L1	PCB- roep9w497ffvgejiy 0y8-1	CMP- bcc17660c9806306 -2	1	
	Vurth Elektronik 1774040243R	Spacer Material: Steel, Tin-Plated Mounting: SMT Series: WA-SMST Thread D: M2	P1, P2, P3, P4	PCB- 6bnlwl84ripo9jvz9 fp6-1	CMP- 48c4825e7a369703 -1	4	
В	C848BLT3G	General Purpose Transistor, NPN	Q1	ONSC-SOT-23-3- 318-08_V	CMP-860696-2	1	
	AGEO RC0603JR- 1747RL	Res Thick Film 0603 47 Ohm 5% 0.1W(1/10W) ?100ppm/C Molded SMD Paper T/R	R1	R0603_A	CMP- c8530329081a1794 -1	1	47
	AGEO RC0603JR- 17510RL	Res Thick Film 0603 47 Ohm 5% 0.1W(1/10W) ?100ppm/C Molded SMD Paper T/R	R3, R5	R0603_A	CMP- c8530329081a1794 -1	2	510
		Res Thick Film 0603 47 Ohm 5% 0.1W(1/10W)	R4, R6, R7, R8, R9, R10, R11	R0603_A	CMP- c8530329081a1794 -1	7	10k
Т	'estPad	TestPad	IPI, IP2, IP3, IP4, IP5, IP7, IP6, IP9, IP91, IP7, IP7, IP8, IP9, IP91, IP92, IP92, IP92, IP92, IP93, IP94, IP94, IP95, IP93, IP94, IP95, IP96, IP97, IP96, IP97, IP98, IP99, IP98, IP89, IP98, IP88,	PCB- qqaworq3uifq0h8 koz5g-1	CMP- 822f97gjbv438nmx igx5-1	82	
S	TM32F407VGT6	ARM Cortex-M4 32-bit MCU+FPU, 210 DMIPS, 1024 kB Flash, 192 kB Internal RAM, 82 I/Os, 100-pin LQFP, -40 to 85 degC. Tray	U1	STM-LQFP100_N	STM32F407VGT6-4	1	
	CR2EF33 3.3V nos. LDO SOT23-5	LDO Regulator Pos 3.3V 0.2A 5-	U2	PCB- vnad9jnmv6teh67t	CMP- a34c689ca3827c8b	1	
	/urata CSTNE8M00	Pin SOT-25 Ceramic Resonator	Y1	clgx-1 CAPMP3213X05M	-1 CMP-9b4a57327c60	1	



