



Portable Energy Storage NR Series



Output

AC Output: 2x100~120V or 2x220V~240V(EU/CH)
Continuous 300W, instant startup 600W, pure sine wave output

1*USB-C Output: 5V/3A 9V/3A 12V/3A 15V/3A
20V/2.25A*PD 45W

2*USB-A Output: 5V/3A 9V/2A 12V/1.5A*QC3.0
18W Quick Charge

4*DC Output: 4*5521/12V10A Max 120W

1*LED Light

input

AC Input: 90V~240V(Max 55W)

Solar(MPPT)Input: 11-30V(MAX 60W)

Other information

Capacity: 300wh

Battery type: LFP (Lithium Iron Phosphate)

Life Cycles: 2000+ Cycles to 80% Original Capacity

Weight: ~3.5kg

Dimensions (LxWxD): 350x170x240mm

Operating Temperature: -20~55°C

Charging temperature: 0~50°C



NR-01-300W



NR-02-500W

Output

AC Output:2x100~120V or 2×220V~240V(EU/CH)
Continuous 300W, instant startup 600W, pure sine wave output

1*USB-C Output:5V/3A 9V/3A 12V/3A 15V/3A
20V/2.25A *PD 45W

2*USB-A Output:5V/3A 9V/2A 12V/1.5A QC3.0
18W Quick Charge

4*DC Output:4*5521/12V10A Max 120W

1*LED Light

input

AC Input:90V~240V(Max 100W)

Solar(MPPT)Input:11-30V(MAX 120W)

Other information

Capacity:536wh

Battery type:LFP (Lithium Iron Phosphate)

Life Cycles:2000+Cycles to 80%Original Capacity

Weight:≈5.0kg

Dimensions (LxW×D):350×170×240mm

Operating Temperature:-20-55℃

Charging temperature:0-50℃

