

Topic 6: MapReduce Framework and Model

1. MapReduce Overview

What is MapReduce?

- **Most important processing framework** in Hadoop
- **Platform and language-independent** programming model
- Core of most big data and NoSQL platforms
- **Pattern/format** for writing programs to process large datasets

Historical Context

- Introduced by **Google in 2004**
- Breakthrough in big data technology history
- **Hadoop v1** supported MapReduce only
- Basis for high-level languages (Hive, Pig)
- Heavily influenced Spark concepts

Programming Model Structure

- **Map phase:** Process input data
- **Reduce phase:** Aggregate results
- Additional phases: Partition, Shuffle and Sort, Combine

2. Problems MapReduce Solves

Limitations of Early Distributed Computing

1. Complexity in parallel programming

- Manual data distribution
- Complex synchronization
- Error-prone coding

2. Hardware failures

- Node failures common in large clusters
- Difficult to handle programmatically

3. Bottlenecks in data exchange

- Network congestion
- Data movement overhead

4. Scalability problems

- Difficulty adding more nodes
- Performance degradation

MapReduce Design Goals (2004 Google Paper)

1. Automatic parallelization and distribution

- Framework handles data distribution
- Developer focuses on business logic

2. Fault tolerance

- Automatic recovery from failures
- Task re-execution on failure

3. Input/Output (I/O) scheduling

- Optimized data access
- Data locality awareness

4. Status and monitoring

- Progress tracking
- Job monitoring tools

3. MapReduce Data Model: Key-Value Pairs

Fundamental Concept

- **All data** represented as key-value pairs
- Input, output, and intermediate records
- Also called name-value or attribute-value pairs

Key-Value Pair Structure

Key: Identifier (e.g., attribute name)
Value: Data associated with key

Example:

Key: "City"	Value: "Sydney"
Key: "Employer"	Value: "Cloudera"

Important Properties

- Keys **not required to be unique** in MapReduce
- Values can be **simple** or **complex objects**
- Flexible data representation

4. MapReduce Processing Model

Complete Data Flow

```
Input Data (HDFS)
  ↓
InputFormat & RecordReader
  ↓
Map Phase (Multiple Mappers in parallel)
  ↓
Partition (Group by key)
  ↓
Shuffle and Sort (Transfer and organize)
  ↓
[Optional: Combine Phase]
  ↓
Reduce Phase (Multiple Reducers in parallel)
  ↓
Output (HDFS)
```

Processing Stages

1. InputFormat and RecordReader

- **InputFormat:** Defines how to split input data
- **RecordReader:** Converts input into key-value pairs
- Input split typically = HDFS block (128MB default)

2. Map Phase

- **Function signature:** `map(in_key, in_value) → list(intermediate_key, intermediate_value)`
- Processes one record at a time
- Emits zero or more key-value pairs
- **n blocks → at least n Map tasks**

3. Partition Phase

- **Partitioner** function determines which Reducer gets each key
- **Ensures:** Each key → exactly one Reducer
- **Number of partitions** = number of Reducers
- Can be customized for specific requirements

4. Shuffle and Sort

- **"Magic" of MapReduce** - where optimization happens
- **Shuffle:** Transfer data from Mappers to Reducers
- **Sort:** Group all values for each key together
- **Goal:** Minimize network data transmission

5. Combine Phase (Optional)

- **Local aggregation** on Mapper node

- Reduces data sent to Reducers
- **Requirements:** Function must be **commutative** and **associative**
- **Examples:** SUM, COUNT work; AVERAGE doesn't

6. Reduce Phase

- **Function signature:** `reduce(intermediate_key, list(intermediate_value)) → (out_key, out_value)`
- Processes all values for one key
- Emits zero or more output key-value pairs

5. WordCount Example (MapReduce "Hello World")

Problem

Count frequency of each word in a large text corpus

Map Function

```
function Map(Long lineNo, String line):  
    // lineNo: line position in text  
    // line: actual text of line  
    for each word w in line:  
        emit(w, 1)
```

Example:

```
Input:  "Hello World Hello"  
Output: (Hello, 1), (World, 1), (Hello, 1)
```

Shuffle and Sort (Automatic)

```
Groups:  
(Hello, [1, 1])  
(World, [1])
```

Reduce Function

```
function Reduce(String word, List<int> counts):  
    // word: the word  
    // counts: list of all counts for this word  
    sum = 0  
    for each c in counts:
```

```
    sum += c
    emit(word, sum)
```

Example:

```
Input: (Hello, [1, 1])
Output: (Hello, 2)

Input: (World, [1])
Output: (World, 1)
```

6. Common Map and Reduce Patterns

Common Map Functions

1. Filtering

```
// Filter log messages for errors only
Map(k, v) =
    if (ERROR in v) then
        emit(k, v)
```

2. Value Transformation

```
// Convert text to lowercase
Map(k, v) =
    emit(k, v.toLowerCase())
```

3. Projection

```
// Extract specific fields
Map(k, v) =
    emit(v.field1, v.field2)
```

Common Reduce Functions

1. Sum Reducer (Most Common)

```
reduce(k, list) =
    sum = 0
    for int i in list:
```

```
    sum += i
    emit(k, sum)
```

2. Count Reducer

```
reduce(k, list) =
    emit(k, list.length)
```

3. Max/Min Reducer

```
reduce(k, list) =
    max_val = MIN_VALUE
    for val in list:
        if val > max_val:
            max_val = val
    emit(k, max_val)
```

4. Average Reducer

```
reduce(k, list) =
    sum = 0
    count = 0
    for val in list:
        sum += val
        count += 1
    emit(k, sum/count)
```

7. Real-World Example: Shopping Cart Analysis

Problem

Analyze abandoned shopping carts to understand purchasing behavior

Input Data

```
User logs containing:
- User ID
- Items added to cart
- Items purchased
- Session information
```

Map Function

```
Map(logEntry):  
  userId = logEntry.userId  
  abandoned = logEntry.cartItems - logEntry.purchased  
  
  for item in abandoned:  
    emit(item, 1) // Count abandoned items
```

Reduce Function

```
Reduce(item, counts):  
  totalAbandoned = sum(counts)  
  emit(item, totalAbandoned)
```

Result

Identify most commonly abandoned items for business insights

8. Average Social Contacts Example

Problem

For 1 billion people, compute average number of social contacts by age

SQL Equivalent

```
SELECT age, AVG(contacts)  
FROM social.person  
GROUP BY age
```

Map Function

```
function Map:  
  input: integer K (batch of 1M records)  
  
  for each social.person record in K-th batch:  
    let Y = person.age  
    let N = person.contacts  
    produce output (Y, (N, 1))  
  end for  
end function
```

Example:

```

Input records:
{age: 25, contacts: 150}
{age: 25, contacts: 200}
{age: 30, contacts: 300}

```

```

Map output:
(25, (150, 1))
(25, (200, 1))
(30, (300, 1))

```

Shuffle and Sort

```

Groups by age:
(25, [(150, 1), (200, 1)])
(30, [(300, 1)])

```

Reduce Function

```

function Reduce:
  input: age Y

  S = 0      // Sum of contacts
  C_new = 0  // Count of people

  for each (N, C) in values:
    S += N * C
    C_new += C
  end for

  A = S / C_new  // Average
  produce output (Y, (A, C_new))
end function

```

Example:

```

Input:  (25, [(150, 1), (200, 1)])
Output: (25, (175, 2))  // Average = 350/2

Input:  (30, [(300, 1)])
Output: (30, (300, 1))  // Average = 300/1

```

9. Map-Only Jobs

When to Use

- No aggregation or reduction needed
- ETL (Extract, Transform, Load) operations
- File format conversions
- Image processing
- Simple filtering or transformation

Characteristics

- **Zero Reducers** configured
- **Only Map phase** executes
- **Direct output** to HDFS
- **Faster** than full MapReduce job

Example Use Cases

1. **ETL Routines:** Extract and transform data without aggregation
2. **File Conversion:** Convert CSV to JSON
3. **Image Processing:** Resize or filter images
4. **Data Validation:** Check data quality, emit errors

10. Combiner Function

Purpose

- **Local aggregation** on Mapper node **before** Shuffle and Sort
- **Reduces network traffic** between Map and Reduce
- **Mini-Reducer** running on Mapper output

Requirements for Combiner

Function must be:

1. **Commutative:** Order doesn't matter
 - Example: $a + b = b + a$ ✓
2. **Associative:** Grouping doesn't matter
 - Example: $(a + b) + c = a + (b + c)$ ✓

Examples

Can Use Combiner:

- SUM: Commutative and associative ✓
- COUNT: Commutative and associative ✓
- MAX/MIN: Commutative and associative ✓

Cannot Use Combiner:

- AVERAGE: Not associative X
 - $(1 + 2)/2 + 3 \neq 1 + (2 + 3)/2$

- **MEDIAN:** Not commutative or associative \times

Performance Impact

Without Combiner:

Mapper output: 1M records \rightarrow Network \rightarrow Reducer

Network traffic: HIGH

With Combiner:

Mapper output: 1M records \rightarrow Combiner \rightarrow 1K records \rightarrow Network \rightarrow Reducer

Network traffic: LOW (99.9% reduction)

11. Election Analogy for MapReduce

Voting Process

Map Phase (Polling Stations):

- Each polling station (Mapper) collects votes
- Outputs: (Candidate, Vote) pairs
- Multiple stations work in parallel

Partition (Courier Assignment):

- Group votes by district/region
- Assign to counting centers

Shuffle and Sort (Vote Transport):

- Transport votes to counting centers
- Sort by candidate at each center

Combine (Preliminary Count):

- Each station pre-counts votes
- Reduces data sent to central count

Reduce Phase (Central Counting):

- Each counting center (Reducer) totals votes for candidates
- Final output: (Candidate, Total Votes)

Key Points for Exam

Core Concepts

1. **MapReduce = Map + Shuffle/Sort + Reduce**
2. **Key-Value Pairs:** Fundamental data model
3. **Automatic Parallelization:** Framework handles distribution

4. **Fault Tolerance:** Automatic recovery from failures
5. **Data Locality:** Process data where it's stored

Function Signatures

Map: $(K1, V1) \rightarrow \text{list}(K2, V2)$ **Reduce:** $(K2, \text{list}(V2)) \rightarrow \text{list}(K3, V3)$ **Combiner:** Same as Reduce (must be commutative and associative)

Processing Flow

1. InputFormat \rightarrow RecordReader
2. Map Phase (parallel)
3. Partition
4. Shuffle and Sort
5. [Optional: Combine]
6. Reduce Phase (parallel)
7. OutputFormat

Key Characteristics

- **n input blocks \rightarrow at least n Mappers**
- **Each Mapper:** Processes one block
- **Each Reducer:** Processes one or more keys
- **Partitioner:** Determines Reducer for each key
- **Shuffle and Sort:** Groups values by key

Combiner Requirements

- Must be **commutative**: $a \oplus b = b \oplus a$
- Must be **associative**: $(a \oplus b) \oplus c = a \oplus (b \oplus c)$
- **Examples:** SUM \checkmark , COUNT \checkmark , AVG \times

Common Patterns

Map Functions:

- Filtering
- Transformation
- Projection
- Parsing

Reduce Functions:

- Sum
- Count
- Max/Min
- Average
- Join

Design Goals (2004)

1. Automatic parallelization
2. Fault tolerance
3. I/O scheduling
4. Status monitoring

Map-Only Jobs

- No Reducers (0 Reducers)
- Direct output to HDFS
- Use for: ETL, conversions, filtering
- Faster than full MapReduce

WordCount Pattern

Map: `(lineNo, line) → list(word, 1)` **Reduce:** `(word, list(1,1,1,...)) → (word, count)`

Important to Remember

- Keys don't need to be unique
- Values can be complex objects
- Hadoop handles distribution automatically
- Developer focuses on Map and Reduce logic
- Shuffle and Sort is automatic ("magic")
- 90% of MapReduce time is HDFS I/O