FAIRCHILD
SEMICONDUCTOR®

BC237/238/239

Switching and Amplifier Applications

- Low Noise: BC239



TO-92

1. Collector 2. Base 3. Emitter

NPN Epitaxial Silicon Transistor

Absolute Maximum Ratings T_a=25°C unless otherwise noted

Symbol	Parameter		Value	Units
V_{CES}	Collector-Emitter Voltage	: BC237 : BC238/239	50 30	V V
V_{CEO}	Collector-Emitter Voltage	: BC237 : BC238/239	45 25	V V
V_{EBO}	Emitter-Base Voltage	: BC237 : BC238/239	6 5	V V
I_C	Collector Current (DC)		100	mA
P_C	Collector Power Dissipation		500	mW
T_J	Junction Temperature		150	°C
T_{STG}	Storage Temperature		-55 ~ 150	°C

Electrical Characteristics T_a=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
BV_{CEO}	Collector-Emitter Breakdown Voltage : BC237 : BC238/239	I_C=2mA, I_B=0	 45 25			 V V
BV_{EBO}	Emitter Base Breakdown Voltage : BC237 : BC238/239	I_E=1μA, I_C=0	 6 5			 V V
I_{CES}	Collector Cut-off Current : BC237 : BC238/239	 V_{CE}=50V, V_{BE}=0 V_{CE}=30V, V_{BE}=0		 0.2 0.2	 15 15	 nA nA
h_{FE}	DC Current Gain	V_{CE}=5V, I_C=2mA	120		800	
V_{CE} (sat)	Collector-Emitter Saturation Voltage	I_C=10mA, I_B=0.5mA I_C=100mA, I_B=5mA		0.07 0.2	0.2 0.6	V V
V_{BE} (sat)	Collector-Base Saturation Voltage	I_C=10mA, I_B=0.5mA I_C=100mA, I_B=5mA		0.73 0.87	0.83 1.05	V V
V_{BE} (on)	Base-Emitter On Voltage	V_{CE}=5V, I_C=2mA	0.55	0.62	0.7	V
f_T	Current Gain Bandwidth Product	V_{CE}=3V, I_C=0.5mA, f=100MHz V_{CE}=5V, I_C=10mA, f=100MHz	 150	85 250		MHz MHz
C_{ob}	Output Capacitance	V_{CB}=10V, I_E=0, f=1MHz		3.5	6	pF
C_{ib}	Input Base Capacitance	V_{EB}=0.5V, I_C=0, f=1MHz		8		pF
NF	Noise Figure : BC237/238 : BC239 : BC239	V_{CE}=5V, I_C=0.2mA, f=1KHz R_G=2KΩ V_{CE}=5V, I_C=0.2mA R_G=2KΩ, f=30~15KHz		 2	 10 4 4	 dB dB dB

h_{FE} Classification

Classification	A	B	C
h_{FE}	120 ~ 220	180 ~ 460	380 ~ 800

Typical Characteristics



Figure 1. Static Characteristic



Figure 2. Transfer Characteristic



Figure 3. DC current Gain



Figure 4. Base-Emitter Saturation Voltage Collector-Emitter Saturation Voltage



Figure 5. Output Capacitance



Figure 6. Current Gain Bandwidth Product

Package Dimensions

TO-92



Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FACT™	ImpliedDisconnect™	PACMAN™	SPM™
ActiveArray™	FACT Quiet series™	ISOPLANAR™	POP™	Stealth™
Bottomless™	FAST®	LittleFET™	Power247™	SuperSOT™-3
CoolFET™	FASTr™	MicroFET™	PowerTrench®	SuperSOT™-6
CROSSVOLT™	FRFET™	MicroPak™	QFET™	SuperSOT™-8
DOME™	GlobalOptoisolator™	MICROWIRE™	QS™	SyncFET™
EcoSPARK™	GTO™	MSX™	QT Optoelectronics™	TinyLogic™
E^2CMOS™	HiSeC™	MSXPro™	Quiet Series™	TruTranslation™
EnSigna™	I^2C™	OCX™	RapidConfigure™	UHC™
Across the board. Around the world.™		OCXPro™	RapidConnect™	UltraFET®
The Power Franchise™		OPTOLOGIC®	SILENT SWITCHER®	VCX™
Programmable Active Droop™		OPTOPLANAR™	SMART START™	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.