PANJIT SEMI CONDUCTOR

DATA SHEET

MMBT3904

NPN GENERAL PURPOSE SWITCHING TRANSISTOR

VOLTAGE 40 Volts **POWER** 225 mWatts

SOT- 23 Unit: inch (mm)



FEATURES

- NPN epitaxial silicon, planar design
- Collector-emitter voltage VCE = 40V
- Collector current IC = 200mA
- Pb free product are available : 99% Sn above can meet Rohs environment substance directive request

MECHANICAL DATA

Case: SOT-23, Plastic

Terminals: Solderable per MIL-STD-202G, Method 208

Approx. Weight: 0.008 gram

Marking: S1A



ABSOLUTE RATINGS

PARAMETER	Symbol	Value	Units
Collector-Emitter Voltage	V_{CEO}	40	V
Collector-Base Voltage	V_{CBO}	60	V
Emitter-Base Voltage	V_{EBO}	6.0	V
Collector Current-Continuous	I_C	200	mA

THERMAL CHARACTERISTICS

PARAMETER	Symbol	Value	Units
Max Power Dissipation (Note 1)	P_{TOT}	225	mW
Thermal Resistance, Junction to Ambient	$R\theta_{JA}$	556	°C/W
Junction Temperature	T_J	-55 to 150	°C
Storage Temperature	T_{STG}	-55 to 150	°C

Note 1: Transistor mounted on FR-5 board 1.0 x 0.75 x 0.062 in.

ELECTRICAL CHARACTERISTICS T_A=25°C

PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Collector - Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C=1.0mA, I_B=0	40	-	-	V
Collector - Base Breakdown Voltage	$V_{(BR)CBO}$	I_C=10uA, I_E=0	60	-	-	V
Emitter - Base Breakdown Voltage	$V_{(BR)EBO}$	I_E=10uA, I_C=0	6.0	-	-	V
Base Cutoff Current	I_{BL}	V_{CE}=30V, V_{EB}=3.0V	-	-	50	nA
Collector Cutoff Current	I_{CEX}	V_{CE}=30V, V_{EB}=3.0V	-	-	50	nA
DC Current Gain (Note 2)	h_{FE}	I_C=0.1mA, V_{CE}=1.0V I_C=1.0mA, V_{CE}=1.0V I_C=10mA, V_{CE}=1.0V I_C=50mA, V_{CE}=1.0V I_C=100mA, V_{CE}=1.0V	40 70 100 60 30	- - - - -	- - 300 - -	-
Collector - Emitter Saturation Voltage (Note 2)	$V_{CE(SAT)}$	I_C=10mA, I_B=1.0mA I_C=50mA, I_B=5.0mA	-	-	0.2 0.3	V
Base - Emitter Saturation Voltage (Note 2)	$V_{BE(SAT)}$	I_C=10mA, I_B=1.0mA I_C=50mA, I_B=5.0mA	0.65 -	- -	0.85 0.95	V
Collector - Base Capacitance	C_{CBO}	V_{CB}=5V, I_E=0, f=1MHz	-	-	4.0	pF
Emitter - Base Capacitance	C_{EBO}	V_{CB}=0.5V, I_C=0, f=1MHz	-	-	8.0	pF
Delay Time	td	V_{CC}=3V,V_{BE}=-0.5V, I_C=10mA,I_B=1.0mA	-	-	35	ns
Rise Time	tr	V_{CC}=3V,V_{BE}=-0.5V, I_C=10mA,I_B=1.0mA	-	-	35	ns
Storage Time	ts	V_{CC}=3V,I_C=10mA I_{B1}=I_{B2}=1.0mA	-	-	200	ns
Fall Time	tf	V_{CC}=3V,I_C=10mA I_{B1}=I_{B2}=1.0mA	-	-	50	ns

Note 2: Pulse Test: Pulse Width < 300 us, Duty Cycle < 2.0%.

SWITCHING TIME EQUIVALENT TEST CIRCUITS



Delay and Rise Time Equivalent Test Circuit



Storage and Fall Time Equivalent Test Circuit

ELECTRICAL CHARACTERISTICS CURVE



Fig. 1. Typical h_{FE} vs Collector Current



Fig. 2. Typical V_{BE} vs Collector Current



Fig. 3. Typical V_{CE} (sat) vs Collector Current



Fig. 4. Typical V_{BE} (sat) vs Collector Current



Fig. 5. Typical Capacitances vs Reverse Voltage

MOUNTING PAD LAYOUT

SOT-23 Unit: inch (mm)



ORDER INFORMATION

- Packing information

  T/R - 12K per 13" plastic Reel

  T/R - 3.0K per 7" plastic Reel

LEGAL STATEMENT

IMPORTANT NOTICE

This information is intended to unambiguously characterize the product in order to facilitate the customer's evaluation of the device in the application. The information will help the customer's technical experts determine that the device is compatible and interchangeable with similar devices made by other vendors. The information in this data sheet is believed to be reliable and accurate. The specifications and information herein are subject to change without notice. New products and improvements in products and product characterization are constantly in process. Therefore, the factory should be consulted for the most recent information and for any special characteristics not described or specified.