BC856,BC857,BC858,BC859 SERIES

PNP GENERAL PURPOSE TRANSISTORS

VOLTAGE 30/45/65 Volts **POWER** 330 mWatts

FEATURES

- General Purpose Amplifier Applications
- Collector Current IC = -100mA
- Complimentary (PNP) Devices : BC846/BC847/BC848/BC849 Series

ð Lead free in comply with EU RoHS 2002/95/EC directives.

ð Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

Case: SOT-23

Terminals: Solderable per MIL-STD-750, Method 2026

Approx. Weight: 0.008 gram

Marking:

Device Marking:			
BC856A=56A	BC857A=57A	BC858A=58A	
BC856B=56B	BC857B=57B	BC858B=58B	BC859B=59B
	BC857C=57C	BC858C=58C	BC859C=59C

SOT-23 Unit : inch(mm)





ABSOLUTE RATINGS

PARAMETER	Symbol	BC856	BC857	BC858	BC859	Units
Collector - Emitter Voltage	V_{CEO}	-65	-45	-30		V
Collector - Base Voltage	V_{CBO}	-80	-50	-30		V
Emitter - Base Voltage	V_{EBO}	-5				V
Collector Current - Continuous	I_C	-100				mA
Max Power Dissipation(Note1)	P_{TOT}	330				mW
Typical Thermal Resistance, Junction to Ambient	$R_{\Theta JA}$	375				°C/W
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-50 to 150				°C

NOTES:

1. Transistor mounted on FR-4 board 8 cm^2.

BC856,BC857,BC858,BC859 SERIES

ELECTRICAL CHARACTERISTICS

PARAMETER		Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Collector - Emitter Breakdown Voltage	BC856A,B BC857A,B,C BC858A,B,C,BC859B,C	$V_{(BR)CEO}$	I_C=-10mA, I_B=0	-65 -45 -30	-	-	V
Collector - Base Breakdown Voltage	BC856A,B BC857A,B,C BC858A,B,C,BC859B,C	$V_{(BR)CBO}$	I_C=-10μA, I_E=0	-80 -50 -30	-	-	V
Emitter - Base Breakdown Voltage		$V_{(BR)EBO}$	I_E=-1.0μA, I_C=0	-5.0	-	-	V
Emitter-Base Cutoff Current		I_{EBO}	V_{EB}=-5V	-	-	-100	nA
Collector-Base Cutoff Current		I_{CBO}	V_{CB}=-30V, I_E=0 V_{CB}=-30V, I_E=0,T_J=150°C	-	-	-15 -4.0	nA μA
DC Current Gain	BC856A,BC857A,BC858A BC856B,BC857B,BC858B,BC859B BC857C,BC858C,BC859C	h_{FE}	I_C=-10μA, V_{CE}=-5V	-	90 150 270	-	-
DC Current Gain	BC856A,BC857A,BC858A BC856B,BC857B,BC858B,BC859B BC857C,BC858C,BC859C	h_{FE}	I_C=-2.0mA, V_{CE}=-5V	110 220 420	180 290 520	220 475 800	-
Collector - Emitter Saturation Voltage		$V_{CE(SAT)}$	I_C=-10mA, I_B=-0.5mA I_C=-100mA, I_B=-5.0mA	-	-	-0.3 -0.65	V
Base - Emitter Saturation Voltage		$V_{BE(SAT)}$	I_C=-10mA, I_B=-0.5mA I_C=-100mA, I_B=-5.0mA	-	-0.7 -0.9	-	V
Base - Emitter On Voltage		$V_{BE(ON)}$	I_C=-2mA, V_{CE}=-5.0V I_C=-10mA, V_{CE}=-5.0V	-0.60 -	- -	-0.75 -0.82	V
Collector - Base Capacitance		C_{CB}	V_{CB}=-10V, I_E=0, f=1MH	-	-	4.5	pF
Current-Gain-Bandwidth Product		F_T	I_C=-10mA, V_{CE}=-5.0V,f=100MHz	-	200	-	MHz

BC856,BC857,BC858,BC859 SERIES

ELECTRICAL CHARACTERISTICS CURVES



Fig.1- TYPICAL h_{FE} vs. Collector Current



Fig.2- TYPICAL $V_{BE(ON)}$ vs. Collector Current



Fig.3- TYPICAL $V_{CE(SAT)}$ vs. Collector Current



Fig.4- TYPICAL CAPACITANCES vs. REVERSE VOLTAGE

BC856,BC857,BC858,BC859 SERIES

MOUNTING PAD LAYOUT

SOT-23 Unit: inch (mm)



ORDER INFORMATION

- Packing information

  T/R - 12K per 13" plastic Reel

  T/R - 3K per 7” plastic Reel

LEGAL STATEMENT