LITE-ON SEMICONDUCTORS

BC846W

NPN General Purpose Transistor





FEATURES

- Ideally suited for automatic insertion
- For Switching and AF Amplifier Applications

MECHANICAL DATA

- Case: SOT-323 Plastic
- Case material: “Green” molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl)
- Lead Free in RoHS 2002/95/EC Compliant

Maximum Ratings @ T_A = 25℃

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	80	V
Collector-Emitter Voltage	V_{CEO}	65	V
Emitter-Base Voltage	V_{EBO}	6	V
Collector Current -Continuous	I_C	100	mA
Collector Power Dissipation	P_C	150	mW
Junction Temperature	T_J	150	℃
Storage Temperature Range	T_{STG}	-55~+150	℃

Electrical Characteristics @ T_A = 25℃ unless otherwise specified

Characteristic	Test Condition		Symbol	Min.	Typ.	Max.	Unit
Collector-base breakdown voltage	I_C=10μA,I_E=0		V_{CBO}	80			V
Collector-emitter breakdown voltage	I_C=10mA,I_B=0		V_{CEO}	65			V
Emitter-base breakdown voltage	I_E=1μA,I_C=0		V_{EBO}	6			V
Collector-base cut-off current	V_{CB}=30V		I_{CBO}			15	nA
DC current gain	V_{CE}=5V,I_C=10uA	AW BW	h_{FE1}		90 150		
	V_{CE}=5V,I_C=2mA	AW BW	h_{FE2}	110 200		220 450	
Collector-emitter saturation voltage	I_C=10mA,I_B=0.5mA I_C=100mA,I_B=5mA		V_{CE}(sat)			0.25 0.6	V
Base-emitter saturation voltage	I_C=10mA,I_B=0.5mA I_C=100mA,I_B=5mA		V_{BE}(sat)		0.7 0.9		V
Base-emitter voltage	I_C=2mA,V_{CE}=5V I_C=10mA,V_{CE}=5V		V_{BE}	580	660	700 770	mV
Transition frequency	V_{CE}=5V,I_C=10mA, f=100MHz		f_T	100			MHz
Collector output capacitance	V_{CB}=10V,f=1MHz		C_{ob}			4.5	pF
Noise figure	VCE=5V,Ic=0.2mA, f=1KHz,RS=2KΩ Bandwidth=200Hz	BW	NF			10	dB

REV. 2, Jun-2012, KSNR04

SOT-323 Outline Dimension



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

Device Marking :

Device P/N	Classification of h_{FE}	Marking code
BC846AW	110-220	1A
BC846BW	200-450	1B

Electrical characteristic curves

Fig.1 Normalized DC Current Gain



Fig.2 "Saturation" and "On" Voltages



Fig.3 Collector Saturation Region



Fig.4 Base–Emitter Temperature Coefficient



Fig.5 Capacitances



Fig.6 Current–Gain – Bandwidth Product



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.