MODULE 2: ROBOT OPERATING SYSTEM

Nicholas Ho, PhD
Institute of System Science, NUS

About Nicholas Ho

- nicholas.ho@nus.edu.sg
- Lecturer at NUS ISS; Courses covered include:
  - Robotic Systems
  - Autonomous Robots and Vehicles
  - Human-Robot System Engineering
- BEng and PhD degree from School of Mechanical Engineering, NUS
- Specialized in architecture, design & development
  - Artificial Intelligence
  - Augmented/Virtual Reality
  - Internet-of-Things (IoT) & Cyber-Physical System (CPS)

Robots within HRI Topic

Human-Robot Interaction (HRI) is a field of study dedicated to understanding, designing, and evaluating robotic systems **for use by or with humans**. Interaction, by definition, requires **communication between robots and humans**

What is ROS?

- Flexible framework for writing robot software
- Tools, libraries and conventions
- Open-source

Why ROS?

- Creating truly robust, general-purpose robot software is **hard**
  - From the robot's perspective, problems that seem trivial to humans often vary wildly between instances of tasks and environments.
  - Dealing with these variations is so hard that no single individual, laboratory, or institution can hope to do it on their own

ROS Core Components

- **Executable**
  - ROS Nodes
- **Communication**
  - ROS Messages, ROS Topics
  - Publisher and Subscriber
  - ROS Services, ROS Actionlibs
- **Record and playback**
  - ROS Bags
- **Visualization**
  - rviz

ROS Nodes

- **A ROS Node is an executable process that uses ROS to communicate with other Nodes**
- **E.g., Magic Cards**
  - The cameras need to see
    - CameraDriver
  - The “magic cards” need to be understood
    - Parser
  - The robots need to be localized at all time
    - Localization
  - The parsed card info needs to be aggregated as a plan for execution
    - Planner
  - The plan needs to be break down into low-level control commands
    - RobotDriver

Magic Cards



hardware

ROS Node

N Cameras

CameraDriver

Parser

Planner

Localization

Computer/Server

M Robots

RobotDriver

ROS Messages

- **A ROS Message is a ROS data type for communication among the Nodes**
- **ROS built-in default message types**
  - **std_msgs**
    - basic data types, such as int, float, string
  - **geometry_msgs**
    - geometry-related data types, such as point, vector, pose
  - **sensor_msgs**:
    - sensory data types, such as batterystate, image, pointcloud
  - etc…
- **Customized message type**
  - Developer can define a new message type using the existing message types

std_msgs

- **Basic**
  - Bool, Byte, Char
  - Int8, Int16, Int32, Int64,
  - UInt8, UInt16, UInt32, UInt64
  - Float32, Float64
  - String
  - Time, Duration
- **Signal**
  - Empty: a message usually used as a signal
- **Compound**
  - Header: a message in sequence with timestamp
  - ColorRGBA: a message to describe a pixel

std_msgs/Header.msg

```
uint32          seq
time            stamp
string          frame_id
```

std_msgs/ColorRGBA.msg

```
float32         r
float32         g
float32         b
float32         a
```

std_msgs (cont)

- **Array-related**
  - MultiArrayDimension

std_msgs/MultiArrayDimension.msg

```
string  label
uint32  size
uint32  stride
```

  - IntXXMultiArray, UIntXXMultiArray, FloatXXMultiArray

std_msgs/Int16MultiArray.msg

```
MultiArrayLayout        layout
uint8[]                 data
```

std_msgs (cont)

- **Array-related**
  - MultiArrayLayout

std_msgs/MultiArrayLayout.msg

```
MultiArrayDimension[]   dim
uint32                  data_offset
```

E.g., a standard, 3-channel 640x480 image with interleaved color channels:

```
dim[0].label = “height”
dim[0].size = 480
dim[0].stride = 3*640*480
dim[1].label = “width”
dim[1].size = 640
dim[1].stride = 3*640
dim[2].label = “channel”
dim[2].size = 3
dim[2].stride = 3
```

geometry_msgs

- **Pose related**
  - Point, Point32, PointStamped
  - Quaternion, QuaternionStamped
  - Pose, Pose2D, PoseStamped, PoseWithCovariance, PoseWithCovarianceStamped
  - PoseArray
- **Control related**
  - Vector3, Vector3Stamped
  - Transform, TransformStamped
  - Twist, TwistStamped, TwistWithCovariance, TwistWithCovarianceStamped
  - Wrench, WrenchStamped
- **Etc.**

geometry_msgs (cont)

geometry_msgs/Pose.msg

```
Point           position
Quaternion      orientation
```

geometry_msgs/PoseStamped.msg

```
Header          header
Pose            pose
```

geometry_msgs/Point.msg

```
float64         x
float64         y
float64         z
```

geometry_msgs/Quaternion.msg

```
float64         x
float64         y
float64         z
float64         w
```

sensor_msgs

- **Camera related**
  - RegionOfInterest, CameraInfo
  - Image, CompressedImage
- **PointCloud related**
  - LaserEcho, LaserScan, MultiEchoLaserScan
  - PointCloud, PointCloud2
- **GPS related**
  - NavSatFix, NavSatStatus
- **Joystick related**
  - Joy, JoyFeedback, JoyFeedbackArray
- **Others**
  - BatteryState, Temperature, RelativeHumidity, FluidPressure, etc

Customized Message

- Create a msg file
- Follow the format of the default message
- Add in the fields using already defined message types
- E.g.

std_msgs/Header.msg

```
uint32          seq
time            stamp
string          frame_id
```

msgs/MagicCard.msg

```
uint32          card_id
string          card_txt
time            stamp
pose2D          pose
twist           control
...
```

ROS Topics

- A **ROS Topic** is a channel for communicating Messages among the Nodes
- A ROS Topic has a fixed Message type
- A Node ***publishes*** on a Topic to broadcast Messages
- A Node ***subscribes*** to a Topic to get Messages from other Nodes

- *Many-to-many* communication
  - One Node can publish/subscribe multiple Topics
  - One Topic can be published/subscribed by different Nodes

Magic Cards (v1.0)



*The Parser subscribes all N topics published by the N CameraDrivers.

^The Planner publishes M topics subscribed by the M RobotDrivers respectively.

Magic Cards (v1.0)



*The Parser subscribes all N topics published by the N CameraDrivers.

^The Planner publishes M topics subscribed by the M RobotDrivers respectively.

Publisher and Subscriber (v1.0)



Magic Cards (v1.0)



Publisher and Subscriber (v1.0) cont



Magic Cards (v1.0)



*The Parser subscribes all N topics published by the N CameraDrivers.

^The Planner publishes M topics subscribed by the M RobotDrivers respectively.

Magic Cards (v2.0)



Publisher and Subscriber (v2.0)



sensor_msgs/Image.msg

```
Header          header
uint32          height
...
```

std_msgs/Header.msg

```
uint32          seq
time            stamp
string          frame_id
```

Magic Cards (v2.0)



Publisher and Subscriber (v2.0)

geometry_msgs/TwistStamped.msg

```
Header          header
Twist           twist
```



std_msgs/Header.msg

```
uint32          seq
time            stamp
string          frame_id
```

ROS Services

The **publish / subscribe** model is a very flexible communication paradigm, but its many-to-many one-way transport is not appropriate for **request / reply** interactions

- **ROS Services** are another way that nodes can communicate with each other (i.e. two-way)
- ROS Services allow nodes to send a request and receive a response
- **ROS built-in services**
- **Customized service**
  - Developer can define a new service call based on existing message types

Magic Cards (v3.0)



Built-in Service in sensor_msgs

sensor_msgs/setCameraInfo.srv

```
CameraInfo          info
---
bool                success
string              status_message
```

Request

Response

Customized Service

sensor_msgs/setCameraInfo.srv

```
CameraInfo      info
---
bool            success
string          status_message
```

srvs/getPID.srv

```
Pose            goal_pose
Pose            current_pose
---
Twist           twist
```

Magic Cards (v3.0)



Service and Client



ROS Architecture Construction (Practice)

Consider an autonomous drone that is in an environment with humans. You are required to **consider the following components and the respective features:**

1. One camera for it to see; its collected data aid in the localization of the robot and the machine vision system
2. A computer to identify things (be it humans or objects), to plan routes, and to localize the robot
3. The motors for the propellers

ROS Architecture Construction (Practice)

Based on the below information, **construct a ROS architecture** using the given template, “ROS Architecture Template”.

The various **node names** that are required for the ROS programme for this drone, together with their respective **topics and messages** involved are summarized in the table below (assume only topics are used):

Hardware	ROS Node	/ROS Topic	ROS:Message
Camera	CameraDriver	/image	sensor_msgs::Image
Computer	Parser	/thingsData	Things
	Localization	/pose	geometry_msgs::PoseArray
	Planner	/cmd	geometry_msgs::Twist
Motors	MotorDriver	N.A.	N.A.

ROS Architecture Construction (Practice)

ROS Architecture Template:



Extra: ROS Actionlibs

In some cases, if the service takes a long time to execute, the developer might want the ability to cancel the request during execution or get periodic feedback about how the request is progressing.

- **ROS Actionlibs** create servers that execute long-running goals that can be preempted
- ROS Actionlibs provide a client interface to send requests to the server

action/CleanRooms.action

```
uint32[]        room_ids
---
uint32          total_rooms_cleaned
---
float32         percentage_completed
```

Goal

Result

Feedback

ROS Bags

Real-world robot data are generally hard and costly to acquire. **ROS Bags** enables easy record / playback for store, process, analysis and visualization, etc.

- **Record**
  - A ROS Bag is a special Node that subscribes to one or more Topics, and stores the message data in a file as it is received.
- **Playback**
  - The bag files can also be played back in ROS to the same topics they were recorded from.

Data Playback on Collaborative 3D SLAM

Collaborative SLAM between UAV and UGV



Source: https://www.youtube.com/watch?v=ZZQT_REkItU

Data Playback on Collaborative 3D SLAM (cont)

Collaborative SLAM in NUS forest



Source: https://www.youtube.com/watch?v=1JoPp7GbN4E

Extra: practical issues

ROS is a middleware which faces practical problems while passing data around

- **Data loss**
  - Network breaks down
- **Data delay**
  - Data may not be received in order
- **Data non-synchronization**
  - Messages played back from the Bags at the recorded pace

ROS Visualization

RViz is the goto (built-in) 3D visualizer for ROS

It is essentially a Node subscribing a fixed set of Message types to be visualized





ROS Visualization (Example: Collision Avoidance)



ROS Visualization (Example: Collision Avoidance)



ROS Visualization (Example: Collision Avoidance)



Source: https://www.youtube.com/watch?v=pUOdwGLYmN8

ROS cheatsheet

Logging Tools

rqt_console

A tool to display and filtering messages published on rosout.

Usage:

```
$ rqt_console
```

rqt_bag

A tool for visualizing, inspecting, and replaying bag files.

Usage, viewing:

```
$ rqt_bag bag_file.bag
```

Usage, bagging:

```
$ rqt_bag *press the big red record button.*
```

rqt_logger_level

Change the logger level of ROS nodes. This will increase or decrease the information they log to the screen and rqt_console.

Usage:

```
viewing $ rqt_logger_level
```

Introspection & Command Tools

rqt_topic

A tool for viewing published topics in real time.

Usage:

```
$ rqt
Plugin Menu->Topic->Topic Monitor
```

rqt_msg, rqt_srv, and rqt_action

A tool for viewing available msgs, srvs, and actions.

Usage:

```
$ rqt
Plugin Menu->Topic->Message Type Browser
Plugin Menu->Service->Service Type Browser
Plugin Menu->Action->Action Type Browser
```

rqt_top

A tool for ROS specific process monitoring.

Usage:

```
$ rqt
Plugin Menu->Introspection->Process Monitor
```

rqt_publisher, and rqt_service_caller

Tools for publishing messages and calling services.

Usage:

```
$ rqt
Plugin Menu->Topic->Message Publisher
Plugin Menu->Service->Service Caller
```

rqt_reconfigure

A tool for dynamically reconfiguring ROS parameters.

Usage:

```
$ rqt
Plugin Menu->Configuration->Dynamic Reconfigure
```

rqt_graph, and rqt_dep

Tools for displaying graphs of running ROS nodes with connecting topics and package dependancies respectively.

Usage:

```
$ rqt_graph
$ rqt_dep
```

Development Er

rqt_shell, and rqt_p

Two tools for accessing a respectively.

Usage:

```
$ rqt
Plugin Menu->Miscell
Plugin Menu->Miscell
```

Data Visualizati

view_frames

A tool for visualizing the

Usage:

```
$ rosrun tf2_tools v
$ evince frames.pdf
```

rqt_plot

A tool for plotting data f



Examples:

To graph the data in di

```
$ rqt_plot /topic1/f
```

To graph the data all o

```
$ rqt_plot /topic1/f
```

To graph multiple fields

```
$ rqt_plot /topic1/f
```

rqt_image_view

A tool to display image t

Usage:

```
$ rqt_image_view
```

ROS Kinetic Catkin Workspaces

Create a catkin workspace

Setup and use a new catkin workspace from scratch.

Example:

```
$ source /opt/ros/kinetic/setup.bash
$ mkdir -p ~/catkin_ws/src
$ cd ~/catkin_ws/src
```

ROS Kinetic Cheatsheet

Filesystem Management Tools

rospack	A tool for inspecting packages.
rospack profile	Fixes path and pluginlib problems.
roscd	Change directory to a package.
rospd/rosd	Pushd equivalent for ROS.
rosls	Lists package or stack information.
rosed	Open requested ROS file in a text editor.
roscp	Copy a file from one place to another.
rosdep	Installs package system dependencies.
roswtf	Displays a errors and warnings about a running ROS system or launch file.
catkin_create_pkg	Creates a new ROS stack.
wstool	Manage many repos in workspace.
catkin_make	Builds a ROS catkin workspace.
rqt_dep	Displays package structure and dependencies.

Usage:

```
$ rospack find [package]
$ roscd [package[/subdir]]
$ rospd [package[/subdir] | +N | -N]
$ rosd
$ rosls [package[/subdir]]
$ rosed [package] [file]
$ roscp [package] [file] [destination]
$ rosdep install [package]
$ roswtf or roswtf [file]
$ catkin_create_pkg [package_name] [depend1]..[dependN]
$ wstool [init | set | update]
$ catkin_make
$ rqt_dep [options]
```

Start-up and Process Launch Tools

roscore

The basis nodes and programs for ROS-based systems. A roscore must be running for ROS nodes to communicate.

Usage:

```
$ roscore
```

rosrun

Runs a ROS package's executable with minimal typing.

Usage:

```
$ rosrun package_name executable_name
```

Example (runs turtlesim):

```
$ rosrun turtlesim turtlesim_node
```

roslaunch

Starts a roscore (if needed), local nodes, remote nodes via SSH, and sets parameter server parameters.

Examples:

Launch a file in a package:

```
$ roslaunch package_name file_name.launch
```

Launch on a different port:

```
$ roslaunch -p 1234 package_name file_name.launch
```

Launch on the local nodes:

```
$ roslaunch --local package_name file_name.launch
```

Introspection and Command Tools

rosnode

Displays debugging information about ROS nodes, including publications, subscriptions and connections.

Commands:

rosnode ping	Test connectivity to node.
rosnode list	List active nodes.
rosnode info	Print information about a node.
rosnode machine	List nodes running on a machine.
rosnode kill	Kill a running node.

Examples:

Kill all nodes:

```
$ rosnode kill -a
```

List nodes on a machine:

```
$ rosnode machine aqy.local
```

Ping all nodes:

```
$ rosnode ping --all
```

rostopic

A tool for displaying information about ROS topics, including publishers, subscribers, publishing rate, and messages.

Commands:

rostopic bw	Display bandwidth used by topic.
rostopic echo	Print messages to screen.
rostopic find	Find topics by type.
rostopic hz	Display publishing rate of topic.
rostopic info	Print information about an active topic.
rostopic list	List all published topics.
rostopic pub	Publish data to topic.
rostopic type	Print topic type.

Examples:

Publish hello at 10 Hz:

```
$ rostopic pub -r 10 /topic_name std_msgs/String hello
```

Clear the screen after each message is published:

```
$ rostopic echo -c /topic_name
```

Display messages that match a given Python expression:

```
$ rostopic echo --filter "m.data=='foo'" /topic_name
```

Pipe the output of rostopic to rosmsg to view the msg type:

```
$ rostopic type /topic_name | rosmsg show
```

rosservice

A tool for listing and querying ROS services.

Commands:

rosservice list	Print information about active services.
rosservice node	Print name of node providing a service.
rosservice call	Call the service with the given args.
rosservice args	List the arguments of a service.
rosservice type	Print the service type.
rosservice uri	Print the service ROSRPC uri.
rosservice find	Find services by service type.

Examples:

Call a service from the command-line:

```
$ rosservice call /add_two_ints 1 2
```

Pipe the output of rosservice to rossrv to view the srv type:

```
$ rosservice type add_two_ints | rossrv show
```

Display all services of a particular type:

```
$ rosservice find rospy_tutorials/AddTwoInts
```

rosparam

A tool for getting and setting ROS parameters on the parameter server using YAML-encoded files.

Commands:

rosparam set	Set a parameter.
rosparam get	Get a parameter.
rosparam load	Load parameters from a file.
rosparam dump	Dump parameters to a file.
rosparam delete	Delete a parameter.
rosparam list	List parameter names.

Examples:

List all the parameters in a namespace:

```
$ rosparam list /namespace
```

Setting a list with one as a string, integer, and float:

```
$ rosparam set /foo "['1', 1, 1.0]"
```

Dump only the parameters in a specific namespace to file:

```
$ rosparam dump dump.yaml /namespace
```

rosmsg/rossrv

Displays Message/Service (msg/srv) data structure definitions.

Commands:

rosmsg show	Display the fields in the msg/srv.
rosmsg list	Display names of all msg/srv.
rosmsg md5	Display the msg/srv md5 sum.
rosmsg package	List all the msg/srv in a package.
rosmsg packages	List all packages containing the msg/srv.

Examples:

Display the Pose msg:

```
$ rosmsg show Pose
```

List the messages in the nav_msgs package:

```
$ rosmsg package nav_msgs
```

List the packages using sensor_msgs/CameraInfo:

```
$ rosmsg packages sensor_msgs/CameraInfo
```

Logging Tools

rosbag

A set of tools for recording and playing back of ROS topics.

Commands:

rosbag record	Record a bag file with specified topics.
rosbag play	Play content of one or more bag files.
rosbag compress	Compress one or more bag files.
rosbag decompress	Decompress one or more bag files.
rosbag filter	Filter the contents of the bag.

Examples:

Record select topics:

```
$ rosbag record topic1 topic2
```

Replay all messages without waiting:

```
$ rosbag play -a demo_log.bag
```

Replay several bag files at once:

```
$ rosbag play demo1.bag demo2.bag
```

tf_echo

A tool that prints the information about a particular transformation between a source_frame and a target_frame.

Usage:

```
$ rosrun tf tf_echo <source_frame> <target_frame>
```

Examples:

To echo the transform between /map and /odom:

```
$ rosrun tf tf_echo /map /odom
```

https://w3.cs.jmu.edu/spragunr/CS354_S19/handouts/ROSCheatsheet.pdf

MODULE 2 WORKSHOP: WORKSHOP DAY 1

HANDS-ON ANALYSIS OF STATE-OF-THE-ART HRI PROJECTS: INTERACTIONS WITH DOMESTIC ROBOTS

Introducing Internet-of-Things (IoT)

What is IoT?

- Internet connects all people, so it is called “the Internet of People”
- **IoT connects all things**, so it is called “the Internet of Things”
- Remember the key elements of IoT:
  1. **Connect** devices
  2. **Process** (i.e. data collection, analysis and management)
  3. **Act**

Internet-of-Things (IoT) plays which important role(s) in Human-Robot Interactions (HRI)? (you may choose more than one)

- Storing Data in the Cloud (i.e. online servers)
- Data Analysis
- Offsite Monitoring of Robotic System
- Offsite Control of Robotic System (include actuators)
- Offsite Alert Prompt to Humans

IoT Supporting HRI

Offsite Real-time Monitoring via the Internet

Offsite Control via the Internet

Offsite Alert Prompt to Humans

ThingSpeak (Intro)

- Main features: **Collect, Analyze, Act**
- An IoT analytics platform service that allows you to **aggregate, visualize, and analyze live data streams in the cloud**
- Able to **send data to ThingSpeak from your devices (e.g. sensors within robots)**, create instant visualization of live data, and send alerts (only Twitter for this Platform)
- **Free to public** but with limitations (limited 3 million messages and 4 channels; ok for this workshop)

Access to ThingSpeak to View Data Update

- You do not need to sign up any account for this process for now
- **Follow the steps below:**
  1. Using phone or laptop, navigate to https://thingspeak.com/
  2. On top of the site, click "*Channels*", then point to and click on "*Public Channels*"
  3. Search for "Search by user ID" where there is an empty field box
  4. CopyPaste or Type my userID "**mwa0000018877967**" in this field
  5. Click "Submit" and you will see 2 boxes that you can select
  6. Depending on the Demo to be shown by the lecturer, click on the relevant demo to view the data update, i.e. click on the words "Demo for HRSE (TB3 Laser Scan)"

IoT Monitoring DEMO

Topic to monitor for this DEMO is **TB3 Laser Scan**



ThingSpeak (SignUp)

Follow the steps below:

- Navigate to https://thingspeak.com/
- The lecturer will go through the steps on how to sign up
- Note that you will need an email at least to sign up an account (no need to be nus email)



ThingSpeak

Creating Channels on ThingSpeak:

1. Once your MathWorks account is created, click on '*Channels*' (on top bar), and then click on '*My Channels*'
2. Click on the button '*New Channel*'
3. Type in the Name of your Channel (e.g. Monitoring of TB3 Laser Scan)
4. Click on the ticks under the field section; the number of ticks depends on how many topic messages you would like to publish in this platform (you may adjust this later on if needed; to be illustrated by lecturer)
5. Once done, scroll to bottom and click '*Save Channel*'

Download & Install hrse ROS Package

Steps:

1. Change to the source space directory of the catkin workspace:

```
$ cd ~/catkin_ws/src
```

2. Git Clone the hrse package:

```
$ git clone
https://github.com/nicholashojunhui/hrse.git
```

3. Build the packages in the catkin workspace:

```
$ cd ~/catkin_ws && catkin_make
```

4. Go to *catkin_ws/src/hrse/src* and make all python files executable

Creating a new ROS Package (Optional)

Steps:

1. Change to the source space directory of the catkin workspace:

```
$ cd ~/catkin_ws/src
```

2. Use the catkin_create_pkg script to create a new package called '***new_package***' which depends on std_msgs, roscpp, and rospy:

```
$ catkin_create_pkg new_package std_msgs rospy roscpp
```

3. Build the packages in the catkin workspace:

```
$ cd ~/catkin_ws
$ catkin_make
```

4. Add the workspace to your ROS environment by sourcing the generated setup file:

```
$ . ~/catkin_ws/devel/setup.bash
```

Group Project 1

IoT plays an important role within systems that involve human-robot interactions. Be it monitoring, control, big data analysis, data management and storage, emergency alerts from the robots, etc, the key advantage of IoT is that it enables us humans to communicate with the robots via the Internet, hence we do not have to be onsite or physically near the robot for these communications.

For this project, we will be focusing on the real-time and retrospective IoT monitoring aspect. Instead of the example shown previously to monitor laser scans (i.e. LiDAR readings from the TB3), this time you have to **configure an IoT system that enables us to monitor the pose parameters taken from the `/odom` topic** (i.e. the x, y, z positions and x, y, z, w orientations of the TB3). Similarly like in the demo, **use rospy and ThingSpeak in your configurations**.

Group Project 1:
Ideal Result for HRSE (TB3 Pose)

Group Project 1:
Ideal Result for HRSE (TB3 Pose DEMO)

Follow the steps below:

1. Using phone or laptop, navigate to https://thingspeak.com/
2. On top of the site, click "*Channels*", then point to and click on "*Public Channels*"
3. Search for "Search by user ID" where there is an empty field box
4. CopyPaste or Type my userID "**mwa0000018877967**" in this field
5. Click "Submit" and you will see 2 boxes that you can select
6. Depending on the Demo to be shown by the lecturer, click on the relevant demo to view the data update, i.e. click on the words "Demo for HRSE (TB3 Pose)"

Group Project 1: Setup Instructions

1. Create Channel and the required details (e.g. field section) in your ThingSpeak channel
2. In the created ThingSpeak channel, take note of your Channel ID and Write API Key; you may copy and paste these details into a notepad first
3. In your Ubuntu platform, in terminal, type the command to install the Paho client library; you need this to execute the MQTT communications

- `$ sudo pip install paho-mqtt`

Group Project 1:
RECAP on Sequences
(Refer to README for detailed instructions)

1. Launch Gazebo in TB3 World
2. Run node to send required data to TS Channel (node to be developed in this project: Project1.py)
3. Check if your ThingSpeak Channel receives the data from your running node
4. Move TB3 around using the Teleop key node
5. The collected data should change as the TB3 moves around the map
6. Once done, export the collected data in CSV

Instructions

This is a group project. Each group submits one zip file of all your codes/files (i.e. py and CSV) into LumiNUS at the end of the workshop

A123456_A234567_A345678_P1.zip

- Download all files in the directory **/workshops/day1** for reference codes
- Refer to the README file for instructions

OPTIONAL TASKS

PHYSICAL TB3 TEST, IOT MONITORING OF IMU, IOT CONTROL OF TB3

(A) Physical TB3 Test
RECAP on Sequences
(Refer to README for detailed instructions)

1. Do the OpenCR Setup (if have not done so)
2. Run roscore and do bring up procedures
3. Run node to send required data to TS Channel (i.e. Project1.py)
4. Check if your ThingSpeak Channel receives the data from your running node
5. Move TB3 around using the Teleop key node
6. The collected data should change as the TB3 moves around the map

(B) IoT Monitoring of IMU

Just for practice ONLY if you have time

- Create a node (i.e. imu.py) that is able to send data to ThingSpeak for monitoring purposes
- You may create a new channel for this
- **Interested variables:** Angular Velocities and Linear Accelerations at the various directions
- **Hint:** you may use rqt's topic monitor to guide you to understand which topic and its respective parameters are relevant

(C) IoT Control

- Apart from IoT Monitoring, IoT Control enables us to **control the robot at an offsite location**
- We will explore using an Android App (i.e. **ROS Control**) for this example
- Note that you will require an **Android Device (i.e. phone, tablet)** to do this
- Although this example is not considered as a complete IoT system (using TCP/IP), it can be easily configured to be one

(C) IoT Control

Setup:

1. Download and install the following app in your Android device: https://play.google.com/store/apps/details?id=com.robotca.ControlApp
2. If you are using VirtualBox for your platform, go to Settings, Network, then change from 'NAT' to 'Bridged Adapter' mode
3. Ensure both your device and Ubuntu is connected to the same router
4. Within your Ubuntu, open terminal and type `$ ifconfig` to find out your IP address (i.e. 192.168.X.XXX)
5. Type command `$ nano ~/.bashrc` and press `alt+/` to go to end of line or you can scroll manually to the end of the line
6. Modify the IP address under `ROS_MASTER_URI` and `ROS_HOSTNAME` by replacing `localhost` with 192.168.X.XXX

(C) IoT Control

Setup (Cont):

7. Once done, type ^X to exit and source the bashrc with `$ source ~/.bashrc`
8. Once done, go to your downloaded app and add a robot (Robot name can be anything you want)
9. Refer to next slide for the other details to fill in (i.e. Master URI, Topic Names)

(C) IoT Control

Setup (Cont):



Can be used for both Virtual and Physical Robot; note that camera topic is different for virtual and physical robots



https://192.168.X.XXX:11311

/cmd_vel

/scan

/camera/rgb/image_raw

/odom

/pose

(C) IoT Control

Execution (for Virtual TB3):

1. Launch Gazebo in TurtleBot3 world
2. Launch ROS Control Android App and under home, click on the robot that you have created (e.g. Robot1, Robot2)
3. A User Interface will appear which allows you to control the TB3 with the joystick (next slide)

Take note that the app is very buggy; unable to load the camera data and will occasionally break connection. It is still not robust enough

(C) IoT Control

Execution (for Virtual TB3):



Interface to visualize the camera data (unable to load)

Interface to visualize the scans and TB3 pose

Joystick to move the TB3

THANK YOU

Email: nicholas.ho@nus.edu.sg