

NuForm™

Concrete Formwork Panel

PHENOLIC FILM FACES • WOVEN BAMBOO MAT • BUILT FOR REPEATED POURS

NuForm is an engineered bamboo concrete formwork panel, built around a woven bamboo mat with bamboo sawdust filling the weave and faced with phenolic film on both sides. The phenolic surface strips clean and stands up to repeated pours, reaching 8 to 10 pours on site where marine plywood manages 4 to 5. Built for casting and forming concrete on site.

SPECIFICATIONS

Thickness	12, 14, 16 and 18 mm
Standard width	1220 mm (4 ft)
Standard length	2440 mm (8 ft)
Density (typical)	800 to 1,000 kg/m3
Moisture content	6 to 10%
Surface	Phenolic film, both sides
Edge finish	Sealed edges
Adhesive	Exterior grade phenol formaldehyde
Body	Woven bamboo mat, 1 to 5 plies
Filler	Bamboo sawdust filling the weave crevices

CONSTRUCTION

- 1 Phenolic film, top face
- 2 Woven bamboo mat, top ply
- 3 Bamboo sawdust filling the weave
- 4 Woven bamboo mat, inner plies
- 5 Woven bamboo mat, bottom ply
- 6 Phenolic film, bottom face

ASTM D1037 TEST RESULTS

Modulus of elasticity (MOE)	4,210.56 MPa
Modulus of rupture (MOR)	89.01 MPa
Internal bond strength	1.24 MPa
Water absorption, 24 hr	12.7%
Thickness swelling	3.2%

Independently tested to ASTM D1037 by the DOST Regional Standards and Testing Laboratory. Results apply to the samples submitted and may vary by configuration, thickness, moisture content and manufacturing lot.

PRODUCT HIGHLIGHTS

- Waterproof phenolic surface
- Clean release across pours
- Reaches 8 to 10 pours on site
- Phenolic film, both sides
- Smooth finish
- DOST tested to ASTM D1037

APPLICATIONS

- Concrete formwork panels
- Wall and column forming
- Slab and beam soffit forming
- Precast and cast in place concrete
- Repeated pour formwork
- Industrial and infrastructure

COMPARISON WITH OTHER BOARDS

Feature	NuForm	Plywood	MDF	Particle board	Plastic formwork
Strength	High	Good	Fair	Fair	Good
Moisture resistance	High	Fair	Low	Low	High
Screw holding	High	Good	Fair	Fair	Fair
Surface hardness	High	Fair	Fair	Low	Good
Reusability, formwork	8 to 10 uses	4 to 5 uses	Not suitable	Not suitable	50+ uses
Sustainability	High	Fair	Low	Low	Low
Cost efficiency	High	Good	Fair	Fair	Fair

NUMAT SUSTAINABLE MANUFACTURING, INC.

B22, Global Agro Milling Corporation, Alae, Manolo Fortich, 8703 Bukidnon, Philippines
+63 961 307 6458 • sales@numat.ph • www.numatbamboo.com

TESTED AND VERIFIED BY DOST

Rapid renewable • Made in the Philippines