

NuWeave™

Woven Bamboo Mat Board

PHENOLIC SURFACE • WOVEN BAMBOO MAT • BAMBOO SAWDUST WITH PF RESIN CORE

NuWeave Woven Bamboo Mat Board is an engineered panel made from two or more plies of woven bamboo mats laminated with thin layers of compressed bamboo sawdust and bonded with exterior grade phenol formaldehyde resin. Both surfaces are laminated with a high performance phenolic film, giving exceptional durability, moisture resistance, abrasion resistance and a smooth surface. Built for construction, furniture and industrial applications where strength, stability and long service life are required.

SPECIFICATIONS

Thickness	10, 12, 15, 16, 18 and 20 mm
Standard width	1220 mm (4 ft)
Standard length	2440 mm (8 ft)
Density (typical)	800 to 1,000 kg/m3
Moisture content	6 to 10%
Surface	Phenolic film, both sides
Edge finish	Sealed edges
Adhesive	Exterior grade phenol formaldehyde
Core material	Bamboo sawdust with PF resin, 1 mm or less
Reinforcement	Woven bamboo mat, 2 or more plies

CONSTRUCTION

- 1 Phenolic film, top
- 2 PF resin layer
- 3 Woven bamboo mat, top ply
- 4 Bamboo sawdust core, 1 mm or less
- 5 PF resin layer
- 6 Woven bamboo mat, bottom
- 7 Phenolic film, bottom

ASTM D1037 TEST RESULTS

Modulus of elasticity (MOE)	4,210.56 MPa
Modulus of rupture (MOR)	89.01 MPa
Internal bond strength	1.24 MPa
Water absorption, 24 hr	12.7%
Thickness swelling	3.2%

Independently tested to ASTM D1037 by the DOST Regional Standards and Testing Laboratory. Results apply to the samples submitted and may vary by configuration, thickness, moisture content and manufacturing lot.

PRODUCT HIGHLIGHTS

- Waterproof surface
- High strength
- Abrasion resistant
- Phenolic surface, both sides
- Smooth finish
- DOST tested to ASTM D1037

APPLICATIONS

- Interior wall panels
- Cabinets and furniture
- Concrete formwork
- Industrial panels
- Packaging and crates
- Partitions

COMPARISON WITH OTHER BOARDS

Feature	NuWeave	Plywood	MDF	Particle board	Plastic formwork
Strength	High	Good	Fair	Fair	Good
Moisture resistance	High	Fair	Low	Low	High
Screw holding	High	Good	Fair	Fair	Fair
Surface hardness	High	Fair	Fair	Low	Good
Reusability, formwork	30+ uses	10 to 20 uses	Not suitable	Not suitable	50+ uses
Sustainability	High	Fair	Low	Low	Low
Cost efficiency	High	Good	Fair	Fair	Fair

NUMAT SUSTAINABLE MANUFACTURING, INC.

B22, Global Agro Milling Corporation, Alae, Manolo Fortich, 8703 Bukidnon, Philippines
+63 961 307 6458 • sales@numat.ph • www.numatbamboo.com

TESTED AND VERIFIED BY DOST

Rapid renewable • Made in the Philippines