```
grep '^[^:]' /etc/passwd | cut -d: -f1 | sort
```

```
localhost:~# cat /etc/passwd | cut -d ":" -f 1 | sort
adm
at
bin
cron
cyrus
daemon
dhcp
ftp
games
guest
halt
1p
mail
man
news
nobody
ntp
operator
postmaster
root
shutdown
smmsp
squid
sshd
svn
sync
uucp
vpopmail
xfs
localhost:~#
```

```
cat /etc/protocols | awk '{print $2, $1}' | sort -nr | head -n5
        localhost:~# cat /etc/protocols | awk '{print $2, $1}' | sort -nr | head -n 5
        103 pim
        98 encap
        94 ipip
        89 ospf
        81 vmtp
        localhost:~#
                                                localhost:~# ./banner "I love MIREA"
         #!/bin/bash
                                                +-----
         string=" "
                                                 I love MIREA
         string+=$1
         string+=" |"
         length=${#string}
         str1="+"
         for (( i=0; i < length - 2; i++ ))
         str1+="-"
         done
         str1+="+"
         echo $str1
         echo "$string"
         echo $str1
        #!/bin/bash
        cat "$1" | tr -c "abcdefghijklmnopqrstuvwxyz" " " | xargs | tr " " "\n" | sort -u |
        xarqs
       localhost:~# ./identificators hello.c
       h hello include int main n printf return stdio void world
         #!/bin/bash
         touch "$1"
         chmod +x "$1"
         cp "$1" /usr/local/bin
        localhost:~# ./reg banner
        localhost:~# ls -l /usr/local/bin
        total 4404
                                                  0 Sep 9 09:16 banner
                      1 root
        rwxr-xr-x
                                 root
                                              42500 Jul 5 2020 export file
         rwxr-xr-x
                      1 root
                                 root
```

```
#!/bin/bash
if [[ "$1" =~ \.c$|\.js$|\.py$ ]]; then
   first_line=$(head -n 1 "$1")
   if [[ "$1" =~ \.c$|\.js$ ]]; then
        if [[ "$first_line" =~ ^[[:space:]]*// ]] || [[ "$first_line" =~
^[[:space:]]*/\* ]]; then
            echo "Комментарий найден в $1"
        else
            echo "Комментарий отсутствует в $1"
   elif [[ "$1" =~ \.py$ ]]; then
        if [[ "$first_line" =~ ^[[:space:]]*# ]]; then
            echo "Комментарий найден в $1"
        else
            echo "Комментарий отсутствует в $1"
        fi
    fi
else
    echo "Файл должен иметь расширение .c, .js или .py"
fi
```

localhost:~# ./comm test\_file.c Комментарий найден в test\_file.c localhost:~# ./comm hello.c Комментарий отсутствует в hello.c

```
#!/bin/bash
find "$1" -type f | while read -r file; do
    sha256sum "$file"
done | sort | uniq -w64 -d
```

```
localhost:~# ./dublicate /usr/local/bin
e3b0c44298fc1c149afbf4c8996fb92427ae41e4649b934ca495991b7852b855 /usr/local/bi
/dub
localhost:~# ls -l /usr/local/bin
total 4404
                                          0 Sep 9 09:41 dub
-rw-r--r--
              1 root
                         root
                                          0 Sep 9 09:41 dub2
rw-r--r--
              1 root
                         root
                                     42500 Jul
rwxr-xr-x
              1 root
                         root
                                                5 2020 export_file
                                     325844 Jul 6 2020 ffasn1dump
 rwxr-xr-x
             1 root
                         root
             1 root
                                     205012 Aug 17 2020 fldev
rwxr-xr-x
                         root
                                          6 Jul
                                                5 2020 qe -> qemacs
              1 root
lrwxrwxrwx
                         root
                                     712292 Jul 5 2020 gemacs
              1 root
rwxr-xr-x
                         root
                                    1045720 Jul 5 2020 qjs
             1 root
rwxr-xr-x
                         root
              1 root
                                     816284 Jul 5 2020 qjsc
rwxr-xr-x
                         root
                                          3 Jul
              1 root
                                                 5
                                                    2020 qjscalc -> qjs
lrwxrwxrwx
                         root
1rwxrwxrwx
              1 root
                                         11 Jul
                                                5
                                                    2020 set_import_dir -> expo
                         root
file
             1 root
                                      13404 Nov 21 2020 settime
rwxr-xr-x
                         root
                                                5
              1 root
                                     267584 Jul
                                                    2020 tcc
rwxr-xr-x
                         root
                                     678504 Jan 9 2021 temu
-rwxr-xr-x
              1 root
                         root
rwxr-xr-x
             1 root
                         root
                                      50268 Jul
                                                 5 2020 tinypi
                                     45636 Jul
              1 root
                                                 5 2020 vfagent
rwxr-xr-x
                         root
                                      35304 Jul
                                                 5
                                                    2020 vflogin
 rwxr-xr-x
              1 root
                         root
                                     204336 Jul
                                                 5
              1 root
                                                    2020 vfsync
 rwxr-xr-x
                         root
                                      24360 Jul
                                                 5 2020 vmtime
 rwxr-xr-x
              1 root
                         root
```

```
#!/bin/bash
 dir="$1"
  ext="$2"
  archive="archive.tar"
 find "$dir" -type f -name "*$ext" | tar -cf "$archive" -T -
localhost:~# ./archive /usr/local/bin .txt
localhost:~# tar -tf archive.tar
usr/local/bin/1.txt
usr/local/bin/2.txt
usr/local/bin/3.txt
 #!/bin/bash
            /\t/g' "$1" > "$2"
 sed 's/
localhost:~# ./sp 1.txt 2.txt
localhost:~#
  GNU nano 4.9.3
                                        1.txt
     1
  GNU nano 4.9.3
                                       2.txt
       1
 #!/bin/bash
find "$1" -type f -name "*.txt" -exec test ! -s {} \; -print
localhost:~# ./empty ~/
/root/.mozilla/firefox/j4k7jsk5.default-default/SecurityPreloadState.txt
/root/.mozilla/firefox/j4k7jsk5.default-default/AlternateServices.txt
/root/.mozilla/firefox/j4k7jsk5.default-default/TRRBlacklist.txt
/root/1.txt
```

localhost:~#