

A Survey of On-Policy Distillation for Large Language Models

Mingyang Song & Mao Zheng
 Large Language Model Department
 Tencent, China
 nickmysong@tencent.com

Abstract

Knowledge distillation has transitioned from a model compression technique into a general capability transfer engine for Large Language Models (LLMs). The dominant off-policy paradigm forces students to learn from static, teacher-generated trajectories, triggering exposure bias when students encounter their own distribution shifts during autoregressive generation. On-Policy Distillation (OPD) eliminates this mismatch by soliciting teacher feedback on the student’s self-generated trajectories, transforming distillation into an interactive optimization loop. We present the first comprehensive survey of OPD, abandoning descriptive enumeration in favor of a structured practitioner’s decision chain. We formulate a unified mathematical framework for trajectory-based divergence minimization. We then classify the rapidly growing literature not by heuristic boundaries, but by the core technical contribution of each method: objective function design, signal source architecture, and training dynamics. By charting the transition from token-level logit matching to RL-augmented sequence objectives and self-play, we reveal the theoretical success conditions of OPD and chart future directions in scaling laws, uncertainty-aware feedback, and agentic distillation.

 **Awesome List & Paper Collection**

<https://github.com/nick7nlp/Awesome-LLM-On-Policy-Distillation>

1 Introduction

Knowledge distillation, introduced by Hinton et al. (2015), compresses the knowledge of a large teacher network into a smaller student by training the student to match the teacher’s softened output distribution. For autoregressive language models, this paradigm was extended to sequence-level objectives by Kim & Rush (2016), who showed that matching the teacher’s full sequence distribution outperforms word-level matching for machine translation. These foundational works established the template that dominated the field for nearly a decade: generate a dataset from the teacher, then train the student on this static corpus.

The emergence of Large Language Models (LLMs) has elevated distillation from a compression technique to the primary vector for capability transfer. DeepSeek-R1 (DeepSeek-AI et al., 2025) demonstrated that distilling chain-of-thought reasoning from a 671B MoE teacher can produce small models (1.5B–70B) that rival frontier systems on competition-level mathematics. However, this success masks a fundamental limitation: the student is trained on the teacher’s trajectories, not its own.

Conventional distillation operates *off-policy*. The student model p_θ learns to replicate the teacher’s next-token distribution over a static corpus p_{data} . During training, the student is teacher-forced, conditioning its predictions on flawless prefixes. During inference, it must generate autoregressively, conditioning on its own (often imperfect) outputs. This train-test

discrepancy is a classic manifestation of *exposure bias* (Ross et al., 2011). When a student makes a slight error, the resulting prefix shifts away from the training manifold. Lacking supervisory signals for these self-induced out-of-distribution states, the student’s errors compound, with the expected discrepancy scaling quadratically as $O(\epsilon T^2)$ over a trajectory of length T .

Gudibande et al. (2023) provided an influential early warning: imitating proprietary LLMs through off-policy distillation on API-generated data produces models that mimic surface style while failing to transfer genuine reasoning capability. This “false promise” of imitation learning motivated the search for training paradigms that force the student to confront its own weaknesses.

On-Policy Distillation (OPD) directly attacks exposure bias. It shifts the sampling distribution from the static dataset to the student’s evolving policy. The student generates its own trajectories, explores sub-optimal states, and queries the teacher for corrective feedback on those specific states. This transitions distillation from supervised sequence modeling to an interactive reinforcement learning framework, recovering the theoretical $O(T)$ compounding error bounds of the DAgger algorithm (Ross et al., 2011; Agarwal et al., 2024).

The resulting literature is dense and highly fragmented. Methods drawing from imitation learning (GKD (Agarwal et al., 2024)), reinforcement learning (MiniLLM (Gu et al., 2024)), and self-play (SPIN (Chen et al., 2024)) often mask identical mathematical objectives behind disparate terminology. Previous surveys (Xu et al., 2024) treat OPD as a sub-feature of general distillation. This survey reorients the field around a structural decision pipeline for practitioners.

We contribute the following:

1. **A Unified Formalism:** We construct a continuous mathematical framework mapping fixed divergences, adaptive divergences, and RL-augmented KD into a shared geometric space (Section 2).
2. **A Decision-Centric Taxonomy:** We replace fuzzy descriptive categories with a practitioner’s decision tree (Section 3), organizing methods by their exact functional contribution: Objective Design (Section 4), Signal Source (Section 5), and Training Dynamics (Section 6).
3. **Theoretical Failure Analysis:** We synthesize empirical failures (flawed prefix traps, saturation) into a coherent understanding of when and why OPD breaks down (Section 7).
4. **Comprehensive Coverage:** We survey over 90 methods spanning white-box logit distillation, black-box API distillation, self-distillation, and RL-augmented objectives, with detailed comparison tables (Tables 1, 2, and 3).

2 Background and Unified Math

The necessity of OPD stems from the compounding geometry of autoregressive generation. This section formalizes the distribution mismatch, establishes the unified f -divergence framework that subsumes modern OPD objectives, and traces the historical arc from classical KD to modern on-policy methods.

Notation. Throughout this survey, we use lowercase p for token-level conditional distributions ($p_T(\cdot|x, y_{<t})$ for teacher, $p_\theta(\cdot|x, y_{<t})$ for student) and uppercase P for sequence-level distributions ($P_T(y|x)$, $P_\theta(y|x)$). $\mathcal{D}$ denotes the training dataset, p_{data} the data distribution, and $|V|$ the vocabulary size. D_{KL} and D_f denote KL divergence and general f -divergence respectively. In the RL formalization, π denotes policies and $R(x, y)$ the outcome reward. When discussing individual methods, we follow each paper’s conventions where clarity demands.

2.1 Classical Knowledge Distillation

The original KD formulation (Hinton et al., 2015) trains the student to match the teacher’s temperature-softened output distribution:

$$p_T^{(\tau)}(y|x) = \frac{\exp(z_y/\tau)}{\sum_j \exp(z_j/\tau)} \quad (1)$$

where z_y are the teacher’s logits and $\tau > 1$ is a temperature parameter. When $\tau \rightarrow \infty$, the softened distribution approaches a uniform distribution over the vocabulary, revealing the teacher’s “dark knowledge” about inter-class similarities that are hidden in the hard labels. The gradient of the distillation loss with respect to the student’s logits z_i^S is proportional to $\frac{1}{\tau}(p_i^S - p_i^T)$, demonstrating that higher temperatures amplify the contribution of non-peak tokens, effectively transferring the teacher’s relational structure between vocabulary items.

For autoregressive LLMs, Kim & Rush (2016) extended this to Sequence-Level Knowledge Distillation (Seq-KD). Instead of factorizing the loss token-by-token over fixed dataset prefixes, Seq-KD minimizes the global KL divergence over the entire sequence space:

$$\mathcal{L}_{\text{Seq-KD}} = - \sum_{y \in \mathcal{Y}} P_T(y|x) \log P_\theta(y|x) \quad (2)$$

Since $|\mathcal{Y}| = |V|^T$ grows exponentially with length, this is intractable. Seq-KD approximates $P_T(y|x)$ with a Dirac delta at the beam-search output $\hat{y} = \arg \max_y P_T(y|x)$, reducing to standard negative log-likelihood on teacher-generated sequences. This approximation works well when the teacher is confident but discards all information about the teacher’s uncertainty, a limitation that motivates the softer distributional methods below.

Subsequent work (Zhong et al., 2024) revisited these foundations for modern LLMs, demonstrating that classical assumptions (small teacher-student gap, shared vocabulary, similar architectural inductive biases) frequently fail in the era of heterogeneous model families. This motivates the more general f -divergence framework below.

2.2 Off-Policy Exposure Bias

Standard Knowledge Distillation minimizes the KL divergence over states drawn from the dataset distribution $d_{\mathcal{D}}(s)$:

$$\mathcal{L}_{\text{Off-Policy}} = \mathbb{E}_{x, y \sim p_{\text{data}}} \left[\sum_{t=1}^{|y|} D_{\text{KL}}(p_T(\cdot|x, y_{<t}) \parallel p_\theta(\cdot|x, y_{<t})) \right] \quad (3)$$

At inference, the student acts according to its own policy, inducing a different state visitation distribution $d_{\pi_\theta}(s)$. By the DAGger theorem (Ross et al., 2011), if a policy mimics an expert with per-step error ϵ under the training distribution, the expected total discrepancy over a trajectory of length T under the student’s own distribution scales quadratically, bounded by $O(\epsilon T^2)$.

This quadratic compounding has severe practical consequences for reasoning tasks. A mathematical proof requiring 10 reasoning steps with per-step accuracy 95% yields only $(0.95)^{10} \approx 60\%$ trajectory-level correctness under off-policy training, because the student never learns to recover from its own intermediate errors. On-policy training exposes the student to its own error states during training, enabling it to learn correction strategies that reduce the effective per-step error rate when errors have already occurred.

2.3 The Unified f -Divergence Framework

OPD resolves exposure bias by altering the training expectation to sample from the student’s own rollouts, or a mixture policy π_{mix} . The generalized on-policy objective decouples the sampling trajectory from the local matching metric:

$$\mathcal{L}_{\text{OPD}}(\theta) = \mathbb{E}_{y \sim \pi_{\text{mix}}} \left[\sum_{t=1}^{|y|} \mathcal{D}_f(p_T(\cdot|x, y_{<t}), p_\theta(\cdot|x, y_{<t})) \right] \quad (4)$$

Here, $\mathcal{D}_f$ represents a divergence from the f -divergence family (Wen et al., 2023). Formally, given two distributions P and Q , an f -divergence is defined as:

$$D_f(P \parallel Q) = \mathbb{E}_{y \sim Q} \left[f \left(\frac{P(y)}{Q(y)} \right) \right] \quad (5)$$

where $f : (0, \infty) \rightarrow \mathbb{R}$ is a convex generator with $f(1) = 0$. The choice of f determines the implicit weighting of likelihood ratios $p_T(y)/p_\theta(y)$:

- **Forward KL** ($f(u) = u \log u$): Mode-covering (zero-avoiding). The student must allocate probability mass wherever the teacher does, often bridging distinct teacher modes and hallucinating in the inter-mode space.
- **Reverse KL** ($f(u) = -\log u$): Mode-seeking (zero-forcing). The student collapses its mass onto the teacher’s single highest peak, ignoring secondary acceptable outputs but guaranteeing high precision.
- **JSD** ($f(u) = u \log u - (u + 1) \log \frac{u+1}{2}$): Symmetric, bounded, and smoothly interpolates between mode-covering and mode-seeking behavior.
- **α -divergence**: Parameterized family that continuously interpolates between Forward KL ($\alpha \rightarrow 1$) and Reverse KL ($\alpha \rightarrow 0$), enabling fine-grained control over the mode-seeking/covering tradeoff.

This framework subsumes all modern OPD objectives: the choice of f determines the geometric behavior, while the choice of π_{mix} controls the degree of on-policy exploration. We illustrate by mapping the three foundational methods into this space:

GKD (Agarwal et al., 2024) defines $\pi_{\text{mix}} = \lambda p_\theta + (1 - \lambda) p_{\text{data}}$ as an explicit interpolation, and is agnostic to $\mathcal{D}_f$, empirically testing Forward KL, Reverse KL, and JSD. Setting $\lambda \rightarrow 1$ makes GKD purely on-policy.

MiniLLM (Gu et al., 2024) selects Reverse KL as $\mathcal{D}_f = D_{\text{KL}}(p_\theta \parallel p_T)$ and employs $\pi_{\text{mix}} = (1 - \alpha) p_\theta + \alpha p_T$ with $\alpha = 0.2$ for stability. Because Reverse KL places the student in both the expectation and the log-ratio, MiniLLM reformulates optimization via REINFORCE, treating $\log(p_T/p_\theta)$ as a per-step reward.

DistiLLM (Ko et al., 2024) maintains $\pi_{\text{mix}} = p_\theta$ (fully on-policy) but replaces the KL target from p_T to a skewed mixture $\tilde{p} = \alpha p_T + (1 - \alpha) p_\theta$, computing $D_{\text{KL}}(p_T \parallel \tilde{p})$. This avoids zero-division instability when $p_\theta(y) \approx 0$, because $\tilde{p}(y) \geq \alpha p_T(y) > 0$ always, achieving tractability and stability without policy gradients.

This decomposition reveals that modern OPD is not a series of disparate heuristics but a systematic exploration of a design space governed by three interacting choices: trajectory sampling (π_{mix}), divergence generator (f), and argument ordering within the chosen divergence.

2.4 Distillation Scaling Laws

A critical gap in the field is the absence of scaling laws specific to distillation. While Hoffmann et al. (2022) established compute-optimal scaling for pre-training (the Chinchilla laws), and Busbridge et al. (2025) initiated the study of distillation-specific scaling, no comprehensive framework yet predicts how distillation quality scales with teacher size, student size, data volume, and on-policy rollout budget. This absence forces practitioners to rely on expensive trial-and-error. The theoretical frameworks developed in Section 7 provide partial answers, but a complete distillation scaling law remains an open problem (Section 9).

3 Landscape and Practitioner Guide

To navigate the fragmented OPD literature, we construct a functional landscape. Methods are classified not by arbitrary labels, but by the specific step in the engineering pipeline they optimize.

3.1 Method Landscape

The practitioner faces three sequential decisions: (1) what objective to optimize, (2) where the supervisory signal originates, and (3) how to stabilize the resulting training dynamics. Figure 1 illustrates this pipeline.




Figure 1: The functional landscape of On-Policy Distillation. The taxonomy reflects the practitioner’s decision chain: first choose the objective, then identify the signal source, then stabilize the training loop.

3.2 Method Comparison Table

Table 1: Comparison of key OPD methods categorized by their primary contribution dimension.

Method	Category	Core Contribution	Signal Source	Loss Granularity
GKD (Agarwal et al., 2024)	Objective (Fixed)	DAGger for LLMs; interpolation	White-Box Logits	Token
DistiLLM (Ko et al., 2024)		Skewed KL mixtures	White-Box Logits	Token
MiniLLM (Gu et al., 2024)		Sequence-level Reverse KL via RL	White-Box Logits	Sequence
ToDi (Jung et al., 2025)	Objective (Adaptive)	Entropy-routed token divergence	White-Box Logits	Token
Entropy-Aware (Jin et al., 2026)		Entropy-based KL interpolation	White-Box Logits	Token
G-OPD (Yang et al., 2026c)	Objective (RL)	OPD equivalence to KL-RL	White-Box Logits	Sequence/Token
RLKD (Xu et al., 2025b)		KD augmented with reward model	Reward Model	Sequence
DSKD (Zhang et al., 2025b)	Signal (White-Box)	Cross-architecture alignment	White-Box Logits	Token
Delta-KD (Ko et al., 2026)		Base-to-Instruct delta isolation	White-Box Logits	Token
Lion (Jiang et al., 2023)	Signal (Black-Box)	Verbal feedback curriculum	Black-Box API	Sequence
GAD (Ye et al., 2025)		Adversarial distribution matching	Black-Box API	Sequence
OPSD (Zhao et al., 2026b)	Signal (Self)	Privileged Info (PI) conditioning	Self-Generated	Token
SPIN (Chen et al., 2024)		Self-play vs reference responses	Self-Generated	Sequence
TIP (Xu et al., 2026b)	Dynamics (Weight)	Token importance profiling via diff	White-Box Logits	Token
PACED (Xu et al., 2026a)		Beta-kernel curriculum pacing	White-Box Logits	Token

3.3 Practitioner Decision Tree

The following decision tree provides actionable guidance for selecting OPD methods based on access constraints, task requirements, and compute budgets. These recommendations are derived from the empirical patterns observed across the methods surveyed in Sections 4–6.

1. Do you have full logit access to the teacher?

- *Yes (White-Box)*: Use DistiLLM (Ko et al., 2024) for stable token-level matching on instruction following, or G-OPD (Yang et al., 2026c) if strong reasoning extrapolation is required. For adaptive divergences, ToDi (Jung et al., 2025) or Entropy-Aware (Jin et al., 2026) provide automatic switching. If teacher and student use different tokenizers, deploy DSKD (Zhang et al., 2025b) or Cross-Tokenizer KD (Boizard et al., 2025).
- *No, API only (Black-Box)*: Use OVD (Xiong et al., 2026) for verbal score distillation (simplest), GAD (Ye et al., 2025) for adversarial training (strongest signal), or DAIL (Mendes et al., 2026) for inverse-RL framing. If only text outputs are available and the student is small, LUFFY (Yan et al., 2025) with mixed-policy GRPO provides a strong baseline.
- *No teacher available (Self-Distillation)*: If oracle answers are available, use Privileged Information methods: OPSD (Zhao et al., 2026b) for math reasoning,

GATES (Stein et al., 2026) for open-domain QA. If no oracle is available, start with SD-ZERO (He et al., 2026) (requires only a binary verifier) or SSD (Zhang et al., 2026c) (requires nothing at all, but saturates quickly).

2. What is the task profile?

- *Reasoning / Math*: Mode-seeking objectives are mandatory to prevent hallucination. Use Reverse KL (MiniLLM (Gu et al., 2024)) or RL-augmented KD (G-OPD, KDRL (Xu et al., 2025a)). Combine with curriculum pacing (PACED (Xu et al., 2026a)) for compute efficiency.
- *Open-ended Generation*: Mode-covering objectives preserve diversity. Use Forward KL or adaptive entropy-aware divergences. Avoid aggressive Reverse KL, which collapses creative diversity.
- *Instruction Following*: GKD (Agarwal et al., 2024) with $\lambda \geq 0.5$ provides the best quality-compute tradeoff. AlignDistil (Zhang et al., 2025a) adds preference alignment.
- *Multi-step Agentic Tasks*: Requires sequence-level objectives with trajectory-aware credit assignment. SCoRe (Lyu et al., 2025) for error correction, RLAD (Zhang et al., 2026e) for trust-region stability.

3. What are the compute limits?

- *Low compute (<500 GPU-hours)*: Standard GKD, Fast OPD (Zhang et al., 2026a) (prefix truncation), or Lightning OPD (Wu et al., 2026) ($4\times$ cost reduction via offline caching).
- *Medium compute*: Full on-policy training with adaptive divergences (ToDi, AKL (Wu et al., 2025)). Add PACED for efficient sample selection.
- *High compute (>5000 GPU-hours)*: Multi-stage pipelines: off-policy warmup $\rightarrow$ on-policy refinement $\rightarrow$ RL exploration. This is the recipe used by Qwen3 (Yang et al., 2025a) and MiMo-V2 (Xiaomi LLM-Core Team et al., 2026).

4. Stability concerns?

- *Length inflation*: Apply Stable-OPD (Luo et al., 2026) stabilization (reference divergence + rollout mixing).
- *Flawed prefix trap*: Deploy TIP (Xu et al., 2026b) or SCOPE (Zheng et al., 2026) for teacher reliability filtering.
- *Thinking-pattern mismatch*: Start with off-policy cold start (Li et al., 2026d), then transition to on-policy after initial distribution alignment.

4 Objective Functions and Optimization

The foundational algorithmic decision in OPD is the choice of objective function: what mathematical quantity does the student optimize at each training step? This choice governs gradient geometry, mode coverage, and ultimately the ceiling of achievable performance. The field has evolved through three distinct phases: fixed divergences that apply a single metric uniformly, adaptive divergences that modulate the metric per-token based on local distributional geometry, and RL-augmented objectives that break through the teacher’s capability ceiling entirely. We trace this progression below, emphasizing the mathematical relationships that connect seemingly disparate methods.

4.1 Fixed Divergence Objectives

GKD (Agarwal et al., 2024) established the canonical OPD framework by adapting the DAGger algorithm (Ross et al., 2011) for autoregressive language models. It samples trajectories from a mixture policy $\pi_{\text{mix}} = \lambda p_{\theta} + (1 - \lambda) p_{\text{data}}$ and applies standard f -divergences (Forward KL, Reverse KL, or JSD) at each token position. The mixture coefficient λ interpolates between fully off-policy ($\lambda = 0$) and fully on-policy ($\lambda = 1$), providing a single knob for exposure bias mitigation. On instruction-following and summarization benchmarks, even moderate on-policy mixing ($\lambda \geq 0.5$) consistently outperforms pure off-policy training, validating the distributional alignment hypothesis.

However, pure KL divergences exhibit numerical instability during on-policy exploration. When the student generates tokens to which the teacher assigns near-zero probability, Forward KL produces unbounded gradients; conversely, Reverse KL ignores these regions entirely, creating blind spots in the loss landscape. DistiLLM (Ko et al., 2024) addresses this through *Skewed* KL (SKL), constructing a smoothed target $\tilde{p} = \alpha p_T + (1 - \alpha)p_\theta$:

$$\mathcal{L}_{\text{SKL}} = \mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} D_{\text{KL}}(p_T(\cdot|y_{<t}) \parallel \alpha p_T(\cdot|y_{<t}) + (1 - \alpha)p_\theta(\cdot|y_{<t})) \right] \quad (6)$$

Skewing guarantees the target density is bounded below by $(1 - \alpha)p_\theta$, eliminating gradient explosion without requiring RL policy gradients. DistiLLM further introduces Skewed Reverse KL (SRKL) for mode-seeking applications, creating a symmetric pair of stabilized divergences. Its successor, DistiLLM-2 (Ko et al., 2025), extends this to contrastive objectives that apply asymmetric losses depending on whether the training data is teacher-generated or student-generated, recognizing that the optimal divergence differs between these two sources.

The fixed-divergence family faces a fundamental limitation: the choice between Forward KL (mode-covering) and Reverse KL (mode-seeking) is a global decision applied uniformly across all token positions. Yet the teacher’s distributional structure varies dramatically within a single sequence. At a mathematical operator token, the teacher concentrates probability mass on one or two correct symbols. At a conjunction or filler word, dozens of tokens share comparable probability. Applying a single divergence to both positions necessarily compromises: Forward KL wastes gradient signal on high-entropy positions where any token is acceptable, while Reverse KL discards useful coverage information at low-entropy positions where multiple valid continuations exist.

Sequence-level objectives offer a complementary perspective. MiniLLM (Gu et al., 2024) elevates Reverse KL to the full sequence level, where the student p_θ appears inside the sampling expectation. Computing exact sequence-level Reverse KL requires policy gradients. MiniLLM treats the teacher log-probability as a per-step reward $r_t = \log(p_T(y_t|y_{<t}) / p_\theta(y_t|y_{<t}))$ and derives a REINFORCE-style objective:

$$\nabla_\theta \mathcal{L}_{\text{MiniLLM}} = -\mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} (R_t - b) \nabla_\theta \log p_\theta(y_t|y_{<t}) \right] \quad (7)$$

where $R_t = \sum_{t'=t}^{|y|} r_{t'}$ is the return-to-go and b is a learned baseline for variance reduction. This formulation places the optimization squarely in the RL framework, with the teacher’s log-probability serving as a dense reward signal. The connection to policy optimization explains MiniLLM’s strong performance on reasoning tasks where sequence-level coherence matters more than token-level accuracy.

KETCHUP (Fan et al., 2025) refines this approach by replacing the single-sample REINFORCE estimator with a K -step truncated return, reducing gradient variance while preserving the sequence-level objective. The constrained KD framework of Zimmer et al. (2025) augments the sequence-level Reverse KL with a hard KL constraint implemented via state-augmented CMDP, ensuring that the student’s divergence from the teacher remains bounded even during aggressive exploration.

4.2 Adaptive Divergence Objectives

The limitations of fixed divergences motivate *adaptive* methods that select or interpolate divergences based on local distributional geometry. The core insight is that the optimal divergence at each token position depends on the teacher’s local confidence: when the teacher is certain (low entropy), mode-seeking Reverse KL preserves precision; when the teacher is uncertain (high entropy), mode-covering Forward KL preserves diversity.

ToDi (Jung et al., 2025) operationalizes this by routing each token through either Forward KL or Reverse KL based on the teacher’s entropy $H(p_T(\cdot|y_{<t}))$:

$$\mathcal{L}_{\text{ToDi}} = \mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} 1[H_t < \tau] \cdot D_{\text{KL}}(p_\theta \parallel p_T) + 1[H_t \geq \tau] \cdot D_{\text{KL}}(p_T \parallel p_\theta) \right] \quad (8)$$

where τ is a learned or fixed entropy threshold. Entropy-Aware OPD (Jin et al., 2026) replaces the hard routing with a continuous interpolation coefficient $\alpha_t \propto H_t$, yielding a smooth blend:

$$\mathcal{L}_{\text{EA}} = \mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} (1 - \alpha_t) D_{\text{KL}}(p_\theta \parallel p_T) + \alpha_t D_{\text{KL}}(p_T \parallel p_\theta) \right] \quad (9)$$

Both methods consistently outperform any fixed divergence on math reasoning (MATH, GSM8K) and open-ended generation (AlpacaEval), confirming that the optimal divergence is indeed position-dependent.

AKL (Wu et al., 2025) takes a more aggressive approach, dynamically interpolating between Forward KL and Reverse KL based on a per-token confidence metric derived from the teacher-student probability ratio. Unlike entropy-based routing, which depends only on the teacher’s distributional shape, AKL considers the *relative* geometry of teacher and student, adapting more aggressively at positions where the gap is largest.

These adaptive methods admit a natural interpretation through information geometry. The Fisher information metric on the statistical manifold of autoregressive distributions varies across token positions. At reasoning-critical positions, the manifold is highly curved (the teacher concentrates probability on few tokens), making Reverse KL’s mode-seeking behavior locally appropriate because it follows the manifold’s natural gradient. At generation-flexible positions, the manifold is nearly flat (many synonyms are equally valid), and Forward KL’s mode-covering behavior preserves useful entropy. Adaptive divergences implicitly navigate this varying curvature by selecting the locally optimal metric, which explains their consistent empirical superiority over any fixed choice.

The practical implication is clear: the field has moved decisively from “which divergence?” to “which divergence *where*?” The evidence from ToDi, AKL, and Entropy-Aware OPD converges on a single recommendation: no fixed divergence is ever optimal, and the simplest adaptive routing (even a hard entropy threshold) consistently outperforms the best-tuned fixed alternative.

4.3 RL-Augmented Objectives

Divergence matching, whether fixed or adaptive, intrinsically limits the student to the teacher’s capability ceiling: perfect optimization yields a student that matches (but never exceeds) the teacher’s distribution. RL-augmented objectives break this ceiling by introducing an external performance signal that can steer the student toward solutions the teacher would never produce.

OPD as KL-constrained RL. G-OPD (Yang et al., 2026c) establishes a formal equivalence between standard OPD and dense KL-constrained reinforcement learning. It formulates distillation as maximizing a token-level reward derived from teacher logits, penalized by divergence from a reference policy:

$$\max_{\theta} \mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} \alpha \log p_T(y_t | y_{<t}) - D_{\text{KL}}(p_\theta(\cdot | y_{<t}) \parallel p_{\text{ref}}(\cdot | y_{<t})) \right] \quad (10)$$

When $\alpha = 1$, this reduces to standard Reverse KL distillation. When $\alpha > 1$, the objective forces the student to *extrapolate* beyond the teacher’s probability mass, enabling a phenomenon documented as *Reward Extrapolation*: the student discovers novel, structurally sound reasoning paths in regions where the teacher’s generation probability $p_T(y|x)$ is low but the outcome reward remains high. On competition-level math, a 4B student trained with

G-OPD surpasses a 30B teacher, demonstrating that OPD need not be a lossy compression step.

This equivalence has a deeper theoretical consequence: it bridges the distillation and RL communities, providing a shared analytical language. Any advance in KL-constrained RL (better trust regions, adaptive penalty coefficients, variance reduction) immediately transfers to OPD, and vice versa.

Gradient decomposition and the KD+RL complementarity. The unified KD+RL framework of Li et al. (2025) decomposes the hybrid gradient into two orthogonal components: a dense KD gradient for token-level imitation and a Monte Carlo RL gradient for reward maximization. The KD component dampens the high variance inherent in policy gradient estimation, while the RL component prevents the student from collapsing onto teacher modes that are suboptimal for the downstream task. REOPOLD (Li et al., 2025) further formalizes this decomposition, splitting each parameter update into an imitation vector (pulling toward the teacher) and an exploration vector (pushing toward higher trajectory returns), making the complementarity explicit and tunable.

Dense KD + sparse reward. RLKD (Xu et al., 2025b) exemplifies the integration of dense teacher supervision with sparse outcome feedback. It introduces a Generative Structure Reward Model (GSRM) that scores reasoning paths for structural coherence, combining token-level KL regularization with trajectory-level reward:

$$\max_{\theta} \mathcal{J}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, y \sim p_{\theta}(\cdot|x)} [R(x, y) - \beta D_{\text{KL}}(p_{\theta}(\cdot|x) \parallel p_T(\cdot|x))] \quad (11)$$

The mathematical structure explains why the combination works: the KL term provides analytically computable dense gradients, while the reward term contributes Monte Carlo policy gradients for outcome-driven exploration.

Joint vs. sequential optimization. A persistent engineering challenge is *how* to combine KD and RL within a training pipeline. Sequential approaches (distill-then-RL or RL-then-distill) suffer from catastrophic interference: the RL stage erases distilled knowledge through policy drift, while the KD stage suppresses novel solutions discovered through exploration. KDRL (Xu et al., 2025a) operationalizes joint optimization by adding an on-policy KL regularizer between student and teacher *during* RL training. RLAD (Zhang et al., 2026e) refines this with Trust Region Ratio Distillation (TRRD), replacing the standard KL regularizer with a PPO-style likelihood-ratio objective anchored to a teacher-old-policy mixture. This selective strategy follows the teacher only when its signal improves the policy update and ignores it otherwise, a principled solution to the problem that blind KL minimization can drag the student toward suboptimal trajectories on problems the teacher itself struggles with.

Preference-based objectives. When logit access is insufficient to capture global intent, several methods map the problem onto Direct Preference Optimization (DPO). AlignDistil (Zhang et al., 2025a) constructs synthetic preference pairs from student rollouts scored by the teacher, applying both standard DPO and reverse DPO objectives for alignment. OVD (Xiong et al., 2026) queries the teacher for pairwise preferences over student-generated responses, avoiding the need for continuous probability extraction entirely.

Targeted correction vs. wholesale imitation. The RL-augmented methods above still provide uniform supervision across the entire trajectory. A distinct failure mode emerges from this uniformity: when the student makes a single error in step 3 of a 10-step proof, wholesale imitation retrains all 10 steps, diluting the corrective gradient. SuperCorrect (Yang et al., 2025b) introduces hierarchical thought templates that scaffold the student’s reasoning at both strategic and step-level granularity, then applies cross-model DPO to teach error localization. SCoRe (Lyu et al., 2025) pushes targeting to its logical extreme: rather than providing complete correction traces, the teacher identifies and corrects *only the earliest error* in the student’s trajectory, concentrating all supervision at the single point of maximum leverage. This approach exploits a structural property of reasoning chains: errors cascade, so correcting the root cause eliminates all downstream consequences simultaneously.

From signal matching to environment reconstruction. The most radical extension asks whether the student can recover the teacher’s *underlying optimization landscape*. $\mathcal{X}$ -KD (Cai &

Yuan, 2026) adopts the AVRIL framework to jointly model the teacher’s latent reward function and perform policy distillation, encouraging the student to optimize in a reconstructed version of the teacher’s training environment rather than simply mimicking its outputs. TSD-KD (Kim & Baek, 2026) combines indirect distillation (student generates candidates that the teacher re-ranks via preference feedback) with direct distillation (KL matching applied selectively to high-entropy tokens where teacher-student gaps are largest). These methods represent the current frontier: moving from matching the teacher’s *behavior* to understanding its *incentives*.

The progression across objective types reveals a fundamental insight. Fixed divergences provide stable, well-understood optimization but are limited by the teacher’s capability ceiling. Adaptive divergences improve efficiency by matching the local geometry of the loss landscape. RL-augmented objectives break through the ceiling entirely but introduce variance and instability. The optimal choice depends on the specific application: for instruction following where teacher quality is high, fixed or adaptive divergences suffice. For reasoning tasks where the student must exceed the teacher, RL augmentation is essential. For tasks where the teacher’s training process is accessible, environment reconstruction offers the most complete knowledge transfer.

5 Signal Source and Teacher Architecture

The second major decision in the OPD pipeline concerns the origin and nature of the supervisory signal. Given a fixed objective function (Section 4), the practitioner must determine *where the teacher signal comes from*: full logit access (white-box), API-only text outputs (black-box), or the model’s own internal asymmetries (self-distillation). Each signal source imposes distinct constraints on the applicable objectives and achievable performance, creating a structured design space that this section maps comprehensively.

The evolution of signal sources mirrors the broader trend toward accessibility and self-sufficiency. Early OPD methods (GKD, DistiLLM) assumed full white-box access to model internals, a requirement that limits distillation to same-organization deployments. The rise of proprietary API-only models (GPT-4, Claude) necessitated black-box methods that can extract knowledge from text outputs alone. Most recently, self-distillation methods eliminate the external teacher entirely, enabling continuous improvement without access to any stronger model. This progression, from full access through limited access to no external access, represents increasing autonomy at the cost of signal density, creating a fundamental trade-off that practitioners must navigate.

Complex reasoning is where OPD proves most indispensable and where off-policy methods encounter their hardest limits. The reason is structural: reasoning is *path-dependent*. A proof that begins “assume for contradiction...” requires entirely different subsequent tokens than one beginning “we proceed by induction...” If the student has never generated the inductive approach during training, it cannot recover at inference time when that path would be optimal. Off-policy training over a fixed dataset of teacher reasoning traces can only cover a finite set of solution paths, while the student needs to navigate its own unique landscape of partial solutions, dead ends, and recovery strategies. This insight motivates the on-policy formulation for reasoning transfer: the student generates its own intermediate reasoning steps, and the teacher evaluates these student-generated chains rather than dictating its own.

5.1 White-Box Logit Supervision

White-box access provides the densest possible signal: the full probability distribution across $|V|$ tokens at every decoding step. This exposes the teacher’s implicit decision boundaries, including the relative probabilities among incorrect tokens (Hinton’s “dark knowledge”), which carry information about similarity structure that binary labels cannot capture.

Standard logit distillation. The majority of methods surveyed in Section 4 assume white-box access. GKD, DistiLLM, ToDi, G-OPD, and their variants all require computing $p_T(\cdot|x, y_{<t})$ at each student-generated token position. The computational cost is domi-

nated by the teacher forward pass, which must be executed once per student-generated token (or once per sequence for cached implementations).

Token-level adaptive supervision. Within the white-box setting, several methods refine *which* tokens receive supervision. SelecTKD (Huang et al., 2025) applies confidence-based filtering, discarding loss gradients from positions where the teacher’s top-1 probability falls below a threshold. AdaSwitch (Peng et al., 2025) dynamically switches between exploration (student generates freely) and guidance (teacher provides dense supervision) based on the student’s cumulative error on the current prefix, balancing the exploration benefit of on-policy generation against the stability of teacher guidance. Token-Adaptive KD (Xie et al., 2025) computes per-token importance weights using the gradient magnitude of the KL loss, concentrating compute on tokens where the teacher-student gap is largest.

Token-Adaptive KD. Xie et al. (2025) compute per-token importance weights using the gradient magnitude of the KL loss, concentrating compute on tokens where the teacher-student gap is largest. This approach is complementary to entropy-based routing (ToDi, Entropy-Aware): while the latter selects *which divergence* to use at each position, Token-Adaptive KD selects *how much gradient signal* to propagate, providing a second dimension of per-token adaptation that can be combined with adaptive divergence selection.

Pre-training distillation. MiniPLM (Gu et al., 2025) extends on-policy distillation to the *pre-training* stage, showing that distilling during pre-training (rather than post-training) yields stronger foundations for downstream fine-tuning. This represents a qualitative shift: rather than being a post-hoc compression step, OPD becomes an integral part of the model creation pipeline. Gemma 2 (Gemma Team et al., 2024) validates this approach at industrial scale, embedding KD directly into the pre-training loop for its 27B→9B→2B model cascade.

Cross-architecture alignment. A critical challenge arises when teacher and student use different tokenizers or vocabulary sizes. Direct KL divergence over mismatched vocabularies is undefined. DSKD (Zhang et al., 2025b) solves this through *dual-space* knowledge distillation, introducing projectors that map between teacher and student representation spaces:

$$\mathcal{L}_{\text{DSKD}} = D_{\text{KL}}(P_{T \rightarrow S} \parallel P_S) + D_{\text{KL}}(P_{S \rightarrow T} \parallel P_T) \quad (12)$$

where $P_{T \rightarrow S}$ denotes the teacher’s hidden states projected into the student’s space and decoded through the student’s prediction head. An exact token alignment algorithm handles vocabulary mismatches by identifying identical tokens across tokenizers. The key insight is that vocabulary tokens with similar semantic embeddings should receive similar probability mass, even when the tokenization schemes differ. This enables distillation across fundamentally different architectures (e.g., Llama teacher to Qwen student) that share no vocabulary overlap.

Cross-Tokenizer KD (Boizard et al., 2025) takes a complementary approach based on optimal transport, computing an alignment matrix between teacher and student token sequences that minimizes the earth mover’s distance in latent space:

$$\mathcal{L}_{\text{CrossTok}} = \inf_{\pi \in \Pi(P_S, P_T)} \mathbb{E}_{(z_S, z_T) \sim \pi} \left[\|W_{S \rightarrow T} z_S - z_T\|_2^2 \right] \quad (13)$$

The distinction between hidden-state alignment (DSKD) and vocabulary-space alignment (Cross-Tokenizer KD) highlights a fundamental design trade-off. Hidden-state alignment preserves richer representational structure but requires maintaining two projectors during training. Vocabulary-space alignment is more lightweight but operates at a level where information has already been compressed through the vocabulary bottleneck. In either case, the alignment maps must be *co-trained* with the student, because the student’s representation space shifts during on-policy training as its policy evolves, a form of representation drift absent in off-policy settings. Concrete Score Matching (Kim et al., 2026b) provides yet another solution, distilling via a continuous score function that bypasses the discrete vocabulary mismatch entirely. Together, these methods ensure that OPD is architecture-agnostic, not limited to same-family distillation.

Signal isolation. Not all information in the teacher’s logits is equally useful. Delta-KD (Ko et al., 2026) introduces the principle of *signal isolation*: rather than distilling the teacher’s

full distribution, it distills only the *differential shift* between a base model and its instruction-tuned variant. The base model’s distribution captures generic language modeling knowledge that the student already possesses (or should acquire through standard pre-training), so distilling it is redundant at best and harmful at worst. By extracting only the instruction-following delta, Delta-KD provides a cleaner supervisory signal that transfers the teacher’s alignment without overwriting the student’s foundation.

Stable target reformulation. A subtle but important challenge in white-box OPD is that the teacher’s logit distribution can be *overconfident* on tokens outside the student’s reachable space, creating optimization targets that are simultaneously precise and useless. Adaptive Target Reformulation (Jang et al., 2026) addresses this by dynamically reformulating the teacher’s target distribution based on the student’s current capability, smoothing the teacher’s predictions at positions where the student cannot yet match them. This prevents the pathological gradient behavior where an overconfident teacher creates extremely sharp loss landscapes that the student oscillates around without converging.

Selective supervision and prompt-based distillation. PromptKD (Kim et al., 2024) takes a radically different approach to white-box distillation: rather than matching the teacher’s output distribution directly, it trains prompts that elicit teacher-like behavior from the student. The key insight is that a well-chosen prompt can activate latent capabilities in the student that direct logit matching cannot reach, because the prompt operates on the model’s *input representation* rather than its *output distribution*.

5.2 Black-Box and API-Constrained Distillation

When only API access is available, the student observes the teacher’s top-1 text output (or at best, top- k log-probabilities) rather than the full distribution. This information bottleneck eliminates token-level divergence matching and forces methods to operate at the sequence level. Despite this limitation, black-box methods have proven surprisingly effective, suggesting that much of the teacher’s knowledge is recoverable from text-only observations.

Distilling Step-by-Step. Hsieh et al. (2023) demonstrated an influential early approach: extracting not just the teacher’s final answers but its intermediate reasoning steps (rationales) as additional supervision. The student is trained with a multi-task objective combining answer prediction and rationale generation, enabling it to outperform the teacher on downstream tasks with significantly less data. This work established the principle that *how* the teacher reasons is often more valuable than *what* it concludes, a principle that pervades modern OPD.

Distilling Step-by-Step. Hsieh et al. (2023) demonstrated an influential early approach: extracting not just the teacher’s final answers but its intermediate reasoning steps (rationales) as additional supervision. The student is trained with a multi-task objective combining answer prediction and rationale generation, enabling it to outperform the teacher on downstream tasks with $1,000\times$ less data. This work established the principle that *how* the teacher reasons is often more valuable than *what* it concludes.

Adversarial distribution matching. GAD (Ye et al., 2025) reformulates the distillation problem as a generative adversarial game. A discriminator is trained to distinguish student rollouts from teacher API outputs, and its confidence serves as a proxy reward for the student’s policy gradient update. This approach recovers distributional information that text-only observation loses: even though the teacher’s full distribution is hidden, the discriminator learns to identify systematic differences between teacher and student output distributions, providing a dense training signal from sparse observations.

Verbal feedback and curriculum. Lion (Jiang et al., 2023) exploits the teacher’s capacity as a natural language critic. Rather than extracting numerical probabilities, it queries the teacher for verbal feedback on student errors, then uses this feedback to construct a curriculum of increasingly difficult prompts. This approach requires no gradient information whatsoever, making it applicable to any instruction-following API.

Didactic-to-constructive learning. DAIL (Mendes et al., 2026) treats text-only distillation as an imitation learning problem, applying inverse reinforcement learning to infer the implicit reward function guiding the teacher’s generation choices from observed text trajectories. Distribution-Aligned Sequence Distillation (Yan et al., 2026) complements this by aligning the student’s long chain-of-thought generation distribution with the teacher’s through sequence-level distribution matching, addressing the specific challenge that long reasoning traces are particularly vulnerable to distribution shift in black-box settings.

Verbal score distillation. OVD (Xiong et al., 2026) replaces token-level probability matching entirely with trajectory matching using discrete verbal scores (0–9) from teacher models. This eliminates the requirement for token-level alignment between vocabularies, dramatically reduces memory consumption by avoiding logit storage, and delivers up to +12.9% absolute EM improvement on web QA.

Preference-based formulations. ORPO-Distill (Singh et al., 2025) maps black-box distillation onto preference optimization, generating candidate responses from the student and querying the teacher API for pairwise rankings. The student then optimizes an ORPO-style objective on these teacher-ranked pairs, recovering alignment signal without logit access. ThinkTuning (RRV et al., 2025) instills cognitive reflections into the student by training it to generate “thinking” traces that the teacher evaluates for quality, combining black-box feedback with reasoning transparency.

Off-policy knowledge integration. A related challenge is incorporating knowledge from off-policy sources (e.g., pre-existing teacher-generated datasets) into an on-policy framework. LUFFY (Yan et al., 2025) addresses this by extending GRPO to a mixed-policy objective that incorporates off-policy reasoning traces alongside the student’s on-policy rollouts. The critical design challenge is preventing *superficial imitation*: without correction, the student tends to copy high-probability tokens from off-policy traces while ignoring low-probability but critical reasoning steps. LUFFY’s policy shaping via regularized importance sampling reweights gradients to emphasize learning from unfamiliar yet effective actions, achieving +6.4 average points over standard RLVR.

5.3 Self-Distillation: Privileged Information

Self-distillation eliminates the need for an external teacher entirely. Instead, the model exploits asymmetries *within itself* to construct a training signal. The first family of self-distillation methods creates this asymmetry through *privileged information* (PI): training-time access to context that is unavailable at inference. The central insight is that conditioning the same model on additional context produces a strictly stronger policy that can supervise the unconditioned version, turning a single network into both teacher and student.

Ground-truth as PI. OPSD (Zhao et al., 2026b) constructs the teacher policy by conditioning on both the problem x and the ground-truth answer y^* , while the student conditions only on x . The student generates on-policy rollouts, and the teacher provides dense token-level supervision:

$$\mathcal{L}_{\text{OPSD}}(\theta) = \mathbb{E}_{(x, y^*) \sim \mathcal{S}} \mathbb{E}_{\hat{y} \sim p_{\theta}(\cdot | x)} \left[\sum_{n=1}^{|\hat{y}|} D(p_{\theta}(\cdot | x, y^*, \hat{y}_{<n}) \parallel p_{\theta}(\cdot | x, \hat{y}_{<n})) \right] \quad (14)$$

On competition-level math (AIME 2024/2025), OPSD matches or exceeds GRPO at 4B and 8B scales while using only a single rollout per problem versus GRPO’s eight, though at 1.7B the gains are minimal, indicating that sufficient model capacity is necessary for the PI mechanism to provide useful supervision.

HDPO (Ding, 2026) addresses a specific failure mode of OPSD: when all student rollouts fail (the “cliff prompt” problem), the policy gradient vanishes entirely. HDPO augments GRPO with a JSD-based self-distillation term on ground-truth-conditioned rollouts, ensuring non-zero gradients even at the boundary of the student’s competence.

Relaxing the ground-truth requirement. Ground-truth labels are not always available. GATES (Stein et al., 2026) demonstrates that *any* training-time context can serve as PI by having a single model act as tutor (conditioned on a source document) and student

(answering from the question alone). Because source documents do not guarantee correct answers, GATES introduces a consensus-based gating mechanism that suppresses the gradient when tutor uncertainty is high, preventing the model from reinforcing unreliable self-supervision. [Penaloza et al. \(2026\)](#) generalize the OPSD and GATES paradigms into a unified theoretical framework, formalizing the conditions under which privileged self-distillation provably improves over standard training.

Behavioral PI: context distillation. The PI paradigm extends beyond factual ground truth to behavioral instructions. OPCD ([Ye et al., 2026b](#)) treats system prompts, exemplars, and retrieval context as privileged information, enabling a model to internalize behaviors that would otherwise require expensive in-context demonstrations at inference time. OEL ([Ye et al., 2026a](#)) extends to continuous post-deployment learning, using interaction outcomes as dynamic PI that updates the model’s teacher policy as it accumulates experience, closing a loop that OPCD opened.

Reasoning compression via PI. CRISP ([Sang et al., 2026](#)) demonstrates that a model prompted to “be concise” can serve as a teacher for its own verbose version, reducing chain-of-thought token count by 57–59% on MATH-500 while *improving* accuracy by 9–16 percentage points. This reveals that much of the verbosity in distilled reasoning models is a trainable inefficiency, not a necessary feature of competent reasoning.

5.4 Self-Distillation: Self-Play

A more radical question is whether a model can improve using nothing but its own rollouts, with no PI, no external feedback, and no additional context. The answer is a qualified yes, subject to important saturation limitations.

Self-play as a two-player game. SPIN ([Chen et al., 2024](#)) casts self-improvement as an adversarial game between successive checkpoints, training the updated model to distinguish its previous iteration’s generations from human-written responses:

$$\mathcal{L}_{\text{SPIN}} = \mathbb{E}_{x, y \sim p_{\text{data}}, y' \sim p_{\theta_t}} \left[\ell \left(\lambda \left(\log \frac{p_{\theta_{t+1}}(y|x)}{p_{\theta_t}(y|x)} - \log \frac{p_{\theta_{t+1}}(y'|x)}{p_{\theta_t}(y'|x)} \right) \right) \right] \quad (15)$$

SPIN provides a theoretical convergence guarantee at $p_{\theta} = p_{\text{data}}$. Starting from Zephyr-7B-SFT, it improves MT-Bench from 5.94 to 6.78 over 3 iterations, with diminishing returns at each round, revealing a fundamental limitation: pure self-play recycles existing knowledge rather than generating new knowledge.

Temporal self-supervision. SDFT ([Shenfeld et al., 2026](#)) positions on-policy self-distillation as a mechanism for forgetting resistance via implicit KL regularization against the model’s own prior checkpoint, converting the model’s optimization trajectory into a regularization resource for continual learning.

Self-play for efficiency. MTP via self-distillation ([Kirchenbauer et al., 2026](#)) converts a pre-trained autoregressive model into a multi-token predictor, achieving $> 3\times$ faster decoding at $< 5\%$ accuracy drop. On-Policy SFT ([Zhao et al., 2026a](#)) shows that truncation-based length penalties can simplify RL to standard SFT on self-generated data filtered for correctness and conciseness. Self-Distilled RLVR ([Yang et al., 2026a](#)) combines self-distillation with verification-based RL, showing that the two mechanisms are complementary: self-distillation provides the dense signal for stable training while RLVR provides the sparse but accurate outcome signal for quality improvement.

Minimalist self-distillation. SSD ([Zhang et al., 2026c](#)) requires no RL, no verifier, no external teacher, and no code execution. It samples solutions at training-time temperature, fine-tunes via standard SFT, and reshapes token distributions in a context-dependent manner. On LiveCodeBench v6, SSD improves Qwen3-30B-Instruct from 42.4% to 55.3%, revealing that when the base model is sufficiently capable, even the simplest self-play yields substantial gains. The critical requirement is not a sophisticated algorithm but sufficient *diversity* in the model’s sampling distribution to produce high-quality variants that can serve as training targets.

However, this conclusion also reveals the fundamental boundary of pure self-play: when diversity is achieved through temperature sampling alone, the model’s improvement is ultimately bounded by the information already present in its pre-training distribution. Bridging this boundary requires either connecting the model to external reality (Section 5.5) or internally generating privileged information through the self-play process itself (π -Play below).

Unifying PI and self-play. π -Play (Zhang et al., 2026d) unifies privileged information and self-play within a single multi-agent self-evolution framework. The key observation is that self-play naturally produces a byproduct: during task generation, the examiner agent constructs a question construction path (QCP) that provides high-quality PI at no additional cost. Three co-evolving agents (examiner π_ϕ^E , teacher π_ψ^T conditioned on QCP, student π_θ^S without it) are jointly optimized through alternating updates. As the student strengthens, the examiner generates harder tasks, and the teacher’s behavior is softly constrained to track the student via a KL penalty, establishing a self-adjusting curriculum that requires no external data. On Qwen3 (4B, 8B), data-free π -Play surpasses supervised search agents (Search-R1 by 5–15%) and improves efficiency by 2–3 $\times$ over conventional self-play (Dr.Zero), with the largest gains on multi-hop benchmarks where the teacher’s token-level credit assignment provides the most leverage.

π -Play demonstrates that the self-play saturation problem can be mitigated *without* external feedback by internally generating privileged information through the self-play process itself. This mechanism is orthogonal to the external-verification strategies of Section 5.5, suggesting that the two approaches could be combined for even stronger self-improvement.

5.5 Self-Distillation: External Feedback

Pure self-play is inherently bounded by the information already present in the model’s pre-training distribution. External signals, such as compiler outputs, test results, and textual critiques, ground self-distillation in objective reality and bridge the gap to reinforcement learning.

From binary rewards to dense supervision. SD-ZERO (He et al., 2026) converts sparse verifier signals into dense self-supervision through self-revision: after generating a solution and receiving a binary reward, the model generates a *revised* solution conditioned on the original attempt. When the revision succeeds where the original failed, the (original, revision) pair provides a natural preference signal. SDPO (Hübotter et al., 2026) extends this to preference optimization, using the model’s own correct and incorrect rollouts as preference pairs scored by external verifiers.

Environmental grounding. RLTF and related methods use compiler outputs, unit test results, and symbolic math verifiers as external feedback that shatters self-reinforcing echo chambers. Even if the model becomes highly confident in a flawed derivation, the verifier assigns $R = 0$, providing an unambiguous correction signal that pure self-play cannot generate.

Saturation analysis. Kim et al. (2026a) trace self-distillation degradation in mathematical reasoning to the suppression of *epistemic verbalization*: the model’s expression of uncertainty during reasoning. When self-distillation shortens reasoning traces, it disproportionately removes hedging phrases and uncertainty markers that serve as implicit “attention flags” for difficult sub-problems. The result is shorter but less calibrated reasoning, where the model confidently commits to flawed steps. This connects to the teacher uncertainty challenge in Section 7: an overconfident student produces unreliable self-play targets, and the saturation problem ultimately requires either external grounding or the internally generated PI mechanism of π -Play to overcome.

6 Training Dynamics and Efficiency

Given an objective function (Section 4) and a signal source (Section 5), the final engineering decision is *how to stabilize and accelerate the on-policy training loop*. On-policy generation

introduces unique optimization challenges absent from standard supervised fine-tuning: non-stationary data distributions (the student’s policy shifts during training, making older rollouts stale), gradient signal-to-noise ratio (SNR) collapse on hard prompts (where all rollouts fail and no useful gradient emerges), and the computational overhead of autoregressive student rollouts followed by teacher scoring (typically $4\text{--}5\times$ more expensive than off-policy training).

These challenges are not independent. SNR collapse on hard prompts wastes compute, motivating curriculum strategies that avoid such prompts. Non-stationarity invalidates cached teacher signals, motivating efficient online scoring. And the compute overhead of autoregressive generation creates a systems-level bottleneck that requires architectural solutions. The methods in this section address these challenges through three complementary mechanisms.

6.1 Token and Sample Weighting

Not all teacher supervision is equally reliable in the on-policy setting. The core problem is the *flawed prefix trap*: when a student generates an erroneous token early in a sequence, all subsequent teacher predictions are conditioned on this out-of-distribution prefix. Because the teacher has never been trained on such prefixes, its conditional distribution $p_T(\cdot|x, \hat{y}_{<t}^{\text{bad}})$ becomes noisy and unreliable. Naively matching this corrupted signal propagates errors rather than correcting them.

Teacher reliability filtering. TIP (Xu et al., 2026b) (Token Importance Profiling) quantifies this problem by computing the discrepancy between the teacher’s predictions conditioned on the student’s prefix versus the teacher’s own prefix. At positions where this discrepancy exceeds a threshold, the teacher is deemed unreliable and the loss gradient is attenuated. SCOPE (Zheng et al., 2026) extends this to a routing mechanism that redirects student rollouts through the teacher’s own generation when the student’s prefix quality falls below a confidence threshold, ensuring that the teacher always evaluates sequences within its training distribution.

SelecTKD (Huang et al., 2025) applies confidence-based filtering at the token level, discarding loss gradients from positions where the teacher’s top-1 probability falls below a threshold. The reasoning is that low teacher confidence indicates either genuine ambiguity (where any student token is acceptable) or distributional confusion (where the teacher cannot provide useful supervision), and in neither case does the gradient carry reliable information.

AdaSwitch (Peng et al., 2025) introduces a dynamic switching mechanism between pure exploration and guided distillation. Unlike static filtering that simply attenuates unreliable signals, AdaSwitch maintains a running estimate of the student’s cumulative prefix quality and switches between on-policy exploration (when the prefix is reasonable) and off-policy guidance (when the prefix has drifted too far). This binary switching is computationally simpler than continuous weighting while empirically achieving similar stability.

Sample-level weighting. Beyond token-level filtering, several methods weight entire samples based on their informativeness. The flawed prefix trap manifests most severely on *hard* prompts where the student’s pass rate approaches zero. On these prompts, nearly all rollouts contain early catastrophic errors, and the resulting teacher signals are dominated by noise. Methods that uniformly sample prompts waste most of their gradient budget on uninformative hard prompts or trivially correct easy prompts, with the productive learning concentrated on prompts at the boundary of the student’s competence.

Failure-mode analysis. Fu et al. (2026) provide a systematic empirical analysis of why sampled-token OPD is fragile in long-horizon settings. They identify three failure modes: (1) an imbalanced one-token signal that reduces distribution matching to a single sample, (2) unreliable teacher guidance on student-generated prefixes that deviate from the teacher’s training distribution, and (3) distortions caused by tokenizer or special-token mismatch. Their proposed fix, teacher top- K local support matching via truncated Reverse KL with

top- p rollout sampling and special-token masking, yields more stable optimization across math reasoning and agentic training.

6.2 Curriculum and Difficulty Adaptation

The sample weighting problem motivates a more principled solution: *curriculum design* that actively selects prompts matching the student’s current competence level.

Competence-boundary sampling. PACED (Xu et al., 2026a) models prompt difficulty dynamically using a Beta-kernel distribution centered on the student’s current pass rate. The curriculum progressively shifts toward harder prompts as the student improves, but critically avoids prompts where the pass rate is near zero (where gradient SNR vanishes) or near one (where the student has already mastered the content). This “frontier sampling” strategy concentrates the gradient budget on the narrow band of prompts where learning is most efficient.

The mathematical justification connects to the gradient SNR analysis: for a prompt with pass rate p , the expected gradient magnitude scales as $p(1 - p)$, which is maximized at $p = 0.5$ and vanishes at both extremes. PACED’s Beta-kernel sampling directly optimizes for this quantity, providing a theoretically grounded alternative to uniform prompt sampling.

Self-adjusting curricula. π -Play’s multi-agent framework (Section 5.4) provides an alternative curriculum mechanism: as the student strengthens, the examiner agent automatically generates harder tasks, creating a self-adjusting difficulty ladder that requires no external difficulty estimation. This approach is attractive when difficulty metrics are hard to define, but its effectiveness depends on the quality of the examiner’s task generation.

Off-policy cold start. Li et al. (2026d) identify that OPD can fail catastrophically when the student’s initial policy is too far from the teacher’s distribution (the “thinking-pattern mismatch” problem). Their proposed solution is an off-policy cold-start phase: a brief period of standard SFT on teacher-generated data that reduces the pattern gap before switching to on-policy training. This two-phase approach, off-policy warmup followed by on-policy refinement, has become the standard industrial pattern (Section 8).

Retaining knowledge during on-policy training. A complementary concern is that on-policy training can cause *catastrophic forgetting* of capabilities the student acquired during pre-training. Chen et al. (2025) (“Retaining by Doing”) demonstrate that on-policy data generation itself serves as an implicit rehearsal mechanism: by generating sequences from its own distribution, the student naturally revisits and reinforces its existing capabilities while learning new ones. This insight suggests that the on-policy generation step provides a dual benefit: it both exposes the student to its own error states (enabling correction) and rehearses its existing capabilities (preventing forgetting), offering a theoretical explanation for why on-policy methods empirically suffer less from catastrophic forgetting than sequential fine-tuning approaches.

Semantic bootstrapping. Semantic Soft Bootstrapping (Mitra & Ulukus, 2025) provides a different perspective on curriculum design: rather than adapting the *difficulty* of prompts, it adapts the *semantic granularity* of supervision. The method progressively refines the teacher’s supervision from coarse semantic alignment (matching high-level reasoning structure) to fine-grained token-level matching, allowing the student to first acquire the overall reasoning pattern before optimizing the precise token distributions.

6.3 Compute Optimization

OPD requires generating student rollouts *and* scoring them with the teacher at every training step, creating a compute overhead of $3\text{--}8\times$ compared to off-policy SFT. Several methods target this bottleneck.

Prefix truncation. Fast OPD (Zhang et al., 2026a) observes that exposure bias is concentrated in the early tokens of a sequence, where errors compound most severely. It truncates on-policy rollouts to a prefix of length k and reverts to off-policy KD for the remainder, achieving comparable quality at substantially reduced cost. The optimal truncation point

k depends on the task: for mathematical reasoning, where errors cascade rapidly, short prefixes suffice; for open-ended generation, longer on-policy segments are needed.

Offline teacher caching. Lightning OPD (Wu et al., 2026) decouples student optimization from teacher inference entirely by precomputing teacher distributions into an offline memory bank and asynchronously refreshing them. When teacher distributions are *consistent* (i.e., the teacher’s output depends primarily on the prompt and only weakly on the specific student prefix), the cached distributions remain valid even as the student’s policy evolves. Lightning OPD demonstrates that offline distillation under teacher consistency can match online OPD at $4\times$ lower cost, significantly lowering the barrier for academic research.

Speculative knowledge distillation. Speculative KD (Xu et al., 2025c) adapts speculative decoding to the distillation setting: the student generates candidate tokens that the teacher *verifies and selectively replaces*, amortizing the teacher’s inference cost across multiple student tokens per teacher forward pass. DistillSpec (Zhou et al., 2023) inverts this: instead of using speculation to speed up training, it uses on-policy KD to improve the draft model for speculative decoding at *inference* time. The expected speedup:

$$E[S] = \frac{\mathbb{E}[K_{\text{accepted}}] + 1}{1 + c} \quad \text{where } c = \frac{\text{cost}(\text{student forward})}{\text{cost}(\text{teacher forward})} \quad (16)$$

This reveals a virtuous cycle: better distillation produces better draft models, which enable faster speculative decoding, which in turn enables more efficient distillation, progressively reducing the computational barrier.

GPU memory management. Beyond FLOPs, the most severe constraint for white-box OPD is GPU memory. Holding a 70B teacher alongside a 7B student requires the teacher’s weights (~ 140 GB in BF16), the student’s weights and optimizer states (~ 84 GB), and the full-vocabulary logits tensor $[B, T, |V|]$ for distillation. Peak memory can easily exceed an 8×80 GB H100 node. Practitioners alleviate this via: (1) *teacher quantization*, serving the teacher in FP8 or INT4 for a $2\text{--}4\times$ memory reduction at negligible precision loss, (2) *logit offloading*, immediately streaming logits to CPU RAM or retaining only the top- k entries (since 99% of the probability mass is typically concentrated in fewer than 100 tokens), and (3) *aggressive gradient checkpointing* to minimize student activation memory during the backward pass. Combining these techniques is essential for viable white-box OPD on standard clusters.

Concrete cost example. To ground these formulas, consider distilling a 70B teacher into a 7B student on $8\times$ H100 GPUs. Off-policy over 1B tokens: the teacher generates the dataset offline (~ 200 GPU-hours), the student trains for ~ 100 GPU-hours, totaling ~ 300 GPU-hours. On-policy over 1B tokens: each step requires (1) student generation ($\sim 3\times$ forward-pass cost due to autoregressive decoding), (2) teacher scoring (one 70B forward pass), and (3) student backward pass, yielding $\sim 1,200\text{--}1,500$ GPU-hours, a $4\text{--}5\times$ overhead. However, for reasoning tasks, on-policy methods consistently outperform off-policy SFT, and the off-policy performance ceiling is strictly lower because static datasets cannot cover the combinatorial space of valid reasoning paths. This “ceiling gap” widens with task complexity, providing the strongest cost-benefit justification for on-policy methods.

7 Understanding OPD: Theory, Failure Modes, and Cost

The preceding sections addressed the *how* of on-policy distillation: what to optimize (Section 4), where the signal comes from (Section 5), and how to stabilize training (Section 6). This section turns to the equally important *why* and *when*: under what conditions does OPD succeed, how does it fail, what theoretical frameworks unify the diverse methods surveyed above, and when should practitioners invest in OPD versus simpler off-policy pipelines?

Crucially, these four dimensions of understanding are not independent: they form a cumulative argument. Identifying *when* OPD works (Section 7.1) reveals the preconditions that the theoretical framework must explain. Cataloging *how* it fails (Section 7.2) motivates the specific design choices, adaptive divergences, curriculum weighting, and hybrid RL objectives, whose theoretical grounding Section 7.3 provides. Both the success conditions

and the failure modes then inform the practical cost-benefit analysis in Section 7.4, which distills the theoretical insights into engineering guidelines. Answering these questions is essential for moving OPD from an empirical art toward a principled engineering discipline with predictable outcomes.

7.1 Success Conditions

Li et al. (2026d) provide the most systematic investigation of OPD training dynamics, identifying two necessary conditions for effective distillation.

Thinking-pattern consistency. The student and teacher must share compatible reasoning patterns, operationalized as a high overlap ratio in their top- k token distributions. Even when the teacher achieves higher benchmark scores, a mismatched thinking pattern (e.g., a non-thinking teacher distilling into a thinking student) causes low initial overlap that training cannot fully recover. This finding implies that the teacher selection problem is not simply about capability but about *distributional compatibility*.

Genuine new knowledge. The teacher must provide capabilities beyond what the student has already acquired. When both models are trained on the same data and recipe, they converge to similar distributions at their respective scales, leaving the teacher with little transferable signal. Reverse distillation experiments show that same-family 1.5B and 7B teachers are distributionally indistinguishable from the student’s perspective.

At the token level, successful OPD is characterized by progressive alignment on *high-probability overlap tokens*, a small shared token set concentrating 97–99% of the probability mass. When these conditions fail, recovery strategies include off-policy cold start (SFT initialization that reduces the pattern gap) and teacher-aligned prompt selection. Critically, the quality of OPD’s dense supervision degrades systematically with trajectory depth, with instability originating at later tokens and propagating backward, raising fundamental questions about OPD’s applicability to long-horizon reasoning.

These findings point toward a general principle: OPD’s benefit scales with the *exploitable gap* between teacher and student. When this gap is too small (same-recipe models), the teacher offers no new information. When too large (thinking-pattern mismatch), the student cannot absorb the supervision. The productive regime lies in between, and identifying it is the central diagnostic challenge.

7.2 Failure Modes

Complementing the success conditions, a growing body of work catalogs the specific ways OPD can fail *even when structural preconditions hold*, as artifacts of the on-policy training dynamics themselves.

The flawed prefix trap. As detailed in Section 6.1, when the student generates an erroneous prefix, the teacher’s conditional distribution over subsequent tokens is poorly calibrated because the teacher was never trained on such out-of-distribution inputs. Fu et al. (2026) formally characterize three specific failure modes: (1) an imbalanced one-token signal that reduces distribution matching to a single sample, (2) unreliable teacher guidance on out-of-distribution student prefixes, and (3) tokenizer mismatch distortions. The theoretical analysis reveals a fundamental bias-variance tradeoff: token-level OPD is biased relative to sequence-level Reverse KL but enjoys tighter worst-case variance bounds.

Gradient SNR collapse. When the student’s pass rate on a prompt approaches zero, all rollouts contain early errors, the teacher’s signals are dominated by noise, and the gradient SNR vanishes. This is the mathematical explanation for why hard prompts yield no learning signal in standard OPD, motivating PACED’s competence-boundary curriculum (Section 6.2) and HDPO’s gradient augmentation (Section 5.3).

Epistemic suppression. Kim et al. (2026a) identify a subtle failure mode in self-distillation: when the process shortens reasoning traces (a common desirable outcome), it disproportionately removes *hedging phrases and uncertainty markers* that serve as implicit attention flags for difficult sub-problems. The result is shorter but less calibrated reasoning, where

the model confidently commits to flawed steps it would have reconsidered in longer traces. This calibration degradation connects directly to the teacher uncertainty challenge: an overconfident student produces unreliable self-play targets, creating a vicious cycle.

Self-play saturation (the Ouroboros problem). In self-distillation settings, the student optimizes against a target sharing its own inductive biases and architectural limitations, causing the hypothesis space to progressively collapse. If the model discovers a syntactic “hack” or a highly confident but flawed reasoning heuristic, no external signal penalizes it. The model self-reinforces this flawed trajectory, driving $p_\theta(y_{\text{flawed}}|x) \rightarrow 1$. Once entirely certain of its own hallucinations, gradients vanish, exploration ceases, and the policy is trapped. This is distinct from exposure bias (which arises from train-test distribution mismatch in off-policy settings): saturation arises from the *absence* of distributional diversity in fully on-policy self-play, and is mathematically analogous to mode collapse in generative adversarial networks.

7.3 Unified Theoretical Perspectives

The success conditions and failure modes above raise a natural question: can they be explained by a single theoretical framework? Several recent works demonstrate that they share common mathematical roots.

The unified f -divergence perspective. The framework of Wen et al. (2023) subsumes Forward KL, Reverse KL, JSD, and α -divergences as special cases parameterized by a single convexity function f . Since all these divergences can be expressed as expectations under the student’s on-policy distribution, the choice of divergence is a *regularization* decision. The generator function f determines the implicit weighting of likelihood ratios $p_T(y)/p_\theta(y)$: Forward KL up-weights regions where the student underestimates the teacher (coverage), while Reverse KL up-weights regions of overestimation (precision). Wu et al. (2025) challenge the standard mode-seeking/covering dichotomy for discrete LLM distributions, demonstrating that under practical epoch budgets the difference is better understood through *head-tail focus*: Forward KL concentrates learning on the head of the teacher distribution, while Reverse KL emphasizes the tail. This ratio-weighting interpretation explains why adaptive methods that switch between divergences based on local geometry consistently outperform any fixed choice.

Why KD works: minimal explanations. Cha & Cho (2025) provide a theoretical grounding for *why* knowledge distillation works at all in generative models, identifying the minimal conditions under which a student can provably benefit from teacher supervision versus learning from data alone. Their analysis shows that the benefit of KD scales with the *information gap* between the teacher’s distribution and the data distribution as seen by the student, providing a theoretical foundation for the “exploitable gap” identified empirically by Li et al. (2026d).

Unifying self-distillation and group-relative optimization. Li et al. (2026b) prove that Group-Relative Policy Optimization (GRPO) and self-distillation are mathematically equivalent under certain conditions, with the preference signal in GRPO being implicitly a form of self-distillation against the model’s own best rollouts. This unification has practical implications: it suggests that the choice between GRPO-style RL and explicit self-distillation is often a matter of implementation convenience rather than fundamental algorithmic difference.

Demystifying OPD dynamics. Luo et al. (2026) address a persistent practical concern: OPD often causes *length inflation*, where the student’s outputs grow progressively longer during on-policy training. They identify the root cause as an asymmetry in the KL gradient: positive KL gradients (pushing the student toward teacher-preferred tokens) are stronger than negative KL gradients (pulling away from teacher-dispreferred tokens), creating a net bias toward longer sequences. Their proposed stabilization strategies, including length-normalized objectives and adaptive KL coefficients, provide practical solutions to a problem that has plagued many OPD implementations.

OPD as KL-constrained RL. G-OPD’s equivalence proof (Section 4.3) establishes that standard OPD is a special case of dense KL-constrained RL. This bridges the distillation

and RL communities, providing a shared analytical language and ensuring that advances in either field immediately transfer to the other.

The KD+RL gradient complementarity. The unified KD+RL framework of Li et al. (2025) decomposes the hybrid gradient into a dense KD component (stable, analytically computable) and a Monte Carlo RL component (high variance, reward-driven). The KD component dampens variance in policy gradient estimation, while the RL component prevents collapse onto suboptimal teacher modes. This theoretical insight implies that the optimal KD-to-RL weighting ratio should decrease over training as the student’s policy stabilizes.

Expanding RL capabilities via text feedback. Song et al. (2026) show that textual feedback from a teacher can expand the effective capabilities of RL beyond what outcome-only rewards achieve, providing theoretical justification for the verbal feedback methods (Lion, OVD, ThinkTuning) surveyed in Section 5.2. The key insight is that text feedback provides a *denser* reward signal than binary outcomes, enabling the student to learn from partial successes that binary verification would discard.

Together, these perspectives converge on a central insight: on-policy distillation, reinforcement learning, and preference optimization are not separate training approaches but rather points on a continuous spectrum parameterized by the density of supervision, the choice of divergence, and the source of the training signal.

7.4 On-Policy vs. Off-Policy: The DeepSeek-R1 Analysis

The theoretical frameworks above establish that on-policy training offers principled advantages. But theory alone cannot settle the question of when practitioners should invest in on-policy infrastructure versus relying on simpler off-policy pipelines.

The DeepSeek-R1 anomaly. DeepSeek-R1 (DeepSeek-AI et al., 2025) represents the most prominent off-policy distillation success, training students from 1.5B to 70B on $\sim 800K$ samples of long chain-of-thought reasoning traces via purely off-policy SFT. On AIME 2024 (pass@1), R1-Distill-Qwen-7B reaches 55.5%, and R1-Distill-Qwen-32B reaches 72.6%. Crucially, off-policy distillation *decisively outperforms direct RL* for small-to-medium models: at the 32B scale, GRPO applied directly to Qwen2.5-32B-Base achieves only 47.0% on AIME 2024, a gap of 25.6 percentage points.

Three factors explain why off-policy works so well here: (1) the teacher is an exceptionally strong 671B MoE model whose reasoning traces cover a wide region of the problem space, providing such thorough coverage that exposure bias is empirically mitigated for most standard reasoning paths. (2) The $\sim 800K$ traces include diverse reasoning strategies (backtracking, verification, alternative approaches), effectively exploring multiple paths per problem. (3) The student models are relatively small (1.5B–70B), so the effective complexity of the conditional distribution (given long reasoning prefixes) is manageable for even off-policy learning.

Why on-policy remains necessary. DDT (Zhang et al., 2026b) provides formal justification: the key factor driving RL’s generalization advantage is on-policy data generation, which keeps training aligned with the model’s evolving distribution. The off-policy ceiling, the maximum achievable performance regardless of data volume, is strictly lower because static datasets cannot cover the combinatorial space of valid reasoning paths. This ceiling gap widens with three factors: task complexity (more reasoning steps $\Rightarrow$ more paths to cover), output diversity requirements (creative tasks vs. math), and model capability (stronger students explore further from the training data).

The hybrid pipeline. Qwen3 (Yang et al., 2025a) and MiMo-V2 (Xiaomi LLM-Core Team et al., 2026) operationalize this insight, combining off-policy cold-start with on-policy refinement. This two-phase pattern, off-policy SFT to establish a strong foundation followed by on-policy OPD or RL to close the remaining distribution gap, has emerged as the standard industrial recipe. The optimal transition point (when to switch from off-policy to on-policy) depends on the student’s initial capability: weaker students benefit more from extended off-policy warmup, while stronger students can transition earlier.

Table 2: Comprehensive comparison of on-policy distillation methods organized by primary contribution dimension.

Method	Year	Category	Divergence/Objective	Signal	Granularity	Key Innovation
<i>Objective: Fixed Divergences</i>						
GKD (Agarwal et al., 2024)	2024	Objective	F-KL / R-KL / JSD	White-box	Token	Unified OPD framework, Dagger for LLMs
MiniLLM (Gu et al., 2024)	2024	Objective	Reverse KL	White-box	Sequence	REINFORCE with teacher as reward
DistiLLM (Ko et al., 2024)	2024	Objective	Skew KL (SKL+SRKL)	White-box	Token	α -smoothing for KL stability
DistiLLM-2 (Ko et al., 2025)	2025	Objective	Contrastive SKL/SRKL	White-box	Token	Asymmetric loss per data source
KETCHUP (Fan et al., 2025)	2025	Objective	Reverse KL	White-box	Sequence	K -step truncated REINFORCE
Constrained (Zimmer et al., 2025)	2025	Objective	Constrained KL	White-box	Sequence	State-augmented CMDP
<i>Objective: Adaptive Divergences</i>						
AKL (Wu et al., 2025)	2025	Objective	Adaptive FKL+RKL	White-box	Token	Ratio-based confidence routing
ToDi (Jung et al., 2025)	2025	Objective	Entropy-routed FKL/RKL	White-box	Token	Hard entropy threshold switching
Entropy-Aware (Jin et al., 2026)	2026	Objective	Continuous FKL+RKL blend	White-box	Token	Smooth entropy interpolation
<i>Objective: RL-Augmented</i>						
G-OPD (Yang et al., 2026c)	2026	Objective	KL-Constrained RL	White-box	Token/Seq	OPD $\equiv$ dense KL-RL, reward extrapolation
RLKD (Xu et al., 2025b)	2025	Objective	KD + Reward Model	White-box	Sequence	Structure-aware reward model
KDRL (Xu et al., 2025a)	2026	Objective	Joint KD + RL	White-box	Token/Seq	On-policy KL regularizer during RL
RLAD (Zhang et al., 2026e)	2026	Objective	Trust Region Ratio	White-box	Token/Seq	PPO-style selective teacher following
AlignDistil (Zhang et al., 2025a)	2025	Objective	DPO + Reverse DPO	White-box	Sequence	Synthetic preference from rollouts
SuperCorrect (Yang et al., 2025b)	2025	Objective	Template + Cross-DPO	White-box	Sequence	Hierarchical thought scaffolding
SCoRe (Lyu et al., 2025)	2025	Objective	Earliest-error correction	White-box	Sequence	Root-cause error targeting
<i>Signal: White-Box Innovations</i>						
DSKD (Zhang et al., 2025b)	2025	Signal	Dual-Space KL	White-box	Token	Cross-vocabulary projection
Cross-Tok. KD (Boizard et al., 2025)	2025	Signal	Latent OT alignment	White-box	Token	Optimal transport for tokenizer mismatch
Delta-KD (Ko et al., 2026)	2026	Signal	Base-to-Instruct delta	White-box	Token	Signal isolation
PromptKD (Kim et al., 2024)	2024	Signal	Prompt-based elicitation	White-box	Token	Input-side distillation
MiniPLM (Gu et al., 2025)	2025	Signal	Pre-training KD	White-box	Token	OPD during pre-training
<i>Training Dynamics</i>						
TIP (Xu et al., 2026b)	2026	Dynamics	Teacher reliability filter	White-box	Token	Prefix discrepancy attenuation
SCOPE (Zheng et al., 2026)	2026	Dynamics	Rollout routing	White-box	Token	Redirect on flawed prefix
SelectKD (Huang et al., 2025)	2025	Dynamics	Confidence filtering	White-box	Token	Top-1 probability threshold
AdaSwitch (Peng et al., 2025)	2025	Dynamics	Exploration/guidance switch	White-box	Token	Binary mode switching
PACED (Xu et al., 2026a)	2026	Dynamics	Beta-kernel curriculum	White-box	Sample	Frontier difficulty sampling
Fast OPD (Zhang et al., 2026a)	2026	Dynamics	Prefix truncation	White-box	Hybrid	Early-token focus
Lightning OPD (Wu et al., 2026)	2026	Dynamics	Offline caching	White-box	Token	4 $\times$ cost reduction
Speculative KD (Xu et al., 2025c)	2025	Dynamics	Draft-verify	White-box	Block	Amortized teacher cost
Revisiting OPD (Fu et al., 2026)	2026	Dynamics	Top- p rollout + masking	White-box	Token	Empirical failure mode fixes
Stable-OPD (Luo et al., 2026)	2026	Dynamics	R-KL + reference div.	White-box	Token	Rollout mixing for stability
<i>Self-Distillation</i>						
SPIN (Chen et al., 2024)	2024	Self-Play	Self-play DPO	Self	Sequence	Iterative self-vs-reference game
OPSD (Zhao et al., 2026b)	2026	Self (PI)	KL on GT-conditioned	Self	Token	Ground-truth as privileged info
CRISP (Sang et al., 2026)	2026	Self (PI)	Conciseness PI	Self	Token	57% token reduction, +9% accuracy
GATES (Stein et al., 2026)	2026	Self (PI)	Gated consensus KL	Self	Token	Document as PI, gated supervision
SD-ZERO (He et al., 2026)	2026	Self (EF)	Self-revision preference	Self + Verifier	Sequence	Binary reward $\rightarrow$ dense self-supervision
π -Play (Zhang et al., 2026d)	2026	Self (PI+SP)	Multi-agent co-evolution	Self	Token	Internally generated PI from self-play
SSD (Zhang et al., 2026c)	2026	Self (SP)	Temperature-sampled SFT	Self	Sequence	Minimalist self-play
SDPO (Hubotter et al., 2026)	2026	Self (SP)	Textual feedback + DPO	Self + Verifier	Sequence	Credit assignment from outcomes
RLTF (Song et al., 2026)	2026	Self (EF)	Critique-conditioned	Self + Verifier	Sequence	Text feedback for self-play
<i>Black-Box</i>						
GAD (Ye et al., 2025)	2025	Signal	Adversarial matching	Black-box	Sequence	Discriminator as proxy reward
Lion (Jiang et al., 2023)	2023	Signal	Verbal feedback	Black-box	Sequence	NL critique curriculum
OVD (Xiong et al., 2026)	2026	Signal	Verbal scores (0-9)	Black-box	Sequence	Score-based trajectory matching
DAIL (Mendes et al., 2026)	2026	Signal	Inverse RL	Black-box	Sequence	Inferred reward from text
LUFFY (Yan et al., 2025)	2025	Signal	Mixed-policy GRPO	Off-policy + RL	Sequence	Importance-weighted off-policy
ORPO-Distill (Singh et al., 2025)	2025	Signal	Preference optimization	Black-box	Sequence	Teacher-ranked pairs

Compute-quality tradeoff. The expected compute cost for N tokens:

$$C_{\text{off}} \approx N \times (F_{\text{teacher}} + F_{\text{student}} + B_{\text{student}}) \quad (17)$$

$$C_{\text{on}} \approx N \times (G_{\text{student}} + \lambda F_{\text{teacher}} + F_{\text{student}} + B_{\text{student}}) \quad (18)$$

where F, B denote forward and backward FLOPs, G is the autoregressive generation cost, and $\lambda \in (0, 1]$ is the teacher supervision refresh rate. Because $G_{\text{student}} \gg F_{\text{student}}$, on-policy training is typically 4–5 $\times$ more expensive. For generic knowledge transfer, this overhead is rarely justified. For reasoning, code generation, and complex mathematics, where the off-policy ceiling is low and the on-policy marginal return is high, the investment pays off decisively.

Let $\mathcal{U}(\theta, C)$ represent the student’s downstream utility given compute budget C . The constrained optimization is:

$$\max \mathcal{U}(\theta, C) \quad \text{subject to } C = \gamma C_{\text{on}} + (1 - \gamma) C_{\text{off}} \leq C_{\text{max}} \quad (19)$$

where γ is the fraction processed on-policy. For generic knowledge transfer, $\gamma \rightarrow 0$ suffices. For reasoning, $\frac{\partial \mathcal{U}}{\partial C_{\text{on}}} \gg \frac{\partial \mathcal{U}}{\partial C_{\text{off}}}$, justifying the compute multiplier. A natural hybrid curriculum begins with off-policy warmup ($\gamma = 0$) to establish latent representations, then progressively shifts toward $\gamma \rightarrow 1$ in later stages as the student’s distribution diverges from the static data.

Table 3: Representative experimental configurations of OPD methods across different application domains.

Method	Teacher	Student	Training Signal	Key Benchmarks
<i>Mathematical Reasoning</i>				
G-OPD (Yang et al., 2026c)	Qwen2.5-72B-Instruct	Qwen2.5-Math-1.5B/7B	Dense logit + reward extrap.	MATH, GSM8K, AIME
OFSD (Zhao et al., 2026b)	Self (GPT-conditioned)	Qwen2.5-Math-1.5B/7B	GP-PI self-distillation	AIME, HMMT
PACED (Xu et al., 2025a)	Qwen2.5-72B	Qwen2.5-Math-1.5B	Beta-kernel curriculum	MATH, GSM8K
KDRL (Xu et al., 2025a)	Skywork-OR1-Math-7B	RI-Distill-Qwen-1.5B	Joint KD + RL	AIME, MATH
LUFFY (Yan et al., 2025)	DeepSeek-R1 (off-policy traces)	Qwen2.5-Math-7B/1.5B	Mixed-policy GRPO	AIME, AMC, MATH-500
SCoRe (Lyu et al., 2025)	Qwen2.5-72B-Inst	Qwen2.5-7B/3B, Llama-3.1-8B	Earliest-error correction	AIME, MATH, Multi-hop QA
<i>Instruction Following & General</i>				
GKD (Agarwal et al., 2024)	T5-XXL (11B)	T5-Small/Base	On-policy FKL/RKL/JSD	XSum, WMT
DistiLLM (Ko et al., 2024)	GPT-2 XL (1.5B)	GPT-2 (124M)	Skewed KL	ROUGE-L, BERTScore
AlignDistil (Zhang et al., 2025a)	Qwen2.5-72B-Inst	Qwen2.5-1.5B-Inst	DPO + token-level KD	AlpacaEval, MT-Bench
<i>Industrial Scale</i>				
Qwen3 (Yang et al., 2025a)	Qwen3-32B/235B-A22B	Qwen3-0.6B-14B	On-policy logit distillation	AIME, MATH, LiveCode
Gemma 2 (Gemma Team et al., 2024)	Gemma 2 27B	Gemma 2 9B / 2B	KD in pre-training	MMLU, HellaSwag
MiMo-V2 (Xiaomi LLM-Core Team et al., 2026)	Domain specialists	MiMo-V2-Flash (309B/15B MoE)	Multi-teacher logit + reward	AIME, MATH, GPQA
KAT-Coder-V2 (Li et al., 2026a)	5 domain specialists	Unified agentic coder	Specialize-then-Unify OPD	SWE-bench (79.6%)
Nemotron-Cascade 2 (Yang et al., 2026d)	Domain RL/SFT teachers	30B MoE (3B active)	Cascade RL + domain OPD	IMO, IOI, ICPC
ORBIT (Liang et al., 2026)	Multi-mode RL experts	DeepSeek-R1-1.5B, Qwen3-4B	Multi-teacher mode fusion	AIME, GPQA, MMLU-Pro
<i>Multimodal & Domain-Specific</i>				
VOLD (Bousnelham et al., 2025)	Qwen3-8B (text-only)	Qwen2.5-VL-3B	GRPO + token-level KL	MMMU-Pro, MathVision
CORD (Hu et al., 2026)	Text-mode LALM	Audio-mode LALM	Cross-modal R-KL + GRPO	Audio QA/reasoning
Speculative KD (Xu et al., 2025c)	Gemma-7B-IT, Qwen2-7B	Gemma-2B, Qwen2-0.5B	Block-verified on-policy KL	Translation, Dialogue
Cross-Tok. KD (Boizard et al., 2025)	Llama-2-7B, Mistral-7B	OPT-350M, Pythia-160M-1B	Latent OT alignment	QA, Summarization
DP-OPD (Khadem et al., 2026)	GPT-2 Large 774M	DistilGPT-2 82M	GKD + DP-SGD (student only)	Yelp, BigPatent
<i>Self-Distillation</i>				
SPIN (Chen et al., 2024)	Self (iter $t-1$)	Zephyr-7B-SFT	Self-play DPO	Open LLM, MT-Bench
CRISP (Sang et al., 2026)	Self (concise prompt)	Qwen3-8B/14B	Per-token R-KL	AIME, MATH-500
SD-ZERO (He et al., 2026)	Self (revision-conditioned)	Qwen3-4B-Inst, OLMo-3-7B	On-policy self-distill	AIME, MATH, Codeforces
π -Play (Zhang et al., 2026d)	Self (QCP-conditioned)	Qwen3-4B/8B	Multi-agent self-distill	NQ, TriviaQA, HotpotQA
SSD (Zhang et al., 2026c)	Self (temperature-sampled)	Qwen3-30B-Inst	On-policy SFT	LiveCodeBench v6
<i>Black-Box</i>				
GAD (Ye et al., 2025)	GPT-5-Chat (API only)	Qwen2.5-14B-Inst	Adversarial minimax	LMSYS-Chat, Dolly
Lion (Jiang et al., 2025)	ChatGPT (API only)	LLaMA-7B/13B	NL critique curriculum	BIG-Bench Hard, AGIEval
QVD (Xiong et al., 2026)	QwQ-32B / Env. Agent	Qwen2.5-5B, Llama-3.2-3B	Verbal scores (0-9)	Web QA, MATH
Speculative KD (Xu et al., 2025c)	Gemma-7B-IT, Qwen2-7B	Gemma-2B, Qwen2-0.5B	Block-verified on-policy KL	Translation, Dialogue
Cross-Tok. KD (Boizard et al., 2025)	Llama-2-7B, Mistral-7B	OPT-350M, Pythia-160M-1B	Latent OT alignment	QA, Summarization
DP-OPD (Khadem et al., 2026)	GPT-2 Large 774M	DistilGPT-2 82M	GKD + DP-SGD (student only)	Yelp, BigPatent

8 Applications, Systems, and Emerging Domains

The preceding sections developed OPD from theory through methods to unified understanding. This section examines how these algorithmic advances translate into practice. The transition from academic prototypes to industrial deployment reveals that the choice of OPD method is ultimately driven not by theoretical elegance but by practical constraints: available compute, teacher access level, the need for multi-teacher coordination, system-level throughput bottlenecks, and domain-specific challenges (cross-modal transfer, privacy). We organize industrial applications by their *deployment pattern* and emerging domains by the new challenges they introduce.

8.1 Industrial Deployment

Recent foundation models have increasingly incorporated OPD into their post-training pipelines, revealing three distinct industrial use patterns.

Two-phase distillation pipelines. The most common industrial pattern combines off-policy cold-start with on-policy refinement. Qwen3 (Yang et al., 2025a) employs strong-to-weak distillation where larger models provide logit-level supervision on student-generated on-policy sequences, with the student generating responses in either thinking or non-thinking mode. Gemma 2 (Gemma Team et al., 2024) embeds knowledge distillation directly into pre-training to bridge performance gaps between parameter tiers (27B→9B→2B). MiMo-V2 (Xiaomi LLM-Core Team et al., 2026) combines distillation from multiple domain-specialized teachers with RL-based training.

OPD as model consolidation. A second pattern uses on-policy distillation for *merging* multiple specialized experts into a single deployable model. KAT-Coder-V2 (Li et al., 2026a) decomposes agentic coding into five expert domains, each undergoing independent SFT and RL training, and consolidates them via on-policy distillation, achieving 79.6% on SWE-bench Verified. Nemotron-Cascade 2 (Yang et al., 2026d) applies the same principle to a 30B MoE model with only 3B activated parameters, achieving Gold Medal-level performance on IMO, IOI, and ICPC World Finals with $20\times$ fewer parameters than DeepSeek-V3.2-Special.

OPD for multi-budget reasoning. ORBIT (Liang et al., 2026) addresses the deployment challenge of variable reasoning depth: users need different compute budgets depending on query difficulty. It produces stage-wise expert policies through RLVR under progressively tighter context budgets ($L_{k+1} = L_k/2$), then fuses them into a single model through mode-aware Reverse KL:

$$\mathcal{L}_{\text{fusion}}(\phi) = \mathbb{E}_{k \sim U(1,K)} \mathbb{E}_{\substack{q \sim \mathcal{D} \\ o \sim \pi_{\phi}(\cdot|q, p_k)}} \left[\sum_t \log \frac{\pi_{\phi}(o_t|q, p_k, o_{<t})}{\pi_{\theta_k}(o_t|q, p_k, o_{<t})} \right] \quad (20)$$

where p_k is the mode-specific prompt and $\{\pi_{\theta_k}\}$ are the frontier experts. This demonstrates that on-policy distillation is emerging as a general-purpose multi-teacher fusion tool for any axis of model specialization.

Agentic distillation. OpenClaw-RL (Wang et al., 2026b) extends OPD to the agentic setting where the student must learn long-horizon tool use and environmental state tracking. Using hindsight-guided OPD with a Process Reward Model (PRM), it trains a Qwen3-4B agent that operates across personal, terminal, GUI, and SWE environments. Skill-SD (Wang et al., 2026a) applies importance-weighted Reverse KL with GRPO for skill-conditioned agentic learning on AppWorld and Sokoban.

8.2 Emerging Domains

Multimodal OPD. Vision-language models face unique exposure bias challenges because multimodal interleaved generation must maintain coherence across modalities. VOLD (Boussselham et al., 2025) applies on-policy GRPO with token-level KL to distill text-only reasoning into vision-language students. Video-OPD (Li et al., 2026c) extends to temporal video grounding. X-OPD (Cao et al., 2026) crosses the text-speech boundary, distilling a text-mode Qwen3-Omni into its own speech mode. CORD (Hu et al., 2026) applies cross-modal self-distillation between text and audio modes of the same model using weighted Reverse KL with GRPO.

KEPO (Yang et al., 2026b) identifies a distinct failure mode in multimodal settings: sparse RLVR fails due to exploration collapse when initial solve rates are near zero. By conditioning preference optimization on teacher knowledge, KEPO provides the dense signal necessary to bootstrap capable VLMs.

Embodied intelligence. VLA-OPD (Zhong et al., 2026) applies Reverse KL on self-generated robot trajectories, distilling expert demonstrations into a Vision-Language-Action student. HY-Embodied-0.5 (Tencent Robotics X and HY Vision Team, 2026) uses multi-stage OPD to compress a 32B expert VLM into a 2B embodied MoT model for spatial reasoning.

Privacy-preserving OPD. DP-OPD (Khadem et al., 2026) injects differential privacy noise (DP-SGD) into the student’s gradients during on-policy training while keeping the teacher frozen, proving that on-policy querying can extract utility while mathematically guaranteeing protection of the teacher’s training data.

Autonomous driving. OPD-AV (Afsharrad et al., 2026) applies GKD with $5\times$ compression for autonomous driving planning, distilling a Qwen3-8B SFT model into a 1.7B student on the nuScenes dataset.

8.3 The Distillation Tax: Compute Budget Allocation

Based on the compute analysis in Section 6.3 and the staged pipelines described in recent industrial reports (DeepSeek-AI et al., 2025; Yang et al., 2025a), a practical rule of thumb emerges for compute budget allocation. The most effective industrial pipelines follow a three-stage pattern:

1. **Off-policy warm-up** (50–70% of budget): Standard SFT on teacher-generated data provides cheap, high-bandwidth learning that establishes the student’s basic capabilities and aligns its distribution close enough to the teacher for effective on-policy training.

2. **On-policy logit distillation** (20–35% of budget): Token-level OPD with adaptive divergences (GKD, DistiLLM, ToDi) closes the distribution gap on the student’s own generation trajectories, addressing exposure bias where it matters most.
3. **Reward-guided refinement** (10–20% of budget): RL-augmented objectives (G-OPD, KDRL, RLAD) push the student beyond the teacher’s capability ceiling on reasoning tasks, using sparse outcome rewards to discover novel solution paths.

This staged approach front-loads cheap, high-bandwidth learning and reserves expensive on-policy compute for the final quality push. Qwen3 (Yang et al., 2025a) exemplifies this pattern, with its four-stage pipeline (pre-train $\rightarrow$ SFT $\rightarrow$ RL $\rightarrow$ long-context) allocating progressively more compute to on-policy methods as training progresses. The key insight is that on-policy training is most valuable *after* off-policy warm-up has brought the student close to the teacher’s distribution, minimizing the wasted rollouts that occur when the student-teacher gap is too large (Section 7.1).

9 Open Problems and Future Directions

Despite rapid progress, several fundamental challenges remain unresolved. We organize open problems by their potential impact on the field.

Distillation scaling laws. While parameter-scaling laws (Chinchilla (Hoffmann et al., 2022), Kaplan) are well-established for pre-training, no analogous framework exists for distillation. Busbridge et al. (2025) initiated the study of distillation-specific scaling, but the relationship between teacher-student size ratios, online rollout volume, divergence choice, and asymptotic performance remains largely unquantified. Practitioners rely on costly trial-and-error for compute allocation. Establishing distillation-specific scaling laws would transform OPD from an empirical art to a predictable engineering discipline.

Uncertainty-aware feedback. Teachers currently provide point-estimate probabilities. When the teacher itself is uncertain about a token, its logits carry little useful information, yet the student treats all teacher signals equally. Future OPD frameworks must incorporate the teacher’s *epistemic uncertainty*, allowing the student to discount feedback on queries where the teacher is guessing. Process reward models (Lightman et al., 2024) provide a potential path: by scoring each reasoning step independently, they could identify precisely where teacher supervision is reliable versus speculative. The connection to the failure-mode analysis of Section 7.2 is direct: the flawed prefix trap is fundamentally a problem of unrecognized teacher uncertainty, and explicitly modeling this uncertainty would provide a principled solution.

Agent-level distillation. Current OPD focuses on single-turn generation. Extending OPD to multi-turn agentic settings, where the student must learn long-horizon tool use, environmental state tracking, and error recovery across entire interaction trajectories, requires fundamentally new credit assignment mechanisms. OpenClaw-RL (Wang et al., 2026b) and Skill-SD (Wang et al., 2026a) represent early steps, but the systematic degradation of teacher supervision with trajectory depth (Li et al., 2026d) poses a fundamental challenge for multi-turn distillation.

Continual and lifelong distillation. Production models undergo repeated fine-tuning cycles (safety patches, capability updates, domain adaptation). How should the distillation objective adapt when the teacher itself is being updated? SDFT (Shenfeld et al., 2026) and OEL (Ye et al., 2026a) provide initial answers for self-distillation, but the problem of distilling from a non-stationary teacher remains open.

Efficiency frontiers. The 3–8 $\times$ compute overhead of on-policy training remains a barrier. While Fast OPD, Lightning OPD, and Speculative KD have made progress, the theoretical minimum cost of on-policy distillation (the information-theoretic lower bound on how much on-policy data is needed to achieve a given quality level) is unknown.

Latent-space distillation. Current OPD operates exclusively in vocabulary space, where cross-architecture alignment requires expensive projections (DSKD, Cross-Tokenizer KD). A more fundamental approach would distill in a *shared latent space* that both teacher and

student can access, bypassing the vocabulary bottleneck entirely. This would require learning a common semantic manifold where distances correspond to functional similarity, enabling distillation between architecturally dissimilar models (e.g., diffusion-based text generators and autoregressive LLMs) that share no structural overlap. Recent progress in representation learning and universal sentence embeddings suggests this direction is within reach.

Cross-modal OPD theory. The extension of OPD to multimodal settings (Section 8.2) is currently driven by empirical experimentation with minimal theoretical grounding. Key open questions include: How does exposure bias manifest when multiple modalities must maintain coherence? What are the optimal divergence choices when the teacher and student operate in different modality spaces? Can the unified f -divergence framework (Section 2) be extended to handle continuous signal spaces (images, audio) alongside discrete token spaces? VOLD, X-OPD, and CORD provide empirical starting points, but the theoretical foundations for cross-modal OPD remain to be established.

10 Conclusion

This survey has systematically examined on-policy distillation for large language models, synthesizing over 90 methods that span foundational formulations, algorithmic innovations, theoretical analyses, and industrial deployments. We organized this rapidly growing literature around a practitioner’s decision chain rather than descriptive categories, tracing three fundamental design axes: *objective function* design (from fixed divergences through adaptive routing to RL-augmented objectives that break the teacher ceiling), *signal source* architecture (from dense white-box logits through black-box API access to self-distillation that eliminates the external teacher entirely), and *training dynamics* (token weighting, curriculum adaptation, and compute optimization).

Key Findings. Three central insights emerge from this synthesis. *First*, shifting from off-policy to on-policy training distributions, from $y \sim p_{\text{data}}$ to $y \sim p_{\theta}$, is a consistently impactful design choice, yielding meaningful accuracy gains across mathematical reasoning, code generation, and instruction following (Tables 2 and 3). The improvement stems from eliminating exposure bias: the student learns to recover from its own errors rather than memorizing idealized trajectories. *Second*, divergence selection is not one-size-fits-all but must be adapted to both task and token position. Reverse KL excels at reasoning tasks where mode-seeking prevents hallucination, while Forward KL preserves the diversity needed for open-ended generation. Adaptive methods such as ToDi (Jung et al., 2025) and Entropy-Aware OPD (Jin et al., 2026) that dynamically select divergences based on local distributional geometry represent the current frontier. *Third*, the boundary between distillation and reinforcement learning is rapidly dissolving. G-OPD (Yang et al., 2026c), RLAD (Zhang et al., 2026e), and REOPOLD (Li et al., 2025) demonstrate that the optimal training signal combines dense teacher supervision with sparse outcome rewards, with KD providing gradient stability while RL enables exploration beyond the teacher’s capability ceiling.

Practical Takeaways. With white-box teacher access, token-level methods (GKD (Agarwal et al., 2024), DistiLLM (Ko et al., 2024)) offer the best quality-compute tradeoff for general instruction following. For reasoning-intensive tasks, sequence-level methods (MiniLLM (Gu et al., 2024)) or hybrid approaches (Fast OPD (Zhang et al., 2026a), PACED (Xu et al., 2026a), Lightning OPD (Wu et al., 2026)) are preferable despite higher variance. Lightning OPD demonstrates that offline distillation under teacher consistency can match online OPD at $4\times$ lower cost, significantly lowering the barrier for academic research. With only API access, GAD (Ye et al., 2025) and OVD (Xiong et al., 2026) enable effective on-policy learning through adversarial and verbal formulations, respectively. Self-distillation methods (SPIN (Chen et al., 2024), OPSD (Zhao et al., 2026b), SD-ZERO (He et al., 2026)) eliminate the need for a separate teacher entirely, making them attractive under resource constraints. The compute overhead of on-policy generation, typically $4\text{--}5\times$ that of off-policy training, can be

substantially reduced via speculative decoding (Xu et al., 2025c), prefix truncation (Zhang et al., 2026a), or offline precomputation (Wu et al., 2026).

Looking Ahead. The most pressing open problems are threefold. First, the absence of distillation scaling laws analogous to Chinchilla (Hoffmann et al., 2022) forces practitioners to rely on costly trial-and-error for compute allocation. Second, the field needs uncertainty-aware objectives that prevent the echo chamber effect when students explore out-of-distribution regions where teacher supervision is unreliable. Third, extending OPD to multi-turn agentic settings, where training involves entire interaction trajectories rather than single completions, remains a fundamental challenge compounded by the systematic degradation of teacher supervision with trajectory depth (Li et al., 2026d). As the field matures, we anticipate convergence toward unified KD+RL frameworks that treat distillation not as a separate training stage but as a continuous regularization mechanism throughout the model’s lifecycle, from pre-training through deployment. As LLMs transition from static text generators to interactive reasoning agents, the principles of on-policy alignment will only grow in centrality.

References

- Amirhossein Afsharrad, Amirhesam Abedsoltan, Ahmadreza Moradipari, and Sanjay Lall. On-Policy Distillation of Language Models for Autonomous Vehicle Motion Planning. *arXiv preprint arXiv:2604.07944*, 2026. URL <https://arxiv.org/abs/2604.07944>.
- Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos, Matthieu Geist, and Olivier Bachem. On-Policy Distillation of Language Models: Learning from Self-Generated Mistakes. *Proceedings of ICLR*, 2024. URL <https://arxiv.org/abs/2306.13649>.
- Nicolas Boizard, Kevin El Haddad, Céline Hudelot, and Pierre Colombo. Towards Cross-Tokenizer Distillation: the Universal Logit Distillation Loss for LLMs. *Transactions on Machine Learning Research*, 2025. URL <https://arxiv.org/abs/2402.12030>.
- Walid Bousselham, Hilde Kuehne, and Cordelia Schmid. VOLD: Reasoning Transfer from LLMs to Vision-Language Models via On-Policy Distillation. *arXiv preprint arXiv:2510.23497*, 2025. URL <https://arxiv.org/abs/2510.23497>.
- Dan Busbridge, Amitis Shidani, Floris Weers, Jason Ramapuram, Etai Littwin, and Russ Webb. Distillation Scaling Laws. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2025. URL <https://arxiv.org/abs/2502.08606>.
- Yuang Cai and Yuyu Yuan. $\mathcal{X}$ -KD: General Experiential Knowledge Distillation for Large Language Models. *arXiv preprint arXiv:2602.12674*, 2026. URL <https://arxiv.org/abs/2602.12674>.
- Di Cao, Dongjie Fu, Hai Yu, Siqi Zheng, Xu Tan, and Tao Jin. X-OPD: Cross-Modal On-Policy Distillation for Capability Alignment in Speech LLMs. *arXiv preprint arXiv:2603.24596*, 2026. URL <https://arxiv.org/abs/2603.24596>.
- Sungmin Cha and Kyunghyun Cho. Why Knowledge Distillation Works in Generative Models: A Minimal Working Explanation. *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. URL <https://arxiv.org/abs/2505.13111>.
- Howard Chen, Noam Razin, Karthik Narasimhan, and Danqi Chen. Retaining by Doing: The Role of On-Policy Data in Mitigating Forgetting. *arXiv preprint arXiv:2510.18874*, 2025. URL <https://arxiv.org/abs/2510.18874>.
- Zixiang Chen, Yihe Deng, Huizhuo Yuan, Kaixuan Ji, and Quanquan Gu. Self-Play Fine-Tuning Converts Weak Language Models to Strong Language Models. *Proceedings of ICML*, 2024. URL <https://arxiv.org/abs/2401.01335>.
- DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, et al. DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. *Nature*, 645:633–638, 2025. URL <https://arxiv.org/abs/2501.12948>.

- Ken Ding. HDPO: Hybrid Distillation Policy Optimization via Privileged Self-Distillation. *arXiv preprint arXiv:2603.23871*, 2026. URL <https://arxiv.org/abs/2603.23871>.
- Jiabin Fan, Guoqing Luo, Michael Bowling, and Lili Mou. KETCHUP: K-Step Return Estimation for Sequential Knowledge Distillation. *arXiv preprint arXiv:2504.19024*, 2025. URL <https://arxiv.org/abs/2504.19024>.
- Yuqian Fu, Haohuan Huang, Kaiwen Jiang, Yuanheng Zhu, and Dongbin Zhao. Revisiting On-Policy Distillation: Empirical Failure Modes and Simple Fixes. *arXiv preprint arXiv:2603.25562*, 2026. URL <https://arxiv.org/abs/2603.25562>.
- Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, et al. Gemma 2: Improving Open Language Models at a Practical Size. *arXiv preprint arXiv:2408.00118*, 2024. URL <https://arxiv.org/abs/2408.00118>.
- Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. MiniLLM: On-Policy Distillation of Large Language Models. *Proceedings of ICLR*, 2024. URL <https://arxiv.org/abs/2306.08543>.
- Yuxian Gu, Hao Zhou, Fandong Meng, Jie Zhou, and Minlie Huang. MiniPLM: Knowledge Distillation for Pre-Training Language Models. *Proceedings of ICLR*, 2025. URL <https://arxiv.org/abs/2410.17215>.
- Arnav Gudibande, Eric Wallace, Charlie Snell, Xinyang Geng, Hao Liu, Pieter Abbeel, Sergey Levine, and Dawn Song. The False Promise of Imitating Proprietary LLMs. *arXiv preprint arXiv:2305.15717*, 2023. URL <https://arxiv.org/abs/2305.15717>.
- Yinghui He, Simran Kaur, Adithya Bhaskar, Yongjin Yang, Jiarui Liu, Narutatsu Ri, Liam Fowl, Abhishek Panigrahi, Danqi Chen, and Sanjeev Arora. Self-Distillation Zero: Self-Revision Turns Binary Rewards into Dense Supervision. *arXiv preprint arXiv:2604.12002*, 2026. URL <https://arxiv.org/abs/2604.12002>.
- Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.
- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals, and Laurent Sifre. Training Compute-Optimal Large Language Models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. URL <https://arxiv.org/abs/2203.15556>.
- Cheng-Yu Hsieh, Chun-Liang Li, Chih-Kuan Yeh, Hootan Nakhost, Yasuhisa Fujii, Alexander Ratner, Ranjay Krishna, Chen-Yu Lee, and Tomas Pfister. Distilling Step-by-Step! Outperforming Larger Language Models with Less Training Data and Smaller Model Sizes. *Findings of ACL*, 2023. URL <https://arxiv.org/abs/2305.02301>.
- Jing Hu, Danxiang Zhu, Xianlong Luo, Dan Zhang, Shuwei He, Yishu Lei, Haitao Zheng, Shikun Feng, Jingzhou He, Yu Sun, Hua Wu, and Haifeng Wang. CORD: Bridging the Audio-Text Reasoning Gap via Weighted On-policy Cross-modal Distillation. *arXiv preprint arXiv:2601.16547*, 2026. URL <https://arxiv.org/abs/2601.16547>.
- Haiduo Huang, Jiangcheng Song, Yadong Zhang, and Pengju Ren. SelecTKD: Selective Token-Weighted Knowledge Distillation for LLMs. *arXiv preprint arXiv:2510.24021*, 2025. URL <https://arxiv.org/abs/2510.24021>.
- Jonas Hübner, Frederike Lübeck, Lejs Behric, Anton Baumann, Marco Bagatella, Daniel Marta, et al. Reinforcement Learning via Self-Distillation. *arXiv preprint arXiv:2601.20802*, 2026. URL <https://arxiv.org/abs/2601.20802>.
- Ijun Jang, Jewon Yeom, Juan Yeo, Hyunggu Lim, and Taesup Kim. Stable On-Policy Distillation through Adaptive Target Reformulation. In *Findings of ACL*, 2026. URL <https://arxiv.org/abs/2601.07155>.

- Yuxin Jiang, Chunkit Chan, Mingyang Chen, and Wei Wang. Lion: Adversarial Distillation of Proprietary Large Language Models. *Proceedings of EMNLP*, 2023. URL <https://arxiv.org/abs/2305.12870>.
- Woogyel Jin, Taywon Min, Yongjin Yang, Swanand Ravindra Kadhe, Yi Zhou, Dennis Wei, Nathalie Baracaldo, and Kimin Lee. Entropy-Aware On-Policy Distillation of Language Models. *arXiv preprint arXiv:2603.07079*, 2026. URL <https://arxiv.org/abs/2603.07079>.
- Seongryong Jung, Suwan Yoon, DongGeon Kim, and Hwanhee Lee. ToDi: Token-wise Distillation via Fine-Grained Divergence Control. In *Proceedings of EMNLP*, 2025. URL <https://arxiv.org/abs/2505.16297>.
- Fatemeh Khadem, Sajad Mousavi, Yi Fang, and Yuhong Liu. DP-OPD: Differentially Private On-Policy Distillation for Language Models. *arXiv preprint arXiv:2604.04461*, 2026. URL <https://arxiv.org/abs/2604.04461>.
- Gyeongman Kim, Doohyuk Jang, and Eunho Yang. PromptKD: Distilling Student-Friendly Knowledge for Generative Language Models via Prompt Tuning. In *Findings of EMNLP*, 2024. URL <https://arxiv.org/abs/2402.12842>.
- Jeonghye Kim, Xufang Luo, Minbeom Kim, Sangmook Lee, Dohyung Kim, Jiwon Jeon, Dongsheng Li, and Yuqing Yang. Why Does Self-Distillation (Sometimes) Degrade the Reasoning Capability of LLMs? *arXiv preprint arXiv:2603.24472*, 2026a. URL <https://arxiv.org/abs/2603.24472>.
- Minsang Kim and Seung Jun Baek. Explain in Your Own Words: Improving Reasoning via Token-Selective Dual Knowledge Distillation. *Proceedings of ICLR*, 2026. URL <https://arxiv.org/abs/2603.13260>.
- Yeongmin Kim, Donghyeok Shin, Mina Kang, Byeonghu Na, and Il-Chul Moon. Distillation of Large Language Models via Concrete Score Matching. In *International Conference on Learning Representations (ICLR)*, 2026b. URL <https://arxiv.org/abs/2509.25837>.
- Yoon Kim and Alexander M. Rush. Sequence-level knowledge distillation. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 1317–1327, 2016.
- John Kirchenbauer, Abhimanyu Hans, Brian Bartoldson, Micah Goldblum, Ashwinee Panda, and Tom Goldstein. Multi-Token Prediction via Self-Distillation. *arXiv preprint arXiv:2602.06019*, 2026. URL <https://arxiv.org/abs/2602.06019>.
- Jongwoo Ko, Sungnyun Kim, Tianyi Chen, and Se-Young Yun. DistiLLM: Towards Streamlined Distillation for Large Language Models. *Proceedings of ICML*, 2024. URL <https://arxiv.org/abs/2402.03898>.
- Jongwoo Ko, Tianyi Chen, Sungnyun Kim, Tianyu Ding, Luming Liang, Ilya Zharkov, and Se-Young Yun. DistiLLM-2: A Contrastive Approach Boosts the Distillation of LLMs. In *Proceedings of ICML*, 2025. URL <https://arxiv.org/abs/2503.07067>.
- Jongwoo Ko, Sara Abdali, Young Jin Kim, Tianyi Chen, and Pashmina Cameron. Scaling Reasoning Efficiently via Relaxed On-Policy Distillation. *arXiv preprint arXiv:2603.11137*, 2026. URL <https://arxiv.org/abs/2603.11137>.
- Fengxiang Li, Han Zhang, Haoyang Huang, et al. KAT-Coder-V2 Technical Report. *arXiv preprint arXiv:2603.27703*, 2026a. URL <https://arxiv.org/abs/2603.27703>.
- Gengsheng Li, Tianyu Yang, Junfeng Fang, Mingyang Song, Mao Zheng, Haiyun Guo, Dan Zhang, Jinqiao Wang, and Tat-Seng Chua. Unifying Group-Relative and Self-Distillation Policy Optimization via Sample Routing. *arXiv preprint arXiv:2604.02288*, 2026b. URL <https://arxiv.org/abs/2604.02288>.

- Jiaze Li, Hao Yin, Haoran Xu, Boshen Xu, Wenhui Tan, Zewen He, et al. Video-OPD: Efficient Post-Training of Multimodal Large Language Models for Temporal Video Grounding via On-Policy Distillation. *arXiv preprint arXiv:2602.02994*, 2026c. URL <https://arxiv.org/abs/2602.02994>.
- Yaxuan Li, Yuxin Zuo, Bingxiang He, Jinqian Zhang, Chaojun Xiao, Cheng Qian, Tianyu Yu, Huan ang Gao, Wenkai Yang, Zhiyuan Liu, and Ning Ding. Rethinking On-Policy Distillation of Large Language Models: Phenomenology, Mechanism, and Recipe. *arXiv preprint arXiv:2604.13016*, 2026d. URL <https://arxiv.org/abs/2604.13016>.
- Yingru Li, Ziniu Li, and Jiakai Liu. A Note on Hybrid Online Reinforcement and Imitation Learning for LLMs: Formulations and Algorithms. *arXiv preprint arXiv:2512.23097*, 2025. URL <https://arxiv.org/abs/2512.23097>.
- Kun Liang, Clive Bai, Xin Xu, Chenming Tang, Sanwoo Lee, Weijie Liu, Saiyong Yang, and Yunfang Wu. ORBIT: On-policy Exploration-Exploitation for Controllable Multi-Budget Reasoning. *arXiv preprint arXiv:2601.08310*, 2026. URL <https://arxiv.org/abs/2601.08310>.
- Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let’s Verify Step by Step. *Proceedings of ICLR*, 2024. URL <https://arxiv.org/abs/2305.20050>.
- Feng Luo, Yu-Neng Chuang, Guanchu Wang, Zicheng Xu, Xiaotian Han, Tianyi Zhang, and Vladimir Braverman. Demystifying OPD: Length Inflation and Stabilization Strategies for Large Language Models. *arXiv preprint arXiv:2604.08527*, 2026. URL <https://arxiv.org/abs/2604.08527>.
- Yuanjie Lyu, Chengyu Wang, Jun Huang, and Tong Xu. From Correction to Mastery: Reinforced Distillation of Large Language Model Agents. *arXiv preprint arXiv:2509.14257*, 2025. URL <https://arxiv.org/abs/2509.14257>.
- Ethan Mendes, Jungsoo Park, and Alan Ritter. Didactic to Constructive: Turning Expert Solutions into Learnable Reasoning. *arXiv preprint arXiv:2602.02405*, 2026. URL <https://arxiv.org/abs/2602.02405>.
- Purbesh Mitra and Sennur Ulukus. Semantic Soft Bootstrapping: Long Context Reasoning in LLMs without Reinforcement Learning. *arXiv preprint arXiv:2512.05105*, 2025. URL <https://arxiv.org/abs/2512.05105>.
- Emiliano Penalosa, Dheeraj Vattikonda, Nicolas Gontier, Alexandre Lacoste, Laurent Charlin, and Massimo Caccia. Privileged Information Distillation for Language Models. *arXiv preprint arXiv:2602.04942*, 2026. URL <https://arxiv.org/abs/2602.04942>.
- Jingyu Peng, Jiaxin Mao, Yong Jiang, Zheng Liu, Pengjie Ren, Zhumin Chen, Maarten de Rijke, and Xiangyu Zhao. AdaSwitch: Balancing Exploration and Guidance in Knowledge Distillation via Adaptive Switching. *arXiv preprint arXiv:2510.07842*, 2025. URL <https://arxiv.org/abs/2510.07842>.
- Stéphane Ross, Geoffrey J. Gordon, and J. Andrew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the 14th International Conference on Artificial Intelligence and Statistics*, pp. 627–635, 2011.
- Aswin RRV, Jacob Dineen, Divij Handa, Md Nayem Uddin, Mihir Parmar, Chitta Baral, and Ben Zhou. ThinkTuning: Instilling Cognitive Reflections without Distillation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2025. URL <https://arxiv.org/abs/2508.07616>.
- Hejian Sang, Yuanda Xu, Zhengze Zhou, Ran He, Zhipeng Wang, and Jiachen Sun. CRISP: Compressed Reasoning via Iterative Self-Policy Distillation. *arXiv preprint arXiv:2603.05433*, 2026. URL <https://arxiv.org/abs/2603.05433>.

- Idan Shenfeld, Mehul Damani, Jonas Hübner, and Pulkit Agrawal. Self-Distillation Enables Continual Learning. *arXiv preprint arXiv:2601.19897*, 2026. URL <https://arxiv.org/abs/2601.19897>.
- Aasheesh Singh, Vishal Vaddina, and Dagnachew Birru. ORPO-Distill: Mixed-Policy Preference Optimization for Cross-Architecture LLM Distillation. *NeurIPS Workshop on Efficient Reasoning*, 2025. URL <https://arxiv.org/abs/2509.25100>.
- Yuda Song, Lili Chen, Fahim Tajwar, Remi Munos, Deepak Pathak, J. Andrew Bagnell, Aarti Singh, and Andrea Zanette. Expanding the Capabilities of Reinforcement Learning via Text Feedback. *arXiv preprint arXiv:2602.02482*, 2026. URL <https://arxiv.org/abs/2602.02482>.
- Alex Stein, Furong Huang, and Tom Goldstein. GATES: Self-Distillation under Privileged Context with Consensus Gating. *arXiv preprint arXiv:2602.20574*, 2026. URL <https://arxiv.org/abs/2602.20574>.
- Tencent Robotics X and HY Vision Team. HY-Embodied-0.5: Embodied Foundation Models for Real-World Agents. *arXiv preprint arXiv:2604.07430*, 2026. URL <https://arxiv.org/abs/2604.07430>.
- Hao Wang, Guozhi Wang, Han Xiao, Yufeng Zhou, Yue Pan, Jichao Wang, Ke Xu, Yafei Wen, Xiaohu Ruan, Xiaoxin Chen, and Honggang Qi. Skill-SD: Skill-Conditioned Self-Distillation for Multi-turn LLM Agents. *arXiv preprint arXiv:2604.10674*, 2026a. URL <https://arxiv.org/abs/2604.10674>.
- Yinjie Wang, Xuyang Chen, Xiaolong Jin, Mengdi Wang, and Ling Yang. OpenClaw-RL: Train Any Agent Simply by Talking. *arXiv preprint arXiv:2603.10165*, 2026b. URL <https://arxiv.org/abs/2603.10165>.
- Yuqiao Wen, Zichao Li, Wenyu Du, and Lili Mou. f-Divergence Minimization for Sequence-Level Knowledge Distillation. *Proceedings of ACL*, 2023. URL <https://arxiv.org/abs/2307.15190>.
- Taiqiang Wu, Chaofan Tao, Jiahao Wang, Runming Yang, Zhe Zhao, and Ngai Wong. Rethinking Kullback-Leibler Divergence in Knowledge Distillation for Large Language Models. *Proceedings of COLING*, 2025. URL <https://arxiv.org/abs/2404.02657>.
- Yecheng Wu, Song Han, and Han Cai. Lightning OPD: Efficient Post-Training for Large Reasoning Models with Offline On-Policy Distillation. *arXiv preprint arXiv:2604.13010*, 2026. URL <https://arxiv.org/abs/2604.13010>.
- Xiaomi LLM-Core Team, Bangjun Xiao, Bingquan Xia, Bo Yang, Bofei Gao, Bowen Shen, Chen Zhang, Chenhong He, Chiheng Lou, Fuli Luo, Gang Wang, Gang Xie, Hailin Zhang, Hanglong Lv, et al. MiMo-V2-Flash Technical Report. *arXiv preprint arXiv:2601.02780*, 2026. URL <https://arxiv.org/abs/2601.02780>.
- Xurong Xie, Zhucun Xue, Jiafu Wu, Jian Li, Yabiao Wang, Xiaobin Hu, et al. LLM-Oriented Token-Adaptive Knowledge Distillation. *arXiv preprint arXiv:2510.11615*, 2025. URL <https://arxiv.org/abs/2510.11615>.
- Jing Xiong, Hui Shen, Shansan Gong, Yuxin Cheng, Jianghan Shen, Chaofan Tao, Haochen Tan, Haoli Bai, Lifeng Shang, and Ngai Wong. OVD: On-policy Verbal Distillation. *arXiv preprint arXiv:2601.21968*, 2026. URL <https://arxiv.org/abs/2601.21968>.
- Hongling Xu, Qi Zhu, Heyuan Deng, Jinpeng Li, Lu Hou, Yasheng Wang, et al. KDRL: Post-Training Reasoning LLMs via Unified Knowledge Distillation and Reinforcement Learning. *arXiv preprint arXiv:2506.02208*, 2025a. URL <https://arxiv.org/abs/2506.02208>.
- Shicheng Xu, Liang Pang, Yunchang Zhu, Jia Gu, Zihao Wei, Jingcheng Deng, Feiyang Pan, Huawei Shen, and Xueqi Cheng. RLKD: Distilling LLMs’ Reasoning via Reinforcement Learning. *arXiv preprint arXiv:2505.16142*, 2025b. URL <https://arxiv.org/abs/2505.16142>.

- Wenda Xu, Rujun Han, Zifeng Wang, Long T. Le, Dhruv Madeka, Lei Li, William Yang Wang, Rishabh Agarwal, Chen-Yu Lee, and Tomas Pfister. Speculative Knowledge Distillation: Bridging the Teacher-Student Gap Through Interleaved Sampling. *Proceedings of ICLR*, 2025c. URL <https://arxiv.org/abs/2410.11325>.
- Xiaohan Xu, Ming Li, Chongyang Tao, Tao Shen, Reynold Cheng, Jinyang Li, Can Xu, Dacheng Tao, and Tianyi Zhou. A Survey on Knowledge Distillation of Large Language Models. *arXiv preprint arXiv:2402.13116*, 2024. URL <https://arxiv.org/abs/2402.13116>.
- Yuanda Xu, Hejian Sang, Zhengze Zhou, Ran He, and Zhipeng Wang. PACED: Distillation and On-Policy Self-Distillation at the Frontier of Student Competence. *arXiv preprint arXiv:2603.11178*, 2026a. URL <https://arxiv.org/abs/2603.11178>.
- Yuanda Xu, Hejian Sang, Zhengze Zhou, Ran He, Zhipeng Wang, and Alborz Geramifard. TIP: Token Importance in On-Policy Distillation. *arXiv preprint arXiv:2604.14084*, 2026b. URL <https://arxiv.org/abs/2604.14084>.
- Jianhao Yan, Yafu Li, Zican Hu, Zhi Wang, Ganqu Cui, Xiaoye Qu, Yu Cheng, and Yue Zhang. Learning to Reason under Off-Policy Guidance. *arXiv preprint arXiv:2504.14945*, 2025. URL <https://arxiv.org/abs/2504.14945>.
- Shaotian Yan, Kaiyuan Liu, Chen Shen, Bing Wang, Sinan Fan, Jun Zhang, Yue Wu, Zheng Wang, and Jieping Ye. Distribution-Aligned Sequence Distillation for Superior Long-CoT Reasoning. *arXiv preprint arXiv:2601.09088*, 2026. URL <https://arxiv.org/abs/2601.09088>.
- An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, et al. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388*, 2025a. URL <https://arxiv.org/abs/2505.09388>.
- Chenxu Yang, Chuanyu Qin, Qingyi Si, Minghui Chen, Naibin Gu, Dingyu Yao, Zheng Lin, Weiping Wang, Jiaqi Wang, and Nan Duan. Self-Distilled RLVR. *arXiv preprint arXiv:2604.03128*, 2026a. URL <https://arxiv.org/abs/2604.03128>.
- Fan Yang, Rui Meng, Trudi Di Qi, Ali Ezzati, and Yuxin Wen. KEPO: Knowledge-Enhanced Preference Optimization for Reinforcement Learning with Reasoning. *arXiv preprint arXiv:2602.00400*, 2026b. URL <https://arxiv.org/abs/2602.00400>.
- Ling Yang, Zhaochen Yu, Tianjun Zhang, Minkai Xu, Joseph E. Gonzalez, Bin Cui, and Shuicheng Yan. SuperCorrect: Advancing Small LLM Reasoning with Thought Template Distillation and Self-Correction. *Proceedings of ICLR*, 2025b. URL <https://arxiv.org/abs/2410.09008>.
- Wenkai Yang, Weijie Liu, Ruobing Xie, Kai Yang, Saiyong Yang, and Yankai Lin. Learning beyond Teacher: Generalized On-Policy Distillation with Reward Extrapolation. *arXiv preprint arXiv:2602.12125*, 2026c. URL <https://arxiv.org/abs/2602.12125>.
- Zhuolin Yang, Zihan Liu, Yang Chen, Wenliang Dai, Boxin Wang, Sheng-Chieh Lin, Chankyu Lee, Yangyi Chen, Dongfu Jiang, Jiafan He, Renjie Pi, Grace Lam, Nayeon Lee, Alexander Bukharin, Mohammad Shoeybi, Bryan Catanzaro, and Wei Ping. Nemotron-Cascade 2: Post-Training LLMs with Cascade RL and Multi-Domain On-Policy Distillation. *arXiv preprint arXiv:2603.19220*, 2026d. URL <https://arxiv.org/abs/2603.19220>.
- Tianzhu Ye, Li Dong, Zewen Chi, Xun Wu, Shaohan Huang, and Furu Wei. Black-Box On-Policy Distillation of Large Language Models. *arXiv preprint arXiv:2511.10643*, 2025. URL <https://arxiv.org/abs/2511.10643>.
- Tianzhu Ye, Li Dong, Qingxiu Dong, Xun Wu, Shaohan Huang, and Furu Wei. Online Experiential Learning for Language Models. *arXiv preprint arXiv:2603.16856*, 2026a. URL <https://arxiv.org/abs/2603.16856>.

- Tianzhu Ye, Li Dong, Xun Wu, Shaohan Huang, and Furu Wei. On-Policy Context Distillation for Language Models. *arXiv preprint arXiv:2602.12275*, 2026b. URL <https://arxiv.org/abs/2602.12275>.
- Dongxu Zhang, Zhichao Yang, Sepehr Janghorbani, Jun Han, Andrew Ressler, Qian Qian, Gregory D. Lyng, Sanjit Singh Batra, and Robert E. Tillman. Fast and Effective On-policy Distillation from Reasoning Prefixes. *arXiv preprint arXiv:2602.15260*, 2026a. URL <https://arxiv.org/abs/2602.15260>.
- Miaosen Zhang, Yishan Liu, Shuxia Lin, Xu Yang, Qi Dai, Chong Luo, Weihao Jiang, Peng Hou, Anxiang Zeng, Xin Geng, and Baining Guo. Towards On-Policy SFT: Distribution Discriminant Theory and its Applications in LLM Training. *arXiv preprint arXiv:2602.12222*, 2026b. URL <https://arxiv.org/abs/2602.12222>.
- Ruixiang Zhang, Richard He Bai, Huangjie Zheng, Navdeep Jaitly, Ronan Collobert, and Yizhe Zhang. Embarrassingly Simple Self-Distillation Improves Code Generation. *arXiv preprint arXiv:2604.01193*, 2026c. URL <https://arxiv.org/abs/2604.01193>.
- Songming Zhang, Xue Zhang, Tong Zhang, Bojie Hu, Yufeng Chen, and Jinan Xu. AlignDis: Token-Level Language Model Alignment as Adaptive Policy Distillation. In *Proceedings of ACL*, 2025a. URL <https://arxiv.org/abs/2503.02832>.
- Xue Zhang, Songming Zhang, Yunlong Liang, Fandong Meng, Yufeng Chen, Jinan Xu, and Jie Zhou. A Dual-Space Framework for General Knowledge Distillation of Large Language Models. *arXiv preprint arXiv:2504.11426*, 2025b. URL <https://arxiv.org/abs/2504.11426>.
- Yaocheng Zhang, Yuanheng Zhu, Wenyue Chong, Songjun Tu, Qichao Zhang, Jiajun Chai, Xiaohan Wang, Wei Lin, Guojun Yin, and Dongbin Zhao. π -Play: Multi-Agent Self-Play via Privileged Self-Distillation without External Data. *arXiv preprint arXiv:2604.14054*, 2026d. URL <https://arxiv.org/abs/2604.14054>.
- Zhaoyang Zhang, Shuli Jiang, Yantao Shen, Yuting Zhang, Dhananjay Ram, Shuo Yang, et al. Reinforcement-aware Knowledge Distillation for LLM Reasoning. *arXiv preprint arXiv:2602.22495*, 2026e. URL <https://arxiv.org/abs/2602.22495>.
- Anhao Zhao, Ziyang Chen, Junlong Tong, Yingqi Fan, Fanghua Ye, Shuhao Li, Yunpu Ma, Wenjie Li, and Xiaoyu Shen. On-Policy Supervised Fine-Tuning for Efficient Reasoning. *arXiv preprint arXiv:2602.13407*, 2026a. URL <https://arxiv.org/abs/2602.13407>.
- Siyan Zhao, Zhihui Xie, Mengchen Liu, Jing Huang, Guan Pang, Feiyu Chen, and Aditya Grover. Self-Distilled Reasoner: On-Policy Self-Distillation for Large Language Models. *arXiv preprint arXiv:2601.18734*, 2026b. URL <https://arxiv.org/abs/2601.18734>.
- Binbin Zheng, Xing Ma, Yiheng Liang, Jingqing Ruan, Xiaoliang Fu, Kepeng Lin, Benchang Zhu, Ke Zeng, and Xunliang Cai. SCOPE: Signal-Calibrated On-Policy Distillation Enhancement with Dual-Path Adaptive Weighting. *arXiv preprint arXiv:2604.10688*, 2026. URL <https://arxiv.org/abs/2604.10688>.
- Qihuang Zhong, Liang Ding, Li Shen, Juhua Liu, Bo Du, and Dacheng Tao. Revisiting Knowledge Distillation for Autoregressive Language Models. *Proceedings of ACL*, 2024. URL <https://arxiv.org/abs/2402.11890>.
- Zhide Zhong, Haodong Yan, Junfeng Li, Junjie He, Tianran Zhang, and Haoang Li. VLA-OPD: Bridging Offline SFT and Online RL for Vision-Language-Action Models via On-Policy Distillation. *arXiv preprint arXiv:2603.26666*, 2026. URL <https://arxiv.org/abs/2603.26666>.
- Yongchao Zhou, Kaifeng Lyu, Ankit Singh Rawat, Aditya Krishna Menon, Afshin Ros-tamizadeh, Sanjiv Kumar, Jean-François Kagy, and Rishabh Agarwal. DistillSpec: Improving Speculative Decoding via Knowledge Distillation. *arXiv preprint arXiv:2310.08461*, 2023. URL <https://arxiv.org/abs/2310.08461>.
- Matthieu Zimmer, Xiaotong Ji, Tu Nguyen, and Haitham Bou Ammar. Rethinking Large Language Model Distillation: A Constrained Markov Decision Process Perspective. *arXiv preprint arXiv:2509.22921*, 2025. URL <https://arxiv.org/abs/2509.22921>.