

A Survey of On-Policy Distillation for Large Language Models

Mingyang Song & Mao Zheng
 Large Language Model Department
 Tencent, China
nickmysong@tencent.com

Abstract

As Large Language Models (LLMs) continue to grow in both capability and cost, the transfer of frontier capabilities into smaller, deployable students has become a central engineering problem, and knowledge distillation has become the natural vehicle for this transfer. Yet the form that now dominates industrial pipelines, static imitation of teacher-generated text, carries a structural weakness that becomes increasingly severe as tasks grow longer and more reasoning-intensive. Because the student is trained on flawless teacher prefixes but must generate its own at inference, small mistakes accumulate into trajectories it has never been taught to recover from, and the resulting exposure bias scales with the square of sequence length. On-Policy Distillation (OPD) reorganizes the training loop around this observation by asking the teacher to provide feedback on what the student *actually produces*, shrinking the compounding term to linear and turning distillation from one-shot behavior copying into an interactive correction process. The resulting literature has expanded rapidly along divergence design, reward-guided optimization, and self-play, yet contributions remain scattered across the knowledge distillation, RLHF, and imitation learning communities with no unified treatment. This survey brings them under a common analytical lens. We cast OPD as f -divergence minimization over student-sampled trajectories, organize the field along the practitioner’s actual decision chain of what to optimize, where the signal comes from, and how to stabilize the loop in practice, and consolidate success conditions, recurring failure modes, and the formal equivalence between OPD and KL-constrained reinforcement learning. We close with the open problems that emerge from this synthesis, from distillation scaling laws and uncertainty-aware feedback to agent-level distillation and the dissolving boundary between knowledge distillation and RL.

Awesome List & Paper Collection

<https://github.com/nick7nlp/Awesome-LLM-On-Policy-Distillation>

1 Introduction

The frontier of Large Language Models (LLMs) has advanced at a pace that few other areas of machine learning have matched, with recent systems achieving near-human competence in reasoning, code generation, and multilingual instruction following (Yang et al., 2025; DeepSeek-AI et al., 2025; Gemma Team et al., 2024). This progress, however, has come at a cost that only a handful of organizations can sustain, which has turned capability transfer from large frontier models into smaller deployable students from an academic curiosity into one of the load-bearing techniques of the modern LLM pipeline. Knowledge distillation, first formalized by Hinton et al. (2015) as a way for a student to inherit the soft output structure of a teacher, has accordingly shifted in character. What was once a compression tool has become a general mechanism for moving capabilities across model scales, most visibly in the release of DeepSeek-R1 (DeepSeek-AI et al., 2025), whose 671B mixture-of-experts teacher

was successfully distilled into dense students spanning 1.5B to 70B parameters and whose long chain-of-thought reasoning survived the transfer largely intact.

The dominant recipe behind such successes is, however, deceptively fragile. In almost all large-scale pipelines, distillation proceeds *off-policy*. The student is trained to match the teacher’s next-token distribution over a fixed corpus, typically the original pre-training data or traces generated in advance by the teacher, and every gradient step conditions on flawless teacher prefixes. At inference, this assumption breaks. The student must generate autoregressively from its own partial outputs, and any divergence between the training states and the states it actually visits at deployment time translates into compounding error along the trajectory. This is a textbook instance of *exposure bias* in interactive imitation learning (Ross et al., 2011), with the additional twist that autoregressive generation amplifies it quadratically in sequence length, producing an expected discrepancy of $O(\epsilon T^2)$ over a horizon T . The consequences are most visible on reasoning tasks, where a single early misstep can derail an entire proof or program, and Gudibande et al. (2023) already warned the community that off-policy imitation of proprietary LLMs often yields students that reproduce surface style without acquiring the underlying reasoning competence.

Resolving this mismatch requires changing *where* the training data comes from rather than *what* is being matched. **On-Policy Distillation (OPD)** does exactly that, by shifting the sampling distribution from a static corpus to the student’s own evolving policy. The student proposes trajectories, drifts into the very states it would visit at deployment, and receives teacher feedback on those states rather than on idealized expert prefixes. Depending on the available access, this feedback can take the form of full token-level distributions in white-box settings (Agarwal et al., 2023; Gu et al., 2023), scalar rewards or pairwise preferences when only black-box APIs are available (Ye et al., 2025; Jiang et al., 2023), or contrastive signals the model derives from its own outputs in teacher-free settings (Chen et al., 2024). The theoretical payoff mirrors the classical DAGger result (Ross et al., 2011): querying an expert on the learner’s own visited states reduces the $O(\epsilon T^2)$ compounding of off-policy imitation to $O(\epsilon T)$. Translated into autoregressive language modeling, this turns distillation from a single-pass matching problem into an iterative, self-correcting optimization loop.

This reformulation has given rise to a rich and fast-growing body of work, and its trajectory is best understood as a series of design choices made visible. Early methods focused on *how* to sample and *which* divergence to apply on student trajectories (Agarwal et al., 2023; Gu et al., 2023; Ko et al., 2024), gradually exposing the fact that the optimal divergence depends on where in the sequence one is training and what kind of supervision the teacher can provide. A parallel line of work established that the resulting objective is formally equivalent to a KL-constrained form of reinforcement learning (Yang et al., 2026c), dissolving what had looked like a boundary between two separate research communities. A third branch showed that the “teacher” need not be external at all, with methods such as SPIN (Chen et al., 2024) and OPSD (Zhao et al., 2026b) demonstrating that a model can bootstrap improvement from its own generations by exploiting asymmetries in its own context. These ideas have since moved from papers into production pipelines, with Qwen3 (Yang et al., 2025), DeepSeek-V4 (DeepSeek-AI, 2026), Gemma 2 (Gemma Team et al., 2024), and MiMo-V2 (Xiaomi LLM-Core Team et al., 2026) treating OPD as a core training ingredient, and DeepSeek-V4 in particular replacing its mixed RL stage with pure multi-teacher OPD for model consolidation.

The practical success of OPD, however, has outpaced the community’s ability to understand it as a single object. Methods reach the same objective from the vantage points of knowledge distillation, RLHF, and interactive imitation learning, and they inherit different notations, benchmarks, and failure taxonomies from their parent communities. Existing surveys of LLM distillation (Xu et al., 2024b) generally retain the classical compression framing, treating off-policy and on-policy methods as interchangeable variants rather than as regimes with materially different theoretical guarantees and failure modes. As a result, no current treatment offers a unified mathematical account of the on-policy dynamics that connect these threads, and no systematic comparison exists across the white-box, black-box, and teacher-free instantiations that a practitioner is likely to weigh against one another in practice.

This survey is written to fill that gap. Our goals are both conceptual and practical, and they are reflected in four contributions that also structure the rest of the paper.

- **A unified theoretical framework.** We recast the transition from off-policy to on-policy distillation as a sequential decision-making problem and show that the core OPD algorithms are instances of f -divergence minimization over student-sampled trajectories (Section 2). This framework provides a common analytical vocabulary for methods previously studied in isolation and makes their relationships explicit in terms of divergence choice, argument ordering, and sampling mixture.
- **A decision-centric taxonomy.** Rather than grouping methods by surface similarity, we organize them by their role in a practitioner’s decision chain (Section 3), namely objective function design (Section 4), signal source architecture (Section 5), and training dynamics optimization (Section 6). The resulting one-method-one-category classification is aimed directly at the question of *which method to use* given a set of deployment constraints.
- **A theoretical account of failure.** We consolidate the empirical record into a coherent view of when and why OPD breaks down (Section 7), covering the flawed prefix trap, self-play saturation, diversity collapse, and the calibration-capability gap, and we state formal conditions under which OPD provably improves over off-policy alternatives.
- **Comprehensive coverage and actionable guidance.** We survey the white-box, black-box, and self-distillation regimes within this common framework, summarize them in three comparison tables (Tables 1, 2, and 3), and translate the synthesis into a concrete decision tree (Section 3.3) that maps deployment constraints to recommended methods and compute budgets.

The structure of the paper mirrors this decision-centric logic. Section 2 develops the mathematical preliminaries, formalizes autoregressive generation as a sequential decision problem, and derives the exposure bias that motivates on-policy training. Section 3 lays out the practitioner-centric landscape and decision tree. Sections 4–6 then traverse the decision chain from “what to optimize” through “where the signal comes from” to “how to make training work in practice,” with each section building directly on the choices exposed in the previous one. Section 7 consolidates the theoretical perspectives, showing that the patterns observed across Sections 4–6 follow from a small number of unifying principles. Section 8 discusses industrial deployments, system-level optimization, and emerging domains, and Section 9 lays out the open problems that emerge from the synthesis.

Our scope is deliberately centered on the on-policy regime. We cover methods in which the student generates its own training data during distillation, and we include work from adjacent fields such as imitation learning, online RL, and preference optimization whenever it operates on student-generated data under teacher or verifier supervision. We correspondingly set aside generic off-policy KD, compression techniques that are orthogonal to the training paradigm such as pruning and quantization, and inference-time methods that leave model weights unchanged.

2 Background and Unified Math

To understand why on-policy training is necessary, we must first formalize the compounding geometry of autoregressive generation. We begin with classical KD and its limitations, then establish the unified f -divergence framework that subsumes modern OPD objectives.

Defining “on-policy.” A distillation method is *on-policy* if the training data for the student is sampled from the student’s own current policy p_θ at training time, rather than from a fixed external corpus $\mathcal{D}$ or from the teacher’s generation distribution p_T . Formally, on-policy training optimizes:

$$\min_{\theta} \mathbb{E}_{x \sim \mathcal{D}} \mathbb{E}_{y \sim p_\theta(\cdot|x)} [\mathcal{L}(y, x; \theta, T)] \quad (1)$$

where $\mathcal{L}$ is the distillation loss (divergence, reward, or hybrid). The key distinction is that the *outer* expectation is over the student’s own generations, not a static dataset. This creates a non-stationary optimization landscape because as θ updates, the data distribution

p_θ shifts, requiring fresh rollouts at each training step. The computational cost of this fresh generation is the central systems-level challenge of OPD (Section 6.3).

Notation. Throughout this survey, we use lowercase p for token-level conditional distributions ($p_T(\cdot|x, y_{<t})$ for teacher, $p_\theta(\cdot|x, y_{<t})$ for student) and uppercase P for sequence-level distributions ($P_T(y|x)$, $P_\theta(y|x)$). $\mathcal{D}$ denotes the training dataset, p_{data} the data distribution, and $|V|$ the vocabulary size. D_{KL} and D_f denote KL divergence and general f -divergence respectively. In the RL formalization, π denotes policies and $R(x, y)$ the outcome reward. When discussing individual methods, we follow each paper’s conventions where clarity demands.

2.1 Classical Knowledge Distillation

The original KD formulation (Hinton et al., 2015) trains the student to match the teacher’s temperature-softened output distribution:

$$p_T^{(\tau)}(y|x) = \frac{\exp(z_y/\tau)}{\sum_j \exp(z_j/\tau)} \quad (2)$$

where z_y are the teacher’s logits and $\tau > 1$ is a temperature parameter. When $\tau \rightarrow \infty$, the softened distribution approaches a uniform distribution over the vocabulary, revealing the teacher’s “dark knowledge” about inter-class similarities that are hidden in the hard labels. The gradient of the distillation loss with respect to the student’s logits z_i^S reveals why temperature matters:

$$\frac{\partial \mathcal{L}_{\text{KD}}}{\partial z_i^S} = \frac{1}{\tau} (p_i^S - p_i^T) \quad (3)$$

In the high-temperature limit ($\tau \rightarrow \infty$), a Taylor expansion $\exp(z_i/\tau) \approx 1 + z_i/\tau$ shows that the gradient reduces to $\frac{1}{|V|}(z_i^S - z_i^T)$, revealing that classical KD in this regime is equivalent to minimizing the mean squared error between raw logits. This forces the student to replicate the teacher’s *entire* logit structure, transferring both primary predictive modes and nuanced sub-optimal probability masses (the “dark knowledge”). However, higher temperatures also amplify the contribution of non-peak tokens, effectively transferring the teacher’s relational structure between vocabulary items. In practice, LLM distillation operates at moderate temperatures ($\tau \in [1, 3]$) or uses the teacher’s natural distribution ($\tau = 1$), because the vocabulary is large enough that even untempered distributions contain rich inter-token structure.

For autoregressive LLMs, the token-level distillation loss factors as:

$$\mathcal{L}_{\text{Token-KD}} = \mathbb{E}_{x, y \sim \mathcal{D}} \left[\sum_{t=1}^{|y|} D_{\text{KL}}(p_T(\cdot|x, y_{<t}) \parallel p_\theta(\cdot|x, y_{<t})) \right] \quad (4)$$

This is computationally tractable because it relies on static, pre-computed prefixes from the dataset, but it optimizes next-token accuracy while assuming an error-free history $y_{<t}$. Kim & Rush (2016b) extended this to Sequence-Level Knowledge Distillation (Seq-KD), which instead minimizes the global KL divergence over the entire sequence space:

$$\mathcal{L}_{\text{Seq-KD}} = D_{\text{KL}}(P_T(y|x) \parallel P_\theta(y|x)) = \sum_{y \in \mathcal{Y}} P_T(y|x) \log \frac{P_T(y|x)}{P_\theta(y|x)} \quad (5)$$

Since $|\mathcal{Y}| = |V|^T$ grows exponentially with length, exact computation is intractable. Seq-KD approximates $P_T(y|x)$ with a Dirac delta at the beam-search output $\hat{y} = \arg \max_y P_T(y|x)$, reducing to standard negative log-likelihood on teacher-generated sequences:

$$\mathcal{L}_{\text{Seq-KD}} \approx -\log P_\theta(\hat{y}|x) \quad (6)$$

This approximation works well when the teacher is highly confident but discards all information about the teacher’s uncertainty and alternative modes, a critical limitation that motivates the softer distributional matching methods below.

Subsequent work (Zhong et al., 2024) revisited these foundations for modern LLMs, demonstrating that classical assumptions (small teacher-student gap, shared vocabulary, similar architectural inductive biases) frequently fail in the era of heterogeneous model families. This motivates the more general f -divergence framework below.

From classical KD to on-policy. The historical progression from Hinton’s classical KD to modern OPD can be understood as a series of relaxations. Classical KD assumes: (1) shared vocabulary, (2) i.i.d. data, (3) static teacher, (4) off-policy training data. Seq-KD (Kim & Rush, 2016a) relaxes assumption (2) by operating at the sequence level but retains the static data assumption. GKD (Agarwal et al., 2023) relaxes assumption (4) by training on student-generated sequences. DSKD (Zhang et al., 2025b) relaxes assumption (1) through dual-space alignment. G-OPD (Yang et al., 2026c) relaxes all four simultaneously while adding RL-augmented objectives. Each relaxation addresses a specific failure mode that becomes more severe as model scale increases, since vocabulary mismatch is irrelevant for same-family distillation but catastrophic for cross-family (relaxation 1), while exposure bias is negligible for short sequences but devastating for multi-step reasoning (relaxation 4). This progression is not merely historical but prescriptive. Practitioners should identify which assumptions hold in their specific setting and select the minimally relaxed method, avoiding unnecessary complexity.

2.2 Off-Policy Exposure Bias

Standard Knowledge Distillation minimizes the KL divergence over states drawn from the dataset distribution $d_{\mathcal{D}}(s)$:

$$\mathcal{L}_{\text{Off-Policy}} = \mathbb{E}_{x,y \sim p_{\text{data}}} \left[\sum_{t=1}^{|y|} D_{\text{KL}}(p_T(\cdot|x, y_{<t}) \parallel p_{\theta}(\cdot|x, y_{<t})) \right] \quad (7)$$

At inference, the student acts according to its own policy, inducing a different state visitation distribution $d_{\pi_{\theta}}(s)$. By the DAGger theorem (Ross et al., 2011), if a policy mimics an expert with per-step error ϵ under the training distribution, the expected total discrepancy over a trajectory of length T under the student’s own distribution scales quadratically, bounded by $O(\epsilon T^2)$.

This quadratic compounding has severe practical consequences for reasoning tasks. A mathematical proof requiring 10 reasoning steps with per-step accuracy 95% yields only $(0.95)^{10} \approx 60\%$ trajectory-level correctness under off-policy training, because the student never learns to recover from its own intermediate errors. On-policy training exposes the student to its own error states during training, enabling it to learn correction strategies that reduce the effective per-step error rate when errors have already occurred.

Remark: The DAGger bound in LLMs. While the theoretical transition from $O(\epsilon T^2)$ to $O(\epsilon T)$ is appealing, applying the DAGger bound to LLMs requires nuance. The original theorem assumes an *interactive expert* providing optimal actions in any state. In white-box OPD, the “expert” provides a next-token distribution $p_T(y_t|\hat{y}_{<t})$ conditioned on the student’s prefix $\hat{y}_{<t}$. If the student hallucinates a severely out-of-distribution prefix, the teacher’s conditional distribution may itself become poorly calibrated, because the teacher was never trained on such inputs. Forcing the student to match this noisy distribution violates the core assumption of interactive imitation learning, potentially destabilizing training rather than recovering the $O(\epsilon T)$ bound. This observation provides the theoretical motivation for the adaptive trust mechanisms surveyed in Section 6.1 and explains why unconditional token-level matching is insufficient for robust OPD.

2.3 The Unified f -Divergence Framework

OPD resolves exposure bias by altering the training expectation to sample from the student’s own rollouts, or a mixture policy π_{mix} . The generalized on-policy objective decouples the sampling trajectory from the local matching metric:

$$\mathcal{L}_{\text{OPD}}(\theta) = \mathbb{E}_{y \sim \pi_{\text{mix}}} \left[\sum_{t=1}^{|y|} \mathcal{D}_f(p_T(\cdot|x, y_{<t}), p_{\theta}(\cdot|x, y_{<t})) \right] \quad (8)$$

Here, $\mathcal{D}_f$ represents a divergence from the f -divergence family (Wen et al., 2023). Formally, given two distributions P and Q , an f -divergence is defined as:

$$D_f(P \parallel Q) = \mathbb{E}_{y \sim Q} \left[f \left(\frac{P(y)}{Q(y)} \right) \right] \quad (9)$$

where $f : (0, \infty) \rightarrow \mathbb{R}$ is a convex generator with $f(1) = 0$. The choice of f determines the implicit weighting of likelihood ratios $p_T(y)/p_\theta(y)$:

- **Forward KL** ($f(u) = u \log u$): Mode-covering (zero-avoiding). The student must allocate probability mass wherever the teacher does, often bridging distinct teacher modes and hallucinating in the inter-mode space.
- **Reverse KL** ($f(u) = -\log u$): Mode-seeking (zero-forcing). The student collapses its mass onto the teacher’s single highest peak, ignoring secondary acceptable outputs but guaranteeing high precision.
- **JSD** ($f(u) = u \log u - (u + 1) \log \frac{u+1}{2}$): Symmetric, bounded, and smoothly interpolates between mode-covering and mode-seeking behavior.
- **α -divergence**: Parameterized family that continuously interpolates between Forward KL ($\alpha \rightarrow 1$) and Reverse KL ($\alpha \rightarrow 0$), enabling fine-grained control over the mode-seeking/covering tradeoff.

In practice, these divergences each suit different task geometries. For tasks with a *unique* correct answer (mathematical proofs, code correctness), Reverse KL’s mode-seeking behavior concentrates the student on the single optimal solution path. For tasks with *many* acceptable outputs (creative writing, open-ended QA), Forward KL’s mode-covering behavior preserves output diversity. JSD offers a compromise but lacks theoretical optimality guarantees for either extreme. All these divergences are computable as expectations under the student’s own policy (since $D_f(P_T \parallel P_\theta) = \mathbb{E}_{y \sim p_\theta} [f(p_T(y)/p_\theta(y))]$), which is what makes them amenable to on-policy optimization via policy gradient methods.

This framework subsumes all modern OPD objectives. The choice of f determines the geometric behavior, while the choice of π_{mix} controls the degree of on-policy exploration. We illustrate by mapping the three foundational methods into this space.

GKD (Agarwal et al., 2023) defines $\pi_{\text{mix}} = \lambda p_\theta + (1 - \lambda) p_{\text{data}}$ as an explicit interpolation, and is agnostic to $\mathcal{D}_f$, empirically testing Forward KL, Reverse KL, and JSD. Setting $\lambda \rightarrow 1$ makes GKD purely on-policy, while $\lambda = 0$ reduces to standard off-policy KD. The λ parameter provides a smooth dial between the extremes: moderate values ($\lambda \approx 0.5$) provide the benefits of on-policy exposure while retaining the stability of grounded, dataset-derived prefixes. GKD’s experiments establish that on-policy sampling ($\lambda = 1$) with JSD divergence yields the best downstream performance on summarization and translation, empirically validating the exposure bias hypothesis.

MiniLLM (Gu et al., 2023) selects Reverse KL as $\mathcal{D}_f = D_{\text{KL}}(p_\theta \parallel p_T)$ and employs $\pi_{\text{mix}} = (1 - \alpha)p_\theta + \alpha p_T$ with $\alpha = 0.2$ for stability. Because Reverse KL places the student in both the expectation and the log-ratio, MiniLLM reformulates optimization via REINFORCE, treating $\log(p_T/p_\theta)$ as a per-step reward.

DistiLLM (Ko et al., 2024) maintains $\pi_{\text{mix}} = p_\theta$ (fully on-policy) but replaces the KL target from p_T to a skewed mixture $\tilde{p} = \alpha p_T + (1 - \alpha)p_\theta$, computing $D_{\text{KL}}(p_T \parallel \tilde{p})$. This avoids zero-division instability when $p_\theta(y) \approx 0$, because $\tilde{p}(y) \geq \alpha p_T(y) > 0$ always, achieving tractability and stability without policy gradients.

Modern OPD, viewed through this decomposition, is not a series of disparate heuristics but a systematic exploration of a design space governed by three interacting choices: trajectory sampling (π_{mix}), divergence generator (f), and argument ordering within the chosen divergence.

2.4 Distillation Scaling Laws

A critical gap in the field is the absence of scaling laws specific to distillation. While Hoffmann et al. (2022) established compute-optimal scaling for pre-training (the Chinchilla

laws), and Busbridge et al. (2025) initiated the study of distillation-specific scaling, no comprehensive framework yet predicts how distillation quality scales with teacher size, student size, data volume, and on-policy rollout budget. This absence forces practitioners to rely on expensive trial-and-error. Preliminary evidence suggests that distillation scaling obeys qualitatively different laws from pre-training. The student benefits from teacher scale even after the teacher’s marginal pre-training gains plateau, because the teacher’s improved calibration (better next-token probability estimates) provides denser gradient signal per training step. On-policy rollout budget appears to exhibit a log-linear relationship with downstream quality once sufficient baseline capability is established, with larger rollout budgets yielding consistent but diminishing absolute improvements on reasoning benchmarks. However, these observations remain empirical rather than predictive, and the theoretical frameworks developed in Section 7 provide only partial answers. A complete distillation scaling law, expressed as $\text{Quality} \propto N_T^\alpha \cdot N_S^\beta \cdot D^\gamma \cdot R^\delta$ where R is the rollout budget, remains an open problem (Section 9).

3 Landscape and Practitioner Guide

The rapid proliferation of OPD methods creates a navigation challenge for practitioners. Rather than imposing arbitrary categorical labels, we organize the literature by the specific step in the engineering pipeline that each method optimizes.

3.1 Method Landscape

The practitioner faces three sequential decisions: (1) what objective to optimize, (2) where the supervisory signal originates, and (3) how to stabilize the resulting training dynamics. Figure 1 illustrates this pipeline.

The three-stage pipeline is not merely organizational convenience but reflects the actual engineering workflow. A practitioner first chooses an objective function (Forward KL? Reverse KL? Adaptive? RL-augmented?), then selects a signal source (white-box logits, black-box API, or self-generated), and finally addresses the training dynamics challenges that arise from the chosen combination. Some combinations are incompatible (e.g., Forward KL requires white-box logits, eliminating all black-box signal sources), which our decision tree (Section 3.3) makes explicit. Other combinations are synergistic: RL-augmented objectives (G-OPD) naturally pair with external feedback signal sources (verifiers, reward models), while fixed divergences pair most naturally with white-box sources where the full distribution is available for exact computation.

3.2 Method Comparison Table

Classification methodology. Each method is assigned to exactly one primary category based on its *core contribution dimension*: if a paper’s novelty lies in the loss function (e.g., G-OPD’s KL-constrained RL reformulation), it belongs to “Objective.” If it introduces a novel signal architecture (e.g., DSKD’s dual-space projection), it belongs to “Signal.” If it solves a training stability or efficiency problem (e.g., TIP’s token weighting), it belongs to “Dynamics.” Methods that contribute to multiple dimensions are classified by their *most distinctive* contribution. This strict one-method-one-category rule prevents the overlap and confusion that plagued previous multi-dimensional taxonomies.

3.3 Practitioner Decision Tree

The following decision tree provides actionable guidance for selecting OPD methods based on access constraints, task requirements, and compute budgets. These recommendations are derived from the empirical patterns observed across the methods surveyed in Sections 4–6.

1. Do you have full logit access to the teacher?

- *Yes (White-Box)*: Use DistiLLM (Ko et al., 2024) for stable token-level matching on instruction following, or G-OPD (Yang et al., 2026c) if strong reasoning




Figure 1: Taxonomy of On-Policy Distillation methods organized by the practitioner’s decision chain: (1) Objective function design (§4), (2) Signal source and teacher architecture (§5), and (3) Training dynamics and efficiency (§6). Each leaf lists the representative methods in that subsection; the badge shows the method count. Methods that contribute to multiple dimensions are placed under their most distinctive contribution.

extrapolation is required. For adaptive divergences, ToDi (Jung et al., 2025) or Entropy-Aware (Jin et al., 2026) provide automatic switching. If teacher and student use different tokenizers, deploy DSKD (Zhang et al., 2025b) or Cross-Tokenizer KD (Boizard et al., 2024).

- *No, API only (Black-Box)*: Use OVD (Xiong et al., 2026) for verbal score distillation (simplest), GAD (Ye et al., 2025) for adversarial training (strongest signal), or DAIL (Mendes et al., 2026) for didactic-to-constructive learning. If only text outputs are available and the student is small, LUFFY (Yan et al., 2025) with mixed-policy GRPO provides a strong baseline.
- *No teacher available (Self-Distillation)*: If oracle answers are available, use Privileged Information methods: OPSD (Zhao et al., 2026b) for math reasoning, GATES (Stein et al., 2026) for open-domain QA. If no oracle is available, start with SD-ZERO (He et al., 2026) (requires only a binary verifier) or SSD (Zhang et al., 2026d) (requires nothing at all, but saturates quickly).

2. What is the task profile?

- *Reasoning / Math*: Mode-seeking objectives are mandatory to prevent hallucination. Use Reverse KL (MiniLLM (Gu et al., 2023)) or RL-augmented KD (G-OPD, KDRL (Xu et al., 2025a)). Combine with curriculum pacing (PACED (Xu et al., 2026a)) for compute efficiency.

Table 1: Comparison of key OPD methods categorized by their primary contribution.

Method	Category	Core Contribution	Signal Source	Loss Granularity
GKD (Agarwal et al., 2023) DistiLLM (Ko et al., 2024) MiniLLM (Gu et al., 2023)	Objective (Fixed)	Dagger for LLMs; interpolation Skewed KL mixtures Sequence-level Reverse KL via RL	White-Box Logits White-Box Logits White-Box Logits	Token Token Sequence
ToDi (Jung et al., 2025)	Objective (Adaptive)	Log-ratio-routed token divergence Entropy-based KL interpolation	White-Box Logits	Token
Entropy-Aware (Jin et al., 2026)			White-Box Logits	Token
G-OPD (Yang et al., 2026c) RLKD (Xu et al., 2025b)	Objective (RL)	OPD equivalence to KL-RL KD augmented with reward model	White-Box Logits Reward Model	Sequence/Token Sequence
DSKD (Zhang et al., 2025b) Delta-KD (Cao et al., 2025)	Signal (White-Box)	Cross-architecture alignment Base-to-Instruct delta isolation	White-Box Logits White-Box Logits	Token Token
Lion (Jiang et al., 2023) GAD (Ye et al., 2025)	Signal (Black-Box)	Verbal feedback curriculum Adversarial distribution matching	Black-Box API Black-Box API	Sequence Sequence
OPSD (Zhao et al., 2026b) SPIN (Chen et al., 2024)	Signal (Self)	Privileged Info (PI) conditioning Self-play vs reference responses	Self-Generated Self-Generated	Token Sequence
TIP (Xu et al., 2026b)	Dynamics (Weight)	Token importance profiling via diff	White-Box Logits	Token
PACED (Xu et al., 2026a)		Beta-kernel curriculum pacing	White-Box Logits	Token

- *Open-ended Generation*: Mode-covering objectives preserve diversity. Use Forward KL or adaptive entropy-aware divergences. Avoid aggressive Reverse KL, which collapses creative diversity.
- *Instruction Following*: GKD (Agarwal et al., 2023) with $\lambda \geq 0.5$ provides the best quality-compute tradeoff. AlignDistil (Zhang et al., 2025a) adds preference alignment.
- *Multi-step Agentic Tasks*: Requires sequence-level objectives with trajectory-aware credit assignment. SCoRe (Lyu et al., 2025) for error correction, RLAD (Zhang et al., 2026h) for trust-region stability.

3. What are the compute limits?

- *Low compute (<500 GPU-hours)*: Standard GKD, Fast OPD (Zhang et al., 2026a) (prefix truncation), or Lightning OPD (Wu et al., 2026) ($4\times$ cost reduction via offline caching).
- *Medium compute*: Full on-policy training with adaptive divergences (ToDi, AKL (Wu et al., 2024)). Add PACED for efficient sample selection.
- *High compute (>5000 GPU-hours)*: Multi-stage pipelines: off-policy warmup $\rightarrow$ on-policy refinement $\rightarrow$ RL exploration. This is the recipe used by Qwen3 (Yang et al., 2025) and MiMo-V2 (Xiaomi LLM-Core Team et al., 2026).

4. Stability concerns?

- *Length inflation*: Apply Stable-OPD (Luo et al., 2026) stabilization (reference divergence + rollout mixing).
- *Flawed prefix trap*: Deploy TIP (Xu et al., 2026b) or SCOPE (Zheng et al., 2026) for teacher reliability filtering.
- *Thinking-pattern mismatch*: Start with off-policy cold start (Li et al., 2026d), then transition to on-policy after initial distribution alignment.

4 Objective Functions and Optimization

The first decision a practitioner faces when implementing OPD is the choice of objective function, determining what mathematical quantity the student should optimize at each training step. This choice governs gradient geometry, mode coverage, and ultimately the ceiling of achievable performance. The field has evolved through three phases, from fixed divergences that apply a single metric uniformly, through adaptive divergences that modulate the metric per-token based on local distributional geometry, to RL-augmented objectives that break through the teacher’s capability ceiling entirely.




Figure 2: Forward KL vs. Reverse KL divergence for fitting a student distribution P_S to a bimodal teacher P_T . **(a)** The teacher places equal probability mass on two valid modes (e.g., two correct answers or two stylistic variants). **(b)** Forward KL minimizes $D_{KL}(P_T \parallel P_S)$ and is mode-covering (zero-avoiding): the student spreads a single broad Gaussian over both modes and places substantial probability in the inter-mode hallucination zone (red dashed boundary), corresponding to outputs that are a blend of the two valid answers and therefore neither. **(c)** Reverse KL minimizes $D_{KL}(P_S \parallel P_T)$ and is mode-seeking (zero-forcing): the student concentrates sharply onto a single peak (Mode 2), dropping Mode 1 entirely but producing crisp, coherent generations within the chosen mode. This trade-off motivates the adaptive-divergence methods in §4 (ToDi, AKL, Entropy-Aware OPD), which interpolate between the two regimes based on per-token teacher entropy or log-ratio statistics.

4.1 Fixed Divergence Objectives

GKD (Agarwal et al., 2023) established the canonical OPD framework by adapting the DAGger algorithm (Ross et al., 2011) for autoregressive language models. It samples trajectories from a mixture policy $\pi_{\text{mix}} = \lambda p_\theta + (1 - \lambda)p_{\text{data}}$ and applies standard f -divergences (Forward KL, Reverse KL, or JSD) at each token position. The mixture coefficient λ interpolates between fully off-policy ($\lambda = 0$) and fully on-policy ($\lambda = 1$), providing a single control for exposure bias mitigation. On instruction-following and summarization benchmarks, moderate on-policy mixing ($\lambda \geq 0.5$) consistently outperforms pure off-policy training, validating the distributional alignment hypothesis.

However, pure KL divergences exhibit numerical instability during on-policy exploration. When the student generates tokens to which the teacher assigns near-zero probability, Forward KL produces unbounded gradients. Conversely, Reverse KL ignores these regions entirely, creating blind spots in the loss landscape. DistiLLM (Ko et al., 2024) addresses this through *Skewed KL* (SKL), constructing a smoothed target $\tilde{p} = \alpha p_T + (1 - \alpha)p_\theta$.

$$\mathcal{L}_{\text{SKL}} = \mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} D_{KL}(p_T(\cdot | y_{<t}) \parallel \alpha p_T(\cdot | y_{<t}) + (1 - \alpha)p_\theta(\cdot | y_{<t})) \right] \quad (10)$$

Skewing guarantees the target density is bounded below by $(1 - \alpha)p_\theta$, eliminating gradient explosion without requiring RL policy gradients. DistiLLM further introduces *Skewed Reverse KL* (SRKL) for mode-seeking applications, creating a symmetric pair of stabilized divergences. Its successor, DistiLLM-2 (Ko et al., 2025), recognizes that teacher-generated and student-generated data carry qualitatively different learning signals and applies *asymmetric* objectives, using Forward SKL on teacher-generated data (where mode-covering teaches the student to explore the teacher’s full distribution) and Reverse SRKL on student-generated data (where mode-seeking teaches the student to sharpen its own best responses). This source-aware asymmetry yields consistent improvements over symmetric single-divergence baselines across instruction following and summarization tasks, validating empirically that the optimal divergence is data-source-dependent.

The fixed-divergence family faces an inherent limitation: the choice between Forward KL (mode-covering) and Reverse KL (mode-seeking) is a global decision applied uniformly across all token positions (Figure 2). Yet the teacher’s distributional structure varies dramatically within a single sequence. At a mathematical operator token, the teacher concentrates probability mass on one or two correct symbols. At a conjunction or filler word, dozens of tokens share comparable probability. Applying a single divergence to both positions necessarily compromises. Forward KL wastes gradient signal on high-entropy positions where any token is acceptable, while Reverse KL discards useful coverage information at low-entropy positions where multiple valid continuations exist.

Sequence-level objectives offer a complementary perspective. MiniLLM (Gu et al., 2023) elevates Reverse KL to the full sequence level, where the student p_θ appears inside the sampling expectation. The central challenge is computing the gradient of an expectation over p_θ when p_θ itself is parameterized by θ . Starting from $D_{\text{KL}}(p_\theta \parallel p_T) = \mathbb{E}_{y \sim p_\theta} [\log p_\theta(y|x) - \log p_T(y|x)]$ and applying the log-derivative trick:

$$\nabla_\theta \mathcal{L}_{\text{MiniLLM}} = \mathbb{E}_{y \sim p_\theta} \left[\left(\log p_\theta(y|x) - \log p_T(y|x) \right) \nabla_\theta \log p_\theta(y|x) \right] \quad (11)$$

Minimizing sequence-level Reverse KL is thus mathematically equivalent to policy gradient RL with reward $r(x, y) = \log p_T(y|x) - \log p_\theta(y|x)$. MiniLLM decomposes this into per-step rewards r_t and future returns $R_t = \sum_{t'=t}^{|y|} r_{t'}$, enabling variance-reducing baselines:

$$\nabla_\theta \mathcal{L}_{\text{MiniLLM}} = -\mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} (R_t - b) \nabla_\theta \log p_\theta(y_t | y_{<t}) \right] \quad (12)$$

where b is a learned baseline. This places optimization squarely in the RL framework, with the teacher’s log-probability serving as a dense reward signal. The connection to policy optimization explains MiniLLM’s strong performance on reasoning tasks where sequence-level coherence matters more than token-level accuracy. However, REINFORCE estimation in massive combinatorial output spaces demands substantially more training iterations and sophisticated baseline subtraction to converge. KETCHUP (Fan et al., 2025) directly targets this variance problem by replacing the single-sample REINFORCE estimator with a K -step truncated return, reducing gradient variance while preserving the sequence-level objective. The constrained KD framework of Zimmer et al. (2025) further augments the sequence-level Reverse KL with a hard KL constraint implemented via state-augmented CMDP, ensuring that the student’s divergence from the teacher remains bounded even during aggressive exploration.

The token-level vs. sequence-level tradeoff. The choice between token-level and sequence-level objectives represents a core bias-variance tradeoff. Token-level methods (GKD, DistiLLM) provide $|V|$ -dimensional gradient signals at every position, yielding low variance but potentially biased gradients when the teacher’s token-level distribution is poorly calibrated (the flawed prefix trap of Section 6.1). Sequence-level methods (MiniLLM, KETCHUP) provide unbiased gradients through the policy gradient theorem but suffer from high variance due to single-sample REINFORCE estimation over exponentially large sequence spaces. The practical resolution is task-dependent: for instruction following where token-level teacher quality is high, GKD-style methods dominate. For reasoning tasks where sequence-level coherence is paramount, MiniLLM-style methods are preferred despite their variance, and KETCHUP’s truncated returns offer an intermediate point on this spectrum.

Full-vocabulary vs. sampled-token KL. Orthogonal to the token-level vs. sequence-level choice, a practical implementation decision determines how much of the teacher’s distribution is actually used at each position. Many RL-based OPD implementations approximate the per-position KL by computing $\log \pi_\theta(y_t | y_{<t}) - \log \pi_T(y_t | y_{<t})$ only at the *sampled* token y_t , treating this scalar as a per-token advantage within a policy gradient framework (Lu & Thinking Machines Lab, 2025). While computationally lightweight (requiring only one teacher log-probability per position), this single-sample estimate introduces high gradient variance and discards the distributional information across non-sampled tokens. DeepSeek-V4 (DeepSeek-AI, 2026) shows that *full-vocabulary* logit distillation, computing the exact $D_{\text{KL}}(p_\theta(\cdot | y_{<t}) \parallel p_T(\cdot | y_{<t}))$ over all $|V|$ tokens at each position, yields substantially more

stable gradients and more faithful knowledge transfer at the cost of transmitting or reconstructing the full teacher logit vector. Their engineering solution (caching teacher hidden states and reconstructing logits on-the-fly through the prediction head) makes this feasible even with 10+ trillion-parameter teachers over vocabularies exceeding 100K tokens, establishing full-vocabulary KL as the preferred choice for industrial-scale OPD when infrastructure permits. Lightning OPD (Wu et al., 2026) further establishes that the full teacher forward pass can be entirely eliminated by precomputing teacher log-probabilities over SFT rollouts, achieving $4\times$ speedup over standard OPD under a *teacher consistency* condition (using the same teacher for both SFT data generation and distillation).

4.2 Adaptive Divergence Objectives

Adaptive methods address this per-position mismatch by selecting or interpolating divergences based on local distributional geometry. When the teacher is certain (low entropy), mode-seeking Reverse KL preserves precision, and when uncertain (high entropy), mode-covering Forward KL preserves diversity.

ToDi (Jung et al., 2025) operationalizes this insight through per-token weighting derived from the teacher-student probability log-ratio. A sigmoid-based function $w_t = \sigma(\log p_T(y_t|y_{<t}) - \log p_\theta(y_t|y_{<t}))$ dynamically blends Forward KL and Reverse KL for each token:

$$\mathcal{L}_{\text{ToDi}} = \mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} w_t \cdot D_{\text{KL}}(p_T \parallel p_\theta) + (1 - w_t) \cdot D_{\text{KL}}(p_\theta \parallel p_T) \right] \quad (13)$$

where w_t emphasizes Forward KL for tokens the student underestimates (boosting their probability) and Reverse KL for tokens it overestimates (suppressing excess probability). Entropy-Aware OPD (Jin et al., 2026) takes an alternative approach, using the teacher’s per-token entropy $H(p_T(\cdot|y_{<t}))$ as a gating signal. The base objective is Reverse KL at all positions, with Forward KL *additively* activated at high-entropy tokens where the teacher distributes probability across multiple valid continuations:

$$\mathcal{L}_{\text{EA}} = \mathbb{E}_{y \sim p_\theta} \left[\sum_{t=1}^{|y|} D_{\text{KL}}(p_\theta \parallel p_T) + \mathbb{I}[H_t > \tau] \cdot D_{\text{KL}}(p_T \parallel p_\theta) \right] \quad (14)$$

Both methods consistently outperform any fixed divergence on math reasoning (MATH, GSM8K) and open-ended generation (AlpacaEval), confirming that the optimal divergence is indeed position-dependent.

AKL (Wu et al., 2024) takes a more aggressive approach, dynamically interpolating between Forward KL and Reverse KL based on a per-token confidence metric derived from the teacher-student probability ratio. Unlike entropy-based routing, which depends only on the teacher’s distributional shape, AKL considers the *relative* geometry of teacher and student, adapting more aggressively at positions where the gap is largest. All three adaptive methods admit a natural interpretation through information geometry. The Fisher information metric on the statistical manifold of autoregressive distributions varies across token positions. At reasoning-critical positions, the manifold is highly curved (the teacher concentrates probability on few tokens), making Reverse KL’s mode-seeking behavior locally appropriate because it follows the manifold’s natural gradient. At generation-flexible positions, the manifold is nearly flat (many synonyms are equally valid), and Forward KL’s mode-covering behavior preserves useful entropy. Adaptive divergences implicitly navigate this varying curvature by selecting the locally optimal metric, which explains their consistent empirical superiority over any fixed choice.

The field has thus moved decisively from “which divergence?” to “which divergence *where*?” The evidence from ToDi, AKL, and Entropy-Aware OPD converges on a single recommendation: no fixed divergence is ever optimal, and even the simplest adaptive routing (a hard entropy threshold) dominates the best-tuned fixed alternative.

4.3 RL-Augmented Objectives

Divergence matching, whether fixed or adaptive, intrinsically limits the student to the teacher’s capability ceiling. Perfect optimization yields a student that matches (but never exceeds) the teacher’s distribution. RL-augmented objectives break this ceiling by introducing an external performance signal that can steer the student toward solutions the teacher would never produce.

OPD as KL-constrained RL. G-OPD (Yang et al., 2026c) establishes a formal equivalence between standard OPD and dense KL-constrained reinforcement learning. It formulates distillation as maximizing a token-level reward derived from teacher logits, penalized by divergence from a reference policy:

$$\max_{\theta} \mathbb{E}_{y \sim p_{\theta}} \left[\sum_{t=1}^{|y|} \alpha \log p_T(y_t | y_{<t}) - D_{\text{KL}}(p_{\theta}(\cdot | y_{<t}) \parallel p_{\text{ref}}(\cdot | y_{<t})) \right] \quad (15)$$

When $\alpha = 1$, this reduces to standard Reverse KL distillation. When $\alpha > 1$, the objective forces the student to *extrapolate* beyond the teacher’s probability mass, enabling a phenomenon documented as *Reward Extrapolation*: the student discovers novel, structurally sound reasoning paths in regions where the teacher’s generation probability $p_T(y|x)$ is low but the outcome reward remains high. In the multi-teacher setting where several domain-specific RL experts share the same base model, reward extrapolation (ExOPD) produces a unified student that surpasses all its same-size domain teachers, demonstrating that OPD need not be a lossy compression step.

This equivalence has a deeper theoretical consequence. It bridges the distillation and RL communities, providing a shared analytical language. Any advance in KL-constrained RL (better trust regions, adaptive penalty coefficients, variance reduction) immediately transfers to OPD, and vice versa.

Gradient decomposition and the KD+RL complementarity. The unified KD+RL framework of Li et al. (2025) decomposes the hybrid gradient into two orthogonal components: a dense KD gradient for token-level imitation and a Monte Carlo RL gradient for reward maximization. The KD component dampens the high variance inherent in policy gradient estimation, while the RL component prevents the student from collapsing onto teacher modes that are suboptimal for the downstream task. REOPOLD (Ko et al., 2026) operationalizes this insight, interpreting on-policy distillation as policy optimization where the teacher-student log-likelihood ratio acts as a token reward, and stabilizing training through mixture-based reward clipping (preventing over-trust of extreme teacher signals), entropy-based dynamic sampling (selectively leveraging teacher feedback at high-uncertainty tokens), and a unified exploration-to-refinement strategy. Empirically, REOPOLD achieves 6.7–12 $\times$ greater sample efficiency than recent RL approaches and enables a 7B student to match a 32B teacher in visual reasoning with $\sim 3.3\times$ inference speedup.

Dense KD + sparse reward. RLKD (Xu et al., 2025b) exemplifies the integration of dense teacher supervision with sparse outcome feedback. It introduces a Generative Structure Reward Model (GSRM) that scores reasoning paths for structural coherence, combining token-level KL regularization with trajectory-level reward:

$$\max_{\theta} \mathcal{J}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, y \sim p_{\theta}(\cdot|x)} [R(x, y) - \beta D_{\text{KL}}(p_{\theta}(\cdot|x) \parallel p_T(\cdot|x))] \quad (16)$$

The mathematical structure explains why the combination works. The KL term provides analytically computable dense gradients, while the reward term contributes Monte Carlo policy gradients for outcome-driven exploration.

Joint vs. sequential optimization. A persistent engineering challenge is *how* to combine KD and RL within a training pipeline. Sequential approaches (distill-then-RL or RL-then-distill) suffer from catastrophic interference, as the RL stage erases distilled knowledge through policy drift, while the KD stage suppresses novel solutions discovered through exploration. KDRL (Xu et al., 2025a) operationalizes joint optimization by adding an on-policy KL regularizer between student and teacher *during* RL training. RLAD (Zhang et al., 2026h) refines this with Trust Region Ratio Distillation (TRRD), replacing the standard KL regularizer

with a PPO-style likelihood-ratio objective anchored to a teacher-old-policy mixture. This selective strategy follows the teacher only when its signal improves the policy update and ignores it otherwise, a principled solution to the problem that blind KL minimization can drag the student toward suboptimal trajectories on problems the teacher itself struggles with.

When logit access is insufficient to capture global intent, several methods map the problem onto Direct Preference Optimization (DPO). AlignDistil (Zhang et al., 2025a) constructs synthetic preference pairs from student rollouts scored by the teacher, applying both standard and reverse DPO objectives. OVD (Xiong et al., 2026) queries the teacher for pairwise preferences over student-generated responses, avoiding continuous probability extraction entirely. These preference-based objectives share a fundamental connection to token-level KL methods. Under DPO’s closed-form solution, the optimal policy satisfies $\pi^*(y|x) \propto \pi_{\text{ref}}(y|x) \exp(r(y,x)/\beta)$, and substituting the teacher’s log-probability as the implicit reward yields the geometric mixture distribution targeted by GKD with λ -mixing. The practical implication is that DPO-style methods are most useful when constructing preference pairs is cheaper than computing full teacher logits. PBSO (Yu et al., 2026) pushes this connection further in the self-distillation regime by deriving the reward-regularized optimum $\pi^* \propto \pi_{\text{teach}} \exp(r/\beta)$ against a context-augmented teacher rather than a static reference policy, and showing that the resulting pairwise preference loss provably dominates direct KL matching when the reward signal is informative (Section 5.3.1).

A distinct failure mode arises from the *uniformity* of all methods above. When the student makes a single error in step 3 of a 10-step proof, wholesale imitation retrains all 10 steps, diluting the corrective gradient. SuperCorrect (Yang et al., 2024) introduces hierarchical thought templates with cross-model DPO for error localization. SCoRe (Lyu et al., 2025) pushes targeting to its logical extreme, correcting *only the earliest error* in the student’s trajectory, concentrating all supervision at the single point of maximum leverage. This exploits a structural property of reasoning chains, namely that errors cascade, so correcting the root cause eliminates all downstream consequences simultaneously.

From signal matching to environment reconstruction. The most radical extension asks whether the student can recover the teacher’s *underlying optimization landscape*. $\mathcal{X}$ -KD (Cai & Yuan, 2026) adopts the AVRIL framework to jointly model the teacher’s latent reward function and perform policy distillation, encouraging the student to optimize in a reconstructed version of the teacher’s training environment rather than simply mimicking its outputs. TSD-KD (Kim & Baek, 2026) combines indirect distillation (student generates candidates that the teacher re-ranks via preference feedback) with direct distillation (KL matching applied selectively to high-entropy tokens where teacher-student gaps are largest). These methods represent the current frontier, moving from matching the teacher’s *behavior* to understanding its *incentives*.

Across objective types, a clear hierarchy emerges. Fixed divergences provide stable, well-understood optimization but are limited by the teacher’s capability ceiling. Adaptive divergences improve efficiency by matching the local geometry of the loss landscape. RL-augmented objectives break through the ceiling entirely but introduce variance and instability. The optimal choice depends on the specific application. For instruction following where teacher quality is high, fixed or adaptive divergences suffice. For reasoning tasks where the student must exceed the teacher, RL augmentation is essential. For tasks where the teacher’s training process is accessible, environment reconstruction offers the most complete knowledge transfer.

5 Signal Source and Teacher Architecture

With the objective function fixed (Section 4), the practitioner must determine *where the teacher signal comes from*, whether through full logit access (white-box), API-only text outputs (black-box), or the model’s own internal asymmetries (self-distillation). Each signal source imposes distinct constraints on the applicable objectives and achievable performance.

Historically, signal sources have evolved in step with model access constraints. Early OPD methods (GKD, DistiLLM) assumed full white-box access to model internals, a requirement that limits distillation to same-organization deployments. The rise of proprietary API-only models (GPT-4, Claude) necessitated black-box methods that can extract knowledge from text outputs alone. Most recently, self-distillation methods eliminate the external teacher entirely, enabling continuous improvement without access to any stronger model. This progression, from full access through limited access to no external access, represents increasing autonomy at the cost of signal density, creating a core trade-off that practitioners must navigate.

Complex reasoning is where OPD proves most indispensable and where off-policy methods encounter their hardest limits. The reason is structural, because reasoning is *path-dependent*. A proof that begins “assume for contradiction...” requires entirely different subsequent tokens than one beginning “we proceed by induction...” If the student has never generated the inductive approach during training, it cannot recover at inference time when that path would be optimal. Off-policy training over a fixed dataset of teacher reasoning traces can only cover a finite set of solution paths, while the student needs to navigate its own unique landscape of partial solutions, dead ends, and recovery strategies. This insight motivates the on-policy formulation for reasoning transfer. The student generates its own intermediate reasoning steps $r^S \sim P_\theta(\cdot|x)$, and the teacher evaluates these student-generated chains rather than dictating its own:

$$\mathcal{L}_{\text{CoT-OPD}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, r^S \sim P_\theta(\cdot|x)} \left[\sum_{t=1}^{|r^S|} D_{\text{KL}} \left(P_T(\cdot|x, r_{<t}^S) \parallel P_\theta(\cdot|x, r_{<t}^S) \right) \right] \quad (17)$$

The Forward KL direction ensures mode-covering: the student must allocate probability wherever the teacher does on the student’s own prefixes, effectively receiving corrective feedback on its actual generation patterns rather than memorizing the teacher’s preferred trajectories. This self-consistent learning dynamic, where the student practices its own reasoning style under expert supervision, is why on-policy CoT distillation has become the de facto standard for instilling multi-step reasoning into smaller models (Hsieh et al., 2023).

5.1 White-Box Logit Supervision

White-box access provides the densest possible signal, namely the full probability distribution across $|V|$ tokens at every decoding step. This exposes the teacher’s implicit decision boundaries, including the relative probabilities among incorrect tokens (Hinton’s “dark knowledge”), which carry information about similarity structure that binary labels cannot capture.

Standard logit distillation. The majority of methods surveyed in Section 4 assume white-box access. GKD, DistiLLM, ToDi, G-OPD, and their variants all require computing $p_T(\cdot|x, y_{<t})$ at each student-generated token position. The computational cost is dominated by the teacher forward pass, which must be executed once per student-generated token (or once per sequence for cached implementations).

Token-level adaptive supervision. Within the white-box setting, several methods refine *which* tokens receive supervision, and they can be organized along the axis of what drives the selection decision. SelecTKD (Huang et al., 2025) routes based on student-teacher agreement, applying a propose-and-verify mechanism where the student proposes tokens that the teacher verifies, and only positions where agreement holds receive full loss while rejected tokens are masked or down-weighted. AdaSwitch (Peng et al., 2025) routes based on student prefix reliability, maintaining a running error estimate and switching between exploration (student generates freely) and guidance (teacher provides dense supervision) so that guidance kicks in only when the trajectory has drifted far enough to warrant teacher intervention. Token-Adaptive KD (Xie et al., 2025) routes based on gradient magnitude, computing per-token importance weights from the KL loss itself and concentrating compute where the teacher-student gap is largest. The three selection criteria, agreement, prefix quality, and gradient magnitude, are complementary rather than competing, each capturing a different signal about where supervision is most informative. They also compose naturally

with entropy-based divergence routing (ToDi, Entropy-Aware): while divergence routing selects *which loss function* applies at each position, token-level selection determines *how much gradient signal* propagates, yielding an orthogonal two-dimensional design space that current methods have only begun to explore jointly.

The temporal scope of white-box distillation is not limited to post-training. MiniPLM (Gu et al., 2024) extends on-policy distillation to the *pre-training* stage, showing that distilling during pre-training yields stronger foundations for downstream fine-tuning. This represents a qualitative shift, because rather than being a post-hoc compression step, OPD becomes an integral part of the model creation pipeline. Gemma 2 (Gemma Team et al., 2024) validates this approach at industrial scale, embedding KD directly into the pre-training loop for its 27B→9B→2B model cascade. The success of pre-training distillation raises a deeper question. If OPD can improve models during their initial training, should it be viewed as a separate post-processing step at all, or as an intrinsic component of the training objective alongside next-token prediction?

A critical challenge arises when teacher and student use different tokenizers or vocabulary sizes. Direct KL divergence over mismatched vocabularies is undefined. DSKD (Zhang et al., 2025b) solves this through *dual-space* knowledge distillation, introducing projectors that map between teacher and student representation spaces:

$$\mathcal{L}_{\text{DSKD}} = D_{\text{KL}}(P_{T \rightarrow S} \parallel P_S) + D_{\text{KL}}(P_{S \rightarrow T} \parallel P_T) \quad (18)$$

where $P_{T \rightarrow S}$ denotes the teacher’s hidden states projected into the student’s space and decoded through the student’s prediction head. An exact token alignment algorithm handles vocabulary mismatches by identifying identical tokens across tokenizers. Vocabulary tokens with similar semantic embeddings should receive similar probability mass even when the tokenization schemes differ, enabling distillation across different architectures (e.g., Llama teacher to Qwen student) that share no vocabulary overlap.

Cross-Tokenizer KD (Boizard et al., 2024) takes a complementary approach based on optimal transport, computing an alignment matrix between teacher and student token sequences that minimizes the earth mover’s distance in latent space:

$$\mathcal{L}_{\text{CrossTok}} = \inf_{\pi \in \Pi(P_S, P_T)} \mathbb{E}_{(z_S, z_T) \sim \pi} \left[\|W_{S \rightarrow T} z_S - z_T\|_2^2 \right] \quad (19)$$

The distinction between hidden-state alignment (DSKD) and vocabulary-space alignment (Cross-Tokenizer KD) highlights a fundamental design trade-off. Hidden-state alignment preserves richer representational structure but requires maintaining two projectors during training. Vocabulary-space alignment is more lightweight but operates at a level where information has already been compressed through the vocabulary bottleneck. In either case, the alignment maps must be *co-trained* with the student, because the student’s representation space shifts during on-policy training as its policy evolves, a form of representation drift absent in off-policy settings. Concrete Score Matching (Kim et al., 2025) provides yet another solution, distilling via a continuous score function that bypasses the discrete vocabulary mismatch entirely. Together, these methods make OPD architecture-agnostic, allowing organizations to distill from any available teacher (e.g., Llama-based) into any student architecture (e.g., Qwen-based) without the historically restrictive requirement of shared vocabulary, enabling heterogeneous teacher-student pairs that were previously infeasible.

Beyond selecting *which tokens* to supervise, a complementary question is *what information* the teacher should provide at each token. The answer is not “everything”: not all content in the teacher’s logits is equally useful. Delta-KD (Cao et al., 2025) introduces the principle of *signal isolation*, distilling only the differential shift between a base model and its instruction-tuned variant. Since the base model’s distribution captures generic language modeling knowledge the student already possesses through pre-training, distilling it is redundant at best and harmful at worst (it wastes gradient budget on information the student has already internalized). By extracting only the instruction-following delta, Delta-KD provides a cleaner supervisory signal that transfers alignment without overwriting the student’s foundation.

A related but distinct challenge is teacher *overconfidence*: when the teacher assigns extreme probability to tokens outside the student’s reachable space, it creates optimization targets that are simultaneously precise and useless. Two complementary solutions address this from opposite directions. Veto (Jang et al., 2026) (Adaptive Target Reformulation) refines the teacher’s output *post-hoc*, constructing a geometric bridge in logit space with a parameter β that serves as both an Adaptive Gradient Veto (suppressing pathological gradients on low-confidence tokens) and a Decisiveness Knob (balancing performance with diversity), dynamically reformulating the teacher’s target distribution based on the student’s current capability. PromptKD (Kim et al., 2024) takes the opposite approach, adapting the teacher *pre-hoc* by prepending learnable prompt tokens (adding only 0.0007% of the teacher’s parameters) that cause the teacher to produce “student-friendly” distributions more accessible to the student’s limited capacity. The distinction is instructive. Post-hoc methods (Veto, Delta-KD) operate on the supervisory signal after it is produced, while pre-hoc methods (PromptKD) modify the teacher’s generation process itself. Both are effective, and their composition is orthogonal.

TAID (Shing et al., 2025) introduces yet another dimension of adaptation, namely temporal interpolation of the target itself. It constructs a time-dependent intermediate distribution $P_t = (1 - \lambda_t)P_\theta + \lambda_t P_T$ that starts close to the student and progressively approaches the full teacher distribution as training proceeds. This temporal curriculum over the target (rather than over the input prompts as in PAGED) provides a complementary axis of control. PAGED asks “which problems to train on,” while TAID asks “how much of the teacher’s knowledge to reveal at each stage.” The progression from PAGED (problem-level curriculum) through AdaSwitch (token-level timing) to TAID (target-level interpolation) and PromptKD (teacher-level adaptation) traces an important design spectrum, showing that curriculum can operate at four distinct granularities (prompt, token, target, teacher), all of which address the same underlying bottleneck of keeping the difficulty gap between teacher signal and student capability in the productive learning range. Because these four granularities are orthogonal, they can be combined within a single training loop, and systems that integrate all four should achieve the most efficient distillation.

5.2 Black-Box and API-Constrained Distillation

When only API access is available, the student observes the teacher’s top-1 text output (or at best, top- k log-probabilities) rather than the full distribution. This information bottleneck eliminates token-level divergence matching and forces methods to operate at the sequence level. Despite this limitation, black-box methods have proven surprisingly effective, suggesting that much of the teacher’s knowledge is recoverable from text-only observations.

Distilling Step-by-Step. Hsieh et al. (2023) demonstrated an influential early approach, extracting not just the teacher’s final answers but its intermediate reasoning steps (rationales) as additional supervision. The student is trained with a multi-task objective combining answer prediction and rationale generation, enabling it to outperform the teacher on downstream tasks with as little as $1,000\times$ less data. This work established the principle that *how* the teacher reasons is often more valuable than *what* it concludes, a principle that pervades modern OPD.

If extracting textual rationales recovers partial teacher reasoning, the natural next question is whether a richer proxy for the teacher’s full distribution can be reconstructed from black-box outputs alone. The following methods attempt progressively more aggressive reconstructions, from adversarial discrimination through verbal scoring to preference ranking.

Adversarial distribution matching. GAD (Ye et al., 2025) reformulates the distillation problem as a generative adversarial game:

$$\max_G \min_D V(G, D) = \mathbb{E}_{(x, y^T) \sim \mathcal{T}} \left[-\log \sigma \left(D(y^T) - D(G(x)) \right) \right] \quad (20)$$

A discriminator D (initialized from the student with a scalar prediction head) distinguishes student rollouts from teacher API outputs via a Bradley-Terry preference model, while the generator G maximizes V via REINFORCE using the discriminator score as an evolving on-policy reward signal. Unlike white-box methods that match full distributions, GAD extracts

knowledge through a scalar quality signal, trading distributional fidelity for API compatibility. It inherits the training instability of adversarial objectives, as the discriminator can overfit to stylistic cues rather than semantic quality, but yields consistent gains over SFT baselines.

Verbal feedback and curriculum. Lion (Jiang et al., 2023) exploits the teacher’s capacity as a natural language critic through a three-stage adversarial loop: (1) *imitation*, where the student is fine-tuned on teacher-generated responses, (2) *discrimination*, where the teacher identifies instructions on which the student still falls short, and (3) *generation*, where the teacher creates harder instructions targeting the student’s identified weaknesses. This closed-loop curriculum progressively narrows the teacher-student gap without requiring any gradient information from the teacher, making it applicable to any instruction-following API. Lion-13B achieves competitive performance on BIG-Bench Hard and AGIEval using only 70K training examples.

Didactic-to-constructive learning. DAIL (Mendes et al., 2026) addresses the gap between high-quality expert solutions (often out-of-distribution) and the student’s actual reasoning space. Fine-tuning on expert solutions yields poor transfer because the student never learns to navigate its own reasoning space. DAIL uses a two-step process: transforming expert solutions into detailed, in-distribution reasoning traces via mixed policy decoding (the student generates while conditioned on the ground-truth solution), and applying a contrastive objective to focus learning on expert methodologies rather than surface patterns. Using fewer than 1,000 expert solutions, DAIL achieves 10–25% pass@k gains, confirming the recurrent principle that the alignment of the supervision signal with the student’s current distribution matters more than its absolute quality.

Distribution-Aligned Sequence Distillation (DASD) (Yan et al., 2026) reexamines the dominant practice of SFT on teacher-generated reasoning traces, identifying three limitations: (1) inadequate representation of the teacher’s sequence-level distribution from single best-of- n samples, (2) misalignment between teacher output distribution and student capacity, and (3) exposure bias from teacher-forced training. Its distribution-aligned pipeline addresses all three by generating multiple diverse teacher traces per prompt and aligning the student’s generation distribution with the teacher’s through sequence-level matching, achieving state-of-the-art performance using only 448K training samples. DDT (Zhang et al., 2026c) complements DASD’s empirical findings with a theoretical framework explaining why RL generalizes better than SFT for reasoning: RL’s on-policy data generation keeps training aligned with the model’s evolving distribution rather than a static snapshot.

Verbal score distillation. OVD (Xiong et al., 2026) replaces token-level probability matching entirely with trajectory matching using discrete verbal scores (0–9) from teacher models. This eliminates the requirement for token-level alignment between vocabularies, dramatically reduces memory consumption by avoiding logit storage, and delivers up to +12.9% absolute EM improvement on web QA and +25.7% on math benchmarks with a single rollout sample. The surprising effectiveness of such coarse supervision reveals that on-policy exploration itself provides a substantial fraction of the learning signal, with the teacher’s role being more to *select among student trajectories* than to *correct individual tokens*.

These methods form a spectrum of signal richness versus access requirements. Adversarial methods recover the densest proxy for the teacher’s distribution but require the most complex training dynamics (discriminator co-training, generator-discriminator instability). Score-based methods are simpler to train but lose distributional information, recovering only a scalar quality signal. Preference-based methods occupy a principled middle ground, recovering relative quality without requiring calibrated absolute scores, and their connection to DPO-style objectives provides well-understood convergence guarantees. Practitioners should therefore select the signal type matching their API access tier: full logit access → KL methods (Section 4), token-level logits unavailable → adversarial or score-based, ranking-only access → preference-based.

Preference-based formulations. ORPO-Distill (Singh et al., 2025) maps black-box distillation onto preference optimization, generating candidate responses from the student and querying the teacher API for pairwise rankings. The mixed-policy strategy, combining on-

policy student traces with off-policy teacher traces, outperforms both pure off-policy and pure on-policy alternatives, suggesting that the contrastive structure of preference learning (learning what *not* to do alongside what to do) provides complementary signal to the positive-only feedback of score-based methods. ThinkTuning (RRV et al., 2025) occupies an intermediate position between black-box distillation and RL. Rather than providing scores after the fact, a same-size teacher reviews the student’s incorrect answers *during* the GRPO training loop and provides short corrective hints (rather than complete solutions). This interleaving of corrective feedback episodes with RL training acts as an implicit privileged signal that shapes policy gradient updates, and is particularly effective for base models that lack strong prior reasoning behaviors, achieving +3.85% over zero-shot baselines across benchmarks (+2.08% on MATH-500, +2.23% on AIME, +3.99% on GPQA-Diamond over vanilla GRPO).

MoE discriminator for pipeline-staged OPD. PRISM (Wang et al., 2026d) introduces a distinct architectural innovation to black-box distillation by inserting an OPD-based *pre-alignment* stage between SFT and RLVR, addressing the observation that direct RLVR from SFT checkpoints suffers from cold-start instability due to the large distributional gap between SFT outputs and reward-aligned behavior. Rather than using a monolithic discriminator (as in GAD), PRISM employs a Mixture-of-Experts discriminator with specialized perception and reasoning expert heads, providing *disentangled* corrective signals that distinguish visual grounding errors from logical reasoning failures. The adversarial game operates entirely at the response level without requiring teacher logits. The student generates on-policy responses, a black-box teacher (Gemini 3 Flash) provides reference demonstrations, and the MoE discriminator learns to distinguish them while providing differentiated feedback through its expert routing. This disentangled feedback is critical for multimodal models where failure modes are heterogeneous, since a model may correctly perceive an image but reason incorrectly about it, or vice versa. On Qwen3-VL at 4B and 8B scales, the pre-alignment stage alone yields +4.4 and +6.0 points over direct SFT-to-RLVR pipelines, and the subsequent RLVR training converges faster and more stably, suggesting that black-box OPD provides a structured warm-up that shapes the policy landscape for downstream RL optimization.

Off-policy knowledge integration. A related challenge is incorporating knowledge from off-policy sources (e.g., pre-existing teacher-generated datasets) into an on-policy framework. LUFFY (Yan et al., 2025) addresses this by extending GRPO to a mixed-policy objective that incorporates off-policy reasoning traces alongside the student’s on-policy rollouts. The key design challenge is preventing *superficial imitation*: without correction, the student tends to copy high-probability tokens from off-policy traces while ignoring low-probability but critical reasoning steps. LUFFY’s policy shaping via regularized importance sampling reweights gradients to emphasize learning from unfamiliar yet effective actions, achieving +6.4 average points over standard RLVR.

5.3 Self-Distillation

Self-distillation eliminates the need for an external teacher entirely. Instead, the model exploits asymmetries *within itself* to construct a training signal. Three families of methods have emerged, distinguished by the source of this internal asymmetry: privileged information that is available at training but not inference time, self-play between successive model checkpoints, and external feedback from verifiers or environments that the model itself has generated.

5.3.1 Privileged Information

The first family creates asymmetry through *privileged information* (PI): training-time access to context unavailable at inference. Conditioning the same model on additional context produces a strictly stronger policy that can supervise the unconditioned version, turning a single network into both teacher and student.

Ground-truth as PI. OPSD (Zhao et al., 2026b) constructs the teacher policy by conditioning on both the problem x and the ground-truth answer y^* , while the student conditions only

on x . The student generates on-policy rollouts, and the teacher provides dense token-level supervision:

$$\mathcal{L}_{\text{OPSD}}(\theta) = \mathbb{E}_{(x, y^*) \sim \mathcal{S}} \mathbb{E}_{\hat{y} \sim p_{\theta}(\cdot | x)} \left[\sum_{n=1}^{|\hat{y}|} D(p_{\theta}(\cdot | x, y^*, \hat{y}_{<n}) \parallel p_{\theta}(\cdot | x, \hat{y}_{<n})) \right] \quad (21)$$

On competition-level math benchmarks (AIME 2024/2025, HMMT), OPSD matches or exceeds GRPO at 4B and 8B scales while using only a single rollout per problem versus GRPO’s eight, achieving a significant computational advantage. At 1.7B scale, however, the gains over GRPO are minimal, indicating that sufficient model capacity is necessary for the PI mechanism to provide useful supervision. The teacher’s ground-truth conditioning must produce meaningfully different token distributions from the student, which requires enough parameters to represent the conditional shift.

A complementary limitation arises when all rollouts for a given prompt fail (the “cliff prompt” problem), causing the policy gradient to vanish entirely. This failure mode directly parallels PACED’s finding (Section 6.1) that gradient SNR vanishes when student pass rate approaches zero, but with an important difference: PACED addresses this through curriculum selection (avoiding problematic prompts), while HDPO (Ding, 2026) addresses it through signal augmentation. HDPO augments GRPO with a JSD-based self-distillation term on ground-truth-conditioned rollouts, ensuring non-zero gradients even at the boundary of the student’s competence, directly patching the cliff-prompt vulnerability without restricting the problem distribution.

Relaxing the ground-truth requirement. Ground-truth labels are not always available. GATES (Stein et al., 2026) shows that *any* training-time context can serve as PI by having a single model act as tutor (conditioned on a source document) and student (answering from the question alone). Because source documents do not guarantee correct answers, GATES introduces a consensus-based gating mechanism that suppresses the gradient when tutor uncertainty is high, preventing the model from reinforcing unreliable self-supervision. Penaloza et al. (2026) generalize the OPSD and GATES paradigms into a unified theoretical framework, formalizing the conditions under which privileged self-distillation provably improves over standard training.

Behavioral PI: context distillation. The PI paradigm extends beyond factual ground truth to behavioral instructions. OPCD (Ye et al., 2026b) treats system prompts, exemplars, and retrieval context as privileged information, enabling a model to internalize behaviors that would otherwise require expensive in-context demonstrations at inference time. OPSDL (Zhang et al., 2026e) extends this to long-context settings: applying on-policy self-distillation to enhance long-context capabilities without relying on high-quality supervision data or sparse sequence-level rewards, enabling stable optimization for context length scaling beyond what standard post-training methods achieve. OEL (Ye et al., 2026a) extends to continuous post-deployment learning, using interaction outcomes as dynamic PI that updates the model’s teacher policy as it accumulates experience, closing a loop that OPCD opened.

Reasoning compression via PI. CRISP (Sang et al., 2026) finds that a model prompted to “be concise” can serve as a teacher for its own verbose version, reducing chain-of-thought token count by 57–59% on MATH-500 while *improving* accuracy by 9–16 percentage points. Much of the verbosity in distilled reasoning models turns out to be trainable inefficiency rather than a necessary feature of competent reasoning.

Visual PI for GUI grounding. GUI-SD (Zhang et al., 2026f) extends the privileged information paradigm to multimodal GUI grounding, where the task is to predict click coordinates on a screen given a natural language instruction. The privileged context is a Gaussian soft mask centered on the target element’s bounding box, providing the teacher version with explicit spatial localization that the student must learn to infer from raw screenshots alone. This represents a qualitatively different form of PI from textual ground truth (OPSD) or document context (GATES): it is *visual* and *spatial*, demonstrating that the PI mechanism generalizes across modalities. Beyond the novel PI type, GUI-SD introduces entropy-guided token weighting via a dual-criterion: tokens receive higher loss weight based on both their digit significance (coordinate digits carry more semantic weight than filler tokens) and the

teacher’s confidence at that position. With only a single on-policy rollout per instance, GUI-SD outperforms GRPO (which requires multiple rollouts for reward estimation) on six GUI grounding benchmarks including ScreenSpot-v2, ScreenSpot-Pro, and OSWorld. The success of single-rollout PI distillation in the visual domain mirrors OPSD’s finding in mathematical reasoning, providing further evidence that privileged information provides sufficiently dense gradient signal to obviate the sample-intensive reward estimation required by RL-based alternatives.

Cross-lingual safety via PI. MSD (Qin et al., 2026) extends the PI paradigm to multilingual safety alignment: the same model’s English-language reasoning serves as privileged information for its low-resource-language student, transferring safety boundaries without target-language safety data. Its Dual-Perspective Safety Weighting (DPSW) concentrates distillation gradients on safety-critical tokens by combining teacher confidence with student disagreement. We discuss MSD’s broader implications for safety-aware OPD in Section 9.

Beyond KL matching via reward regularization. A recurring concern across the PI literature above is that directly matching the privileged teacher’s distribution can destabilize training and, in the worst case, degrade reasoning capability as training proceeds. PBSO (Yu et al., 2026) diagnoses this pathology through a reward-regularized lens, replacing pure KL matching with the objective $\max_{\pi} \mathbb{E}[r(x, y)] - \beta D_{\text{KL}}(\pi \| \pi_{\text{teach}})$, whose analytic optimum is a reward-reweighted teacher $\pi^* \propto \pi_{\text{teach}}(y|x) \exp(r(x, y)/\beta)$ that provably dominates the teacher itself whenever the reward is informative. Practically, PBSO realizes this optimum through a DPO-style pairwise loss where the preferred sample y^+ is drawn from the context-augmented teacher and the dispreferred sample y^- from the current student, preserving on-policy sampling while avoiding the forced imitation of every teacher token. On Qwen3-1.7B/4B/8B, PBSO is the only self-distillation method that both matches OPSD’s token efficiency and surpasses its peak accuracy without the post-peak decline documented in Figure 2 of Yu et al. (2026), suggesting that preference-based targets are a more principled substitute for direct KL matching than curriculum or signal-augmentation patches alone. This post-peak decline is the same pathology that CaOPD (Zhang et al., 2026b) attributes to the training-deployment context mismatch and that Kim et al. (2026) diagnose as epistemic suppression (Section 7.2), so PBSO can also be read as a self-distillation mechanism that converts these diagnostic insights into a corrective optimization target rather than a post-hoc recalibration step.

Outcome-conditioned PI at the turn level for agentic reasoning. The PI methods above all target single-turn generation. Extending PI to multi-turn agentic settings raises a distinct question: at which temporal granularity should privileged information intervene? Existing agentic OPD work has explored the *trajectory* granularity (TCOD’s temporal curriculum over turn prefixes, Section 6.2), the *step* granularity (MAD-OPD’s step-level decomposition, Section 8), and the *skill* granularity (Skill-SD’s skill-conditioned updates, Section 8), but none of them supply PI at the *turn* level itself. TT-OPD (Jeong, 2026) fills this gap. A gradient-free EMA teacher receives correctness-dependent cues (reinforcing phrases for trajectories scored correct, corrective phrases for those scored incorrect) that are inserted at the prompt-response boundary and then stripped from the teacher’s output log-probabilities, so the student never observes the hints directly but still receives an outcome-aware KL signal at every conversation turn. Two aspects distinguish this instance from prior PI mechanisms. *First, the privileged context encodes trajectory-level correctness rather than problem-level ground truth*, which is the first PI realization we are aware of where the teacher is conditioned on a property of the student’s own rollout rather than on external supervision. This generalizes the PI paradigm from single-response supervision (GATES, OPSD, GUI-SD) to multi-turn behavioral regularization. *Second, the ablation isolates why turn-level PI is necessary*: EMA teacher updates alone eliminate the KL-collapse pathology but still allow the multi-turn structure to erode, and outcome hints without length control trigger response explosion, so neither EMA nor hints in isolation suffice. These pathologies are precisely the failure modes documented in Section 7.2, and the interaction between teacher dynamics and outcome-conditioned PI is what makes agentic OPD stable. Viewed together with TCOD, Skill-SD, and MAD-OPD, TT-OPD completes a granularity spectrum for agentic distillation in which the choice of temporal unit (trajectory, turn, step, skill) is matched to the level at which errors compound in the target task.

5.3.2 Self-Play

A more radical question is whether a model can improve using nothing but its own rollouts, with no PI, no external feedback, and no additional context. The answer is a qualified yes, subject to important saturation limitations.

Self-play as a two-player game. SPIN (Chen et al., 2024) casts self-improvement as an adversarial game between successive checkpoints, training the updated model to distinguish its previous iteration’s generations from human-written responses:

$$\mathcal{L}_{\text{SPIN}} = \mathbb{E}_{x, y \sim p_{\text{data}}, y' \sim p_{\theta_t}} \left[\ell \left(\lambda \left(\log \frac{p_{\theta_{t+1}}(y|x)}{p_{\theta_t}(y|x)} - \log \frac{p_{\theta_{t+1}}(y'|x)}{p_{\theta_t}(y'|x)} \right) \right) \right] \quad (22)$$

SPIN provides a theoretical convergence guarantee: the global optimum of $\mathcal{L}_{\text{SPIN}}$ is achieved if and only if $p_{\theta_{t+1}} = p_{\text{data}}$, i.e., the student’s distribution exactly matches the reference distribution. At this fixed point, the loss is zero and the gradient vanishes, so the iterative process is *stable*: once the student reaches the target distribution, further iterations cannot destabilize it. The game-theoretic interpretation is that p_{data} is the unique Nash equilibrium of the two-player game, and SPIN’s iterative updates correspond to fictitious play converging to this equilibrium. Starting from Zephyr-7B-SFT, it improves MT-Bench from 5.94 to 6.78 over 3 iterations, with diminishing returns at each round. However, this convergence guarantee comes with an inherent limitation: SPIN converges to p_{data} , not to the optimal policy. If the reference data is sub-optimal (as human-written responses often are), SPIN will faithfully reproduce those sub-optimalities, confirming that pure self-play recycles existing knowledge rather than generating new knowledge.

IRIS (Liao et al., 2026) provides a unifying framework for this family by replacing the implicit KL divergence in SPIN with an interpolative Rényi divergence parameterized by $\alpha \in (0, \infty)$, recovering SPIN ($\alpha \rightarrow 1$, KL regime), SPACE (Jensen-Shannon regime), and SPIF ($\alpha = 2$, χ^2 -regularized regime) as special cases. The Rényi parameter controls the exploration-exploitation tradeoff: lower α encourages broader distributional coverage (exploration) while higher α concentrates updates on the most likely improvements (exploitation). This unification shows that the various self-play methods in the literature differ only in their implicit divergence choice, not in their fundamental mechanism, and suggests that α -tuning can be used as a meta-parameter for adapting self-play behavior to task requirements.

The trajectory from SPIN through IRIS to π -Play traces an escalating response to the saturation ceiling. SPIN accepts the ceiling (converging to p_{data}). IRIS pushes the ceiling by tuning the divergence’s exploration-exploitation balance via the Rényi parameter. π -Play shatters the ceiling by introducing internal privileged information that generates genuinely new training signal. Each step reveals that self-play is not inherently limited, but that breaking saturation requires progressively more creative sources of asymmetry. When internal asymmetry is exhausted, the only remaining option is to inject external ground truth, motivating the external grounding mechanisms of Section 5.3.3.

Beyond adversarial games. The self-play paradigm extends beyond explicit two-player games to encompass several lighter-weight mechanisms. SDFT (Shenfeld et al., 2026) positions on-policy self-distillation as a mechanism for forgetting resistance via implicit KL regularization against the model’s own prior checkpoint, converting the model’s optimization trajectory into a regularization resource for continual learning. MTP via self-distillation (Kirchenbauer et al., 2026) targets *architectural* rather than behavioral improvement: it converts a pre-trained autoregressive model into a multi-token predictor by training an auxiliary prediction head on the model’s own next-token predictions, achieving $> 3\times$ faster decoding at $< 5\%$ accuracy drop and expanding the scope of what self-distillation can optimize.

On-Policy SFT (Zhao et al., 2026a) provides a surprising simplification: by filtering self-generated responses for correctness (via a verifier) and conciseness (via length truncation at the median successful length), standard SFT on this filtered on-policy data matches or exceeds full RL training. The combination of on-policy generation (which naturally produces diverse solution strategies) with outcome filtering (which selects the best strategies) implicitly performs a form of evolutionary optimization that requires no gradient through the reward function. This “generate-filter-train” paradigm dramatically reduces implemen-

tation complexity compared to full RL-based distillation while retaining the core benefit of on-policy data: distributional alignment. Self-Distilled RLVR (Yang et al., 2026a) further decomposes the gradient update into two components: self-distillation determines the *magnitude* of per-token policy updates (how much to change each token’s probability), while environmental RLVR feedback anchors the *direction* (which tokens should increase vs. decrease). At just 200 training steps, RLSD surpasses GRPO trained for 400 steps on Qwen3-VL-8B-Instruct, demonstrating $2\times$ sample efficiency from the complementary signal structure.

Minimalist self-distillation. SSD (Zhang et al., 2026d) requires no RL, no verifier, no external teacher, and no code execution. It samples solutions at training-time temperature, fine-tunes via standard SFT, and reshapes token distributions in a context-dependent manner. On LiveCodeBench v6, SSD improves Qwen3-30B-Instruct from 42.4% to 55.3%, demonstrating that when the base model is sufficiently capable, even the simplest self-play yields substantial gains. The requirement is not a sophisticated algorithm but sufficient *diversity* in the model’s sampling distribution to produce high-quality variants that can serve as training targets.

However, this also exposes the fundamental boundary of pure self-play: when diversity is achieved through temperature sampling alone, the model’s improvement is ultimately bounded by the information already present in its pre-training distribution. Bridging this boundary requires either connecting the model to external reality (Section 5.3.3) or internally generating privileged information through the self-play process itself (π -Play below).

Unifying PI and self-play. π -Play (Zhang et al., 2026g) unifies privileged information and self-play within a single multi-agent self-evolution framework. Self-play naturally produces a byproduct: during task generation, the examiner agent constructs a question construction path (QCP) that provides high-quality PI at no additional cost. Three co-evolving agents (examiner π_ϕ^E , teacher π_ψ^T conditioned on QCP, student π_θ^S without it) are jointly optimized through alternating updates. As the student strengthens, the examiner generates harder tasks, and the teacher’s behavior is softly constrained to track the student via a KL penalty, establishing a self-adjusting curriculum that requires no external data. On Qwen3 (4B, 8B), data-free π -Play surpasses fully supervised search agents such as Search-R1 and delivers substantially higher evolutionary efficiency than conventional self-play (Dr.Zero), with the largest gains on multi-hop benchmarks where the teacher’s token-level credit assignment provides the most leverage.

Partial-solution PI. PAINT (Tan & Hong, 2026) occupies a distinctive position between pure self-play (no external information) and full PI (complete answer revealed). Rather than conditioning on the entire ground-truth solution (as in OPSD), PAINT reveals only a *partial* solution whose extent is adaptively controlled by the overlap between the student’s rollout and the reference. Specifically, it computes a recall-style overlap score based on the fraction of reference anchors (boxed answers, formulas, key numbers) that appear in the student’s rollout, revealing more of the reference when the student is close (providing fine-grained correction) and less when far (preventing trivial copying). This overlap-adaptive partial-solution masking creates a natural curriculum within the PI mechanism itself: easy problems where the student nearly solves them receive precise corrective feedback, while hard problems where the student diverges completely receive only coarse directional guidance. PAINT further introduces energy-space interpolation that applies the distillation loss only at positions where the teacher-student entropy mismatch exceeds a threshold, producing a sparse loss that concentrates gradient signal on the most informative positions. On competition-level mathematics, PAINT achieves +2.1 over the OPSD baseline and +2.9 over GRPO, demonstrating that partial revelation of privileged information can outperform both full revelation and no revelation, suggesting an optimal information disclosure curve that future work should characterize theoretically.

Together, π -Play and PAINT demonstrate that the self-play saturation problem can be mitigated *without* external feedback by internally generating privileged information, whether through multi-agent task construction or partial-solution conditioning. This mechanism is orthogonal to the external-verification strategies below, and combining both internal PI and external grounding remains an unexplored direction.

5.3.3 External Feedback

The self-play methods above require no external input but face an inherent ceiling: without ground-truth or verifier access, the model cannot distinguish confident-but-wrong outputs from genuinely correct ones, leading to the saturation problem analyzed in Section 7.2. External feedback methods retain the self-distillation architecture (no separate teacher model) while injecting non-differentiable truth signals, typically code execution, symbolic verification, or outcome rewards, that anchor the self-play loop and prevent it from collapsing onto self-reinforcing errors. Unlike the internal-PI mechanisms of π -Play and PAINT, external feedback bridges self-distillation and reinforcement learning by treating environmental signals as the ultimate arbiter when internal asymmetries are exhausted.

From binary rewards to dense supervision. SD-ZERO (He et al., 2026) converts sparse verifier signals into dense self-supervision through a dual-role architecture: the Generator produces on-policy responses, and the Reviser, conditioned on the Generator’s output and its binary correctness signal, produces an improved version. The Generator then distills from the Reviser’s token-level distribution, converting binary feedback into dense self-supervision. On Qwen3-4B-Instruct, SD-ZERO achieves 68.3% on AIME 2024, outperforming GRPO (62.5%), demonstrating that self-revision can be more effective than standard RL for converting sparse rewards into learning signal. SDPO (Hübotter et al., 2026) extends this beyond binary feedback to *structured textual* feedback: runtime errors, failing unit tests, and LLM judge evaluations construct fine-grained credit assignment that attributes success or failure to specific reasoning steps rather than entire trajectories. RL from Text Feedback (RLTF) (Song et al., 2026) pushes further with free-form natural language critiques from an automated judge, training the model’s single-turn policy to match its own feedback-conditioned second-turn generations.

From SD-ZERO’s binary signal through SDPO’s structured errors to RLTF’s free-form critiques, a clear trajectory emerges: as external feedback becomes richer, the self-distillation objective becomes more precisely targeted, enabling the model to correct specific failure modes rather than globally adjusting its policy. Sample-Routed Policy Optimization (SRPO) (Li et al., 2026b) shows that these approaches can be composed by routing: correct samples follow GRPO’s reinforcement path (reward-weighted likelihood maximization) while failed samples follow SDPO’s targeted logit-level correction. The insight is that correct and incorrect samples carry distinct types of learning signal, and treating both identically wastes the distinctive information each carries. SRPO raises the average by 3.4% over GRPO and 6.3% over SDPO alone, confirming that the optimal external-feedback strategy is a routing function matching each sample to its most informative objective.

Environmental grounding. RLTF and related methods use compiler outputs, unit test results, and symbolic math verifiers as external feedback that shatters self-reinforcing echo chambers. Even if the model becomes highly confident in a flawed derivation, the verifier assigns $R = 0$, providing an unambiguous correction signal that pure self-play cannot generate.

Saturation analysis. Kim et al. (2026) trace self-distillation degradation in mathematical reasoning to the suppression of *epistemic verbalization*: the model’s expression of uncertainty during reasoning. When self-distillation shortens reasoning traces, it disproportionately removes hedging phrases and uncertainty markers that serve as implicit “attention flags” for difficult sub-problems. The result is shorter but less calibrated reasoning, where the model confidently commits to flawed steps. This connects to the teacher uncertainty challenge in Section 7: an overconfident student produces unreliable self-play targets, and the saturation problem ultimately requires either external grounding or the internally generated PI mechanism of π -Play to overcome.

Across signal sources, from white-box logits through black-box APIs to self-distillation, a fundamental trade-off between signal density and autonomy governs the design space. White-box methods provide the richest supervision ($|V|$ -dimensional distributions at every token) but require same-organization deployment and co-location of teacher and student. Black-box methods sacrifice distributional information but operate across organizational boundaries, with recent methods (GAD, OVD) recovering surprisingly effective proxy signals.

Self-distillation eliminates external dependencies entirely but is bounded by the model’s pre-existing capabilities unless augmented by external verification or internally generated PI. This continuum is not merely descriptive: it predicts where future methods will have the most impact. The white-box extreme is well-explored (GKD, DistiLLM, DSKD are mature), while the self-distillation extreme still lacks principled convergence guarantees for complex reasoning. The greatest innovation potential lies at the boundaries: methods like ThinkTuning that blur the line between black-box feedback and RL, or methods like π -Play that blur the line between self-play and externally grounded verification.

6 Training Dynamics and Efficiency

Given an objective function (Section 4) and a signal source (Section 5), the final engineering decision is *how to stabilize and accelerate the on-policy training loop*. On-policy generation introduces unique optimization challenges absent from standard supervised fine-tuning: non-stationary data distributions (the student’s policy shifts during training, making older rollouts stale), gradient signal-to-noise ratio (SNR) collapse on hard prompts (where all rollouts fail and no useful gradient emerges), and the computational overhead of autoregressive student rollouts followed by teacher scoring (several times more expensive than off-policy training).

These challenges are not independent. SNR collapse on hard prompts wastes compute, motivating curriculum strategies that avoid such prompts. Non-stationarity invalidates cached teacher signals, motivating efficient online scoring. And the compute overhead of autoregressive generation creates a systems-level bottleneck that requires architectural solutions. The methods in this section address these challenges through three complementary mechanisms.

6.1 Token and Sample Weighting

Not all teacher supervision is equally reliable in the on-policy setting. The core problem is the *flawed prefix trap*: when a student generates an erroneous token early in a sequence, all subsequent teacher predictions are conditioned on this out-of-distribution prefix. Because the teacher has never been trained on such prefixes, its conditional distribution $p_T(\cdot|x, \hat{y}_{<t}^{\text{bad}})$ becomes noisy and unreliable. Naively matching this corrupted signal propagates errors rather than correcting them.

Teacher reliability filtering. TIP (Xu et al., 2026b) (Token Importance Profiling) provides a principled framework for token weighting by organizing importance along two axes: student entropy h_t and teacher-student divergence δ_t . Crossing these axes yields four quadrants with qualitatively distinct learning roles: high-entropy, high-divergence tokens (Q1) carry the dominant corrective signal, high-entropy, low-divergence tokens (Q2) indicate agreement on uncertainty, low-entropy, high-divergence tokens (Q3) represent *overconfident errors* where the student is certain but wrong, and low-entropy, low-divergence tokens (Q4) are genuinely mastered. The theoretical result shows that Q3 tokens are structurally invisible to any entropy-only weighting scheme, because no non-decreasing function of entropy with $f(0) = 0$ can distinguish them from Q4. TIP’s parameter-free Soft-OR score $s_t = \hat{h}_t + \hat{\delta}_t - \hat{h}_t \cdot \hat{\delta}_t$ recovers Q3 coverage while preserving Q1/Q2 sensitivity, achieving consistent improvements at 50% token retention across three model families with capacity gaps from $2\times$ to $9\times$.

SCOPE (Zheng et al., 2026) elevates this analysis from tokens to *rollouts*. Its dual-path architecture routes rollouts by correctness: incorrect trajectories receive teacher-perplexity-weighted KL distillation (down-weighting unreliable guidance on flawed prefixes), while correct trajectories receive student-perplexity-weighted MLE (concentrating reinforcement at the capability boundary). This addresses diversity collapse, the counterintuitive phenomenon where Pass@1 improves at the expense of Pass@k, yielding +5.5% over standard OPD.

SelecTKD (Huang et al., 2025) applies a propose-and-verify mechanism at the token level: the student proposes tokens that the teacher verifies through greedy Top-k or non-greedy Spec-k matching. Accepted tokens receive full loss while rejected tokens are masked or down-weighted, inducing an implicit curriculum quantified by Token Acceptance Rate (TAR). The

reasoning is that positions where teacher-student agreement fails indicate either genuine ambiguity or distributional divergence, and in neither case does the unfiltered gradient carry reliable information.

AdaSwitch (Peng et al., 2025) introduces a dynamic switching mechanism between pure exploration and guided distillation. Unlike static filtering that simply attenuates unreliable signals, AdaSwitch maintains a running estimate of the student’s cumulative prefix quality and switches between on-policy exploration (when the prefix is reasonable) and off-policy guidance (when the prefix has drifted too far). This single-switch design preserves semantic coherence (avoiding the jarring token-level alternation of prior mixing methods) while ensuring high-quality supervision at critical junctures, and is computationally simpler than continuous weighting while empirically achieving similar stability.

Sample-level weighting. Beyond token-level filtering, several methods weight entire samples based on their informativeness. The flawed prefix trap manifests most severely on *hard* prompts where the student’s pass rate approaches zero. On these prompts, nearly all rollouts contain early catastrophic errors, and the resulting teacher signals are dominated by noise. Methods that uniformly sample prompts waste most of their gradient budget on uninformative hard prompts or trivially correct easy prompts, with the productive learning concentrated on prompts at the boundary of the student’s competence.

Failure-mode analysis. Fu et al. (2026) provide a systematic empirical analysis of why sampled-token OPD is fragile in long-horizon settings. They identify three failure modes: (1) an imbalanced one-token signal that reduces distribution matching to a single sample, (2) unreliable teacher guidance on student-generated prefixes that deviate from the teacher’s training distribution, and (3) distortions caused by tokenizer or special-token mismatch. Their proposed fix, teacher top- K local support matching via truncated Reverse KL with top- p rollout sampling and special-token masking, yields more stable optimization across math reasoning and agentic training.

The token and sample weighting methods above operate *reactively*: they attenuate the loss signal *after* the student has already generated a potentially uninformative rollout. A more proactive approach asks: can we select prompts *before* generation to maximize the expected information gain per rollout? This motivates the curriculum methods below.

6.2 Curriculum and Difficulty Adaptation

The sample weighting problem motivates a more principled solution: *curriculum design* that actively selects prompts matching the student’s current competence level.

Competence-boundary sampling. PACED (Xu et al., 2026a) models prompt difficulty dynamically using a Beta-kernel distribution centered on the student’s current pass rate. The curriculum progressively shifts toward harder prompts as the student improves, while avoiding prompts where the pass rate is near zero (where gradient SNR vanishes) or near one (where the student has already mastered the content). This “frontier sampling” strategy concentrates the gradient budget on the narrow band of prompts where learning is most efficient.

The mathematical justification connects to the gradient SNR analysis. For a prompt with pass rate p , the expected gradient magnitude scales as $p(1 - p)$, which is maximized at $p = 0.5$ and vanishes at both extremes. PACED’s Beta-kernel sampling directly optimizes for this quantity, providing a theoretically grounded alternative to uniform prompt sampling. Concretely, PACED maintains a running estimate of per-prompt difficulty $\hat{p}_i$ (computed from the last m rollouts) and samples each prompt with probability proportional to $\text{Beta}(\hat{p}_i; \alpha, \beta)$ where (α, β) are hyperparameters controlling the width of the competence frontier. Early in training, wide kernels cast a broad net. As training converges, narrow kernels focus on the diminishing frontier of unsolved problems. This concentrates rollouts on problems in the productive learning range and reduces wasteful sampling on already-mastered or intractable problems, translating directly into compute savings proportional to the curriculum efficiency.

This SNR analysis has a deeper implication that extends beyond curriculum design: it explains *why* on-policy training naturally outperforms off-policy on reasoning tasks without explicit curriculum engineering. In off-policy settings, the problem difficulty distribution is fixed by the dataset. As the student improves, an increasing fraction of training data falls into the “too easy” zone where gradients are negligible, leading to diminishing returns. On-policy training, by contrast, automatically adjusts the effective difficulty because the student’s rollouts reflect its current capabilities, naturally generating sequences at the boundary of its competence. PACED makes this automatic adjustment explicit and optimal, but even naive on-policy training captures much of the benefit simply by sampling from p_θ rather than p_{data} .

Self-adjusting curricula. Several methods from earlier sections provide implicit curriculum mechanisms without explicit difficulty estimation: π -Play’s multi-agent framework (Section 5.3.2) automatically generates harder tasks as the student strengthens, PAINT (Tan & Hong, 2026) (Section 5.3.2) adapts its partial-solution disclosure based on student-teacher overlap, and PRISM (Wang et al., 2026d) (Section 5.2) shapes the policy landscape for subsequent RL through a structured multimodal warm-up. These complement PACED’s explicit difficulty estimation with emergent difficulty adaptation.

Dual-perspective curriculum. Uni-OPD (Hou et al., 2026) identifies two independent bottlenecks that limit OPD effectiveness and addresses them through complementary mechanisms. From the *student* perspective, it implements difficulty-aware and correctness-aware data balancing that promotes exploration of informative states during rollout sampling, extending PACED’s frontier-sampling insight from a single pass-rate metric to a dual-criterion that jointly considers problem difficulty and rollout correctness. From the *teacher* perspective, it addresses a subtler failure mode: even when the student generates informative rollouts, aggregated token-level supervision can become inconsistent with outcome-level reward signals, i.e., a trajectory that receives higher token-level teacher scores may actually produce a worse final answer. Uni-OPD’s outcome-guided margin calibration restores order consistency between correct and incorrect trajectories, ensuring that the token-level gradient direction aligns with the sequence-level quality ordering. This dual-perspective framework generalizes across LLMs and MLLMs (5 domains, 16 benchmarks) and accommodates both single-teacher and multi-teacher settings, suggesting that the curriculum and supervision reliability problems are largely orthogonal and can be solved independently.

Temporal curriculum for multi-turn distillation. While the above curricula operate along the *difficulty* axis (selecting which prompts to train on), TCOD (Wang et al., 2026c) introduces curriculum along the *temporal depth* axis, addressing a failure mode unique to multi-turn agent distillation. In standard OPD applied to multi-turn tasks, the student generates entire interaction trajectories and receives teacher supervision at every turn. However, TCOD identifies “Trajectory-Level KL Instability”: as conversation depth increases, KL divergence between student and teacher distributions escalates exponentially because errors in early turns shift the state distribution, making subsequent teacher supervision increasingly misaligned with the student’s actual trajectory context. The proposed temporal curriculum progressively expands the horizon of teacher supervision rather than applying it uniformly across all turns from the start. Two scheduling variants target complementary failure modes: Forward-to-Backward (F2B) begins supervision at early turns and progressively extends to later turns, allowing the student to first establish reliable early-turn behavior before tackling the compounding-error regime. Backward-to-Forward (B2F) uses the teacher to generate early turns (providing a clean state distribution) and applies supervision only at later turns, progressively requiring the student to handle earlier turns independently as training progresses. On ALFWorld, WebShop, and ScienceWorld, TCOD achieves gains of up to +18 points over vanilla multi-turn OPD, with the F2B variant showing particular strength on tasks where early-turn errors are most consequential. The temporal curriculum insight connects directly to the gradient SNR framework developed above: just as PACED identifies that prompts with near-zero pass rates provide negligible gradients, TCOD identifies that later turns in long trajectories suffer analogous gradient degradation because the student’s state has drifted too far from where the teacher’s supervision is meaningful.

Off-policy cold start. Li et al. (2026d) identify that OPD can fail catastrophically when the student’s initial policy is too far from the teacher’s distribution (the “thinking-pattern

mismatch” problem). Their proposed solution is an off-policy cold-start phase: a brief period of standard SFT on teacher-generated data that reduces the pattern gap before switching to on-policy training. This two-phase approach, off-policy warmup followed by on-policy refinement, has become the standard industrial pattern (Section 8).

Retaining knowledge during on-policy training. A complementary concern is that on-policy training can cause *catastrophic forgetting* of capabilities the student acquired during pre-training. Chen et al. (2025) (“Retaining by Doing”) demonstrate that on-policy data generation itself serves as an implicit rehearsal mechanism: by generating sequences from its own distribution, the student naturally revisits and reinforces its existing capabilities while learning new ones. This insight suggests that the on-policy generation step provides a dual benefit: it both exposes the student to its own error states (enabling correction) and rehearses its existing capabilities (preventing forgetting), offering a theoretical explanation for why on-policy methods empirically suffer less from catastrophic forgetting than sequential fine-tuning approaches.

Semantic bootstrapping. Semantic Soft Bootstrapping (Mitra & Ulukus, 2025) provides a different perspective on curriculum design: rather than adapting the *difficulty* of prompts, it adapts the *semantic granularity* of supervision. The method provides the model with both correct and incorrect rollouts as in-context exemplars that shape the next generation, progressively refining from coarse semantic alignment to fine-grained token-level matching. This achieves +10.6% on MATH-500 over GRPO, demonstrating that in-context self-supervision can complement gradient-based optimization.

The hybrid SFT+OPD pipeline. The off-policy cold start (Li et al. (2026d)) combined with on-policy refinement has become the de facto industrial recipe. Empirically, the optimal transition point from off-policy to on-policy training occurs when the student’s generation distribution achieves sufficient overlap with the teacher’s. Transitioning too early wastes on-policy compute on uninformative rollouts (the student is too weak for meaningful self-generation). Transitioning too late leaves the student stuck in the off-policy ceiling. Qwen3 (Yang et al., 2025) follows this two-phase approach, using off-policy distillation to establish basic reasoning and mode-switching capabilities before transitioning to on-policy distillation where the student generates its own sequences for logit-level alignment. DeepSeek-R1 (DeepSeek-AI et al., 2025) uses 100% off-policy (no transition), which works at extreme teacher capability but leaves performance on the table for reasoning tasks where the student could exceed the teacher through on-policy exploration.

6.3 Compute Optimization

OPD requires generating student rollouts *and* scoring them with the teacher at every training step, creating substantial compute overhead relative to off-policy SFT. Several methods target this bottleneck.

The cost breakdown for a typical white-box OPD step consists of

1. **Student rollout:** autoregressive generation of $B \times K$ completions (batch size B , K rollouts per prompt), memory-bound due to KV cache growth. In practice this component typically dominates wall-clock time, since generation is sequential and cannot be trivially parallelized across tokens.
2. **Teacher scoring:** forward pass through the teacher to obtain full-vocabulary logits on student-generated sequences, compute-bound. When the teacher is substantially larger than the student, this pass can rival or exceed the student’s backward pass in cost.
3. **Student update:** standard backward pass computing gradients of the distillation loss, dominated by optimizer state memory. This component is usually the cheapest of the three but sets the lower bound on memory usage.

Each component admits independent optimization, and the methods below attack different bottlenecks.

Prefix truncation. Fast OPD (Zhang et al., 2026a) observes that exposure bias is concentrated in the early tokens of a sequence, where errors compound most severely. It truncates

on-policy rollouts to a prefix of length k and reverts to off-policy KD for the remainder, achieving comparable quality at substantially reduced cost. The optimal truncation point k depends on the task: for mathematical reasoning, where errors cascade rapidly, short prefixes suffice. For open-ended generation, longer on-policy segments are needed.

Offline teacher caching. Lightning OPD (Wu et al., 2026) decouples student optimization from teacher inference entirely by precomputing teacher distributions into an offline memory bank and asynchronously refreshing them. When teacher distributions are *consistent* (i.e., the teacher’s output depends primarily on the prompt and only weakly on the specific student prefix), the cached distributions remain valid even as the student’s policy evolves. Lightning OPD establishes that offline distillation under teacher consistency can match online OPD at $4\times$ lower cost, substantially lowering the barrier for academic research.

These two methods expose a deeper structural point: the “on-policy” requirement is not binary but admits degrees of approximation. Fast OPD shows that partial rollouts preserve most of the distributional alignment benefit. Lightning OPD shows that stale teacher signals are acceptable when the student’s policy drift is bounded. Together, they define a *fidelity-efficiency frontier* that practitioners can navigate based on their compute budget, with full on-policy training at one extreme (maximum alignment, maximum cost) and fully offline SFT at the other (minimum cost, exposure bias ceiling).

Speculative knowledge distillation. Speculative KD (Xu et al., 2024a) adapts speculative decoding to the distillation setting: the student generates candidate tokens that the teacher *verifies and selectively replaces*, amortizing the teacher’s inference cost across multiple student tokens per teacher forward pass. DistillSpec (Zhou et al., 2023) inverts this: instead of using speculation to speed up training, it uses on-policy KD to improve the draft model for speculative decoding at *inference* time. The expected speedup:

$$E[S] = \frac{\mathbb{E}[K_{\text{accepted}}] + 1}{1 + c} \quad \text{where } c = \frac{\text{cost}(\text{student forward})}{\text{cost}(\text{teacher forward})} \quad (23)$$

The result is a virtuous cycle. Better distillation produces better draft models, which enable faster speculative decoding, which in turn enables more efficient distillation, progressively reducing the computational barrier.

GPU memory management. Beyond FLOPs, the most severe constraint for white-box OPD is GPU memory. Holding a 70B teacher alongside a 7B student requires the teacher’s weights (~ 140 GB in BF16), the student’s weights and optimizer states (~ 84 GB), and the full-vocabulary logits tensor $[B, T, |V|]$ for distillation. Peak memory can easily exceed an 8×80 GB H100 node. Practitioners alleviate this via: (1) *teacher quantization*, serving the teacher in FP8 or INT4 for a $2\text{--}4\times$ memory reduction at negligible precision loss, (2) *logit offloading*, immediately streaming logits to CPU RAM or retaining only the top- k entries (since 99% of the probability mass is typically concentrated in fewer than 100 tokens), and (3) *aggressive gradient checkpointing* to minimize student activation memory during the backward pass. Combining these techniques is essential for viable white-box OPD on standard clusters.

Concrete cost example. To ground these formulas, consider distilling a 70B teacher into a 7B student on $8 \times \text{H100}$ GPUs. Off-policy over 1B tokens: the teacher generates the dataset offline (~ 200 GPU-hours), the student trains for ~ 100 GPU-hours, totaling ~ 300 GPU-hours. On-policy over 1B tokens: each step requires (1) student generation ($\sim 3\times$ forward-pass cost due to autoregressive decoding), (2) teacher scoring (one 70B forward pass), and (3) student backward pass, yielding $\sim 1,200\text{--}1,500$ GPU-hours, a $4\text{--}5\times$ overhead. However, for reasoning tasks, on-policy methods uniformly surpass off-policy SFT, and the off-policy performance ceiling is strictly lower because static datasets cannot cover the combinatorial space of valid reasoning paths. This “ceiling gap” widens with task complexity, providing the strongest cost-benefit justification for on-policy methods.

7 Understanding OPD: Theory, Failure Modes, and Cost

The preceding sections addressed the mechanics of on-policy distillation: what to optimize (Section 4), where the signal comes from (Section 5), and how to stabilize training (Section 6).

We now turn to the equally important questions of *why* and *when*: under what conditions does OPD succeed, how does it fail, what theoretical frameworks unify the methods surveyed above, and when should practitioners invest in OPD versus simpler off-policy pipelines?

These four dimensions of understanding are not independent: they form a cumulative argument. Identifying *when* OPD works (Section 7.1) establishes the preconditions that the theoretical framework must explain. Cataloging *how* it fails (Section 7.2) motivates the specific design choices, adaptive divergences, curriculum weighting, and hybrid RL objectives, whose theoretical grounding Section 7.3 provides. Both the success conditions and the failure modes then inform the practical cost-benefit analysis in Section 7.4, which distills the theoretical insights into engineering guidelines. Answering these questions is essential for moving OPD from an empirical art toward a principled engineering discipline with predictable outcomes. The analysis below draws on both theoretical frameworks (imitation learning bounds, information geometry, RL convergence theory) and systematic empirical investigations that isolate individual design choices.

7.1 Success Conditions

Li et al. (2026d) provide the most systematic investigation of OPD training dynamics, identifying two necessary conditions for effective distillation. First, the student and teacher must share compatible reasoning patterns (operationalized as high overlap in their top- k token distributions): even a superior teacher fails to transfer knowledge if its thinking style is fundamentally mismatched with the student’s (e.g., a non-thinking teacher distilling into a thinking student), because low initial distributional overlap cannot be recovered through training alone. Second, the teacher must provide genuinely new capabilities beyond what the student has already acquired. When both models are trained on the same data and recipe, they converge to similar distributions at their respective scales, leaving the teacher with little transferable signal, as reverse distillation experiments show that same-family 1.5B and 7B teachers become distributionally indistinguishable from the student’s perspective.

At the token level, successful OPD is characterized by progressive alignment on *high-probability overlap tokens*, a small shared token set that concentrates the bulk of the probability mass. When these conditions fail, recovery strategies include off-policy cold start (SFT initialization that reduces the pattern gap) and teacher-aligned prompt selection. Critically, the quality of OPD’s dense supervision degrades systematically with trajectory depth, with instability originating at later tokens and propagating backward, raising fundamental questions about OPD’s applicability to long-horizon reasoning.

These findings point toward a general principle: OPD’s benefit scales with the *exploitable gap* between teacher and student. When this gap is too small (same-recipe models), the teacher offers no new information. When too large (thinking-pattern mismatch), the student cannot absorb the supervision. The productive regime lies in between, and identifying it is the central diagnostic challenge.

Diagnostic checklist. Based on the surveyed literature, we distill four pre-training diagnostics that practitioners should evaluate before committing to an OPD pipeline:

1. *Token overlap ratio*: Compute top- k overlap between teacher and student on a held-out set. If too low, apply off-policy cold start first.
2. *Pass rate on target prompts*: If the student cannot solve any problems in the target domain, OPD gradients will vanish. Use curriculum (PACED) or easier warm-up tasks.
3. *Teacher calibration*: Verify that the teacher’s confidence correlates with correctness on student-generated prefixes. Poorly calibrated teachers inject noise.
4. *Length stability*: Monitor output length during early training. Monotonic growth indicates the KL gradient asymmetry identified by Luo et al. (2026). Apply Stable-OPD corrections preemptively.

7.2 Failure Modes

Complementing the success conditions, a growing body of work catalogs the specific ways OPD can fail even when structural preconditions hold, as artifacts of the on-policy training dynamics themselves. Understanding these failure modes is essential for debugging OPD pipelines in practice, and each mode has a corresponding mitigation strategy developed in the methods sections above.

We organize failure modes by their *root cause* rather than their symptom, as multiple failure modes can produce similar surface-level degradation (e.g., accuracy collapse) through different mechanisms.

The flawed prefix trap. As detailed in Section 6.1, when the student generates an erroneous prefix, the teacher’s conditional distribution over subsequent tokens is poorly calibrated because the teacher was never trained on such out-of-distribution inputs. Fu et al. (2026) formally characterize three specific failure modes: (1) an imbalanced one-token signal that reduces distribution matching to a single sample, (2) unreliable teacher guidance on out-of-distribution student prefixes, and (3) tokenizer mismatch distortions. The theoretical analysis shows a fundamental bias-variance tradeoff: token-level OPD is biased relative to sequence-level Reverse KL but enjoys tighter worst-case variance bounds.

Two subtler failure modes compound the prefix trap. *Gradient SNR collapse* occurs when the student’s pass rate on a prompt approaches zero. In this state, all rollouts contain early errors, teacher signals are dominated by noise, and the gradient SNR vanishes. This explains why hard prompts yield no learning signal in standard OPD and motivates PACED’s competence-boundary curriculum (Section 6.2). *Epistemic suppression* (Kim et al., 2026) manifests in self-distillation. When the process shortens reasoning traces, it disproportionately removes hedging phrases and uncertainty markers that serve as implicit attention flags for difficult sub-problems. This produces shorter but less calibrated reasoning where the model confidently commits to flawed steps. This calibration degradation connects directly to the teacher uncertainty challenge: an overconfident student produces unreliable self-play targets, creating a vicious cycle of increasing certainty and decreasing reliability.

Self-play saturation (the Ouroboros problem). In self-distillation settings, the student optimizes against a target sharing its own inductive biases and architectural limitations, causing the hypothesis space to progressively collapse. If the model discovers a syntactic “hack” or a highly confident but flawed reasoning heuristic, no external signal penalizes it. The model self-reinforces this flawed trajectory, driving $p_\theta(y_{\text{flawed}}|x) \rightarrow 1$. Once entirely certain of its own hallucinations, gradients vanish, exploration ceases, and the policy is trapped. This is distinct from exposure bias (which arises from train-test distribution mismatch in off-policy settings). Saturation arises from the absence of distributional diversity in fully on-policy self-play, and is mathematically analogous to mode collapse in generative adversarial networks.

The precision-recall tradeoff. Cha & Cho (2025) formalize a core tension in distillation: as the student concentrates mass on high-quality outputs (improving precision), it necessarily reduces coverage of the teacher’s full output distribution (reducing recall). In the OPD setting, this manifests as the “diversity collapse” problem. Aggressive Reverse KL distillation produces a student that scores highly on Pass@1 (precision) but catastrophically on Pass@k (recall), because the student has collapsed onto a single reasoning strategy per prompt. On-policy generation can shift this tradeoff by allowing the student to explore its own distribution rather than being constrained to teacher-demonstrated paths, potentially improving recall without sacrificing precision. Temperature-scaled sampling during on-policy generation, as used in GKD and G-OPD, provides a direct control knob. Higher sampling temperatures encourage distributional exploration (increasing recall) at the cost of more noisy gradients (potentially reducing precision). This tradeoff is modulated by a single entropy-controlling parameter, providing practitioners with a principled axis for tuning distillation behavior to downstream requirements.

The calibration-capability gap. CaOPD (Zhang et al., 2026b) identifies a “Scaling Law of Miscalibration”. While OPD reliably improves task accuracy, it systematically traps models in severe overconfidence. The root cause is an information mismatch: teacher supervision

is formed under privileged context available during training (full reasoning traces, multiple samples), whereas the deployed model must report confidence using only its deployment-time context. By decoupling capability improvement from calibration degradation, CaOPD reveals that the distilled model becomes more capable but less aware of its own uncertainty boundaries. This finding has important implications for deployment. A distilled model that achieves higher benchmark scores but cannot reliably indicate when it might be wrong is arguably less safe than a weaker but better-calibrated baseline. The “illusion of certainty” connects to the saturation analysis above: both indicate that OPD can produce students that lose metacognitive capabilities (uncertainty awareness, epistemic verbalization) even as task-level performance improves.

Agentic collapse in multi-turn OPD. The preceding failure modes all assume a single-turn response. Extending OPD to multi-turn tool-using agents surfaces a qualitatively different failure family, in which the interaction between teacher dynamics and trajectory structure produces pathologies unseen in single-turn settings. TT-OPD (Jeong, 2026) diagnoses three such pathologies on Healthcare AI Gym, and each maps onto a distinct structural mismatch that other agentic OPD methods also confront from complementary angles. *First, teacher-dynamics collapse.* Periodic hard-copy teacher resets cause a KL collapse (divergence drops from 2.637 to 0.343 at every copy event), erasing the distillation gradient and driving accuracy monotonically downward. This is the multi-turn analogue of TCOD’s “Trajectory-Level KL Instability” (Section 6.2), but surfaced at the teacher-update granularity rather than the turn-depth granularity, and establishes that stable teacher dynamics (EMA rather than hard copy) are a prerequisite for any other structural fix. *Second, trajectory-structure erosion.* Even with EMA teachers that eliminate KL collapse, the multi-turn structure itself erodes: the student learns that verbose single-turn monologues maximize the sparse terminal reward more easily than coordinated tool-use sequences (turns drop from 7.82 to 5.52 per episode). This mirrors the reward-granularity mismatch that motivates Skill-SD’s skill-level decomposition and MAD-OPD’s step-level sampling (Section 8), indicating that sparse terminal rewards alone cannot sustain multi-turn structure regardless of which granularity is chosen. *Third, reward-hint runaway.* Adding outcome-conditioned teacher hints without length control triggers a response explosion, where positive hints reinforce ever-longer reasoning until responses saturate the context limit and accuracy collapses from 54.5% to 49.0%. This is the multi-turn extension of the epistemic-suppression phenomenon documented in Kim et al. (2026): both arise when informative supervision signals that are helpful *on average* are applied without regularizers on the shape of the student’s response. Taken together, these pathologies imply a general principle for agentic OPD: stable teacher dynamics, explicit regularizers on trajectory structure, and granularity-matched credit assignment are jointly necessary, and each existing method (TCOD, Skill-SD, MAD-OPD, TT-OPD) addresses a different combination of the three.

7.3 Unified Theoretical Perspectives

The success conditions and failure modes above share deeper mathematical roots than their diverse surface manifestations suggest. Several recent works demonstrate this common foundation.

The unified f -divergence framework of Wen et al. (2023) subsumes Forward KL, Reverse KL, JSD, and α -divergences as special cases parameterized by a single convexity function f . Since all these divergences can be expressed as expectations under the student’s on-policy distribution, the choice of divergence is fundamentally a regularization decision. The generator function f determines the implicit weighting of likelihood ratios $p_T(y)/p_\theta(y)$, with Forward KL up-weighting regions where the student underestimates the teacher (coverage) and Reverse KL up-weighting regions of overestimation (precision). Wu et al. (2024) refine this picture for discrete LLM distributions, demonstrating that under practical epoch budgets the mode-seeking/covering dichotomy is better understood through head-tail focus. Forward KL concentrates learning on the head of the teacher distribution while Reverse KL emphasizes the tail, explaining why adaptive methods that switch between divergences based on local geometry consistently outperform any fixed choice. At a more foundational level, Cha & Cho (2025) identify the minimal conditions under which a student can provably benefit from teacher supervision versus learning from data alone. The benefit scales with the

information gap between the teacher’s distribution and the data distribution as seen by the student, providing a theoretical foundation for the “exploitable gap” identified empirically by Li et al. (2026d). A complementary unification comes from Li et al. (2026b), who prove that Group-Relative Policy Optimization (GRPO) and self-distillation are mathematically equivalent under certain conditions. The preference signal in GRPO is implicitly a form of self-distillation against the model’s own best rollouts. This suggests that the choice between GRPO-style RL and explicit self-distillation is often a matter of implementation convenience rather than fundamental algorithmic difference.

A persistent practical concern is length inflation: OPD students’ outputs grow progressively longer during on-policy training. Luo et al. (2026) identify the root cause as an asymmetry in the KL gradient, where positive KL gradients (pushing toward teacher-preferred tokens) are stronger than negative ones (pulling away from dispreferred tokens), creating a net bias toward longer sequences. Their Stable-OPD framework introduces a reference divergence term anchoring the student’s length distribution to a pre-distillation baseline, combined with rollout mixing that blends on-policy student generations with off-policy teacher generations in a decaying ratio. These stabilization mechanisms achieve +7.2% over vanilla OPD by breaking the self-amplification cycle, and are composable with any divergence choice.

Taken together, the methods in this section address signal management at progressively larger scales. Token weighting (TIP, SelecTKD, AdaKD) handles within-sequence heterogeneity. Rollout routing (SCOPE) handles across-trajectory heterogeneity. Stability mechanisms (Stable-OPD) control temporal dynamics across the entire training run. Curriculum design (PACED) governs prompt-level selection. Because these four layers operate at orthogonal granularities (token, sequence, step, prompt), they compose without interference. One can select tokens by Soft-OR score within rollouts routed by quality within a training loop stabilized against length inflation across prompts sampled by curriculum difficulty, and the resulting efficiency gains are multiplicative rather than redundant.

G-OPD’s equivalence proof (Section 4.3) establishes that standard OPD is a special case of dense KL-constrained RL, bridging the distillation and RL communities and ensuring that advances in either field immediately transfer to the other. This equivalence extends naturally to Direct Preference Optimization (DPO). Under DPO’s closed-form solution, the optimal policy satisfies $\pi^*(y|x) \propto \pi_{\text{ref}}(y|x) \exp(r(y,x)/\beta)$. Substituting the teacher’s log-probability as the implicit reward ($r(y,x) = \log P_T(y|x)$) yields $\pi^*(y|x) \propto \pi_{\text{ref}}(y|x) \cdot P_T(y|x)^{1/\beta}$, which is the geometric mixture distribution targeted by interpolated methods like GKD with λ -mixing. DPO-based distillation methods (AlignDistil, ORPO-Distill) therefore implicitly optimize toward the same geometric mixture as token-level KL methods, differing only in their optimization trajectory (contrastive pairs vs. direct gradient descent), and are most useful when constructing preference pairs is cheaper than computing full teacher logits.

The unified KD+RL framework of Li et al. (2025) makes this complementarity precise by decomposing the hybrid gradient into a dense KD component (stable, analytically computable) and a Monte Carlo RL component (high variance, reward-driven). KD dampens variance in policy gradient estimation while RL prevents collapse onto suboptimal teacher modes, with the optimal KD-to-RL weighting ratio decreasing over training as the student’s policy stabilizes. Song et al. (2026) further show that textual feedback from a teacher can expand the effective capabilities of RL beyond what outcome-only rewards achieve, providing theoretical justification for the verbal feedback methods (Lion, OVD, ThinkTuning) surveyed in Section 5.2. Text feedback provides a denser reward signal than binary outcomes, enabling the student to learn from partial successes that binary verification would discard.

Together, these perspectives converge on a central insight. On-policy distillation, reinforcement learning, and preference optimization are not separate training approaches but rather points on a continuous spectrum parameterized by the density of supervision, the choice of divergence, and the source of the training signal.

7.4 On-Policy vs. Off-Policy: The DeepSeek-R1 Analysis

The theoretical frameworks above establish that on-policy training offers principled advantages. But theory alone cannot settle the question of when practitioners should invest in on-policy infrastructure versus relying on simpler off-policy pipelines.

The DeepSeek-R1 anomaly. DeepSeek-R1 (DeepSeek-AI et al., 2025) represents the most prominent off-policy distillation success, training students from 1.5B to 70B on $\sim 800K$ samples of long chain-of-thought reasoning traces via purely off-policy SFT. On AIME 2024 (pass@1), R1-Distill-Qwen-7B reaches 55.5%, and R1-Distill-Qwen-32B reaches 72.6%. Counterintuitively, off-policy distillation *decisively outperforms direct RL* for small-to-medium models: at the 32B scale, GRPO applied directly to Qwen2.5-32B-Base achieves only 47.0% on AIME 2024. Three factors explain this off-policy success: (1) the teacher is an exceptionally strong 671B MoE model providing dense coverage of the problem space, mitigating exposure bias; (2) the $\sim 800K$ traces include diverse reasoning strategies (backtracking, verification), exploring multiple paths per problem; and (3) student models are relatively small, making the effective complexity of the conditional distribution manageable for off-policy learning. This suggests that for small models, learning reasoning patterns (knowledge transfer) dominates matching generation characteristics (distributional alignment). On-policy becomes necessary as student capacity grows and diverges from training data.

Multi-teacher theoretical foundation. The industrial pattern of distilling from multiple specialized teachers (Qwen3, KAT-Coder-V2, Nemotron-Cascade 2) has an emerging theoretical justification. When a student distills from K specialized teachers $\{T_1, \dots, T_K\}$ each expert in domain $\mathcal{D}_k$, the resulting student approximates a *mixture-of-experts distribution* without requiring MoE architecture. Formally, the multi-teacher objective $\sum_{k=1}^K w_k D_{\text{KL}}(P_{T_k} \parallel P_\theta)$ produces a student that interpolates between teacher distributions, with the weights w_k controlling the relative emphasis. On-policy generation is critical here because the student must learn to *route* between reasoning strategies depending on input characteristics, a capability that static off-policy data cannot teach since the routing decision depends on the student’s internal state. This explains why ORBIT’s multi-budget fusion and KAT-Coder-V2’s domain consolidation both require on-policy training: the *conditional strategy selection* is itself a learned capability that emerges only through on-policy exploration.

MAD-OPD (Wang et al., 2026b) pushes the multi-teacher paradigm further by recasting the distillation teacher as a *deliberative collective*: multiple teacher models debate over the student’s on-policy state, and the debate process produces an emergent collective intelligence that surpasses any individual teacher’s capability ceiling. Rather than naively averaging teacher logits (which dilutes each teacher’s expertise), MAD-OPD weights each teacher’s contribution by its post-debate confidence, ensuring that the most knowledgeable teacher dominates at each token position. This confidence-weighted ensemble produces token-level supervision that transcends the single-teacher capability ceiling: when one teacher errs, the debate process concentrates weight on teachers that provide more coherent continuations. For agentic tasks where per-step errors compound across long trajectories, MAD-OPD introduces On-Policy Agentic Distillation (OPAD), which adds step-level sampling to stabilize training under multi-step error compounding. The method also derives a task-adaptive divergence principle: JSD for agentic stability (where bounded gradients prevent catastrophic policy swings) and Reverse KL for code generation (where mode-seeking preserves syntactic coherence). Across six teacher-student configurations spanning Qwen3 and Qwen3.5 (1.7B to 14B students, 8B to 32B teachers), MAD-OPD ranks first on all configurations. On the representative 14B+8B $\rightarrow$ 4B setting, it lifts the agentic average by +2.4% and code average by +3.7% over the stronger single-teacher OPD baseline. This result confirms that the single-teacher ceiling identified by Li et al. (2026d) is not an inherent limitation of OPD but rather an artifact of single-source supervision.

Distillation vs. direct RL: a formal comparison. The decision between knowledge distillation and direct RL (e.g., GRPO, PPO with outcome reward) is not binary but depends on three factors: (1) *teacher quality relative to the reward signal*, where distillation is preferred when the teacher provides richer per-token information than sparse outcome rewards can encode, (2) *student scale*, where smaller students ($\leq 7B$) benefit more from dense teacher

supervision because their limited capacity cannot efficiently explore reward landscapes, while larger students ($\geq 32B$) have sufficient capacity for RL exploration, and (3) *target ceiling*, where distillation is bounded by the teacher’s capability while RL can theoretically exceed any fixed teacher through exploration. The hybrid approaches surveyed in Section 4.3 (G-OPD, KDRL, RLAD) resolve this tension by combining both: using teacher logits as a dense baseline reward that reduces variance while allowing sparse outcome rewards to drive exploration beyond the teacher’s ceiling. Empirically, this combination dominates either approach alone across all student scales.

Why on-policy remains necessary. DDT (Zhang et al., 2026c) provides formal justification: the key factor driving RL’s generalization advantage is on-policy data generation, which keeps training aligned with the model’s evolving distribution. The off-policy ceiling, the maximum achievable performance regardless of data volume, is strictly lower because static datasets cannot cover the combinatorial space of valid reasoning paths. This ceiling gap widens with three factors: task complexity (more reasoning steps $\Rightarrow$ more paths to cover), output diversity requirements (creative tasks vs. math), and model capability (stronger students explore further from the training data).

The hybrid pipeline. Qwen3 (Yang et al., 2025) and MiMo-V2 (Xiaomi LLM-Core Team et al., 2026) operationalize this insight, combining off-policy cold-start with on-policy refinement. This two-phase pattern, off-policy SFT to establish a strong foundation followed by on-policy OPD or RL to close the remaining distribution gap, has emerged as the standard industrial recipe. The optimal transition point (when to switch from off-policy to on-policy) depends on the student’s initial capability: weaker students benefit more from extended off-policy warmup, while stronger students can transition earlier.

Compute-quality tradeoff. The expected compute cost for N tokens:

$$C_{\text{off}} \approx N \times (F_{\text{teacher}} + F_{\text{student}} + B_{\text{student}}) \quad (24)$$

$$C_{\text{on}} \approx N \times (G_{\text{student}} + \lambda F_{\text{teacher}} + F_{\text{student}} + B_{\text{student}}) \quad (25)$$

where F, B denote forward and backward FLOPs, G is the autoregressive generation cost, and $\lambda \in (0, 1]$ is the teacher supervision refresh rate. Because $G_{\text{student}} \gg F_{\text{student}}$, on-policy training is substantially more expensive. For generic knowledge transfer, this overhead is rarely justified. For reasoning, code generation, and complex mathematics, where the off-policy ceiling is low and the on-policy marginal return is high, the investment pays off decisively.

Let $\mathcal{U}(\theta, C)$ represent the student’s downstream utility given compute budget C . The constrained optimization is:

$$\max \mathcal{U}(\theta, C) \quad \text{subject to } C = \gamma C_{\text{on}} + (1 - \gamma) C_{\text{off}} \leq C_{\text{max}} \quad (26)$$

where γ is the fraction processed on-policy. For generic knowledge transfer, $\gamma \rightarrow 0$ suffices. For reasoning, $\frac{\partial \mathcal{U}}{\partial C_{\text{on}}} \gg \frac{\partial \mathcal{U}}{\partial C_{\text{off}}}$, justifying the compute multiplier. A natural hybrid curriculum begins with off-policy warmup ($\gamma = 0$) to establish latent representations, then progressively shifts toward $\gamma \rightarrow 1$ in later stages as the student’s distribution diverges from the static data.

8 Applications, Systems, and Emerging Domains

The preceding sections developed OPD from theory through methods to unified understanding. This section examines how these algorithmic advances translate into practice. The transition from academic prototypes to industrial deployment shows that the choice of OPD method is ultimately driven not by theoretical elegance but by practical constraints, including available compute, teacher access level, the need for multi-teacher coordination, system-level throughput bottlenecks, and domain-specific challenges such as cross-modal transfer and privacy. We organize industrial applications by their *deployment pattern* and emerging domains by the new challenges they introduce.

Table 2: Comprehensive comparison of on-policy distillation methods organized by primary contribution dimension.

Method	Year	Category	Divergence/Objective	Signal	Granularity	Key Innovation
<i>Objective: Fixed Divergences</i>						
GKD (Agarwal et al., 2023)	2024	Objective	F-KL / R-KL / JSD	White-box	Token	Unified OPD framework, Dagger for LLMs
MiniLLM (Gu et al., 2023)	2024	Objective	Reverse KL	White-box	Sequence	REINFORCE with teacher as reward
DistiLLM (Ko et al., 2024)	2024	Objective	Skew KL (SKL+SRKL)	White-box	Token	α -smoothing for KL stability
DistiLLM-2 (Ko et al., 2025)	2025	Objective	Contrastive SKL/SRKL	White-box	Token	Asymmetric loss per data source
KETCHUP (Fan et al., 2025)	2025	Objective	Reverse KL	White-box	Sequence	K-step truncated REINFORCE
Constrained (Zimmer et al., 2025)	2025	Objective	Constrained KL	White-box	Sequence	State-augmented CMDP
<i>Objective: Adaptive Divergences</i>						
AKL (Wu et al., 2024)	2025	Objective	Adaptive FKL+RKL	White-box	Token	Head/tail gap-weighted blending
ToDi (Jung et al., 2025)	2025	Objective	Log-ratio-weighted FKL/RKL	White-box	Token	Sigmoid per-token blending
Entropy-Aware (Jin et al., 2026)	2026	Objective	Continuous FKL+RKL blend	White-box	Token	Smooth entropy interpolation
<i>Objective: RL-Augmented</i>						
G-OPD (Yang et al., 2026c)	2026	Objective	KL-Constrained RL	White-box	Token/Seq	OPD $\equiv$ dense KL-RL, reward extrapolation
RLKD (Xu et al., 2025b)	2025	Objective	KD + Reward Model	White-box	Sequence	Structure-aware reward model
KDRL (Xu et al., 2025a)	2026	Objective	Joint KD + RL	White-box	Token/Seq	On-policy KL regularizer during RL
RLAD (Zhang et al., 2026b)	2026	Objective	Trust Region Ratio	White-box	Token/Seq	PPO-style selective teacher following
AlignDistil (Zhang et al., 2025a)	2025	Objective	DPO + Reverse DPO	White-box	Sequence	Synthetic preference from rollouts
SuperCorrect (Yang et al., 2024)	2025	Objective	Template + Cross-DPO	White-box	Sequence	Hierarchical thought scaffolding
SCoRe (Lyu et al., 2025)	2025	Objective	Earliest-error correction	White-box	Sequence	Root-cause error targeting
<i>Signal: White-Box Innovations</i>						
DSKD (Zhang et al., 2025b)	2025	Signal	Dual-Space KL	White-box	Token	Cross-vocabulary projection
Cross-Tok. KD (Boizard et al., 2024)	2025	Signal	Latent OT alignment	White-box	Token	Optimal transport for tokenizer mismatch
Delta-KD (Cao et al., 2025)	2025	Signal	Base-to-Instruct delta	White-box	Token	Signal isolation
PromptKD (Kim et al., 2024)	2024	Signal	Prompt-based elicitation	White-box	Token	Input-side distillation
TAID (Shing et al., 2025)	2025	Signal	Temporal target interpolation	White-box	Token	Progressive target revelation
MiniPLM (Gu et al., 2024)	2025	Signal	Pre-training KD	White-box	Token	OPD during pre-training
MAD-OPD (Wang et al., 2026b)	2026	Signal	Multi-agent debate ensemble	White-box	Token	Confidence-weighted multi-teacher
<i>Training Dynamics</i>						
TIP (Xu et al., 2026b)	2026	Dynamics	Soft-OR token weighting	White-box	Token	Entropy $\times$ divergence quadrant scoring
SCOPE (Zheng et al., 2026)	2026	Dynamics	Rollout routing	White-box	Token	Redirect on flawed prefix
SelectKD (Huang et al., 2025)	2025	Dynamics	Confidence filtering	White-box	Token	Top-1 probability threshold
AdaSwitch (Peng et al., 2025)	2025	Dynamics	Exploration/guidance switch	White-box	Token	Binary mode switching
PACED (Xu et al., 2026a)	2026	Dynamics	Beta-kernel curriculum	White-box	Sample	Frontier difficulty sampling
Fast OPD (Zhang et al., 2026a)	2026	Dynamics	Prefix truncation	White-box	Hybrid	Early-token focus
Lightning OPD (Wu et al., 2026)	2026	Dynamics	Offline caching	White-box	Token	$4\times$ cost reduction
Speculative KD (Xu et al., 2024a)	2025	Dynamics	Draft-verify	White-box	Block	Amortized teacher cost
Revisiting OPD (Fu et al., 2026)	2026	Dynamics	Top- p rollout + masking	White-box	Token	Empirical failure mode fixes
Stable-OPD (Luo et al., 2026)	2026	Dynamics	R-KL + reference div.	White-box	Token	Rollout mixing for stability
Veto (Jang et al., 2026)	2026	Dynamics	Geometric bridge KL	White-box	Token	Adaptive gradient veto
TCOD (Wang et al., 2026c)	2026	Dynamics	Temporal curriculum	White-box	Trajectory	Multi-turn KL stability
Uni-OPD (Hou et al., 2026)	2026	Dynamics	Dual-perspective data balancing	White-box (multi-teacher)	Token	Unified LLM+MLLM OPD
<i>Self-Distillation</i>						
SPIN (Chen et al., 2024)	2024	Self-Play	Self-play DPO	Self	Sequence	Iterative self-vs-reference game
IRIS (Liao et al., 2026)	2026	Self-Play	Interpolative Rényi self-play	Self	Sequence	Unifies SPIN/SPACE/SPIP
OPSD (Zhao et al., 2026b)	2026	Self (PI)	KL on GT-conditioned	Self	Token	Ground-truth as privileged info
CRISP (Sang et al., 2026)	2026	Self (PI)	Conciseness PI	Self	Token	57% token reduction, +9% accuracy
GATES (Stein et al., 2026)	2026	Self (PI)	Gated consensus KL	Self	Token	Document as PI, gated supervision
OPSDL (Zhang et al., 2026c)	2026	Self (PI)	Short-ctx $\rightarrow$ long-ctx	Self	Token	Long-context self-distillation
SD-ZERO (He et al., 2026)	2026	Self (EF)	Self-revision preference	Self + Verifier	Sequence	Binary reward $\rightarrow$ dense self-supervision
π -Play (Zhang et al., 2026g)	2026	Self (PI+SP)	Multi-agent co-evolution	Self	Token	Internally generated PI from self-play
SSD (Zhang et al., 2026d)	2026	Self (SP)	Temperature-sampled SFT	Self	Sequence	Minimalist self-play
SDPO (Hübner et al., 2026)	2026	Self (EF)	Textual feedback + DPO	Self + Verifier	Sequence	Credit assignment from outcomes
RLTF (Song et al., 2026)	2026	Self (EF)	Critique-conditioned	Self + Verifier	Sequence	Text feedback for self-play
SRPO (Li et al., 2026b)	2026	Self (EF)	GRPO + SDPO routing	Self + Verifier	Sequence	Sample-routed multi-objective
CoPD (Gu et al., 2026)	2026	Self (EF)	Co-evolving bidirectional OPD	Mutual (parallel)	Sequence	Multi-capability consolidation
PAINT (Tan & Hong, 2026)	2026	Self (PI)	Partial-solution masking	Self (re-score)	Token	Overlap-adaptive self-distillation
MSD (Qin et al., 2026)	2026	Self (PI)	Cross-lingual safety distill	Self (English PI)	Token	Multilingual safety alignment
GUI-SD (Zhang et al., 2026f)	2026	Self (PI)	Visual spatial PI for GUI	Self (Gaussian mask)	Token	Multimodal GUI grounding
PBSD (Yu et al., 2026)	2026	Self (PI)	Pref.-based reward-reg. KL	Self (ctx-augmented)	Sequence	DPO-style loss, preference margin
TT-OPD (Jeong, 2026)	2026	Self (PI)	Turn-level truncated KL	Self (EMA + outcome hints)	Turn	Multi-turn agentic OPD
<i>Black-Box</i>						
GAD (Ye et al., 2025)	2025	Signal	Adversarial matching	Black-box	Sequence	Discriminator as proxy reward
Lion (Jiang et al., 2023)	2023	Signal	Verbal feedback	Black-box	Sequence	NL critique curriculum
OVD (Xiong et al., 2026)	2026	Signal	Verbal scores (0-9)	Black-box	Sequence	Score-based trajectory matching
DAIL (Mendes et al., 2026)	2026	Signal	Mixed-policy decoding	Black-box	Sequence	Didactic-to-constructive learning
LUFFY (Yan et al., 2025)	2025	Signal	Mixed-policy GRPO	Off-policy + RL	Sequence	Importance-weighted off-policy
ORPO-Distill (Singh et al., 2025)	2025	Signal	Preference optimization	Black-box	Sequence	Teacher-ranked pairs
PRISM (Wang et al., 2026d)	2026	Signal	Black-box pre-alignment	Black-box (API)	Sequence	Multimodal OPD before RLVR

8.1 Industrial Deployment

Recent foundation models have increasingly incorporated OPD into their post-training pipelines, with three distinct deployment patterns emerging that align with the theoretical progression surveyed above.

Two-phase distillation pipelines. The most common industrial pattern combines off-policy cold-start with on-policy refinement. Qwen3 (Yang et al., 2025) employs strong-to-weak distillation where larger models (32B, 235B-A22B) provide logit-level supervision on student-generated on-policy sequences, with the student generating responses in either thinking or non-thinking mode. The central architectural choice is “mode fusion”: the student must learn to produce both short, direct answers (non-thinking mode) and extended chain-of-thought reasoning (thinking mode) by distilling from teachers operating in each mode independently. On-policy generation is essential here because the student’s mode-selection behavior (when to think vs. when to answer directly) is itself a learned policy that cannot be captured by static datasets. Qwen3 reports that on-policy distillation achieves substantially better performance than direct reinforcement learning at roughly one-tenth of the GPU hours, and further improves pass@64 on AIME benchmarks where reinforcement learning from the same off-policy checkpoint does not. Gemma 2 (Gemma Team et al., 2024) em-

Table 3: Representative experimental configurations of OPD methods across different application domains.

Method	Teacher	Student	Training Signal	Key Benchmarks
<i>Mathematical Reasoning</i>				
G-OPD (Yang et al., 2026c)	Qwen3-30B-A3B-Instruct	Qwen3-1.7B/4B	Dense logit + reward extrap.	MATH, GSM8K, Code
OPSD (Zhao et al., 2026b)	Self (GT-conditioned)	Qwen3-1.7B/4B/8B-Inst	GT-P1 self-distillation	AIME, HMMT
PACED (Xu et al., 2026a)	Qwen3-14B	Qwen3-8B	Beta-kernel curriculum	MATH-500, AIME
KDRL (Xu et al., 2025a)	Skywork-OR1-Math-7B	R1-Distill-Qwen-1.5B	Joint KD + RL	AIME, MATH
LUFFY (Yan et al., 2025)	DeepSeek-R1 (off-policy traces)	Qwen2.5-Math-7B/1.5B	Mixed-policy GRPO	AIME, AMC, MATH-500
SCoRe (Lyu et al., 2025)	Qwen2.5-72B-Inst	Qwen2.5-7B/3B, Llama-3.1-8B	Earliest-error correction	12 Agent benchmarks
<i>Instruction Following @ General</i>				
GKD (Agarwal et al., 2023)	T5-XL (3B)	T5-Small/Base	On-policy FKL/RKL/JSD	XSum, WMT
DistiLLM (Ko et al., 2024)	GPT-2 XL (1.5B)	GPT-2 (124M)	Skewed KL	ROUGE-L, Dolly
AlignDistil (Zhang et al., 2025a)	Qwen2.5-72B-Inst	Qwen2.5-1.5B-Inst	DPO + token-level KD	AlpacaEval, MT-Bench
<i>Industrial Scale</i>				
Qwen3 (Yang et al., 2025)	Qwen3-32B/235B-A22B	Qwen3-0.6B-14B	On-policy logit distillation	AIME, MATH, LiveCode
Gemma 2 (Gemma Team et al., 2024)	Gemma 2 27B	Gemma 2 9B / 2B	KD in pre-training	MMLU, HellaSwag
MiMo-V2 (Xiaomi LLM-Core Team et al., 2026)	Domain specialists	MiMo-V2-Fish (309B/15B MoE)	Multi-teacher logit + reward	AIME, MATH, GPQA
KAT-Coder-V2 (Li et al., 2026a)	5 domain specialists	Unified agentic coder	Specialize-then-Unify OPD	SWE-bench (79.6%)
Nemotron-Cascade 2 (Yang et al., 2026d)	Domain RL/SFT teachers	30B MoE (3B active)	Cascade RL + domain OPD	IMO, IOI, ICPC
DeepSeek-V4 (DeepSeek-AI, 2026)	10+ domain experts (1.6T)	DeepSeek-V4-Pro (1.6T MoE)	Full-vocab multi-teacher R-KL	AIME, LiveCode, HMMT
ORBIT (Liang et al., 2026)	Multi-mode RL experts	DeepSeek-Distill-Qwen-1.5B, Qwen3-4B, Openmath-Nemotron-7B	Multi-teacher mode fusion	AIME, GPQA, MMLU-Pro
<i>Multimodal @ Domain-Specific</i>				
VOLD (Boushelham et al., 2025)	Qwen3-8B (text-only)	Qwen2.5-VL-3B	GRPO + token-level KL	MMMU-Pro, MathVision
CORD (Hu et al., 2026)	Text-mode LLaLM	Audio-mode LLaLM	Cross-modal R-KL + GRPO	Audio QA/reasoning
Speculative KD (Xu et al., 2024a)	Gemma-7B-IT, Qwen2-7B	Gemma-2B, Qwen2-0.5B	Block-verified on-policy KL	Translation, Dialogue
Cross-Tok. KD (Boizard et al., 2024)	Llama-2-7B, Mistral-7B	OPT-350M, Pythia-160M-1B	Latent OT alignment	QA, Summarization
DP-OPD (Khudem et al., 2026)	GPT-2 Large 774M	DistilGPT-2 82M	GKD + DP-SCD (student only)	Video, BugPatent
Veto (Jiang et al., 2026)	Qwen2-7B-IT	Qwen2-0.5B-IT	Geometric bridge KL	Reasoning, Generation
TAID (Shing et al., 2025)	GPT-2 XL, Llama-3-8B	GPT-2 Base/Med, Llama-3-2B	Temporal interpolation	Summarization, QA
GUI-SD (Zhang et al., 2026f)	Self (visual P1)	Qwen3-VL-Inst-8B	Entropy-guided KL	ScreenSpot-v2/Pro, OSWorld
MAD-OPD (Wang et al., 2026b)	Multi-teacher debate	Qwen3/3.5 (1.7B-14B)	Confidence-weighted JSD/R-KL	Agentic, Code
MSD (Qu et al., 2026)	Self (English CoT P1)	Qwen2.5-7B, Llama-3-8B	DPSW cross-lingual distill	Multilingual Safety
Uni-OPD (Hou et al., 2026)	Multi-teacher (LLM+MLLM)	Qwen3 (1.7B-4B), Qwen3-VL-4B	Dual-perspective OPD	Math, Code, MLLM (16 benchmarks)
<i>Self-Distillation</i>				
SPIN (Chen et al., 2024)	Self (iter $t-1$)	Zephyr-7B-SFT	Self-play DPO	Open LLM, MT-Bench
CRISP (Sang et al., 2026)	Self (concise prompt)	Qwen3-1.7B	Pre-token R-KL	AIME, MATH-500
SD-ZERO (He et al., 2026)	Self (revision-conditioned)	Qwen3-4B-Inst, OLMo-3-7B	On-policy self-distill	AIME, MATH, Codeforces
π -Play (Zhang et al., 2026g)	Self (QCP-conditioned)	Qwen3-4B/8B	Multi-agent self-distill	NQ, TriviaQA, HotpotQA
SSD (Zhang et al., 2026d)	Self (temperature-sampled)	Qwen3-30B/Inst	On-policy SFT	LiveCodeBench v6
SDPO (Hilbert et al., 2026)	Self (textual feedback)	Qwen3-8B	Credit-assignment self-distill	Code, Math
SRPO (Li et al., 2026b)	Self (SDPO+GRPO)	Qwen3-8B	Sample-rotated dual-objective	AIME, MATH, Code
PBSD (Yu et al., 2026)	Self (ctx-augmented ref.)	Qwen3-1.7B/4B/8B-Inst	Pref.-based reward-reg. KL	AIME/24+/25, HMMT/25, Tool Use
TT-OPD (Jeong, 2026)	Self (EMA + outcome hints)	Qwen3.5-9B	Turn-level truncated KL	Healthcare AI Gym (18 benchmarks)
<i>Black-Box</i>				
GAD (Ye et al., 2025)	GPT-5-Chat (API only)	Qwen2.5-14B-Inst	Adversarial minimax	LMSYS-Chat, Dolly
Lian (Jiang et al., 2023)	ChatGPT (API only)	Llama-3-7B/8B	NL critique curriculum	BIG-Bench Hard, AGIEval
OVD (Xiong et al., 2026)	QwQ-32B / Env. Agent	Qwen2.5-3B, Llama-3.2-3B	Verbal scores (0-9)	Web QA, MATH

beds knowledge distillation directly into pre-training to bridge performance gaps between parameter tiers (27B→9B→2B), representing a more aggressive integration where OPD is not a post-training add-on but a core training ingredient from the start. MiMo-V2 (Xiaomi LLM-Core Team et al., 2026) combines distillation from multiple domain-specialized teachers with RL-based training, achieving frontier performance on mathematical reasoning with a 309B MoE model (15B active parameters).

OPD as model consolidation. A second pattern uses on-policy distillation for *merging* multiple specialized experts into a single deployable model. DeepSeek-V4 (DeepSeek-AI, 2026) entirely replaces the mixed RL stage of its predecessor (DeepSeek-V3.2) with pure multi-teacher OPD, consolidating more than ten domain-specific experts (mathematics, coding, agent, instruction-following) into a unified 1.6T-parameter model through full-vocabulary Reverse KL distillation. Computing the full $|V|$ -dimensional KL at each position (rather than the sampled-token approximation) provides more stable gradients when merging experts with diverse specializations, while hidden-state caching with on-the-fly logit reconstruction makes this feasible across trillion-parameter teachers (Section 4.1). KAT-Coder-V2 (Li et al., 2026a) decomposes agentic coding into five expert domains, each undergoing independent SFT and RL training, and consolidates them via on-policy distillation, achieving 79.6% on SWE-bench Verified. Nemotron-Cascade 2 (Yang et al., 2026d) applies the same principle to a 30B MoE model with only 3B activated parameters, achieving Gold Medal-level performance on IMO, IOI, and ICPC World Finals with $20\times$ fewer parameters than DeepSeek-V3.2-Speciale. CoPD (Gu et al., 2026) identifies a key limitation of sequential expert-then-distill pipelines: large behavioral pattern gaps between fully-trained teachers and untrained students prevent effective capability absorption. Their solution is *co-evolution*: running parallel RLVR expert training with interleaved bidirectional OPD, so experts serve as mutual teachers during their own training rather than after completion. This maintains consistent behavioral patterns among experts while preserving complementary knowledge, achieving all-in-one integration of text, image, and video reasoning capabilities that surpasses both mixed RLVR and sequential multi-teacher OPD (MOPD), and even domain-specific experts.

OPD for multi-budget reasoning. ORBIT (Liang et al., 2026) addresses the deployment challenge of variable reasoning depth: users need different compute budgets depending on query difficulty. It produces stage-wise expert policies through RLVR under progressively tighter context budgets ($L_{k+1} = L_k/2$), then fuses them into a single model through mode-

aware Reverse KL:

$$\mathcal{L}_{\text{fusion}}(\phi) = \mathbb{E}_{k \sim U(1,K)} \mathbb{E}_{\substack{q \sim \mathcal{D} \\ o \sim \pi_{\phi}(\cdot|q, p_k)}} \left[\sum_t \log \frac{\pi_{\phi}(o_t|q, p_k, o_{<t})}{\pi_{\theta_k}(o_t|q, p_k, o_{<t})} \right] \quad (27)$$

where p_k is the mode-specific prompt and $\{\pi_{\theta_k}\}$ are the frontier experts. Model merging initializes the student to mitigate the cold-start problem identified by Jang et al. (2026): without initialization near the expert manifold, the student’s on-policy rollouts rarely reach the teachers’ high-density regions, starving the distillation objective of useful signal. Across DeepSeek-Distill-Qwen-1.5B, Qwen3-4B, and Openmath-Nemotron-7B, ORBIT produces models that smoothly interpolate between four reasoning modes (2K to 32K token budgets) with competitive performance at each budget level, matching the initial model’s accuracy at the highest budget while providing significant token savings at lower budgets. The connection to the consolidation pattern above is instructive: where KAT-Coder-V2 and Nemotron-Cascade 2 merge experts specialized by *domain*, ORBIT merges experts specialized by *compute budget*, suggesting that on-policy distillation is emerging as a general-purpose multi-teacher fusion tool for any axis of model specialization.

Agentic distillation. Extending OPD from single-turn generation to multi-turn agentic tasks introduces a qualitatively new challenge: *error compounding*. In single-turn settings, a flawed token affects only subsequent tokens within the same sequence. In multi-turn agent settings, a flawed action at step t shifts the entire environmental state, causing all subsequent teacher supervision to operate on a distribution the teacher has never encountered. This error compounding problem motivates three complementary solutions that attack it at different granularities.

At the *trajectory level*, TCO (Wang et al., 2026c) prevents compounding by controlling the temporal depth of teacher supervision. Its temporal curriculum progressively expands the horizon: initially supervising only short interaction prefixes (where compounding is minimal) and gradually extending to full trajectories as the student’s early-turn reliability improves. This directly addresses the “Trajectory-Level KL Instability” that TCO identifies empirically, gaining up to +18 points over vanilla multi-turn OPD on ALFWorld, WebShop, and ScienceWorld.

At the *step level*, MAD-OPD’s OPAD variant (Wang et al., 2026b) offers an orthogonal decomposition: rather than limiting *which* steps receive supervision, it treats each agentic step as an independent distillation unit, breaking the error propagation chain by preventing gradients from flowing across step boundaries. This step-level isolation is complemented by the multi-teacher debate ensemble, which addresses a *second* agentic failure mode: single-teacher unreliability at later trajectory steps. When individual teachers err on complex sequential decisions, the collective intelligence of debating teachers provides more robust supervision than any single teacher can. Combined with task-adaptive divergence selection (JSD for agentic stability, Reverse KL for code), OPAD lifts the agentic average by +2.4% over single-teacher OPD.

At the *skill level*, OpenClaw-RL (Wang et al., 2026e) uses hindsight-guided OPD with a Process Reward Model that provides step-level credit assignment, training a Qwen3-4B agent across personal, terminal, GUI, and SWE environments. Skill-SD (Wang et al., 2026a) applies importance-weighted Reverse KL with dynamic teacher synchronization for skill-conditioned learning, achieving +14.0% over GRPO on AppWorld and +10.9% on Sokoban.

The progression from trajectory-level control (TCO) through step-level isolation (MAD-OPD/OPAD) to skill-level decomposition (Skill-SD) points to a general principle. Effective agentic distillation requires matching the granularity of the distillation unit to the granularity at which errors compound. Coarse-grained approaches (full-trajectory OPD) fail because compounding is local. Fine-grained approaches (token-level) waste compute on positions where the agent’s behavior is already correct. The optimal granularity appears to be the *decision boundary*, the step at which the agent commits to an action whose consequences are difficult to reverse.

These four patterns reflect a broader shift in how industry views OPD. The first pattern treats it as a quality refinement tool (making an existing pipeline produce better outputs).

The second treats it as an architectural simplification tool (collapsing a complex multi-expert system into a single deployable model). The third treats it as an inference-time control mechanism (enabling a single model to serve multiple latency-accuracy operating points). The fourth extends it to capability domains where traditional training fails (agentic, multi-turn, multi-modal). The convergence of all four patterns toward on-policy generation, rather than static dataset distillation, confirms that the theoretical advantages of distributional alignment translate directly into industrial value.

8.2 Emerging Domains

Multimodal OPD. Vision-language models face unique exposure bias challenges because multimodal interleaved generation must maintain coherence across modalities, and high-quality visual reasoning data is scarce compared to text. VOLD (Bousselham et al., 2025) shows that a text-only teacher can effectively guide a VLM student through on-policy distillation. The teacher provides reasoning supervision on student-generated visual reasoning traces without ever seeing the image, leveraging the text-based reasoning structure as a modality-agnostic scaffold. The critical finding is that an SFT cold-start phase is essential for cross-modal distributional alignment. Without it, the student’s on-policy rollouts in the visual reasoning space are too far from the teacher’s text-based distribution for distillation to converge. On MMMU-Pro, VOLD improves Qwen2.5-VL-3B from 27.1% to 32.0%, evidencing that cross-modal knowledge transfer through OPD can be surprisingly effective even when the teacher has no access to the visual modality.

Video-OPD (Li et al., 2026c) extends to temporal video grounding, where the student must learn to localize events within video sequences. X-OPD (Cao et al., 2026) crosses the text-speech boundary, distilling a text-mode Qwen3-Omni into its own speech mode by generating on-policy speech responses and aligning them with the model’s own text-mode reasoning. CORD (Hu et al., 2026) applies cross-modal self-distillation between text and audio modes of the same model using weighted Reverse KL:

$$\mathcal{L}_{\text{CORD}} = \mathbb{E}_{x \sim \mathcal{D}} \mathbb{E}_{\hat{y} \sim \pi_{\text{audio}}(\cdot|x)} \left[\sum_t w_t \cdot D_{\text{KL}}(\pi_{\text{audio}}(\cdot|x, \hat{y}_{<t}) \parallel \pi_{\text{text}}(\cdot|x, \hat{y}_{<t})) \right] \quad (28)$$

where the audio mode generates on-policy rollouts and the text mode provides token-level targets through Reverse KL, combined with GRPO for outcome reward maximization. CORD achieves state-of-the-art speech reasoning performance, demonstrating that different modality modes of the same model can serve as effective mutual teachers through on-policy interaction.

KEPO (Yang et al., 2026b) identifies a distinct failure mode in multimodal settings: sparse RLVR fails due to exploration collapse when initial solve rates are near zero. By conditioning preference optimization on teacher knowledge, KEPO provides the dense signal necessary to bootstrap capable VLMs.

Embodied intelligence and physical reasoning. Moving beyond language-only domains, OPD is increasingly applied to settings where the output space is continuous and errors are physically irreversible. VLA-OPD (Zhong et al., 2026) applies Reverse KL on self-generated robot trajectories, distilling expert demonstrations into a Vision-Language-Action student. Because the action space is continuous rather than discrete, the student must learn precise motor control from the teacher’s dense token-level supervision on self-generated trajectories. This significantly improves sample efficiency over RL and robustness over SFT. HY-Embodied-0.5 (Tencent Robotics X et al., 2026) uses multi-stage OPD to compress a 32B expert VLM into a 2B embodied MoT model for spatial reasoning, outperforming similarly sized models on 16 out of 22 benchmarks. OPD-AV (Afsharrad et al., 2026) extends to autonomous driving, applying GKD with $5\times$ compression for planning, distilling a Qwen3-8B SFT model into a 1.7B student on nuScenes. GUI-SD (Zhang et al., 2026f) occupies an intermediate position between text and physical interaction. The student generates click trajectories on graphical interfaces while a privileged version of itself (with access to bounding boxes and Gaussian soft masks) provides token-level KL supervision. Its entropy-guided distillation selectively weights tokens where teacher-student divergence is highest, achieving state-of-the-art on 6 GUI grounding benchmarks with Qwen3-VL-Instruct-8B.

The consistent finding across these physical and multimodal domains is that on-policy generation is even more critical than in text-only settings. The diversity of valid outputs (multiple correct grasping trajectories, multiple valid temporal localizations, multiple acceptable visual descriptions) makes off-policy data coverage impractical, and the consequence of distributional mismatch is not merely lower benchmark scores but physical failure.

Medical agents and tool-augmented clinical reasoning. Clinical decision making exposes a different flavor of emerging-domain challenge: the task itself is inherently multi-turn (history taking, test ordering, result interpretation, treatment selection), tool libraries are large and heterogeneous (medical knowledge bases, imaging interpreters, drug interaction checkers), and the terminal reward is extremely sparse relative to the episode length. Healthcare AI Gym (Jeong, 2026) provides the first gymnasium-compatible environment at this scale, covering 10 clinical domains, 3.6K+ tasks, 135 domain-specific tools, and 828K medical passages, and uses it to systematically study how OPD behaves in tool-augmented clinical reasoning. Beyond benchmarking, the study exposes an agentic-textual transfer gap: RL-based OPD reliably improves procedural competence on multi-turn benchmarks but does not translate into gains on text-only knowledge-recall benchmarks (MedMCQA, MMLU-Med), revealing that agentic training specializes the model for interactive reasoning at the cost of static parametric recall. The proposed TT-OPD method (discussed in Sections 5.3.1 and 7.2) reaches the best score on 10 of 18 benchmarks, with an average +3.9 percentage-point improvement over a non-RL baseline, while sustaining stable multi-turn structure throughout training. Taken together, Healthcare AI Gym suggests that high-stakes specialist domains are not merely *scaled-up* agentic environments but require distillation objectives that explicitly decouple procedural competence from parametric recall, a distinction absent in current single-domain agentic benchmarks.

Privacy-preserving OPD. DP-OPD (Khadem et al., 2026) injects differential privacy noise (DP-SGD) into the student’s gradients during on-policy training while keeping the teacher frozen. This proves that on-policy querying can extract utility while mathematically guaranteeing protection of the teacher’s training data, addressing a growing concern as distillation from proprietary models becomes standard practice. Without privacy guarantees, on-policy querying could memorize and reproduce private training examples from the teacher.

8.3 System-Level Integration

The compute optimization methods surveyed in Section 6.3 address algorithmic efficiency, but industrial-scale OPD also requires systems-level solutions that span the full hardware-software stack.

Production OPD pipelines must orchestrate three concurrent workloads, namely student rollout generation (autoregressive, memory-bound), teacher scoring (compute-bound forward pass), and student gradient update (compute-bound backward pass). Frameworks like OpenRLHF and veRL decompose these into separate process groups with distinct parallelism strategies. Teacher inference uses tensor parallelism across 4–8 GPUs for low latency, student generation uses pipeline parallelism for throughput, and the optimizer uses ZeRO-3 for memory efficiency. The main engineering challenge is synchronization. Since the student’s policy changes after each gradient step, all pending rollouts become stale. Asynchronous architectures that tolerate slight policy staleness can achieve substantially higher throughput at the cost of slightly noisier gradients. High-throughput serving engines (vLLM, TensorRT-LLM) can be repurposed for the generation phase, with continuous batching and PagedAttention enabling efficient rollout generation across large prompt pools. White-box OPD additionally requires exposing the full vocabulary logits rather than just the sampled token. The communication challenge is non-trivial. A 70B teacher with 7B student on 8×H100 must transmit ~ 16 GB of logit data per batch ($[B, T, |V|] \times 2$ bytes in BF16), feasible within a single node via NVLink (900 GB/s) but requiring careful tensor slicing or top- k sparsification for multi-node setups.

DeepSeek-V4 (DeepSeek-AI, 2026) provides the most detailed public account of full-vocabulary OPD systems engineering at trillion-parameter scale, addressing the specific challenges of distilling from 10+ teachers each comprising trillions of parameters. Rather than materializing the full $|V| > 100\text{K}$ logit tensor for each teacher (which is prohibitive

when distilling from 10+ teachers simultaneously), the framework caches only the last-layer hidden states in a centralized buffer. It reconstructs logits on-the-fly through the corresponding prediction head at training time, virtually eliminating memory pressure while incurring negligible recomputation cost. Training samples are ordered by teacher identity within each mini-batch, ensuring that at most one teacher’s prediction head resides in GPU memory at any time. All weight loading and offloading proceed asynchronously without blocking the critical path. The framework further integrates FP4 quantization-aware training during the OPD phase itself, quantizing MoE expert weights and attention QK activations so that the distilled model is natively adapted to deployment-time precision from the start rather than requiring post-hoc quantization.

8.4 When to Use On-Policy vs. Off-Policy

The theoretical framework above yields concrete engineering guidelines. Rather than treating on-policy training as a universal improvement, practitioners should evaluate whether their specific setting satisfies the conditions that make on-policy worth its compute overhead.

The choice between off-policy and on-policy distillation depends on a clear set of conditions. Off-policy SFT suffices when the target distribution is well-covered by the teacher’s beam-search outputs (instruction following, factual QA) and three conditions hold simultaneously: an exceptionally strong teacher ($>500B$), diverse reasoning traces, and a relatively small student ($\leq 70B$). DeepSeek-R1 (DeepSeek-AI et al., 2025) exemplifies this regime. The transition to on-policy becomes necessary when (1) the student exhibits clear exposure bias (performing well on teacher-style but not user-generated prompts), (2) the task involves multi-step reasoning where compounding errors degrade quality (Ross et al., 2011; Gudibande et al., 2023), or (3) the student needs to exceed the teacher via reward-guided exploration (Yang et al., 2026c). The formal criterion is whether the inference-time state visitation $d_{\pi_\theta}(s)$ diverges significantly from training-time $d_{\mathcal{D}}(s)$.

Within on-policy methods, the choice between logit-level and reward-level supervision depends on student scale. Small students ($<7B$) benefit from dense logit supervision (GKD, DistiLLM) to bootstrap competence, while larger students ($\geq 7B$) with reliable verifiers benefit from reward-guided OPD (KDRL (Xu et al., 2025a), G-OPD (Yang et al., 2026c)) that enables discovery beyond the teacher ceiling. The hybrid approach combining off-policy SFT warm-up with on-policy refinement consistently yields the best results across the surveyed literature (Qwen3 (Yang et al., 2025), MiMo-V2 (Xiaomi LLM-Core Team et al., 2026)). At a deeper level, OPD and RLHF share identical computational structures: on-policy rollouts, per-trajectory signals, policy gradient updates. The distinction is purely the signal source (teacher distribution vs. reward model preference). Methods like G-OPD and REOPOLD (Ko et al., 2026) formalize this equivalence, with practical consequence. Any RLHF infrastructure can be directly repurposed for OPD, explaining why frameworks like OpenRLHF serve both communities.

8.5 The Distillation Tax: Compute Budget Allocation

Based on the compute analysis in Section 6.3 and the staged pipelines described in recent industrial reports (DeepSeek-AI et al., 2025; Yang et al., 2025), a practical rule of thumb emerges for compute budget allocation. The most effective industrial pipelines follow a three-stage pattern:

1. **Off-policy warm-up** (majority of budget): Standard SFT on teacher-generated data provides cheap, high-bandwidth learning that establishes the student’s basic capabilities and aligns its distribution close enough to the teacher for effective on-policy training.
2. **On-policy logit distillation** (largest on-policy share): Token-level OPD with adaptive divergences (GKD, DistiLLM, ToDi) closes the distribution gap on the student’s own generation trajectories, addressing exposure bias where it matters most.

3. **Reward-guided refinement** (final smaller share): RL-augmented objectives (G-OPD, KDRL, RLAD) push the student beyond the teacher’s capability ceiling on reasoning tasks, using sparse outcome rewards to discover novel solution paths.

This staged approach front-loads cheap, high-bandwidth learning and reserves expensive on-policy compute for the final quality push. Qwen3 (Yang et al., 2025) exemplifies this pattern, with its four-stage pipeline (pre-train $\rightarrow$ SFT $\rightarrow$ RL $\rightarrow$ long-context) allocating progressively more compute to on-policy methods as training progresses. On-policy training is most valuable after off-policy warm-up has brought the student close to the teacher’s distribution, minimizing the wasted rollouts that occur when the student-teacher gap is too large (Section 7.1).

9 Open Problems and Future Directions

The methods surveyed above trace a clear trajectory, from fixed objectives to adaptive ones, from external teachers to self-generated signals, from single-turn generation to multi-turn trajectories. Extrapolating this trajectory suggests that the field is converging toward a paradigm where distillation, reinforcement learning, and alignment are not separate training stages but facets of a single continuous optimization process, one in which the model perpetually generates, evaluates, and refines its own behavior under evolving constraints. The open problems below are organized not as isolated challenges but as stepping stones toward this unified vision.

Distillation scaling laws. While parameter-scaling laws (Chinchilla (Hoffmann et al., 2022), Kaplan) are well-established for pre-training, no analogous framework exists for distillation. Busbridge et al. (2025) initiated the study of distillation-specific scaling, fitting parametric curves that reveal optimal teacher size grows sub-linearly with compute budget. However, the relationship between teacher-student size ratios, online rollout volume, divergence choice, and asymptotic performance remains largely unquantified. A natural conjecture is that the distillation loss follows a joint power-law:

$$L(N_S, N_T, D_{\text{on}}) = E + \frac{A}{N_S^\alpha} + \frac{B}{N_T^\beta} + \frac{C}{D_{\text{on}}^\gamma} + f(N_S, N_T) \quad (29)$$

where E is the irreducible task entropy and $f(N_S, N_T)$ models the capacity-gap interference. DeepSeek-R1 (DeepSeek-AI et al., 2025) provides empirical grounding: on AIME 2024, performance scales as 28.9% $\rightarrow$ 55.5% $\rightarrow$ 69.7% $\rightarrow$ 72.6% for student sizes 1.5B $\rightarrow$ 7B $\rightarrow$ 14B $\rightarrow$ 32B, with the steepest gain between 1.5B and 7B (26.6% absolute) and the 14B $\rightarrow$ 32B jump yielding only 2.9%. This suggests that α (student scale) exhibits rapid diminishing returns while teacher capacity dominates. Qwen3 (Yang et al., 2025) further suggests that $f(N_S, N_T)$ is non-trivial: distilling from multiple specialized teachers yields better scaling than from a single monolithic teacher of equivalent total parameters. Establishing such scaling laws would transform OPD from an empirical art to a predictable engineering discipline.

Uncertainty-aware feedback. Even with perfect scaling laws, a second foundational gap remains. Teachers currently provide point-estimate probabilities. When the teacher itself is uncertain about a token, its logits carry little useful information, yet the student treats all teacher signals equally. Future OPD frameworks must incorporate the teacher’s *epistemic uncertainty*, allowing the student to discount feedback on queries where the teacher is guessing. Process reward models (Lightman et al., 2023) provide a potential path: by scoring each reasoning step independently, they could identify precisely where teacher supervision is reliable versus speculative. The connection to the failure-mode analysis of Section 7.2 is direct: the flawed prefix trap is at its core a problem of unrecognized teacher uncertainty, and explicitly modeling this uncertainty would provide a principled solution. Concretely, one could augment the OPD objective with a teacher confidence weight $c_t = 1 - H(p_T(\cdot|x, y_{<t})) / \log |V|$, suppressing the gradient at positions where the teacher’s entropy approaches maximum. TIP (Xu et al., 2026b) provides empirical support for this direction, demonstrating that teacher-student divergence-based filtering outperforms entropy-only schemes. The next step is to extend this to *predictive* uncertainty: rather than measuring the teacher’s entropy on the student’s current prefix, estimate what the teacher’s

reliability *would be* several tokens ahead, enabling the student to avoid committing to reasoning paths that will lead to regions of teacher incompetence.

Agent-level, continual, and lifelong distillation. The uncertainty problem intensifies dramatically when distillation extends beyond single-turn generation. Current OPD focuses on single-turn generation. Extending to multi-turn agentic settings requires new credit assignment mechanisms, as the student must learn long-horizon tool use, environmental state tracking, and error recovery across entire interaction trajectories. OpenClaw-RL (Wang et al., 2026e), Skill-SD (Wang et al., 2026a), TCOD (Wang et al., 2026c), and MAD-OPD’s OPAD variant (Wang et al., 2026b) represent early steps, but the systematic degradation of teacher supervision with trajectory depth (Li et al., 2026d) remains a hard open problem. MAD-OPD’s step-level sampling strategy offers a partial mitigation by treating each agentic step as an independent distillation unit rather than propagating errors across the full trajectory, while TCOD’s temporal curriculum controls how much of the trajectory receives teacher supervision at each training stage. Together, these methods suggest that the multi-turn distillation frontier requires *both* temporal decomposition (breaking trajectories into manageable units) and progressive exposure (gradually increasing horizon complexity). Three unsolved sub-problems define this frontier. *First, environment non-stationarity.* Agentic environments change in response to actions, making direct trajectory comparison meaningless unless the teacher provides counterfactual evaluations conditioned on the student’s actual state. *Second, tool-use combinatorics.* Modern agent frameworks expose dozens of tools with structured argument schemas, suggesting distillation may need to operate at the tool-call level rather than individual tokens, with credit assignment mechanisms attributing trajectory success to specific tool selections. *Third, safety-critical exploration.* A single incorrect file write in coding agents or misguided click in web-browsing agents can trigger irreversible actions, requiring safety constraints that prevent exploring catastrophically dangerous action sequences. Complementarily, production models undergo repeated fine-tuning cycles (safety patches, capability updates), raising the question of how distillation objectives should adapt when the teacher itself is being updated. SDFT (Shenfeld et al., 2026) and OEL (Ye et al., 2026a) provide initial answers, but *lifelong distillation*, re-alignment without catastrophic forgetting, without retraining from scratch, and without accumulating distributional drift, connects to continual learning with the added complication that both teacher and student distributions are non-stationary.

Efficiency frontiers. The agentic and multi-turn settings above amplify what is already the central systems bottleneck of OPD. The substantial compute overhead of on-policy training remains a barrier. While Fast OPD, Lightning OPD, and Speculative KD have made progress, the theoretical minimum cost of on-policy distillation (the information-theoretic lower bound on how much on-policy data is needed to achieve a given quality level) is unknown. A promising underexplored direction is *selective teacher inference*: MiniPLM (Gu et al., 2024) shows that selecting training instances based on the log-probability discrepancy between teacher and a reference model (“Difference Sampling”) substantially improves data efficiency under off-policy KD. Transplanting this principle to on-policy rollouts, using teacher-reference divergence to prioritize which student-generated sequences deserve dense teacher feedback, could yield significant compute savings by avoiding expensive teacher inference on uninformative rollouts where the student has already converged.

Latent-space and cross-modal distillation. Efficiency improvements address the *cost* of OPD, but a separate limitation constrains its *scope*. Current OPD operates exclusively in vocabulary space, where cross-architecture alignment requires expensive projections (DSKD, Cross-Tokenizer KD). A more radical approach would distill in a *shared latent space* bypassing the vocabulary bottleneck entirely, enabling distillation between architecturally dissimilar models that share no structural overlap. The extension to multimodal settings raises additional open questions: How does exposure bias manifest when multiple modalities must maintain coherence? What are the optimal divergence choices when teacher and student operate in different modality spaces? Can the unified f -divergence framework be extended to handle continuous signal spaces (images, audio) alongside discrete tokens? VOLD, X-OPD, and CORD provide empirical starting points, but the theoretical foundations for cross-modal OPD remain to be established.

Privacy and evaluation methodology. As OPD becomes more powerful and more widely deployed, questions of trust, both in the training process and in its evaluation, grow correspondingly urgent. DP-OPD (Khadem et al., 2026) provides the first principled framework for differentially private distillation, with an asymmetric design applying DP-SGD only to the student while keeping the teacher frozen. The on-policy formulation is well-suited to the DP setting because training on self-generated prefixes reduces compounding errors from DP noise. Open questions include scaling DP-OPD to reasoning-capable LLMs and integrating DP with self-distillation. On the evaluation front, Fu et al. (2026) demonstrate that token-level OPD can appear successful on standard benchmarks while failing on distribution-shifted prompts, highlighting a gap between benchmark performance and true generalization. The precision-recall framework of Cha & Cho (2025) shows distillation induces a deep trade-off between sample precision and distributional coverage, suggesting that future evaluation must probe whether the student has learned underlying causal mechanisms rather than superficial correlations.

Closing the distillation-RL loop. The open problems above, scaling, uncertainty, agents, efficiency, cross-modal transfer, privacy, are individually significant, but they share a common resolution pathway. Distillation and RL are historically treated as separate, linearly staged processes. Static distillation saturates when the student exhausts the teacher’s knowledge, while pure RL diverges when reward signals are sparse. Chen et al. (2025) show that RL retains more pre-training capabilities than SFT because on-policy rollouts maintain distributional proximity to the student’s prior. KDRL (Xu et al., 2025a) jointly optimizes KD and RL, preventing the catastrophic forgetting that plagues sequential pipelines. RE-OPOLD (Ko et al., 2026) operationalizes the unification, with its relaxed on-policy framework combining dense KD gradients for early-stage stability with RL-style reward signals for late-stage exploration. CoPD (Gu et al., 2026) shows that the sequential paradigm (train experts first, then distill) can be replaced entirely by *co-evolutionary* training where RLVR and bidirectional OPD are interleaved (Section 8.1), maintaining behavioral proximity that enables continuous knowledge absorption rather than post-hoc transfer. This co-evolution principle suggests that the ultimate distillation-RL unification is not alternation between objectives but *simultaneous* optimization where distillation and RL operate as complementary forces throughout training. Principled methods for alternating between objectives, determining when to switch, and ensuring that RL-discovered capabilities are not overwritten during subsequent distillation phases, remain the ultimate algorithmic frontier.

Toward self-improving systems. The logical endpoint of the trajectories surveyed here, from external teachers to self-distillation, from static datasets to on-policy generation, from single-shot training to iterative refinement, is a system that teaches itself continuously without human intervention. π -Play (Zhang et al., 2026g) and SSD (Zhang et al., 2026d) provide early existence proofs: models that improve through self-generated curricula and self-filtered training data. The theoretical ceiling of such systems, whether they can exceed the capability of any fixed teacher given sufficient compute and environmental grounding, connects to deep questions about the limits of self-play in imperfect-information games. The saturation analysis of Section 7.2 identifies the boundary conditions: pure self-play converges to the model’s own prior distribution unless grounded by external verification or internally generated privileged information. Breaking this ceiling without access to a stronger oracle, achieving genuine capability *creation* rather than mere capability *redistribution*, remains perhaps the deepest open question at the intersection of distillation, RL, and machine learning theory.

10 Conclusion

This survey has systematically examined on-policy distillation for large language models, synthesizing methods that span foundational formulations, algorithmic innovations, theoretical analyses, and industrial deployments. We organized this rapidly growing literature around a practitioner’s decision chain rather than descriptive categories, tracing three fundamental design axes. *Objective function* design progresses from fixed divergences through adaptive routing to RL-augmented objectives that break the teacher ceiling. *Signal source* architecture spans from dense white-box logits through black-box API access to self-distillation that

eliminates the external teacher entirely. *Training dynamics* encompasses token weighting, curriculum adaptation, and compute optimization.

Key Findings. Across the methods surveyed, three patterns recur consistently. *First*, shifting from off-policy to on-policy training distributions, from $y \sim p_{\text{data}}$ to $y \sim p_{\theta}$, is a consistently impactful design choice, yielding meaningful accuracy gains across mathematical reasoning, code generation, and instruction following (Tables 2 and 3). The improvement stems from eliminating exposure bias, as the student learns to recover from its own errors rather than memorizing idealized trajectories, with the performance gap widening for longer reasoning chains where error compounding is most severe. *Second*, divergence selection is not one-size-fits-all but must be adapted to both task and token position. Reverse KL excels at reasoning tasks where mode-seeking prevents hallucination, while Forward KL preserves the diversity needed for open-ended generation. Adaptive methods such as ToDi (Jung et al., 2025) and Entropy-Aware OPD (Jin et al., 2026) that dynamically select divergences based on local distributional geometry represent the current frontier. *Third*, the boundary between distillation and reinforcement learning is rapidly dissolving. G-OPD (Yang et al., 2026c), RLAD (Zhang et al., 2026h), and REOPOLD (Ko et al., 2026) demonstrate that the optimal training signal combines dense teacher supervision with sparse outcome rewards, with KD providing gradient stability while RL enables exploration beyond the teacher’s capability ceiling. The unification is not merely conceptual but provides a shared toolkit (trust regions, advantage estimation, policy gradient variance reduction) that benefits both communities.

Practical Takeaways. With white-box teacher access, token-level methods (GKD (Agarwal et al., 2023), DistiLLM (Ko et al., 2024)) offer the best quality-compute tradeoff for general instruction following. For reasoning-intensive tasks, sequence-level methods (MiniLLM (Gu et al., 2023)) or hybrid approaches (Fast OPD (Zhang et al., 2026a), PACED (Xu et al., 2026a), Lightning OPD (Wu et al., 2026)) are preferable despite higher variance. With only API access, GAD (Ye et al., 2025) and OVD (Xiong et al., 2026) enable effective on-policy learning through adversarial and verbal formulations, respectively. Self-distillation methods (SPIN (Chen et al., 2024), OPSD (Zhao et al., 2026b), SD-ZERO (He et al., 2026)) eliminate the need for a separate teacher entirely, making them attractive under resource constraints. The substantial compute overhead of on-policy generation can be reduced via speculative decoding (Xu et al., 2024a), prefix truncation (Zhang et al., 2026a), or offline precomputation (Wu et al., 2026).

Looking Ahead. The trajectory from off-policy imitation to on-policy self-correction mirrors a broader shift in how we think about machine learning itself. Classical supervised learning assumes a fixed target distribution, but on-policy distillation acknowledges that the learner’s distribution is a moving target that must be tracked in real time. The methods surveyed here have progressively relaxed every assumption that once defined distillation as a narrow compression technique. Fixed objectives gave way to adaptive ones. External teachers gave way to self-generated signals. Single-turn optimization gave way to multi-turn trajectory learning. The logical endpoint of these trends is not a better distillation algorithm but a fundamentally new training paradigm, one where models continuously generate, evaluate, and improve their own behavior throughout their entire lifecycle. The absence of distillation scaling laws, the unsolved problem of teacher uncertainty quantification, and the challenge of lifelong adaptation without catastrophic forgetting stand as the primary barriers between the current state of the art and this vision. As LLMs evolve from static text generators into interactive reasoning agents that learn from every deployment interaction, the principles of on-policy alignment surveyed here will transition from an optional training enhancement to an architectural necessity.

Limitations. This survey focuses exclusively on methods that involve on-policy generation from the student during training. We deliberately exclude general knowledge distillation (e.g., feature-based, attention transfer), model compression techniques orthogonal to the training paradigm (pruning, quantization), and methods that use student-generated data only at inference time (self-consistency, majority voting). Our coverage is current through April 2026. Given the field’s rapid pace (approximately 8–10 new OPD papers per month),

some concurrent work may be absent. Additionally, our practitioner decision tree reflects current best practices and hardware constraints. As compute costs decrease and training frameworks mature, the cost-benefit calculus will shift toward more aggressive on-policy methods.

Reproducibility challenges. A significant concern across the OPD literature is the difficulty of fair comparison. Methods are evaluated on different base models, different training compute budgets, different benchmark versions (e.g., MATH-500 vs. full MATH), and with different numbers of rollouts per prompt. Few papers control for all these variables simultaneously, making cross-method comparison unreliable from published numbers alone. Our Tables 2 and 3 report original-paper results rather than controlled reproductions, and readers should interpret cross-row comparisons with appropriate caution. We advocate for standardized OPD benchmarking protocols that fix the base model, compute budget, and evaluation suite, analogous to what HELM (Liang et al., 2022) provides for general LLM evaluation.

Broader impact. OPD has immediate implications for AI accessibility and safety.

On the accessibility front, effective distillation enables smaller, more efficient models that can run on consumer hardware, democratizing access to advanced reasoning capabilities that would otherwise require expensive API access to frontier models. The self-distillation methods surveyed here (OPSD, SD-ZERO, SSD) stand out in this regard, as they enable capability improvement without any external teacher, allowing resource-constrained researchers and developers to iterate rapidly.

On the safety front, OPD introduces both risks and mitigations. The risk is that effective distillation of frontier capabilities lowers barriers to misuse. The mitigation is that the teacher retains a supervisory role during training, providing a natural point for injecting safety constraints, alignment objectives, and capability boundaries. MSD (Qin et al., 2026) provides a concrete instantiation of safety-aware OPD. By using the same model’s English-prompted reasoning as a teacher for its low-resource-language student, MSD transfers safety alignment from high-resource to low-resource languages through on-policy self-distillation without requiring any target-language safety data. Its Dual-Perspective Safety Weighting (DPSW) adaptively upweights safety-critical tokens by combining teacher confidence (high when the teacher recognizes a safety boundary) with student disagreement (high when the student would produce an unsafe response), concentrating the distillation gradient precisely on tokens that determine whether a response is safe or harmful. The result generalizes to unseen languages and more challenging jailbreak attacks, demonstrating that OPD can serve as a scalable mechanism for multilingual safety alignment. As the field matures, we expect safety-aware OPD, where the teacher not only transfers knowledge but also enforces alignment properties during the interactive training loop, to become a critical research direction.

On the environmental front, OPD’s compute overhead (4–5× over off-policy SFT) raises sustainability concerns at industrial scale. However, the resulting smaller, more capable students reduce downstream inference costs by orders of magnitude, and the net carbon footprint over a model’s lifetime is typically lower when amortized across billions of inference calls.

References

- Amirhossein Afsharrad, Amirhesam Abedsoltan, Ahmadreza Moradipari, and Sanjay Lall. On-Policy Distillation of Language Models for Autonomous Vehicle Motion Planning. *arXiv preprint arXiv:2604.07944*, 2026. URL <https://arxiv.org/abs/2604.07944>.
- Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos, Matthieu Geist, and Olivier Bachem. On-Policy Distillation of Language Models: Learning from Self-Generated Mistakes. *Proceedings of ICLR*, 2023. URL <https://arxiv.org/abs/2306.13649>.

- Nicolas Boizard, Kevin El Haddad, Céline Hudelot, and Pierre Colombo. Towards Cross-Tokenizer Distillation: the Universal Logit Distillation Loss for LLMs. *Transactions on Machine Learning Research*, 2024. URL <https://arxiv.org/abs/2402.12030>.
- Walid Bousselham, Hilde Kuehne, and Cordelia Schmid. VOLD: Reasoning Transfer from LLMs to Vision-Language Models via On-Policy Distillation. *arXiv preprint arXiv:2510.23497*, 2025. URL <https://arxiv.org/abs/2510.23497>.
- Dan Busbridge, Amitis Shidani, Floris Weers, Jason Ramapuram, Etai Littwin, and Russ Webb. Distillation Scaling Laws. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2025. URL <https://arxiv.org/abs/2502.08606>.
- Yuang Cai and Yuyu Yuan. $\mathcal{X}$ -KD: General Experiential Knowledge Distillation for Large Language Models. *arXiv preprint arXiv:2602.12674*, 2026. URL <https://arxiv.org/abs/2602.12674>.
- Di Cao, Dongjie Fu, Hai Yu, Siqi Zheng, Xu Tan, and Tao Jin. X-OPD: Cross-Modal On-Policy Distillation for Capability Alignment in Speech LLMs. *arXiv preprint arXiv:2603.24596*, 2026. URL <https://arxiv.org/abs/2603.24596>.
- Yihan Cao, Yanbin Kang, Zhengming Xing, and Ruijie Jiang. Delta Knowledge Distillation for Large Language Models. *arXiv preprint arXiv:2509.14526*, 2025. URL <https://arxiv.org/abs/2509.14526>.
- Sungmin Cha and Kyunghyun Cho. Why Knowledge Distillation Works in Generative Models: A Minimal Working Explanation. *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. URL <https://arxiv.org/abs/2505.13111>.
- Howard Chen, Noam Razin, Karthik Narasimhan, and Danqi Chen. Retaining by Doing: The Role of On-Policy Data in Mitigating Forgetting. *arXiv preprint arXiv:2510.18874*, 2025. URL <https://arxiv.org/abs/2510.18874>.
- Zixiang Chen, Yihe Deng, Huizhuo Yuan, Kaixuan Ji, and Quanquan Gu. Self-Play Fine-Tuning Converts Weak Language Models to Strong Language Models. *Proceedings of ICML*, 2024. URL <https://arxiv.org/abs/2401.01335>.
- DeepSeek-AI. DeepSeek-V4: Towards highly efficient million-token context intelligence. Technical report, DeepSeek, 2026. URL https://huggingface.co/deepseek-ai/DeepSeek-V4-Pro/blob/main/DeepSeek_V4.pdf.
- DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, Bing Xue, Bingxuan Wang, Bochao Wu, Bei Feng, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Han Bao, Hanwei Xu, Haocheng Wang, Honghui Ding, Huajian Xin, Huazuo Gao, Hui Qu, Hui Li, Jianzhong Guo, Jia Shi Li, Jiawei Wang, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, J. L. Cai, Jiaqi Ni, Jian Liang, Jin Chen, Kai Dong, Kai Hu, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Liang Zhao, Litong Wang, Liyue Zhang, Lei Xu, Leyi Xia, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Meng Li, Miaojuan Wang, Mingming Li, Ning Tian, Panpan Huang, Peng Zhang, Qiancheng Wang, Qinyu Chen, Qiushi Du, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, R. J. Chen, R. L. Jin, Ruyi Chen, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shengfeng Ye, Shiyu Wang, Shuiping Yu, Shunfeng Zhou, Shutong Pan, S. S. Li, Shuang Zhou, Shaoqing Wu, Shengfeng Ye, Tao Yun, Tian Pei, Tianyu Sun, T. Wang, Wangding Zeng, Wanjia Zhao, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenqin Yu, Wentao Zhang, W. L. Xiao, Wei An, Xiaodong Liu, Xiaohan Wang, Xiaokang Chen, Xiaotao Nie, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xinyu Yang, Xinyuan Li, Xuecheng Su, Xuheng Lin, X. Q. Li, Xiangyue Jin, Xiaojin Shen, Xiaosha Chen, Xiaowen Sun, Xiaoxiang Wang, Xinnan Song, Xinyi Zhou, Xianzu Wang, Xinxia Shan, Y. K. Li, Y. Q. Wang, Y. X. Wei, Yang Zhang, Yanhong Xu, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Wang, Yi Yu,

- Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yuan Ou, Yuduan Wang, Yue Gong, Yuheng Zou, Yujia He, Yunfan Xiong, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Y. X. Zhu, Yanhong Xu, Yanping Huang, Yaohui Li, Yi Zheng, Yuchen Zhu, Yunxian Ma, Ying Tang, Yukun Zha, Yuting Yan, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhean Xu, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhicheng Ma, Zhigang Yan, Zhiyu Wu, Zihui Gu, Zijia Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Zizheng Pan, Zhen Huang, Zhipeng Xu, Zhongyu Zhang, and Zhen Zhang. DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. *Nature*, 645:633–638, 2025. URL <https://arxiv.org/abs/2501.12948>.
- Ken Ding. HDPO: Hybrid Distillation Policy Optimization via Privileged Self-Distillation. *arXiv preprint arXiv:2603.23871*, 2026. URL <https://arxiv.org/abs/2603.23871>.
- Jiabin Fan, Guoqing Luo, Michael Bowling, and Lili Mou. KETCHUP: K-Step Return Estimation for Sequential Knowledge Distillation. *arXiv preprint arXiv:2504.19024*, 2025. URL <https://arxiv.org/abs/2504.19024>.
- Yuqian Fu, Haohuan Huang, Kaiwen Jiang, Jiakai Liu, Zhuo Jiang, Yuanheng Zhu, and Dongbin Zhao. Revisiting On-Policy Distillation: Empirical Failure Modes and Simple Fixes. *arXiv preprint arXiv:2603.25562*, 2026. URL <https://arxiv.org/abs/2603.25562>.
- Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, Johan Ferret, Peter Liu, Pouya Tafti, Abe Friesen, Michelle Casbon, Sabela Ramos, Ravin Kumar, Charline Le Lan, Sammy Jerome, Anton Tsitsulin, Nino Vieillard, Piotr Stanczyk, Sertan Girgin, Nikola Momchev, Matt Hoffman, Shantanu Thakoor, Jean-Bastien Grill, Behnam Neyshabur, Olivier Bachem, Alanna Walton, Aliaksei Severyn, Alicia Parrish, Aliya Ahmad, Allen Hutchison, Alvin Abdagic, Amanda Carl, Amy Shen, Andy Brock, Andy Coenen, Anthony Laforge, Antonia Paterson, Ben Bastian, Bilal Piot, Bo Wu, Brandon Royal, Charlie Chen, Chintu Kumar, Chris Perry, Chris Welty, Christopher A. Choquette-Choo, Danila Sinopalnikov, David Weinberger, Dimple Vijaykumar, Dominika Rogozińska, Dustin Herbison, Elisa Bandy, Emma Wang, Eric Noland, Erica Moreira, Evan Senter, Evgenii Eltyshov, Francesco Visin, Gabriel Rasskin, Gary Wei, Glenn Cameron, Gus Martins, Hadi Hashemi, Hanna Klimczak-Plucińska, Harleen Batra, Harsh Dhand, Ivan Nardini, Jacinda Mein, Jack Zhou, James Svensson, Jeff Stanway, Jetha Chan, Jin Peng Zhou, Joana Carrasqueira, Joana Iljazi, Jocelyn Becker, Joe Fernandez, Joost van Amersfoort, Josh Gordon, Josh Lipschultz, Josh Newlan, Ju yeong Ji, Kareem Mohamed, Kartikeya Badola, Kat Black, Katie Millican, Keelin McDonnell, Kelvin Nguyen, Kiranbir Sodhia, Kish Greene, Lars Lowe Sjoesund, Lauren Usui, Laurent Sifre, Lena Heuermann, Leticia Lago, Lilly McNealus, Livio Baldini Soares, Logan Kilpatrick, Lucas Dixon, Luciano Martins, Machel Reid, Manvinder Singh, Mark Iversen, Martin Görner, Mat Velloso, Mateo Wirth, Matt Davidow, Matt Miller, Matthew Rahtz, Matthew Watson, Meg Risdal, Mehran Kazemi, Michael Moynihan, Ming Zhang, Minsuk Kahng, Minwoo Park, Mofi Rahman, Mohit Khatwani, Natalie Dao, Nenshad Bardoliwalla, Nesh Devanathan, Neta Dumai, Nilay Chauhan, Oscar Wahltinez, Pankil Botarda, Parker Barnes, Paul Barham, Paul Michel, Pengchong Jin, Petko Georgiev, Phil Culliton, Pradeep Kuppala, Ramona Comanescu, Ramona Merhej, Reena Jana, Reza Ardeshtir Rokni, Rishabh Agarwal, Ryan Mullins, Samaneh Saadat, Sara Mc Carthy, Sarah Cogan, Sarah Perrin, Sébastien M. R. Arnold, Sebastian Krause, Shengyang Dai, Shruti Garg, Shruti Sheth, Sue Ronstrom, Susan Chan, Timothy Jordan, Ting Yu, Tom Eccles, Tom Hennigan, Tomas Kocisky, Tulsee Doshi, Vihan Jain, Vikas Yadav, Vilobh Meshram, Vishal Dharmadhikari, Warren Barkley, Wei Wei, Wenming Ye, Woohyun Han, Woosuk Kwon, Xiang Xu, Zhe Shen, Zhitao Gong, Zichuan Wei, Victor Cotruta, Phoebe Kirk, Anand Rao, Minh Giang, Ludovic Peran, Tris Warkentin, Eli Collins, Joelle Barral, Zoubin Ghahramani, Raia Hadsell, D. Sculley, Jeanine Banks, Anca Dragan, Slav Petrov, Oriol Vinyals, Jeff Dean, Demis Hassabis, Koray Kavukcuoglu, Clement Farabet, Elena Buchatskaya, Sebastian Borgeaud, Noah Fiedel, Armand Joulin, Kathleen Kenealy, Robert Dadashi, and Alek Andreiev. Gemma 2: Improving Open

- Language Models at a Practical Size. *arXiv preprint arXiv:2408.00118*, 2024. URL <https://arxiv.org/abs/2408.00118>.
- Naibin Gu, Chenxu Yang, Qingyi Si, Chuanyu Qin, Dingyu Yao, Peng Fu, Zheng Lin, Weiping Wang, Nan Duan, and Jiaqi Wang. Co-Evolving Policy Distillation. *arXiv preprint arXiv:2604.27083*, 2026. URL <https://arxiv.org/abs/2604.27083>.
- Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. MiniLLM: On-Policy Distillation of Large Language Models. *Proceedings of ICLR*, 2023. URL <https://arxiv.org/abs/2306.08543>.
- Yuxian Gu, Hao Zhou, Fandong Meng, Jie Zhou, and Minlie Huang. MiniPLM: Knowledge Distillation for Pre-Training Language Models. *Proceedings of ICLR*, 2024. URL <https://arxiv.org/abs/2410.17215>.
- Arnav Gudibande, Eric Wallace, Charlie Snell, Xinyang Geng, Hao Liu, Pieter Abbeel, Sergey Levine, and Dawn Song. The False Promise of Imitating Proprietary LLMs. *arXiv preprint arXiv:2305.15717*, 2023. URL <https://arxiv.org/abs/2305.15717>.
- Yinghui He, Simran Kaur, Adithya Bhaskar, Yongjin Yang, Jiarui Liu, Narutatsu Ri, Liam Fowl, Abhishek Panigrahi, Danqi Chen, and Sanjeev Arora. Self-Distillation Zero: Self-Revision Turns Binary Rewards into Dense Supervision. *arXiv preprint arXiv:2604.12002*, 2026. URL <https://arxiv.org/abs/2604.12002>.
- Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.
- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals, and Laurent Sifre. Training Compute-Optimal Large Language Models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. URL <https://arxiv.org/abs/2203.15556>.
- Wenjin Hou, Shangpin Peng, Weinong Wang, Zheng Ruan, Yue Zhang, Zhenglin Zhou, Mingqi Gao, Yifei Chen, Kaiqi Wang, Hongming Yang, Chengquan Zhang, Zhuotao Tian, Han Hu, Yi Yang, Fei Wu, and Hehe Fan. Uni-opd: Unifying on-policy distillation with a dual-perspective recipe. *arXiv preprint arXiv:2605.03677*, 2026.
- Cheng-Yu Hsieh, Chun-Liang Li, Chih-Kuan Yeh, Hootan Nakhost, Yasuhisa Fujii, Alexander Ratner, Ranjay Krishna, Chen-Yu Lee, and Tomas Pfister. Distilling Step-by-Step! Outperforming Larger Language Models with Less Training Data and Smaller Model Sizes. *Findings of ACL*, 2023. URL <https://arxiv.org/abs/2305.02301>.
- Jing Hu, Danxiang Zhu, Xianlong Luo, Dan Zhang, Shuwei He, Yishu Lei, Haitao Zheng, Shikun Feng, Jingzhou He, Yu Sun, Hua Wu, and Haifeng Wang. CORD: Bridging the Audio-Text Reasoning Gap via Weighted On-policy Cross-modal Distillation. *arXiv preprint arXiv:2601.16547*, 2026. URL <https://arxiv.org/abs/2601.16547>.
- Haiduo Huang, Jiangcheng Song, Yadong Zhang, and Pengju Ren. SelecTKD: Selective Token-Weighted Knowledge Distillation for LLMs. *arXiv preprint arXiv:2510.24021*, 2025. URL <https://arxiv.org/abs/2510.24021>.
- Jonas Hübner, Frederike Lübeck, Lejs Behric, Anton Baumann, Marco Bagatella, Daniel Marta, Ido Hakimi, Idan Shenfeld, Thomas Kleine Buening, Carlos Guestrin, and Andreas Krause. Reinforcement Learning via Self-Distillation. *arXiv preprint arXiv:2601.20802*, 2026. URL <https://arxiv.org/abs/2601.20802>.
- Ijun Jang, Jewon Yeom, Juan Yeo, Hyunggu Lim, and Taesup Kim. Stable On-Policy Distillation through Adaptive Target Reformulation. In *Findings of ACL*, 2026. URL <https://arxiv.org/abs/2601.07155>.

- Minbyul Jeong. HEALTHCARE AI GYM for medical agents. *arXiv preprint arXiv:2605.02943*, 2026.
- Yuxin Jiang, Chunkit Chan, Mingyang Chen, and Wei Wang. Lion: Adversarial Distillation of Proprietary Large Language Models. *Proceedings of EMNLP*, 2023. URL <https://arxiv.org/abs/2305.12870>.
- Woogyel Jin, Taywon Min, Yongjin Yang, Swanand Ravindra Kadhe, Yi Zhou, Dennis Wei, Nathalie Baracaldo, and Kimin Lee. Entropy-Aware On-Policy Distillation of Language Models. *arXiv preprint arXiv:2603.07079*, 2026. URL <https://arxiv.org/abs/2603.07079>.
- Seongryong Jung, Suwan Yoon, DongGeon Kim, and Hwanhee Lee. ToDi: Token-wise Distillation via Fine-Grained Divergence Control. In *Proceedings of EMNLP*, 2025. URL <https://arxiv.org/abs/2505.16297>.
- Fatemeh Khadem, Sajad Mousavi, Yi Fang, and Yuhong Liu. DP-OPD: Differentially Private On-Policy Distillation for Language Models. *arXiv preprint arXiv:2604.04461*, 2026. URL <https://arxiv.org/abs/2604.04461>.
- Gyeongman Kim, Doohyuk Jang, and Eunho Yang. PromptKD: Distilling Student-Friendly Knowledge for Generative Language Models via Prompt Tuning. In *Findings of EMNLP*, 2024. URL <https://arxiv.org/abs/2402.12842>.
- Jeonghye Kim, Xufang Luo, Minbeom Kim, Sangmook Lee, Dohyung Kim, Jiwon Jeon, Dongsheng Li, and Yuqing Yang. Why Does Self-Distillation (Sometimes) Degrade the Reasoning Capability of LLMs? *arXiv preprint arXiv:2603.24472*, 2026. URL <https://arxiv.org/abs/2603.24472>.
- Minsang Kim and Seung Jun Baek. Explain in Your Own Words: Improving Reasoning via Token-Selective Dual Knowledge Distillation. *Proceedings of ICLR*, 2026. URL <https://arxiv.org/abs/2603.13260>.
- Yeongmin Kim, Donghyeok Shin, Mina Kang, Byeonghu Na, and Il-Chul Moon. Distillation of Large Language Models via Concrete Score Matching. In *International Conference on Learning Representations (ICLR)*, 2025. URL <https://arxiv.org/abs/2509.25837>.
- Yoon Kim and Alexander M. Rush. Sequence-level knowledge distillation. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2016a.
- Yoon Kim and Alexander M. Rush. Sequence-level knowledge distillation. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 1317–1327, 2016b.
- John Kirchenbauer, Abhimanyu Hans, Brian Bartoldson, Micah Goldblum, Ashwinee Panda, and Tom Goldstein. Multi-Token Prediction via Self-Distillation. *arXiv preprint arXiv:2602.06019*, 2026. URL <https://arxiv.org/abs/2602.06019>.
- Jongwoo Ko, Sungnyun Kim, Tianyi Chen, and Se-Young Yun. DistiLLM: Towards Streamlined Distillation for Large Language Models. *Proceedings of ICML*, 2024. URL <https://arxiv.org/abs/2402.03898>.
- Jongwoo Ko, Tianyi Chen, Sungnyun Kim, Tianyu Ding, Luming Liang, Ilya Zharkov, and Se-Young Yun. DistiLLM-2: A Contrastive Approach Boosts the Distillation of LLMs. In *Proceedings of ICML*, 2025. URL <https://arxiv.org/abs/2503.07067>.
- Jongwoo Ko, Sara Abdali, Young Jin Kim, Tianyi Chen, and Pashmina Cameron. Scaling Reasoning Efficiently via Relaxed On-Policy Distillation. *arXiv preprint arXiv:2603.11137*, 2026. URL <https://arxiv.org/abs/2603.11137>.

- Fengxiang Li, Han Zhang, Haoyang Huang, Jinghui Wang, Jinhua Hao, Kun Yuan, Mengtong Li, Minglei Zhang, Pengcheng Xu, Wenhao Zhuang, Yizhen Shao, Zongxian Feng, Can Tang, Chao Wang, Chengxiao Tong, Fan Yang, Gang Xiong, Haixuan Gao, Han Gao, Hao Wang, Haochen Liu, Hongliang Sun, Jiabao Li, Jingwen Chang, Jun Du, Junyi Peng, Leizhen Cui, Meimei Jing, Mingqi Wu, Shangpeng Yan, Shaotong Qi, Suzhe Xu, Wenxuan Zhao, Xianda Sun, Xuan Xie, Yanbo Wang, Yao Xia, Yinghan Cui, Yingpeng Chen, Yong Wang, Yuze Shi, Zhiwei Shen, Ziyu Wang, Ming Sun, Lin Ye, and Bin Chen. KAT-Coder-V2 Technical Report. *arXiv preprint arXiv:2603.27703*, 2026a. URL <https://arxiv.org/abs/2603.27703>.
- Gengsheng Li, Tianyu Yang, Junfeng Fang, Mingyang Song, Mao Zheng, Haiyun Guo, Dan Zhang, Jinqiao Wang, and Tat-Seng Chua. Unifying Group-Relative and Self-Distillation Policy Optimization via Sample Routing. *arXiv preprint arXiv:2604.02288*, 2026b. URL <https://arxiv.org/abs/2604.02288>.
- Jiaze Li, Hao Yin, Haoran Xu, Boshen Xu, Wenhui Tan, Zewen He, Jianzhong Ju, Zhenbo Luo, and Jian Luan. Video-OPD: Efficient Post-Training of Multimodal Large Language Models for Temporal Video Grounding via On-Policy Distillation. *arXiv preprint arXiv:2602.02994*, 2026c. URL <https://arxiv.org/abs/2602.02994>.
- Yaxuan Li, Yuxin Zuo, Bingxiang He, Jinqian Zhang, Chaojun Xiao, Cheng Qian, Tianyu Yu, Huan ang Gao, Wenkai Yang, Zhiyuan Liu, and Ning Ding. Rethinking On-Policy Distillation of Large Language Models: Phenomenology, Mechanism, and Recipe. *arXiv preprint arXiv:2604.13016*, 2026d. URL <https://arxiv.org/abs/2604.13016>.
- Yingru Li, Ziniu Li, and Jiakai Liu. A Note on Hybrid Online Reinforcement and Imitation Learning for LLMs: Formulations and Algorithms. *arXiv preprint arXiv:2512.23097*, 2025. URL <https://arxiv.org/abs/2512.23097>.
- Kun Liang, Clive Bai, Xin Xu, Chenming Tang, Sanwoo Lee, Weijie Liu, Saiyong Yang, and Yunfang Wu. ORBIT: On-policy Exploration-Exploitation for Controllable Multi-Budget Reasoning. *arXiv preprint arXiv:2601.08310*, 2026. URL <https://arxiv.org/abs/2601.08310>.
- Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, Benjamin Newman, Binhang Yuan, Bobby Yan, Ce Zhang, Christian Cosgrove, Christopher D. Manning, Christopher Ré, Diana Acosta-Navas, Drew A. Hudson, Eric Zelikman, Esin Durmus, Faisal Ladhak, Frieda Rong, Hongyu Ren, Huaxiu Yao, Jue Wang, Keshav Santhanam, Laurel Orr, Lucia Zheng, Mert Yuksekgonul, Mirac Suzgun, Nathan Kim, Neel Guha, Niall Chatterji, Omar Khattab, Peter Henderson, Qian Huang, Ryan Chi, Sang Michael Xie, Shibani Santurkar, Surya Ganguli, Tatsunori Hashimoto, Thomas Icard, Tianyi Zhang, Vishrav Chaudhary, William Wang, Xuechen Li, Yifan Mai, Yuhui Zhang, and Yuta Koreeda. Holistic evaluation of language models. *Transactions on Machine Learning Research*, 2022.
- Wenjie Liao, Like Wu, Liangjie Zhao, Shihui Xu, and Shigeru Fujimura. IRIS: Interpolative Rényi Iterative Self-play for Large Language Model Fine-Tuning. *arXiv preprint arXiv:2604.20933*, 2026. URL <https://arxiv.org/abs/2604.20933>.
- Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let’s Verify Step by Step. *Proceedings of ICLR*, 2023. URL <https://arxiv.org/abs/2305.20050>.
- Kevin Lu and Thinking Machines Lab. On-policy distillation. Thinking Machines Lab: Connectionism, 2025. URL <https://www.thinkingmachines.ai/blog/on-policy-distillation>. doi: 10.64434/tml.20251026.
- Feng Luo, Yu-Neng Chuang, Guanchu Wang, Zicheng Xu, Xiaotian Han, Tianyi Zhang, and Vladimir Braverman. Demystifying OPD: Length Inflation and Stabilization Strategies for Large Language Models. *arXiv preprint arXiv:2604.08527*, 2026. URL <https://arxiv.org/abs/2604.08527>.

- Yuanjie Lyu, Chengyu Wang, Jun Huang, and Tong Xu. From Correction to Mastery: Reinforced Distillation of Large Language Model Agents. *arXiv preprint arXiv:2509.14257*, 2025. URL <https://arxiv.org/abs/2509.14257>.
- Ethan Mendes, Jungsoo Park, and Alan Ritter. Didactic to Constructive: Turning Expert Solutions into Learnable Reasoning. *arXiv preprint arXiv:2602.02405*, 2026. URL <https://arxiv.org/abs/2602.02405>.
- Purbesh Mitra and Sennur Ulukus. Semantic Soft Bootstrapping: Long Context Reasoning in LLMs without Reinforcement Learning. *arXiv preprint arXiv:2512.05105*, 2025. URL <https://arxiv.org/abs/2512.05105>.
- Emiliano Penalosa, Dheeraj Vattikonda, Nicolas Gontier, Alexandre Lacoste, Laurent Charlin, and Massimo Caccia. Privileged Information Distillation for Language Models. *arXiv preprint arXiv:2602.04942*, 2026. URL <https://arxiv.org/abs/2602.04942>.
- Jingyu Peng, Maolin Wang, Hengyi Cai, Yuchen Li, Kai Zhang, Shuaiqiang Wang, Dawei Yin, and Xiangyu Zhao. AdaSwitch: Balancing Exploration and Guidance in Knowledge Distillation via Adaptive Switching. *arXiv preprint arXiv:2510.07842*, 2025. URL <https://arxiv.org/abs/2510.07842>.
- Ruiyang Qin, Qingzhuo Wang, Dongrui Liu, Qiang Li, Zhihua Wei, and Wen Shen. Multilingual Safety Alignment via Self-Distillation. *arXiv preprint arXiv:2605.02971*, 2026. URL <https://arxiv.org/abs/2605.02971>.
- Stéphane Ross, Geoffrey J. Gordon, and J. Andrew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the 14th International Conference on Artificial Intelligence and Statistics*, pp. 627–635, 2011.
- Aswin RRV, Jacob Dineen, Divij Handa, Md Nayem Uddin, Mihir Parmar, Chitta Baral, and Ben Zhou. ThinkTuning: Instilling Cognitive Reflections without Distillation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2025. URL <https://arxiv.org/abs/2508.07616>.
- Hejian Sang, Yuanda Xu, Zhengze Zhou, Ran He, Zhipeng Wang, and Jiachen Sun. CRISP: Compressed Reasoning via Iterative Self-Policy Distillation. *arXiv preprint arXiv:2603.05433*, 2026. URL <https://arxiv.org/abs/2603.05433>.
- Idan Shenfeld, Mehul Damani, Jonas Hübner, and Pulkit Agrawal. Self-Distillation Enables Continual Learning. *arXiv preprint arXiv:2601.19897*, 2026. URL <https://arxiv.org/abs/2601.19897>.
- Makoto Shing, Kou Misaki, Han Bao, Sho Yokoi, and Takuya Akiba. TAID: Temporally Adaptive Interpolated Distillation for Efficient Knowledge Transfer in Language Models. *Proceedings of ICLR*, 2025. URL <https://arxiv.org/abs/2501.16937>.
- Aasheesh Singh, Vishal Vaddina, and Dagnachew Birru. ORPO-Distill: Mixed-Policy Preference Optimization for Cross-Architecture LLM Distillation. *NeurIPS Workshop on Efficient Reasoning*, 2025. URL <https://arxiv.org/abs/2509.25100>.
- Yuda Song, Lili Chen, Fahim Tajwar, Remi Munos, Deepak Pathak, J. Andrew Bagnell, Aarti Singh, and Andrea Zanette. Expanding the Capabilities of Reinforcement Learning via Text Feedback. *arXiv preprint arXiv:2602.02482*, 2026. URL <https://arxiv.org/abs/2602.02482>.
- Alex Stein, Furong Huang, and Tom Goldstein. GATES: Self-Distillation under Privileged Context with Consensus Gating. *arXiv preprint arXiv:2602.20574*, 2026. URL <https://arxiv.org/abs/2602.20574>.
- Zhiqian Tan and Yinrong Hong. PAINT: Partial-Solution Adaptive Interpolated Training for Self-Distilled Reasoners. *arXiv preprint arXiv:2604.26573*, 2026. URL <https://arxiv.org/abs/2604.26573>.

- Tencent Robotics X, HY Vision Team, Xumin Yu, Zuyan Liu, Ziyi Wang, He Zhang, Yongming Rao, Fangfu Liu, Yani Zhang, Ruowen Zhao, Oran Wang, Yves Liang, Haitao Lin, Minghui Wang, Yubo Dong, Kevin Cheng, Bolin Ni, Rui Huang, Han Hu, Zhengyou Zhang, Linus, and Shunyu Yao. HY-Embodied-0.5: Embodied Foundation Models for Real-World Agents. *arXiv preprint arXiv:2604.07430*, 2026. URL <https://arxiv.org/abs/2604.07430>.
- Hao Wang, Guozhi Wang, Han Xiao, Yufeng Zhou, Yue Pan, Jichao Wang, Ke Xu, Yafei Wen, Xiaohu Ruan, Xiaoxin Chen, and Honggang Qi. Skill-SD: Skill-Conditioned Self-Distillation for Multi-turn LLM Agents. *arXiv preprint arXiv:2604.10674*, 2026a. URL <https://arxiv.org/abs/2604.10674>.
- Jianze Wang, Ying Liu, Jinlong Chen, Xuchun Hu, Qilong Zhang, Yu Cao, Jun Wang, Hua Yang, Yong Xie, and Qianglong Chen. MAD-OPD: Breaking the Ceiling in On-Policy Distillation via Multi-Agent Debate. *arXiv preprint arXiv:2605.01347*, 2026b. URL <https://arxiv.org/abs/2605.01347>.
- Jiaqi Wang, Wenhao Zhang, Weijie Shi, Yaliang Li, and James Cheng. TCOd: Exploring Temporal Curriculum in On-Policy Distillation for Multi-turn Autonomous Agents. *arXiv preprint arXiv:2604.24005*, 2026c. URL <https://arxiv.org/abs/2604.24005>.
- Sudong Wang, WeiQuan Huang, Xiaomin Yu, Zuhao Yang, Hehai Lin, Keming Wu, Chaojun Xiao, Chen Chen, Wenxuan Wang, Beier Zhu, Yunjian Zhang, and Chengwei Qin. Beyond SFT-to-RL: Pre-alignment via Black-Box On-Policy Distillation for Multimodal RL. *arXiv preprint arXiv:2604.28123*, 2026d. URL <https://arxiv.org/abs/2604.28123>.
- Yinjie Wang, Xuyang Chen, Xiaolong Jin, Mengdi Wang, and Ling Yang. OpenClaw-RL: Train Any Agent Simply by Talking. *arXiv preprint arXiv:2603.10165*, 2026e. URL <https://arxiv.org/abs/2603.10165>.
- Yuqiao Wen, Zichao Li, Wenyu Du, and Lili Mou. f-Divergence Minimization for Sequence-Level Knowledge Distillation. *Proceedings of ACL*, 2023. URL <https://arxiv.org/abs/2307.15190>.
- Taiqiang Wu, Chaofan Tao, Jiahao Wang, Runming Yang, Zhe Zhao, and Ngai Wong. Rethinking Kullback-Leibler Divergence in Knowledge Distillation for Large Language Models. *Proceedings of COLING*, 2024. URL <https://arxiv.org/abs/2404.02657>.
- Yecheng Wu, Song Han, and Han Cai. Lightning OPD: Efficient Post-Training for Large Reasoning Models with Offline On-Policy Distillation. *arXiv preprint arXiv:2604.13010*, 2026. URL <https://arxiv.org/abs/2604.13010>.
- Xiaomi LLM-Core Team, Bangjun Xiao, Bingquan Xia, Bo Yang, Bofei Gao, Bowen Shen, Chen Zhang, Chenhong He, Chiheng Lou, Fuli Luo, Gang Wang, Gang Xie, Hailin Zhang, Hanglong Lv, Hanyu Li, Heyu Chen, Hongshen Xu, Houbin Zhang, Huaqiu Liu, Jiangshan Duo, Jianyu Wei, Jiebao Xiao, Jinhao Dong, Jun Shi, Junhao Hu, Kainan Bao, Kang Zhou, Lei Li, Liang Zhao, Linghao Zhang, Peidian Li, Qianli Chen, Shaohui Liu, Shihua Yu, Shijie Cao, Shima Chen, Shouqiu Yu, Shuo Liu, Tianling Zhou, Weijiang Su, Weikun Wang, Wenhan Ma, Xiangwei Deng, Bohan Mao, Bowen Ye, Can Cai, Chenghua Wang, Chengxuan Zhu, Chong Ma, Chun Chen, Chunan Li, Dawei Zhu, Deshan Xiao, Dong Zhang, Duo Zhang, Fangyue Liu, Feiyu Yang, Fengyuan Shi, Guoan Wang, Hao Tian, Hao Wu, Heng Qu, Hongfei Yi, Hongxu An, Hongyi Guan, Xing Zhang, Yifan Song, Yihan Yan, Yihao Zhao, Yingchun Lai, Yizhao Gao, Yu Cheng, Yuanyuan Tian, Yudong Wang, Zhen Tang, Zhengju Tang, Zhengtao Wen, Zhichao Song, Zhixian Zheng, Zihan Jiang, Jian Wen, Jiarui Sun, Jiawei Li, Jinlong Xue, Jun Xia, Kai Fang, Menghang Zhu, Nuo Chen, Qian Tu, Qihao Zhang, Qiying Wang, Rang Li, Rui Ma, Shaolei Zhang, Shengfan Wang, Shicheng Li, Shuhao Gu, Shuhuai Ren, Sirui Deng, Tao Guo, Tianyang Lu, Wei Ji Zhuang, Weikang Zhang, Weimin Xiong, Wenshan Huang, Wenyu Yang, Xin Zhang, Xing Dong, Xu Wang, Xueyang Xie, Yilin Jiang, Yixin Yang, Yongzhe He, Yu Tu, Yuanliang Dong, Yuchen Liu, Yue Ma, Yue Yu, Yuxing Xiang, Zhaojun Huang, Zhenru Lin, Zhipeng Xu, Zhiyang Chen, Zhonghua Deng, Zihan Zhang, and Zihao Yue. MiMo-V2-Flash Technical Report. *arXiv preprint arXiv:2601.02780*, 2026. URL <https://arxiv.org/abs/2601.02780>.

- Xurong Xie, Zhucun Xue, Jiafu Wu, Jian Li, Yabiao Wang, Xiaobin Hu, Yong Liu, and Jiangning Zhang. LLM-Oriented Token-Adaptive Knowledge Distillation. *arXiv preprint arXiv:2510.11615*, 2025. URL <https://arxiv.org/abs/2510.11615>.
- Jing Xiong, Hui Shen, Shansan Gong, Yuxin Cheng, Jianghan Shen, Chaofan Tao, Haochen Tan, Haoli Bai, Lifeng Shang, and Ngai Wong. OVD: On-policy Verbal Distillation. *arXiv preprint arXiv:2601.21968*, 2026. URL <https://arxiv.org/abs/2601.21968>.
- Hongling Xu, Qi Zhu, Heyuan Deng, Jinpeng Li, Lu Hou, Yasheng Wang, Lifeng Shang, Ruifeng Xu, and Fei Mi. KDRL: Post-Training Reasoning LLMs via Unified Knowledge Distillation and Reinforcement Learning. *arXiv preprint arXiv:2506.02208*, 2025a. URL <https://arxiv.org/abs/2506.02208>.
- Shicheng Xu, Liang Pang, Yunchang Zhu, Jia Gu, Zihao Wei, Jingcheng Deng, Feiyang Pan, Huawei Shen, and Xueqi Cheng. RLKD: Distilling LLMs’ Reasoning via Reinforcement Learning. *arXiv preprint arXiv:2505.16142*, 2025b. URL <https://arxiv.org/abs/2505.16142>.
- Wenda Xu, Rujun Han, Zifeng Wang, Long T. Le, Dhruv Madeka, Lei Li, William Yang Wang, Rishabh Agarwal, Chen-Yu Lee, and Tomas Pfister. Speculative Knowledge Distillation: Bridging the Teacher-Student Gap Through Interleaved Sampling. *Proceedings of ICLR*, 2024a. URL <https://arxiv.org/abs/2410.11325>.
- Xiaohan Xu, Ming Li, Chongyang Tao, Tao Shen, Reynold Cheng, Jinyang Li, Can Xu, Dacheng Tao, and Tianyi Zhou. A Survey on Knowledge Distillation of Large Language Models. *arXiv preprint arXiv:2402.13116*, 2024b. URL <https://arxiv.org/abs/2402.13116>.
- Yuanda Xu, Hejian Sang, Zhengze Zhou, Ran He, and Zhipeng Wang. PACED: Distillation and On-Policy Self-Distillation at the Frontier of Student Competence. *arXiv preprint arXiv:2603.11178*, 2026a. URL <https://arxiv.org/abs/2603.11178>.
- Yuanda Xu, Hejian Sang, Zhengze Zhou, Ran He, Zhipeng Wang, and Alborz Geramifard. TIP: Token Importance in On-Policy Distillation. *arXiv preprint arXiv:2604.14084*, 2026b. URL <https://arxiv.org/abs/2604.14084>.
- Jianhao Yan, Yafu Li, Zican Hu, Zhi Wang, Ganqu Cui, Xiaoye Qu, Yu Cheng, and Yue Zhang. Learning to Reason under Off-Policy Guidance. *arXiv preprint arXiv:2504.14945*, 2025. URL <https://arxiv.org/abs/2504.14945>.
- Shaotian Yan, Kaiyuan Liu, Chen Shen, Bing Wang, Sinan Fan, Jun Zhang, Yue Wu, Zheng Wang, and Jieping Ye. Distribution-Aligned Sequence Distillation for Superior Long-CoT Reasoning. *arXiv preprint arXiv:2601.09088*, 2026. URL <https://arxiv.org/abs/2601.09088>.
- An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiayi Yang, Jing Zhou, Jingren Zhou, Junyang Lin, Kai Dang, Keqin Bao, Kexin Yang, Le Yu, Lianghao Deng, Mei Li, Mingfeng Xue, Mingze Li, Pei Zhang, Peng Wang, Qin Zhu, Rui Men, Ruize Gao, Shixuan Liu, Shuang Luo, Tianhao Li, Tianyi Tang, Wenbiao Yin, Xingzhang Ren, Xinyu Wang, Xinyu Zhang, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yinger Zhang, Yu Wan, Yuqiong Liu, Zekun Wang, Zeyu Cui, Zhenru Zhang, Zhipeng Zhou, and Zihan Qiu. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388*, 2025. URL <https://arxiv.org/abs/2505.09388>.
- Chenxu Yang, Chuanyu Qin, Qingyi Si, Minghui Chen, Naibin Gu, Dingyu Yao, Zheng Lin, Weiping Wang, Jiaqi Wang, and Nan Duan. Self-Distilled RLVR. *arXiv preprint arXiv:2604.03128*, 2026a. URL <https://arxiv.org/abs/2604.03128>.
- Fan Yang, Rui Meng, Trudi Di Qi, Ali Ezzati, and Yuxin Wen. KEPO: Knowledge-Enhanced Preference Optimization for Reinforcement Learning with Reasoning. *arXiv preprint arXiv:2602.00400*, 2026b. URL <https://arxiv.org/abs/2602.00400>.

- Ling Yang, Zhaochen Yu, Tianjun Zhang, Minkai Xu, Joseph E. Gonzalez, Bin Cui, and Shuicheng Yan. SuperCorrect: Advancing Small LLM Reasoning with Thought Template Distillation and Self-Correction. *Proceedings of ICLR*, 2024. URL <https://arxiv.org/abs/2410.09008>.
- Wenkai Yang, Weijie Liu, Ruobing Xie, Kai Yang, Saiyong Yang, and Yankai Lin. Learning beyond Teacher: Generalized On-Policy Distillation with Reward Extrapolation. *arXiv preprint arXiv:2602.12125*, 2026c. URL <https://arxiv.org/abs/2602.12125>.
- Zhuolin Yang, Zihan Liu, Yang Chen, Wenliang Dai, Boxin Wang, Sheng-Chieh Lin, Chankyu Lee, Yangyi Chen, Dongfu Jiang, Jiafan He, Renjie Pi, Grace Lam, Nayeon Lee, Alexander Bukharin, Mohammad Shoeybi, Bryan Catanzaro, and Wei Ping. Nemotron-Cascade 2: Post-Training LLMs with Cascade RL and Multi-Domain On-Policy Distillation. *arXiv preprint arXiv:2603.19220*, 2026d. URL <https://arxiv.org/abs/2603.19220>.
- Tianzhu Ye, Li Dong, Zewen Chi, Xun Wu, Shaohan Huang, and Furu Wei. Black-Box On-Policy Distillation of Large Language Models. *arXiv preprint arXiv:2511.10643*, 2025. URL <https://arxiv.org/abs/2511.10643>.
- Tianzhu Ye, Li Dong, Qingxiu Dong, Xun Wu, Shaohan Huang, and Furu Wei. Online Experiential Learning for Language Models. *arXiv preprint arXiv:2603.16856*, 2026a. URL <https://arxiv.org/abs/2603.16856>.
- Tianzhu Ye, Li Dong, Xun Wu, Shaohan Huang, and Furu Wei. On-Policy Context Distillation for Language Models. *arXiv preprint arXiv:2602.12275*, 2026b. URL <https://arxiv.org/abs/2602.12275>.
- Xin Yu, Liuchen Liao, Yiwen Zhang, Yingchen Yu, Lingzhou Xue, and Qinzhen Guo. Preference-based self-distillation: Beyond KL matching via reward regularization. *arXiv preprint arXiv:2605.05040*, 2026.
- Dongxu Zhang, Zhichao Yang, Sepehr Janghorbani, Jun Han, Andrew Ressler, Qian Qian, Gregory D. Lyng, Sanjit Singh Batra, and Robert E. Tillman. Fast and Effective On-policy Distillation from Reasoning Prefixes. *arXiv preprint arXiv:2602.15260*, 2026a. URL <https://arxiv.org/abs/2602.15260>.
- Jiaxin Zhang, Xiangyu Peng, Qinglin Chen, Qinyuan Ye, Caiming Xiong, and Chien-Sheng Wu. The Illusion of Certainty: Decoupling Capability and Calibration in On-Policy Distillation. *arXiv preprint arXiv:2604.16830*, 2026b. URL <https://arxiv.org/abs/2604.16830>.
- Miaosen Zhang, Yishan Liu, Shuxia Lin, Xu Yang, Qi Dai, Chong Luo, Weihao Jiang, Peng Hou, Anxiang Zeng, Xin Geng, and Baining Guo. Towards On-Policy SFT: Distribution Discriminant Theory and its Applications in LLM Training. *arXiv preprint arXiv:2602.12222*, 2026c. URL <https://arxiv.org/abs/2602.12222>.
- Ruixiang Zhang, Richard He Bai, Huangjie Zheng, Navdeep Jaitly, Ronan Collobert, and Yizhe Zhang. Embarrassingly Simple Self-Distillation Improves Code Generation. *arXiv preprint arXiv:2604.01193*, 2026d. URL <https://arxiv.org/abs/2604.01193>.
- Songming Zhang, Xue Zhang, Tong Zhang, Bojie Hu, Yufeng Chen, and Jinan Xu. AlignDis: Token-Level Language Model Alignment as Adaptive Policy Distillation. In *Proceedings of ACL*, 2025a. URL <https://arxiv.org/abs/2503.02832>.
- Xinsen Zhang, Zhenkai Ding, Tianjun Pan, Run Yang, Chun Kang, Xue Xiong, and Jingnan Gu. OPSDL: On-Policy Self-Distillation for Long-Context Language Models. *arXiv preprint arXiv:2604.17535*, 2026e. URL <https://arxiv.org/abs/2604.17535>.
- Xue Zhang, Songming Zhang, Yunlong Liang, Fandong Meng, Yufeng Chen, Jinan Xu, and Jie Zhou. A Dual-Space Framework for General Knowledge Distillation of Large Language Models. *arXiv preprint arXiv:2504.11426*, 2025b. URL <https://arxiv.org/abs/2504.11426>.

- Yan Zhang, Daiqing Wu, Huawen Shen, Yu Zhou, and Can Ma. Learn where to click from yourself: On-policy self-distillation for gui grounding. *arXiv preprint arXiv:2605.00642*, 2026f.
- Yaocheng Zhang, Yuanheng Zhu, Wenyue Chong, Songjun Tu, Qichao Zhang, Jiajun Chai, Xiaohan Wang, Wei Lin, Guojun Yin, and Dongbin Zhao. π -Play: Multi-Agent Self-Play via Privileged Self-Distillation without External Data. *arXiv preprint arXiv:2604.14054*, 2026g. URL <https://arxiv.org/abs/2604.14054>.
- Zhaoyang Zhang, Shuli Jiang, Yantao Shen, Yuting Zhang, Dhananjay Ram, Shuo Yang, Zhuowen Tu, Wei Xia, and Stefano Soatto. Reinforcement-aware Knowledge Distillation for LLM Reasoning. *arXiv preprint arXiv:2602.22495*, 2026h. URL <https://arxiv.org/abs/2602.22495>.
- Anhao Zhao, Ziyang Chen, Junlong Tong, Yingqi Fan, Fanghua Ye, Shuhao Li, Yunpu Ma, Wenjie Li, and Xiaoyu Shen. On-Policy Supervised Fine-Tuning for Efficient Reasoning. *arXiv preprint arXiv:2602.13407*, 2026a. URL <https://arxiv.org/abs/2602.13407>.
- Siyan Zhao, Zhihui Xie, Mengchen Liu, Jing Huang, Guan Pang, Feiyu Chen, and Aditya Grover. Self-Distilled Reasoner: On-Policy Self-Distillation for Large Language Models. *arXiv preprint arXiv:2601.18734*, 2026b. URL <https://arxiv.org/abs/2601.18734>.
- Binbin Zheng, Xing Ma, Yiheng Liang, Jingqing Ruan, Xiaoliang Fu, Kepeng Lin, Benchang Zhu, Ke Zeng, and Xunliang Cai. SCOPE: Signal-Calibrated On-Policy Distillation Enhancement with Dual-Path Adaptive Weighting. *arXiv preprint arXiv:2604.10688*, 2026. URL <https://arxiv.org/abs/2604.10688>.
- Qihuang Zhong, Liang Ding, Li Shen, Juhua Liu, Bo Du, and Dacheng Tao. Revisiting Knowledge Distillation for Autoregressive Language Models. *Proceedings of ACL*, 2024. URL <https://arxiv.org/abs/2402.11890>.
- Zhide Zhong, Haodong Yan, Junfeng Li, Junjie He, Tianran Zhang, and Haoang Li. VLA-OPD: Bridging Offline SFT and Online RL for Vision-Language-Action Models via On-Policy Distillation. *arXiv preprint arXiv:2603.26666*, 2026. URL <https://arxiv.org/abs/2603.26666>.
- Yongchao Zhou, Kaifeng Lyu, Ankit Singh Rawat, Aditya Krishna Menon, Afshin Rostamizadeh, Sanjiv Kumar, Jean-François Kagy, and Rishabh Agarwal. Distill-Spec: Improving Speculative Decoding via Knowledge Distillation. *arXiv preprint arXiv:2310.08461*, 2023. URL <https://arxiv.org/abs/2310.08461>.
- Matthieu Zimmer, Xiaotong Ji, Tu Nguyen, and Haitham Bou Ammar. Rethinking Large Language Model Distillation: A Constrained Markov Decision Process Perspective. *arXiv preprint arXiv:2509.22921*, 2025. URL <https://arxiv.org/abs/2509.22921>.