e e	@	≐ ₩	*	тт	.11


XNA Versions

- The latest version of XNA is 4.0
 - This works with Visual Studio 2010, 2012 and 2013
- You can obtain this from:
 - https://msxna.codeplex.com/releases
 - Follow the instructions in the Readme.txt to install it
- Not all installations of Visual Studio on campus have the XNA components installed
- The Fenner Computer Suite and the labs in the Robert Blackburn Building have XNA

Getting Started with XNA

University of Hull

Creating a Game



- Visual Studio 2012 with XNA installed provides Windows Game project types for Windows Phone, Windows PC and Xbox 360
- · We are going to use the Windows Game project
 - The others may not work

Getting Started with XNA

UNIVERSITY OF Hull

The Game Project

- The solution explorer shows the items that make up our game project
- At the moment there are a couple of class files which are created automatically
- The solution will also contain any content that we add to the game project



- o	0	*	*	ķ	тт	1	n

XNA and Programs

- · XNA works by using classes and objects
 - You create instances of objects
 - You use objects built into the framework
- · This lets you create games
- It is also a very good example of how you construct a set of software resources and use them
 - This is a good way to learn how to do this

Getting Started with XNA

University of **Hull**

Running the Game

- · We can build and run our game now if we like
- The initial application contains code which starts our game:

```
static void Main(string[] args)
{
   using (Game1 game = new Game1())
   {
      game.Run();
   }
}
```

Getting Started with XNA

♥®童★► Hull

First Game Display



- · At the moment all our game does is display a blue screen
- This is because the behaviour of the Draw method in a brand new project is to clear the screen to blue

Getting Started with XNA

3

◆ ◆ ★ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆ ◆	TT1

Wh	at a	Game	Does 1	When	it Runs

- 1. Initialise all the resources at the start
 - fetch all textures, models, scripts etc
- 2. Repeatedly run the game:
 - 1. Update the game engine
 - read the controllers, update the state and position of game elements
 - 2. Draw the game environment
 - · render the game elements on the viewing device

Getting Started with XNA

University of Hull

XNA Game Class Methods

Getting Started with XNA

♥®童★► Hull

Some C# Details....

- partial
 - There may be other C# source files which contain other code for this class
- protected
 - This member is visible in child classes, but not ones external to this class hierarchy
- ·usina
 - When you leave this block, garbage collect the thing I'm using

Loading Game Content

```
protected override void LoadContent()
{
    // Create a new SpriteBatch, which can be used to draw
    spriteBatch = new SpriteBatch(GraphicsDevice);

    // TODO: use this.Content to load your game content here
}
```

- LoadContent is called when our game starts
- It is where we put the code that loads the content into our game
- Content includes images, sounds, models etc.

Getting Started with XNA

University of Hull

Game Content

- Games are not just programs, they also contain other content:
 - Images for textures and backgrounds
 - Sound Effects
 - 3D Object Meshes
 - Scripts
 - Videos
- · We need to add this content to our project
- The XNA framework provides a content management system which is integrated into Visual Studio 2008

Getting Started with XNA

UNIVERSITY OF Hull

Image Resources

- · This is my Ball image
- · I have saved it as a PNG file
 - This allows me to use transparency
- You can use any image resource you like
- The resources are added to the Visual Studio project
- They are held in the Content directory as part of your project







e e	@	≐ ₩	*	тт	.11

Storing the Ball Texture in the game

Texture2D ballTexture;

- XNA provides a Texture2D type which holds a 2D (flat) texture to be drawn on the display
- The game class needs to contain a member variable to hold the ball texture that is to be drawn when the game runs
- This variable will be shared by all the methods in the game

Getting Started with XP

UNIVERSITY OF Hull

Using the Content Pipeline

- Each resource is given an asset name
- The Load method from the Content Manager provides access to the resource using the Asset Name that we gave it



ballTexture = Content.Load<Texture2D>("WhiteDot");

Getting Started with XNA

UNIVERSITY OF Hull

Loading Content into the Ball Texture

protected override void LoadContent()
{
 // Create a new SpriteBatch, which can be used to draw
 spriteBatch = new SpriteBatch(GraphicsDevice);
 ballTexture = Content.Load<Texture2D>("WhiteDot");
}

- LoadContent is called when our game starts
- · It loads an image into the ball texture
- The content manager fetches the images which are automatically sent to the target device

Getting Started with XNA

6

•		
,		
•		
,		

XNA Game Draw Method

```
protected override void Draw(GameTime gameTime)
{
    GraphicsDevice.Clear(Color.CornflowerBlue);
    base.Draw(gameTime);
}
```

- The Draw method is called repeatedly when an XNA game is running
 - It has the job of drawing the display on the screen
- A brand new XNA game project contains a Draw method that clears the screen to CornflowerBlue
- · We must add our own code to the method to draw the ball

Getting Started with XI

UNIVERSITY OF Hull

Sprite Batching

- 2D Graphics drawing is handled by a set of "sprite" drawing methods provided by XNA
- These create commands that are passed to the graphics device
- The graphics device will not want to draw everything on a piecemeal basis
- Ideally all the drawing information, textures and transformations should be provided as a single item
- The SpriteBatch class looks after this for us

20

Getting Started with XNA

UNIVERSITY OF Hull

SpriteBatch Begin and End

```
spriteBatch.Begin();
// Code that uses spriteBatch to draw the display
spriteBatch.End();
```

- The call to the Begin method tells SpriteBatch to begin a assembling a new set of drawing operations
- The call to the End method tells SpriteBatch that the there are no more operations and causes the rendering to take place
- · Between the two we put our drawing code

21

♥®童�� Hull

Using SpriteBatch.Draw

```
spriteBatch.Draw(ballTexture,
  new Rectangle(
    0, 0,
    ballTexture.Width, ballTexture.Height),
    Color.White);
```

- The ${\tt SpriteBatch}$ class provides a ${\tt Draw}$ method to do the sprite drawing
- · It is given parameters to tell it what to do:
 - Texture to draw
 - Position (expressed as a Rectangle)
 - Draw colour (expressed as an XNA Color)

Getting Started with XNA

University of Hull


The Rectangle structure

```
new Rectangle(
0, 0,
ballTexture.Width, ballTexture.Height),
Color.White);
```

- Rectangle is a struct type which contains a position and a size
- The code above creates a rectangle positioned at 0,0 (top left hand corner) the same size as ballTexture
- We could move our ball by changing the content of the rectangle

Getting Started with XNA

University of **Hull**



e e	@	≐ ₩	*	тт	.11

Positioning	the	Ball	using	a	Rectang	16

Texture2D ballTexture;
Rectangle ballRectangle;

- If we want to move the ball around the screen we must add a variable to keep track of the ball position
- · This is another member of the game class
- We declare it in the class so that all the methods in the game can use it
- We will initialise it in the LoadContent method

♥®宣**☆~ Hull**

Getting Started with XNA

Screen Size and Scaling

- \bullet We need to make our game images fit the size of the screen
- We can find out the size of the screen Window.ClientBounds.Width Window.ClientBounds.Height
- The game has a Window property we use to get this
- \bullet We can use this information to scale the sprites to fit our screen

Getting Started with XNA

UNIVERSITY OF Hull

Creating the ballRectangle variable

ballRectangle = new Rectangle(
 0, 0,
 Window.ClientBounds.Width / 30,
 Window.ClientBounds.Width / 30);

- If we use this rectangle to draw our ball texture it will be drawn as a square which is a thirtieth of the width of the screen
- We can then set the position parts of the rectangle to move the ball around

7 Getting Started with XNA

9

•			
•			
•			
•			
•			
•			
•			
•			
•			
•			

Drawing with the ballRectangle variable

```
protected override void Draw(GameTime gameTime)
{
    GraphicsDevice.Clear(Color.CornflowerBlue);
    spriteBatch.Begin();
    spriteBatch.Draw(ballTexture, ballRectangle, Color.White);
    spriteBatch.End();
    base.Draw(gameTime);
}
```

• This version of Draw uses the ballRectangle variable to position the ball on the screen

28

Getting Started with XNA

University of Hull

Moving the ball around the screen

- At the moment the ball is drawn in the same position each time
- To move the ball around we need to make this position change
- We need to give the game an update behaviour
- · We must add code to the Update method in the game
- The Update method is where we manage the state of the "game world"

29

Getting Started with XNA

UNIVERSITY OF Hull

The Update Method

```
protected override void Update(GameTime gameTime)
{
    // TODO: Add your update logic here
    base.Update(gameTime);
}
```

- The Update method is automatically called 60 times a second when a game is running
 - 30 times a second for a Windows Phone game
- It is in charge of managing the "game world" of a game
 - In a pong game this means updating the bat and the ball positions and checking for collisions

•	•	

学の音やを	TT11

Simple Update Method

```
protected override void Update(GameTime gameTime)
{
   ballRectangle.X++;
   balRectangle.Y++;
   base.Update(gameTime);
}
```

- Each time the game updates the \boldsymbol{X} and \boldsymbol{Y} position of the ball is increased
- · This will cause it to move across and down the screen
- Note that I call the base method to allow my parent object to update too

Getting Started with XNA

University of Hull

GameTime

- At the moment the Update method is called sixty time a second or once every 16.66 milliseconds
- We can also let the update "free run", in which case we need to know the time since the last call so we can move objects the right distance
- This is what the GameTime parameter is for, it gives the time at which the method was called

Getting Started with XNA

UNIVERSITY OF Hull

Summary

- XNA is a Framework of methods that are used to write games
- You create the games using Visual Studio and XNA 4.0 Game Studio
- · Games have initialise, update and draw behaviours
- Game objects are held as texture objects and their position and dimensions as rectangle structures