



SAPIENZA
UNIVERSITÀ DI ROMA

DEPARTMENT OF MECHANICAL AND AEROSPACE ENGINEERING

Homework 3 — Attitude Control of a Launch Vehicle in Atmospheric Flight

DYNAMICS AND CONTROL OF LAUNCH VEHICLES

Professor:

Prof. A. Zavoli

Student:

Niccolò D'Ambrosio

Academic Year 2025/2026

Contents

1	Introduction	2
1.1	Design methodology: frozen coefficients at $\max\bar{q}$	2
1.2	Plant model	2
1.3	Control architecture	4
1.4	A note on conditional stability	4
2	Task 1 — Rigid Launch Vehicle	5
2.1	Rigid model and loop	5
2.2	Tuning	5
2.3	Wind-gust response	7
3	Task 2 — Full Launch Vehicle Model	10
3.1	Step B — uncompensated full model	10
3.2	Step C — bending filter trade study	10
3.3	Sensitivity to the bending-frequency knowledge	12
3.4	Validation and comparison with the rigid model	13
3.5	A note on the tail-wags-dog zero	14
4	Task 3 — Robustness to Parametric Uncertainty	15
4.1	Frequency- and time-domain analysis	15
4.2	Discussion	15
5	Conclusions	18
A	Implementation: Key Code Excerpts	20
	References	23

1 Introduction

This report addresses the design of an attitude control system for a launch vehicle (LV) during the atmospheric phase of flight, at the instant of maximum dynamic pressure ($t = 72$ s, $\max\bar{q}$). This is the hardest point to control: the aerodynamic moment destabilises the airframe and the wind disturbance is largest. I design the controller with classical frequency-domain tools, using the Nichols chart as the main stability indicator, following the short-period pitch-plane model of Greensite [1].

1.1 Design methodology: frozen coefficients at $\max\bar{q}$

Launch-vehicle attitude control in atmospheric flight is classically handled by the **time-slice** (frozen-coefficient) method: the slowly varying mass, inertia and aerodynamic coefficients are frozen at a representative instant, a linear time-invariant short-period model is built and analysed at that operating point, and the controller is then validated against time-varying simulations [2, Sec. 2]. The main sizing disturbance is the wind profile, which drives both the trajectory dispersion and the structural bending loads—hence the gust analysis of Tasks 1 and 2. I pick $t = 72$ s because it is the load- and stability-critical slice: the aerodynamic destabilising moment and the wind-induced angle of attack are both near their maxima. The catch is that point-wise Nichols margins certify only the frozen model and do not by themselves guarantee stability of the underlying time-varying system; this is what motivates the parametric robustness study of Task 3 and, eventually, gain scheduling along the trajectory.

1.2 Plant model

The pitch-plane short-period dynamics are described by the linear time-invariant model (assignment Eq. 1), with state vector $\mathbf{x} = [z, \dot{z}, \theta, \dot{\theta}, \eta, \dot{\eta}]^\top$ (lateral drift, pitch attitude and first bending mode), control input δ (TVC deflection) and disturbance α_w (wind angle of attack):

$$\dot{\mathbf{x}} = \begin{bmatrix} 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & a_1 & a_1 V + a_4 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & A_6/V & A_6 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & -\omega_1^2 & -2\zeta_1\omega_1 \end{bmatrix} \mathbf{x} + \begin{bmatrix} 0 \\ a_3 \\ 0 \\ K_1 \\ 0 \\ -\phi_{1,TVC}T_c \end{bmatrix} \delta + \begin{bmatrix} 0 \\ -a_1 V \\ 0 \\ -A_6 \\ 0 \\ 0 \end{bmatrix} \alpha_w. \quad (1)$$

The pitch channel is the core of the problem and follows from a moment balance about the centre of mass. The aerodynamic moment $N_\alpha l_\alpha$ acts on the local incidence—built from the pitch attitude θ , the plunging term $\dot{z}/V$ and the wind angle α_w —while the

gimballed thrust contributes a control moment $T_c l_c \delta$; dividing the balance $I_{yy} \ddot{\theta} = N_\alpha l_\alpha (\theta + \dot{z}/V - \alpha_w) + T_c l_c \delta$ by I_{yy} reproduces row 4 of Eq. (1),

$$\ddot{\theta} = A_6 \theta + \frac{A_6}{V} \dot{z} + K_1 \delta - A_6 \alpha_w, \quad (2)$$

and identifies the two structural coefficients: the **aerodynamic moment** $A_6 = N_\alpha l_\alpha / I_{yy} > 0$ (denoted μ_α) and the **control effectiveness** $K_1 = T_c l_c / I_{yy}$ (μ_c). With $A_6 > 0$ the airframe transfer function $\theta/\delta = K_1/(s^2 - A_6)$ carries an open-loop pole at $s = +\sqrt{A_6} = +1.84$ rad/s in the right half-plane: the **statically unstable** airframe of a vehicle whose centre of pressure lies ahead of its centre of mass, for which feedback is mandatory [3, Eqs. (9.2.25)–(9.2.26)]. The TVC coefficient K_1 sets the control authority available to counter it.

The sensed quantities are produced by the inertial unit (assignment Eq. 2), which couples the bending coordinate η into the gyro and accelerometer channels through $\sigma_{1,ins}$ and $\phi_{1,ins}$:

$$\theta_m = \theta + \sigma_{1,ins} \eta, \quad \dot{\theta}_m = \dot{\theta} + \sigma_{1,ins} \dot{\eta}, \quad z_m = z - \phi_{1,ins} \eta, \quad \dot{z}_m = \dot{z} - \phi_{1,ins} \dot{\eta}. \quad (3)$$

This contamination is exactly what makes the lightly damped first bending mode—written with $\omega_1 \equiv \omega_{BM} = 18.9$ rad/s and $\zeta_1 \equiv \zeta_{BM} = 0.005$ in Eq. (1)—visible to the controller and drives the need for a dedicated filter (Task 2).

The actuator is the second-order TVC of Eq. 3,

$$W_{TVC}(s) = \frac{\omega_{TVC}^2}{s^2 + 2\zeta_{TVC}\omega_{TVC}s + \omega_{TVC}^2}, \quad \omega_{TVC} = 70 \text{ rad/s}, \quad \zeta_{TVC} = 0.7, \quad (4)$$

in series with a pure transport delay $\tau = 20$ ms. The delay is approximated by a third-order Padé rational function $e^{-\tau s} \approx P_3(s)$, the diagonal [3/3] member of the family obtained by matching the Taylor expansion of $D(s)e^{-\tau s} = N(s)$ to the highest possible order; the illustrative second-order form is

$$e^{-\tau s} \approx \frac{12 - 6\tau s + (\tau s)^2}{12 + 6\tau s + (\tau s)^2}, \quad (5)$$

an **all-pass** rational function ($|P(j\omega)| = 1$ for all ω) that reproduces the phase lag of the delay while leaving the loop gain unchanged. I keep order three, matching the implementation, so that the approximation stays accurate up to the bending frequency, where $\omega_{BM}\tau \approx 0.38$ is no longer negligible [4]. Parameters at $t = 72$ s are read from the reference data set **GreensiteLPV_DATA.mat** (cross-checked against Table 1 of the assignment); the salient values are reported in Table 1.

Table 1: Pitch-plane LV parameters at the max- $\bar{q}$ condition ($t = 72$ s).

Quantity	Symbol	Value
Aerodynamic moment	$A_6 = \mu_\alpha$	3.382 s^{-2}
Control effectiveness	$K_1 = \mu_c$	4.565 s^{-2}
Drift coefficients	a_1, a_3, a_4	$-0.0154, 20.61, -27.27 \text{ s}^{-2}$
Relative velocity	V	937.7 m/s
Bending mode	ω_{BM}, ζ_{BM}	$18.9 \text{ rad/s}, 0.005$
INS coupling	$\phi_{1,ins} [-], \sigma_{1,ins} [\text{rad/m}]$	$0.8, 0.178$
TVC actuator	$\omega_{TVC}, \zeta_{TVC}, \tau$	$70 \text{ rad/s}, 0.7, 20 \text{ ms}$

1.3 Control architecture

A proportional–derivative attitude law is adopted, augmented by a weak feedback on the lateral-drift channel:

$$\delta_{cmd} = K_{P,\theta} (\theta_{ref} - \theta_m) - K_{D,\theta} \dot{\theta}_m - K_{P,z} z_m - K_{D,z} \dot{z}_m, \quad (6)$$

with $K_{P,z}, K_{D,z}$ small and negative, of order 10^{-3} , as recommended in the assignment guidelines. Closing the loop also on $(z_m, \dot{z}_m)$ trades between two classical objectives in wind: containing the lateral drift (drift minimum) and containing the angle of attack $\alpha = \theta + \dot{z}/V + \alpha_w$, hence the structural load $\bar{q} \alpha$ (load minimum) [5, Lecture 17] — the binding concern at the max- $\bar{q}$ condition studied here. The weak negative gains keep the drift bounded without fighting the natural load-relieving weathercock of the airframe; I therefore monitor both z and $\bar{q} \alpha$ in the gust simulations. The actual deflection follows from the actuator and the bending filter $H_x(s)$ (Task 2): $\delta = W_{TVC}(s) e^{-\tau s} H_x(s) \delta_{cmd}$.

1.4 A note on conditional stability

Because the open-loop airframe carries a single right-half-plane pole ($P_R = 1$, the $+1.84 \text{ rad/s}$ aerodynamic pole), the loop is **conditionally stable**. By the Nyquist criterion $N = P_R - Z_R$, closed-loop stability ($Z_R = 0$) demands exactly one counter-clockwise encirclement of the critical point, so stability is lost if the loop gain is reduced below a threshold, not only if it is increased [3, Eq. (9.4.12), Figs. 9.17–9.18]. An aerodynamically unstable vehicle driven through a second-order (or higher) actuator therefore has two gain margins—a low-frequency aerodynamic margin (reduce gain $\rightarrow$ unstable) and a high-frequency rigid-body margin (increase gain $\rightarrow$ unstable)—which on the Nichols chart show up as two 0 dB crossings of the -180° line. I therefore read the **margin** routine in magnitude, and the assignment targets $|GM| \approx 6 \text{ dB}$ and $|PM| \approx 30^\circ$ refer to this finite stable gain band. This is standard practice for the attitude control of aerodynamically unstable launchers [6, 4].

2 Task 1 — Rigid Launch Vehicle

Figure 1 sketches the design pipeline of `main_task1.m`, which Tasks 2 and 3 reuse with richer plant and actuator models.




Figure 1: Task 1 design pipeline (`main_task1.m`). Tasks 2 and 3 reuse it with the full flexible plant and the TVC+delay+notch chain `Wact`. Listing numbers refer to Appendix A.

2.1 Rigid model and loop

Neglecting the bending mode, the plant reduces to the four states $[z, \dot{z}, \theta, \dot{\theta}]$ (`build_plant_rigid.m`, Listing 1) and the actuator is taken as ideal: $W_{TVC}(s) = 1$ and no transport delay. The open-loop transfer broken at the TVC deflection, in the $1 + L$ convention, is obtained by closing the static PD law of Eq. (6) around the plant (`assemble_loop`, Listing 2):

$$L(s) = K_{P,\theta} G_{\delta \rightarrow \theta}(s) + K_{D,\theta} G_{\delta \rightarrow \dot{\theta}}(s) + K_{P,z} G_{\delta \rightarrow z}(s) + K_{D,z} G_{\delta \rightarrow \dot{z}}(s), \quad (7)$$

where $G_{\delta \rightarrow \bullet}$ are the plant channels from δ to each measurement. The dominant term is the pitch loop $L_\theta(s) = (K_{P,\theta} + K_{D,\theta}s) K_1 / (s^2 - A_6)$, whose closed-loop characteristic polynomial $s^2 + K_1 K_{D,\theta} s + (K_1 K_{P,\theta} - A_6)$ is stable only for $K_{P,\theta} > A_6 / K_1 = 0.74$ and $K_{D,\theta} > 0$, so the proportional gain has to overcome the aerodynamic instability.

2.2 Tuning

The pitch gains were tuned (by a small `fminsearch` wrapper around the margin computation) to meet the assignment targets, while the lateral gains were fixed at

$K_{P,z} = K_{D,z} = -10^{-3}$. The resulting design is

$$K_{P,\theta} = 1.98, \quad K_{D,\theta} = 1.40, \quad K_{P,z} = K_{D,z} = -10^{-3}, \quad (8)$$

with margins $|GM| = 6.0$ dB at 0.34 rad/s and $|PM| = 30^\circ$ at 0.21 rad/s. In the pole-placement language of the course notes [5, Lecture 15] the retained gains place the dominant pitch pair at $\omega_c = \sqrt{K_1 K_{P,\theta} - A_6} = 2.4$ rad/s — inside the usual 1–4 rad/s control band — with an equivalent damping $\zeta = K_1 K_{D,\theta} / (2\omega_c) = 1.34$. That sits above the 0.7–0.8 pole-placement range because here the damping is set by the phase-margin target, not by a step-response specification.

These relations invert the closed-loop characteristic polynomial: matching $s^2 + K_1 K_{D,\theta} s + (K_1 K_{P,\theta} - A_6)$ to $s^2 + 2\zeta\omega_c s + \omega_c^2$ gives the proportional–derivative design equations

$$K_{P,\theta} = \frac{\omega_c^2 + A_6}{K_1}, \quad K_{D,\theta} = \frac{2\zeta\omega_c}{K_1}, \quad (9)$$

the form tabulated by Barrows and Orr for TVC attitude control [3, Eqs. (9.2.37)–(9.2.38)]. The same reference gives a closed-form estimate of the low-frequency aerodynamic gain margin, $GM_a \approx 20 \log_{10}(K_1 K_{P,\theta} / A_6) = 20 \log_{10}(4.565 \times 1.98 / 3.382) \approx 8.5$ dB [3, Eq. (9.2.39)]; this single-channel figure sits a couple of dB above the $|GM| = 6.0$ dB returned by `margin` on the full four-state loop, the difference coming from the weak drift channel and the conditionally-stable low-frequency reading. The gains themselves came from the `fminsearch` wrapper minimising the equal-weight margin miss $(|GM| - 6)^2 + (|PM| - 30)^2$ from the initial guess [2.0, 1.4], so the reported (1.98, 1.40) is the local minimiser of that objective. The Nichols chart of Figure 2 shows the curve passing between the two critical points $(-180^\circ, 0$ dB) and $(-540^\circ, 0$ dB) — which is what conditional stability looks like, the two crossings being the 360° wraps of the single-encirclement Nyquist condition $N = P_R = 1$ of Section 1 — and clearing the 6 dB closed-loop contour; the markers locate the phase and gain crossovers where the margins are read.




Figure 2: Task 1 — Nichols chart of the rigid open-loop transfer. The loop is conditionally stable; the design meets $|GM| \approx 6$ dB and $|PM| \approx 30^\circ$ (markers at the crossover frequencies).

2.3 Wind-gust response

The closed loop is excited by a deterministic “1-cosine” wind gust whose amplitude ($V_g = 6.4$ m/s) is taken from the reference dry-wind dispersion (`drywind.mat`, severe regime) at the current altitude, converted to a wind angle of attack $\alpha_w = v_w/V$ with a peak of 0.39° . The four key time histories requested by the assignment are shown in Figure 3: the pitch attitude peaks at 0.139° , the TVC deflection at 0.38° , and the lateral drift builds up smoothly to 2.5 m, which is what the weak drift feedback gives. The response is well damped and the actuator effort stays small.




Figure 3: Task 1 — response to a severe wind gust: pitch attitude θ , lateral drift z , drift rate $\dot{z}$ and TVC deflection δ .

Since $\max \bar{q}$ is the load-critical point of the trajectory, the total angle of attack $\alpha = \theta + \dot{z}/V + \alpha_w$ and the structural-load indicator $\bar{q}\alpha$ are also monitored (Figure 4). The attitude loop pitches the vehicle slightly into the wind ($\theta \rightarrow -0.14^\circ$ at the gust peak), so the peak total incidence, 0.31° , ends up below the wind contribution alone — a mild load-relieving action. With $\bar{q} = 81$ kPa the peak load indicator is $\bar{q}\alpha = 25$ kPa deg, the incidence remaining an order of magnitude below the few-degree load limit typical of a slender launcher, so at this gust level the drift-minimum-oriented gain choice does not conflict with the load-minimum requirement.

This drift-versus-load tension is the standard trade in launch-vehicle wind control [2, Sec. 3.1]. The characteristic equation of the rigid airframe in wind is a cubic with two oscillatory rigid-body roots plus one real drift (flight-path) root; the final-value theorem applied to a step gust gives a steady drift rate $\dot{z}_{ss} = -V\alpha_w$, independent of the gains — which is why the lateral drift of Figure 3 accumulates smoothly rather than being nulled. Two limiting cases bracket the design. The **drift-minimum** condition (drift-channel coefficient $B_0 = 0$) holds the trajectory dispersion down. The **load-minimum** condition ($K_{P,\theta} = 0$, so the steady incidence $\alpha_{ss} = 0$) minimises $\bar{q}\alpha$, but pays for it with a slow unstable drift mode. The weak negative drift gains I used here are a small step toward the drift-minimum end of this trade.




Figure 4: Task 1 — angle-of-attack budget $\alpha = \theta + \dot{z}/V + \alpha_w$ (left) and aerodynamic load indicator $\bar{q} \alpha$ (right) during the severe gust.

3 Task 2 — Full Launch Vehicle Model

Task 2 reintroduces the full dynamics of Eq. (1): the lightly damped first bending mode, the second-order TVC actuator of Eq. (4) with its 20 ms delay, and the INS measurement model of Eq. (3). I built the design up incrementally, as the assignment guidelines suggest, keeping the Task 1 PD gains fixed throughout. The guideline note says retuning is usually unnecessary, and that holds here.

3.1 Step B — uncompensated full model

Adding the TVC, delay and bending mode to the Task 1 controller leaves the low-frequency margins almost untouched, but the bending resonance shows up in the loop at $|L(\omega_{BM})| = +39$ dB. With a damping of only $\zeta_{BM} = 0.005$ this peak encircles the critical point and the closed loop goes **unstable** (a closed-loop pole at $\text{Re}(s) = +5.6$). The red curve in Figure 5 shows the bending loop crossing into the unstable region.

3.2 Step C — bending filter trade study

The guideline filter of Eq. 4 admits two readings: as printed (negative numerator damping, a non-minimum-phase **lead-lag** that phase-stabilises the resonance by rotating it on the Nichols chart) or in its minimum-phase variant (a band-reject **notch** that gain-stabilises the resonance by driving it below 0 dB) [5, Lecture 18]. Instead of picking one up front, I compare four candidates with the same fixed PD gains (all built by `build_notch_filter.m`, Listing 3); Table 2 collects the resulting margins (rigid-body and minimum gain margin, phase margin, delay margin on top of the 20 ms already modelled, and the residual loop gain at the bending frequency).

- **C-LL — Eq. 4 lead-lag alone.** The filter is swept over the ranges suggested in the assignment ($\zeta_{x,N} \in [0.1, 0.3]$, $\zeta_{x,D} \in [0.4, 0.6]$, $\omega_x = \omega_{BM} \pm 4$ rad/s, 75 combinations): none stabilises the loop. The least-unstable combination ($\omega_x = 18.9$, $\zeta_{x,N} = 0.10$, $\zeta_{x,D} = 0.60$) still leaves a closed-loop pole at $\text{Re}(s) = +0.16$ — the green curve in Figure 5 shows its bending lobe still pinned to the critical region. Phase rotation alone cannot rescue a +39 dB resonance here.
- **C-N — deep minimum-phase notch.** Gain stabilisation needs more than 39 dB of attenuation at ω_{BM} , which forces the numerator damping far below the suggested range: $\zeta_{x,N} = 0.002$, $\zeta_{x,D} = 0.7$ give a -51 dB null and drive $|L(\omega_{BM})|$ to -12 dB. The depth follows the closed-form attenuation of a second-order notch, $K_{\text{notch}} = 20 \log_{10}(\zeta_{x,N}/\zeta_{x,D})$, so that $20 \log_{10}(0.002/0.7) \approx -51$ dB at ω_{BM} [7, Eq. (3.18)]; pulling a +39 dB peak below 0 dB requires $\zeta_{x,N}/\zeta_{x,D} \leq 10^{-39/20} \approx 0.011$, i.e. $\zeta_{x,N} \lesssim 0.008$ with $\zeta_{x,D} = 0.7$, which is why the sizing

has to leave the assignment’s suggested $\zeta_{x,N} \in [0.1, 0.3]$ range. I keep the null narrow because the bending frequency sits only a decade above the rigid crossover ($\omega_{BM}/\omega_c \approx 8$): a wide band-reject section would leak phase lag into the conditionally stable low-frequency region.

- **C-T — notch triplet.** The notch-triplet recipe against bending-frequency uncertainty places three cascaded notches at $\{0.9, 1.0, 1.1\} \omega_{BM}$ [7, Eq. (3.19), Fig. 3.11]. Sized to the same depth, however, the three wide ($\zeta_{x,D} = 0.7$) sections pile up about 30° of phase lag at the rigid crossover and the conditionally stable loop goes unstable at nominal ($|PM|$ collapses to 11.6°). This matches the course view: the triplet belongs to the higher, well-separated modes, while the first mode — too close to the control band — has to be handled either with an exact notch or by phase stabilisation.
- **C-NLL — notch + lead-lag.** Reading the guideline literally (“the Notch filter and possibly other filters”), the deep notch is cascaded with the Eq. 4 lead-lag, the partner swept over the same ranges: 31/75 combinations now stabilise the loop. The best one ($\omega_x = 22.9$, $\zeta_{x,N} = 0.10$, $\zeta_{x,D} = 0.40$, selected for maximum delay margin) is stable but with clearly thinner nominal margins ($|PM| = 9.2^\circ$, $\min |GM| = 0.7$ dB). Its payoff shows up in the robustness analysis below.

Table 2: Task 2 — bending-filter trade with fixed Task-1 PD gains.

Candidate	rigid $ GM $ [dB]	min $ GM $ [dB]	$ PM $ [$^\circ$]	DM [ms]	$ L(\omega_{BM}) $ [dB]	stable
B (no filter)	6.34	6.34	30.8	—	+38.8	no
C-LL (lead-lag)	6.58	0.61	9.0	—	+23.2	no
C-N (deep notch)	6.58	1.81	26.5	58.8	−12.1	yes
C-T (triplet)	7.07	1.48	11.6	—	−46.0	no
C-NLL (notch+LL)	6.72	0.73	9.2	21.9	−18.3	yes

I keep the **deep notch**: it gain-stabilises the resonance while preserving the rigid-body margins ($|GM| = 6.6$ dB, $|PM| = 26.5^\circ$ — a few degrees below the 30° of the ideal-actuator loop of Task 1, the difference being the phase lag of the second-order TVC and the 20 ms transport delay), leaves a 58.8 ms delay margin, and needs no retuning of the PD gains, in line with the guideline note. The bending mode itself stays at its lightly damped but stable open-loop location. One caveat: the minimum gain margin of the stabilised loop, set by the bending shoulder, is 1.8 dB — fine for this exercise but well below the ≥ 12 dB of gain margin (and 45° of phase margin) usually required of gain-stabilised bending modes, as opposed to the 6 dB/ 30° rigid-body figure [3, p. 279]. The tougher bending requirement comes from the larger modelling uncertainty and latency sensitivity at high frequency. Getting the deeper margin would cost a stiffer notch or a retuned loop gain.




Figure 5: Task 2 — bending-filter trade on the Nichols chart (phase wrapped): without compensation the +39 dB resonance destabilises the loop (red); the best Eq.-4 lead-lag alone rotates the bending lobe but cannot clear the critical region (green); the deep notch gain-stabilises it and restores the rigid margins (blue).

3.3 Sensitivity to the bending-frequency knowledge

The deep notch pays for its performance with a -51 dB null only 0.08 rad/s wide, i.e. it assumes ω_{BM} is known exactly — true in this exercise, where the LPV dataset provides it, but never true in practice, which is why the course notes prescribe the $\pm 10\%$ triplet. Table 3 makes the trade explicit: each filter is held fixed while the true plant bending frequency is perturbed. The notch tolerates barely -5% ; the notch+lead-lag combination, by phase-stabilising whatever leaks past the detuned notch, recovers nearly the full $\pm 10\%$ band at the cost of the thin nominal margins seen above. In a flight design, where ω_{BM} drifts with propellant depletion, the robust variant (or a retuned phase-stabilised loop) would be mandatory; for this max- $\bar{q}$ snapshot I keep the exact notch.

Table 3: Task 2 — closed-loop stability with the filters fixed and the true bending frequency perturbed by up to $\pm 10\%$.

Candidate	$0.90\omega_{BM}$	$0.95\omega_{BM}$	ω_{BM}	$1.05\omega_{BM}$	$1.10\omega_{BM}$
C-N — deep notch	no	yes	yes	no	no
C-T — notch triplet	no	no	no	no	no
C-NLL — notch+lead-lag	no	yes	yes	yes	yes

3.4 Validation and comparison with the rigid model

The gust response of the stabilised full model is shown in Figure 6; all four assignment time histories remain well damped, with peaks $\theta = 0.132^\circ$, $z = 2.37$ m, $\delta = 0.39^\circ$ and a load indicator $\bar{q}\alpha = 24.9$ kPa deg, just below the rigid case. Because the notch is localised at the bending frequency and the TVC bandwidth (70 rad/s) is well above the control crossover, the full-model response is almost indistinguishable from the rigid one (Figure 7): the added dynamics affect stability robustness (the bending and delay margins) far more than nominal performance.




Figure 6: Task 2 — full-model response to the severe wind gust: pitch attitude θ , lateral drift z , drift rate $\dot{z}$ and TVC deflection δ .




Figure 7: Task 2 — rigid (Task 1) versus full-model gust response: pitch attitude, lateral drift and TVC deflection are nearly coincident.

3.5 A note on the tail-wags-dog zero

A second flexible effect bounds what any filter can achieve. The gimballed nozzle has its own inertia, so its angular acceleration reacts back on the airframe: at the **tail-wags-dog** (TWD) frequency

$$\omega_{TWD}^2 = -\frac{F_R X_G}{I_{EG} + X_G m_E l_E}, \quad (10)$$

nozzle deflection produces zero net vehicle response, a transmission zero that caps the achievable closed-loop bandwidth [3, Eq. (6.1.11)]. The $-\phi_{1,TVC} T_c$ entry in the bending-forcing column of Eq. (1) is the flexible-mode analogue of this nozzle-reaction term. My model treats the actuator as a stiff second-order block (Eq. (4)) and so neglects the nozzle back-reaction — the dog-wags-tail feedback, which would add the gimbal angle as an extra state. A higher-fidelity design would keep it, one of the extensions noted in the conclusions.

4 Task 3 — Robustness to Parametric Uncertainty

The aerodynamic moment $\mu_\alpha = A_6$ and the control effectiveness $\mu_c = K_1$ are treated as uncertain. The controller designed in Task 2 (PD gains plus bending notch) is held **fixed** and I assess its robustness over the four corner cases of the uncertainty box, i.e. the vertices V1–V4 obtained by independently varying μ_α and μ_c by $\pm 30\%$. Since each vertex perturbs both parameters at once, I also evaluate the four one-at-a-time variations S1–S4 ($\pm 30\%$ on a single parameter): they sit on the edge midpoints of the box rather than on its corners, but they attribute the observed effects to each parameter.

4.1 Frequency- and time-domain analysis

Table 4 collects, for every case, the rigid-body (low-frequency) gain margin, the smallest gain margin over the whole loop (governed by the bending shoulder), the phase margin, the delay margin, and the peak pitch and lateral-drift excursions to the same severe gust. All vertices stay stable: the fixed Task-2 controller tolerates the entire $\pm 30\%$ uncertainty box without re-design.

Table 4: Task 3 — margins and gust-response peaks: box vertices (V1–V4, the assignment corner cases) and one-at-a-time sensitivities (S1–S4).

Case	μ_α	μ_c	rigid $ GM $ [dB]	min $ GM $ [dB]	$ PM $ [°]	DM [ms]	peak θ [°]	peak z [m]
Nominal	1.00	1.00	6.58	1.81	26.5	58.8	0.132	2.37
V1	0.70	0.70	6.42	2.81	31.3	134.9	0.136	2.38
V2	0.70	1.30	11.68	0.88	11.3	19.2	0.061	1.67
V3	1.30	0.70	1.53	1.53	9.1	156.4	0.353	4.20
V4	1.30	1.30	6.66	0.93	12.3	21.3	0.130	2.36
S1	0.70	1.00	9.44	1.79	25.7	56.1	0.085	1.91
S2	1.30	1.00	4.47	1.83	22.1	61.8	0.187	2.88
S3	1.00	0.70	3.59	2.82	18.6	144.6	0.219	3.16
S4	1.00	1.30	8.79	0.91	11.8	20.2	0.093	2.01

The Nichols overlay over the nominal case and the four vertices (Figure 8) shows the curves clustering at low frequency and fanning out near the bending frequency; the time-domain overlay (Figure 9) shows the corresponding spread of the gust response.

4.2 Discussion

The sensitivities S1–S4 attribute the effects: μ_α moves the unstable airframe pole ($\pm 30\%$ shifts the rigid margin by roughly ∓ 2 –3 dB and scales the gust excursions), while μ_c scales the whole loop gain (+30% improves the rigid margin but pushes

the gain-stabilised bending shoulder 2.3 dB closer to 0 dB — the leading-order $20 \log_{10} 1.3 = 2.28$ dB loop-gain shift, only approximate because K_1 also scales the bending-forcing column of Eq. (1) and not merely the loop gain — and halves the delay margin). The vertices then combine these mechanisms:

- **V3** ($\mu_\alpha \uparrow, \mu_c \downarrow$) is the worst case for the rigid loop and for performance, because the two effects compound: the airframe is more unstable and the authority to fight it is reduced at the same time. The rigid gain margin collapses to 1.5 dB with $|PM| = 9.1^\circ$, and the gust excursions grow to 0.35° in pitch and 4.2 m of drift — roughly 60% beyond the worst one-at-a-time case (S3). This is why I test the actual vertices and not only the single-parameter variations.
- **V2 and V4** ($\mu_c \uparrow$) are the worst cases for the bending channel: the loop-gain increase squeezes the minimum gain margin to 0.9 dB and the delay margin to ~ 20 ms. The binding constraint in these corners is the flexible side of the loop, not the rigid one.
- **V1** ($\mu_\alpha \downarrow, \mu_c \downarrow$) is benign on both counts: the two reductions nearly cancel in the rigid loop and relax the bending shoulder.

So performance degradation is driven by μ_α and reduced by μ_c , while the bending channel loses stability margin as μ_c grows, and the worst-case combination V3 leaves single-digit margins. Because the margins are non-monotonic in μ_c (it helps the rigid loop while hurting the bending shoulder), the global worst case over the $\pm 30\%$ box need not sit on a vertex: the four corners and the one-at-a-time sensitivities are only a screening, and a denser grid or Monte-Carlo sweep would be needed to certify an interior worst case. The fixed classical design survives the whole box, but a requirement of, say, ≥ 3 dB and $\geq 10^\circ$ in every corner would already call for either gain scheduling on $\bar{q}$ or a robust-synthesis retune, the standard routes beyond a single fixed classical design [7]. That is the practical takeaway here.




Figure 8: Task 3 — Nichols overlay over the nominal case and the four uncertainty-box vertices.




Figure 9: Task 3 — wind-gust response over the nominal case and the four vertices: pitch attitude (left) and lateral drift (right).

5 Conclusions

I designed and validated a classical attitude control system for an aerodynamically unstable launch vehicle at the max- $\bar{q}$ condition, working entirely in the frequency domain.

- **Task 1.** A proportional–derivative attitude law with weak negative drift feedback stabilises the rigid airframe (open-loop pole at +1.84 rad/s) and meets the design targets $|GM| \approx 6$ dB, $|PM| \approx 30^\circ$. The loop is conditionally stable, and I kept that in mind when reading the margins.
- **Task 2.** Introducing the TVC actuator, the transport delay and the lightly damped bending mode destabilises the loop through a +39 dB resonance. A four-way filter trade showed that the Eq.-4 lead-lag alone never stabilises the loop within the suggested parameter ranges (0/75 combinations), and that a notch triplet sacrifices too much phase at low frequency for a conditionally stable loop; a deep gain-stabilising notch centred on ω_{BM} restores stability while preserving the rigid margins, with negligible change to the nominal gust response. I quantified how much it leans on knowing the bending frequency exactly ($\pm 5\%$ detuning is fatal) and found a robust notch+lead-lag variant that tolerates nearly $\pm 10\%$ at the price of thinner nominal margins.
- **Task 3.** The fixed Task 2 controller is robust to $\pm 30\%$ independent variations of μ_α and μ_c : all four vertices of the uncertainty box remain stable. Uncertainty on μ_α erodes the rigid margin and the gust performance, uncertainty on μ_c erodes the bending and delay margins, and the worst vertex (high μ_α with low μ_c) compounds them, leaving only 1.5 dB and 9° — the quantitative argument for gain scheduling in a flight design.

Limitations and extensions. Four modelling choices bound the scope of this design. (i) The pure proportional–derivative law leaves a steady-state attitude error to a constant gimbal misalignment, which a proportional–integral–derivative extension would null. (ii) The stiff second-order TVC model neglects the nozzle back-reaction (the dog-wags-tail feedback) and the hydraulic load-resonance of the actuator; retaining the gimbal angle as a state, together with the tail-wags-dog zero of Eq. (10) [3, Sec. 6.1], is the natural next fidelity step. (iii) Sensor placement relative to the bending-mode nodes matters as much as the filter — an aft gyro station flips the sign of the modal slope and can phase-stabilise a mode that would otherwise need a notch [2, Sec. 3.3.2.2] — whereas here the INS station is fixed and only the filter is traded. (iv) Propellant sloshing is omitted; it would add low-frequency, lightly damped modes coupling into the rigid loop and the drift channel.

The design shows the textbook trade-off of launch-vehicle attitude control [1, 6, 3]: enough gain to stabilise the unstable airframe, but not so much that it excites the structural modes, and the Nichols chart lets me see both constraints on one plot. A Simulink block-diagram mirror of the closed loop reproduces the script results and is documented in the accompanying `models/SIMULINK_GUIDE.md`.

A Implementation: Key Code Excerpts

The full MATLAB sources live in the HM3/ folder of the repository: `main_task1.m`–`main_task3.m` drive the three tasks, and the helper functions (`load_hw3_params`, `build_plant_rigid`, `build_plant_full`, `build_tvc`, `build_notch_filter`, `design_controller`, `assemble_loop`, `simulate_gust_response`) are shared across them. This appendix collects the three routines that set up the control problem: the rigid plant, the loop closure the Nichols analysis is drawn from, and the bending notch.

Listing 1 builds the rigid pitch-plane state-space model at the $\max\bar{q}$ condition by dropping the bending states from the assignment dynamics; the unstable airframe pole sits at $+\sqrt{A_6}$.

```
1 function G = build_plant_rigid(p)
2 %BUILD_PLANT_RIGID Rigid-body pitch-plane LV plant at max-qbar (Task 1).
3 %
4 % G = BUILD_PLANT_RIGID(p) returns a state-space model of the rigid LV
5 % obtained from Eq. (1) of the assignment by dropping the bending mode
6 % (eta, etadot). The 4 states are
7 %
8 % x = [z, zdot, theta, thetadot]'
9 %
10 % with inputs u = [delta, alpha_w]' (TVC deflection and wind angle of
11 % attack) and outputs
12 %
13 % y = [theta_m, thetadot_m, z_m, zdot_m, theta, z, zdot]'
14 %
15 % The first four are the INS measurements fed back to the controller
16 % (identical to the true states in the rigid case, since there is no
17 % bending contamination) and the last three are convenience signals for
18 % plotting. Parameters come from LOAD_HW3_PARAMS.
19 %
20 % See also BUILD_PLANT_FULL, LOAD_HW3_PARAMS.
21
22 A = [0 1 0 0;
23      0 p.a1 p.a1*p.V+p.a4 0;
24      0 0 0 1;
25      0 p.A6/p.V p.A6 0];
26
27 Bd = [0; p.a3; 0; p.K1]; % delta column
28 Bw = [0; -p.a1*p.V; 0; -p.A6]; % alpha_w column
29
30 % Outputs: [theta_m, thetadot_m, z_m, zdot_m, theta, z, zdot]
31 % state index: z=1 zdot=2 theta=3 thetadot=4
32 C = [0 0 1 0; % theta_m = theta
33      0 0 0 1; % thetadot_m= thetadot
34      1 0 0 0; % z_m = z
35      0 1 0 0; % zdot_m = zdot
36      0 0 1 0; % theta
37      1 0 0 0; % z
38      0 1 0 0]; % zdot
39 D = zeros(7, 2);
40
41 G = ss(A, [Bd Bw], C, D);
42 G.StateName = {'z', 'zdot', 'theta', 'thetadot'};
43 G.InputName = {'delta', 'alpha_w'};
44 G.OutputName = {'theta_m', 'thetadot_m', 'z_m', 'zdot_m', 'theta', 'z', 'zdot'};
45 G.Name = 'Plant_Rigid';
```

46 end

Listing 1: Rigid pitch-plane LV plant (build_plant_rigid.m).

Listing 2 closes the PD attitude and drift loop around the plant, optionally inserting the TVC, delay and notch chain through Wact, and returns the SISO open-loop transfer broken at the TVC deflection. This open-loop transfer is what the Nichols charts in Tasks 1–3 are built from.

```
36 % --- controller as a static gain block (named IO) ---
37 % u_pd = [Kp_th, -Kp_th, -Kd_th, -Kp_z, -Kd_z] * [theta_ref; theta_m; thetadot_m; z_m; zdot_m]
38 Kc = ss([K.Kp_th, -K.Kp_th, -K.Kd_th, -K.Kp_z, -K.Kd_z]);
39 Kc.InputName = {'theta_ref', 'theta_m', 'thetadot_m', 'z_m', 'zdot_m'};
40 Kc.OutputName = {'u_pd'};
41
42 % --- actuator / filter chain u_pd -> delta ---
43 Wa = ss(Wact);
44 Wa.InputName = {'u_pd'};
45 Wa.OutputName = {'delta'};
46
47 % --- closed loop, retaining 'delta' as an analysis point ---
48 T = connect(G, Kc, Wa, {'alpha_w', 'theta_ref'}, {'theta', 'z', 'zdot', 'delta'}, {'delta'});
49
50 % --- open-loop transfer at the break point 'delta' (1+L convention) ---
51 L = getLoopTransfer(T, 'delta', -1);
52 L = minreal(tf(L), 1e-6);
53
54 info = struct('Kc', Kc, 'Wact', Wa);
```

Listing 2: Loop closure and open-loop transfer for the Nichols analysis (assemble_loop.m).

Listing 3 is the second-order lead-lag / notch section used in Task 2 to stabilize the lightly damped first bending mode.

```
1 function Hx = build_notch_filter(wx, zN, zD, numSign)
2 %BUILD_NOTCH_FILTER Lead-lag / notch filter for bending stabilisation (Eq. 4).
3 %
4 % Hx = BUILD_NOTCH_FILTER(wx, zN, zD) returns the second-order filter of
5 % Eq. (4):
6 %
7 % Hx(s) = (s^2 + sgn*2*zN*wx*s + wx^2) / (s^2 + 2*zD*wx*s + wx^2)
8 %
9 % With the default sign sgn = -1 (as written in the assignment) the two
10 % numerator zeros sit in the right half-plane, so the section behaves as
11 % a non-minimum-phase phase-shaper: it introduces a targeted left/right
12 % shift of the bending resonance on the Nichols chart, which is what
13 % stabilises the lightly damped first bending mode.
14 %
15 % Recommended ranges (assignment guidelines):
16 % zN in [0.1, 0.3], zD in [0.4, 0.6], wx ~ WBM +/- 4 rad/s.
17 %
18 % Hx = BUILD_NOTCH_FILTER(wx, zN, zD, +1) uses the minimum-phase
19 % (symmetric notch) variant instead.
20 %
21 % See also BUILD_TVC, ASSEMBLE_LOOP.
22
23 arguments
24 wx (1,1) {mustBeNumeric, mustBeReal, mustBePositive}
```

```

25     zN (1,1) {mustBeNumeric, mustBeReal, mustBeNonnegative}
26     zD (1,1) {mustBeNumeric, mustBeReal, mustBePositive}
27     numSign (1,1) {mustBeMember(numSign, [-1, 1])} = -1
28 end
29
30 num = [1, numSign*2*zN*wx, wx^2];
31 den = [1,          2*zD*wx, wx^2];
32
33 Hx = tf(num, den);
34 Hx.Name = 'Notch_Hx';
35 end

```

Listing 3: Lead-lag / notch filter for bending stabilization (`build_notch_filter.m`).

References

- [1] A. L. Greensite. *Analysis and Design of Space Vehicle Flight Control Systems*. Spartan Books, New York, 1970.
- [2] A. L. Greensite. Analysis and design of space vehicle flight control systems. volume vii — attitude control during launch. Technical Report CR-826, NASA, Washington, DC, July 1967.
- [3] T. M. Barrows and J. S. Orr. *Dynamics and Simulation of Flexible Rockets*. Academic Press (Elsevier), London, 2020.
- [4] G. F. Franklin, J. D. Powell, and A. Emami-Naeini. *Feedback Control of Dynamic Systems*. Pearson, Upper Saddle River, NJ, 7th edition, 2015.
- [5] A. Zavoli. Dynamics and control of launch vehicles — course lecture notes. Graduate course, Sapienza University of Rome, 2026. Academic Year 2025/26.
- [6] B. Wie. *Space Vehicle Dynamics and Control*. AIAA Education Series, Reston, VA, 2nd edition, 2008.
- [7] D. Trotta. *Adaptive Control of Launch Vehicles in Atmospheric Flight*. PhD thesis, Sapienza University of Rome, Rome, Italy, 2021. Ph.D. in Aeronautics and Space Engineering, XXXIII cycle.