

Pipeline Task Manager

A terminal-native looking PyQt5 task manager with SQLite storage.

Setup

```
pip install PyQt5
python app.py
```

tasks.db is created automatically in the same directory on first run.

Features

Feature	Notes
Add / Edit tasks	Title, status, priority 1–10, effort (pts), scope, phase, description
Status system	1 Not Started · 2 In Progress · 3 Started · 4 Kinda Done · 5 Done
Priority	P1 = Critical (red) · P4–6 = Medium (yellow) · P7–10 = Low (green)
Scope	Backend · Frontend · Agent · DB · Compiler · All (multi-select)
Comments	Per-task threaded comments with timestamps
Audit log	Every field change, creation, deletion, and comment is tracked
Filter & sort	Search, status filter, scope filter, sort by any column
What's Next	Smart view: incomplete tasks sorted by priority + effort
Bulk import	Paste or load CSV/JSON — see format below
Export	Export all tasks to CSV
Right-click menu	Quick mark Done / In Progress / Delete from table
Keyboard shortcuts	Ctrl+N = new task · Ctrl+R = refresh

Bulk Import Format

CSV

```
title,description,priority,status,effort,scope,phase
Fix log viewer,,1,1,2,Frontend,Phase 1
Add retry logic,Retry on failure,3,2,5,"Backend,Agent",Phase 2
```

First row must be the header. All fields except title are optional.

JSON

```
[
  {
    "title": "Fix log viewer",
    "description": "",
    "priority": 1,
    "status": 1,
    "effort": 2,
    "scope": "Frontend",
    "phase": "Phase 1"
  }
]
```

Field reference:

Field	Values
priority	1 (highest) – 10 (lowest)
status	1=Not Started, 2=In Progress, 3=Started, 4=Kinda Done, 5=Done
effort	Integer (story points)
scope	Comma-separated: Backend, Frontend, Agent, DB, Compiler, All
phase	Any string

Data Storage

Everything is stored in `tasks.db` (SQLite) in the same directory as `app.py` .

Tables: `tasks` · `comments` · `audit_log`