

CSC 216 Portfolio 1

Nicolas Nytko

Sep 9, 2016

Contents

1	Homework	3
1.1	Linked Lists	3
1.1.1	Problem R-3.7	3
1.1.2	Problem R-3.10	3
1.1.3	Problem C-3.3	4
1.1.4	Problem C-3.4	4
1.1.5	Problem C-3.5	4
1.1.6	Problem C-3.8	5
1.1.7	Problem C-3.9	5
1.1.8	Problem C-3.10	5
1.1.9	Problem C-3.11	5
1.1.10	Problem C-3.22	5
1.1.11	Problem C-3.23	5
2	Projects	7
2.1	Encryption Cipher	7
2.1.1	Compiler Environment	7
2.1.2	Source	7
2.1.3	Compiler Output	14
2.1.4	Program Output	14
3	Labs	15
3.1	Game Highscores	15
3.1.1	Compiler Environment	15
3.1.2	Source	15
3.1.3	Compiler Output	21
3.1.4	Program Output	21
3.2	Matrix Class	21
3.2.1	Compiler Environment	21
3.2.2	Source	22
3.2.3	Compiler Output	24
3.2.4	Program Output	24
3.3	Sort Int Array	25
3.3.1	Compiler Environment	25
3.3.2	Source	25
3.3.3	Compiler Output	26
3.3.4	Program Output	26

1 Homework

1.1 Linked Lists

1.1.1 Problem R-3.7

Give an algorithm for finding the penultimate (second to last) node in a singly linked list where the last element is indicated by a null next link.

Listing 1: ../hw/r-3.7.cpp

```
1 node* getPenultimateNode( node* pStart )
2 {
3     // Check to see if our starting node is NULL or not
4
5     if ( pStart != NULL )
6     {
7         // Make sure we have more than 1 node
8
9         if ( pStart->next == NULL )
10             return pStart;
11
12         node* pCurrent = pStart;
13
14         while ( pCurrent->next->next != NULL ||
15                ( pCurrent->next->next == NULL && pCurrent->next != NULL ) )
16         {
17             pCurrent = pCurrent->next;
18         }
19
20         return pCurrent;
21     }
22     else
23     {
24         return NULL;
25     }
26 }
```

1.1.2 Problem R-3.10

Describe a nonrecursive function for finding, by link hopping, the middle node of a doubly linked list with header and trailer sentinels. (Note: This function must only use link hopping; it cannot use a counter.) What is the running time of this function?

Listing 2: ../hw/r-3.10.cpp

```
1 node* getMiddleNode( list* pList )
2 {
3     if ( pList == NULL )
4         return NULL;
5
6     // Have two nodes, one that starts at the beginning of the list and one that
7     // starts at the end
8
9     node* pStart, pEnd;
10    pStart = list->start;
11    pEnd = list->end;
```

```

12 // Loop until the nodes "intersect" and point to the same data
13
14 while ( !( pStart == pEnd || ( pStart->next == pEnd && pEnd->prev == pStart ) )
15 {
16     pStart = pStart->next;
17     pEnd = pEnd->prev;
18 }
19
20 return pStart;
21 }

```

1.1.3 Problem C-3.3

Let A be an array of size $n \geq 2$ containing integers from 1 to $n - 1$, inclusive, with exactly one repeated. Describe a fast algorithm for finding the integer in A that is repeated.

Listing 3: ../hw/c-3.3.cpp

```

1 int getRepeatNumber( int* pArray, size_t nLength )
2 {
3     bool bFound = false;
4     int nRepeat = -1;
5
6     for ( size_t i=0; i < nLength && !bFound; i++ )
7     {
8         for ( size_t j=i+1; j < nLength && !bFound; j++ )
9         {
10             if ( pArray[i] == pArray[j] )
11             {
12                 nRepeat = pArray[i];
13                 bFound = true;
14             }
15         }
16     }
17
18     return nRepeat;
19 }

```

1.1.4 Problem C-3.4

Let B be an array of size $n \geq 6$ containing integers from 1 to $n - 5$, inclusive, with exactly five repeated. Describe a good algorithm for finding the five integers in B that are repeated.

Sort B . Create a variable that holds how many times the current value has been repeated, and a variable to hold what the last value was. Loop through the array and increment the repeat variable every time the value has been repeated, and reset it to 0 when a new value is introduced. End when the repeat value reaches 5.

1.1.5 Problem C-3.5

Suppose you are designing a multi-player game that has $n \geq 1000$ players, numbered 1 to n , interacting in an enchanted forest. The winner of this game is the first player who can meet all the other players at least once (ties are allowed Assuming that there is a function

meet(i, j), which is called each time a player i meets a player j (with $i \neq j$), describe a way to keep track of the pairs of meeting players and who is the winner.

Create a two dimensional boolean array with the x axis corresponding to the index of the player, and the y axis corresponding to whether that person was met. So to see if player x has met player y, check array index $p[x][y]$. If a full column is filled, then that player has met everyone.

1.1.6 Problem C-3.8

Describe a good algorithm for concatenating two singly linked lists L and M , with header sentinels, into a single list L' that contains all the nodes of L followed by all the nodes of M . Create a new list L' and copy all of the nodes from L into it. At the end of L' , copy all of the nodes of M .

Copy all of the elements from L into L' . Start copying M at the last node of L' after the header sentinel and continue until the null pointer.

1.1.7 Problem C-3.9

Give a fast algorithm for concatenating two doubly linked lists L and M , with header and trailer sentinel nodes, into a single list L .

Remove L 's trailing sentinel and M 's header sentinel and save L 's last node and M 's first node, we will call them L' and M' respectively. Set L' next to M' , the previous of M' to L . The lists are now concatenated. Copy all the nodes from L into L' . Copy the nodes from M into the end of L' . Set the next

1.1.8 Problem C-3.10

Describe in detail how to swap two nodes x and y (and not just their contents) in a singly linked list L given references only to x and y . Repeat this exercise for the case when L is a doubly linked list. Which algorithm takes more time?

For a singly linked list: loop through until the nodes before x and y are found, label them x' and y' . Set x' next node to y , and y next to x original next. Set y' next node to x , and x next node to y original next.

For a doubly linked list: do the same thing except time is not needed to loop through and find the previous nodes. Don't forget to set the previous node values.

1.1.9 Problem C-3.11

Describe in detail an algorithm for reversing a singly linked list L using only a constant amount of additional space and not using any recursion.

Define n to be the size of the linked list. Loop $n-1$ times with iterator i starting at 0, and bring node $n-i$ backwards by swapping it $n-i$ times with the node previous. Save the previous node as a pointer variable.

1.1.10 Problem C-3.22

Suppose you are given two circularly linked lists, L and M , that is, two lists of nodes such that each node has a nonnull next node. Describe a fast algorithm for telling if L and M are really the same list of nodes but with different (cursor) starting points.

Create two node pointers, lowercase l and m , and set them to point to the head of L and M respectively. Loop through the list until l is equal to M and m is equal to L (they are the same list), or l is equal to L and m is equal to M (the whole list has been parsed and L and M are not the same list).

1.1.11 Problem C-3.23

Given a circularly linked list L containing an even number of nodes, describe how to split L into two circularly linked lists of half the size.

Given a circularly linked list L , define M to be the length of L divided by two. Create two node pointers, x and y , and have them point to the beginning of L and the node at M , respectively. For the last node in the first half ($M-1$), set its next node to the first node. For the first node in the first half (0), set its previous node to $M-1$. For node M , set its previous node to the last node in the list. Set the last node's next to M .

2 Projects

2.1 Encryption Cipher

Name: Nicolas Nytko

Course: CSC216

Activity: Encryption Cipher

Level: 5

Description: Write a program that can perform encryption and decryption using an arbitrary substitution cipher. In this case, the encryption array is a random shuffling of the letters in the alphabet. Your program should generate a random encryption array, its corresponding decryption array, and use these to encode and decode a message. Allow for the saving and loading of encrypted messages by storing the 26 letter encryption key amongst the n encoded characters of the message. Note that for an n character message, there will be $n + 1$ slots amongst them. For a 1-character message, for instance, there is a slot before the character and a slot after the character. For a 2-character message, there are slots before and after the first character and after the second character. And so on... Make sure the extra $26 \bmod (n + 1)$ letters from the encryption key are located carefully to make the spread nice and even. (Note that when the message is longer than 25 characters, each letter of the key is alone by itself and, in fact, you are spreading the characters of the message amongst the 27 slots around the key values now.)

2.1.1 Compiler Environment

Listing 4: environment

```
1 tex git:(master) pwd
2 /Users/nicolas/Git/portfolio1/tex
3 tex git:(master) uname -a
4 Darwin Nicolass-MacBook-Pro.local 16.0.0 Darwin Kernel Version 16.0.0: Mon Aug 29
   17:56:20 PDT 2016; root:xnu-3789.1.32~3/RELEASE_ARM_T8020 x86_64
5 tex git:(master) clang --version
6 Apple LLVM version 8.0.0 (clang-800.0.38)
7 Target: x86_64-apple-darwin16.0.0
8 Thread model: posix
9 InstalledDir: /Library/Developer/CommandLineTools/usr/bin
10 ~ harper-cpp --version
11 This is harper-cpp version 1.221 executing under perl v5.18.2 and compiling with:
12
13 Configured with: --prefix=/Library/Developer/CommandLineTools/usr --with-gxx-include
   -dir=/usr/include/c++/4.2.1
14 Apple LLVM version 8.0.0 (clang-800.0.38)
15 Target: x86_64-apple-darwin16.1.0
16 Thread model: posix
17 InstalledDir: /Library/Developer/CommandLineTools/usr/bin
```

2.1.2 Source

Listing 5: ../project/cipher/Makefile

```
1 CC=g++
2 OUTPUT=cipher.out
3 INPUT=main.cpp
4 CCFLAGS=
5
6 all:
```

```
7 $(CC) $(CFLAGS) -std=c++14 $(INPUT) -o $(OUTPUT)
```

Listing 6: ../project/cipher/main.cpp

```
1 #include <iostream>
2 #include <cmath>
3 #include <fstream>
4 #include <cstring>
5 #include <ctime>
6
7 class CipherKey
8 {
9 private:
10     static const unsigned long KEYLENGTH = 26;
11     char pKey[KEYLENGTH + 1]; // Plus one for the null terminator
12
13     unsigned long getKeyIndex( char c ) const
14     {
15         unsigned long nReturn = 0;
16
17         if ( !( c >= 'A' && c <= 'Z' ) )
18             return 0;
19
20         for ( unsigned long i=0; i < KEYLENGTH && nReturn == 0; i++ )
21         {
22             if ( c == pKey[i] )
23                 nReturn = i;
24         }
25
26         return nReturn;
27     }
28
29 public:
30     CipherKey( )
31     {
32         std::memset( pKey, 0, KEYLENGTH + 1 );
33     }
34
35     CipherKey( const CipherKey& pOther )
36     {
37         std::memcpy( pKey, pOther.pKey, KEYLENGTH );
38     }
39
40     CipherKey& operator=( const CipherKey& pOther )
41     {
42         std::memcpy( pKey, pOther.pKey, KEYLENGTH );
43
44         return *this;
45     }
46
47     void generate( unsigned int nSeed )
48     {
49         std::srand( nSeed );
50
51         for ( unsigned long i=0; i < KEYLENGTH; i++ )
52         {
53             pKey[i] = 'A' + static_cast<char>( i );
54         }
55     }
```



```

56     for ( unsigned long i=0; i < KEYLENGTH; i++ )
57     {
58         std::swap( pKey[i], pKey[ static_cast<unsigned int>( std::rand( ) ) %
                    KEYLENGTH ] );
59     }
60 }
61
62 void setKey( const char* pNewKey )
63 {
64     if ( strlen( pNewKey ) != KEYLENGTH )
65     {
66         std::cerr << "CipherKey::setKey(" << pNewKey << "): new key is not "
67                 << KEYLENGTH << "characters long." << std::endl;
68         return;
69     }
70
71     std::strncpy( pKey, pNewKey, KEYLENGTH + 1 );
72 }
73
74 std::string encrypt( const std::string& sEncrypt ) const
75 {
76     std::string sReturn;
77
78     for ( size_t i=0; i < sEncrypt.length( ); i++ )
79     {
80         char c = sEncrypt[i];
81
82         if ( std::islower( c ) )
83             c = static_cast<char>( std::toupper( c ) );
84
85         if ( std::isupper( c ) )
86             sReturn += pKey[ c - 'A' ];
87     }
88
89     return sReturn;
90 }
91
92 std::string decrypt( const std::string& sDecrypt ) const
93 {
94     std::string sReturn;
95
96     for ( size_t i=0; i < sDecrypt.length( ); i++ )
97     {
98         unsigned long nIndex = getKeyIndex( sDecrypt[i] );
99
100        sReturn += 'A' + static_cast<char>( nIndex );
101    }
102
103    return sReturn;
104 }
105
106 unsigned int getKeyLength( ) const
107 {
108     return KEYLENGTH;
109 }
110
111 const char* getKey( ) const
112 {
113     return pKey;

```

```

114     }
115 };
116
117 class FileCipher
118 {
119 private:
120     CipherKey pCipherKey;
121     std::string sMessage;
122
123 public:
124     FileCipher( ): pCipherKey( ), sMessage( "" )
125     {
126         pCipherKey.generate( static_cast<unsigned int>( std::time( NULL ) ) );
127     }
128
129     FileCipher( const std::string sSetMessage ): pCipherKey( ), sMessage(
        sSetMessage )
130     {
131         pCipherKey.generate( static_cast<unsigned int>( std::time( NULL ) ) );
132     }
133
134     FileCipher( const FileCipher& pOther ): pCipherKey( pOther.pCipherKey ),
135                                             sMessage( pOther.sMessage ) { }
136
137     FileCipher& operator=( const FileCipher& pOther )
138     {
139         pCipherKey = pOther.pCipherKey;
140         sMessage = pOther.sMessage;
141
142         return *this;
143     }
144
145     std::string getMessage( ) const
146     {
147         return sMessage;
148     }
149
150     void setMessage( std::string sNewMessage )
151     {
152         sMessage = sNewMessage;
153     }
154
155     std::string encrypt( ) const
156     {
157         return pCipherKey.encrypt( sMessage );
158     }
159
160     std::string decrypt( std::string sToDecrypt )
161     {
162         return pCipherKey.decrypt( sToDecrypt );
163     }
164
165     std::string encryptWithKey( ) const
166     {
167         std::string sEncrypted = encrypt( );
168         std::string sReturn = "";
169         const char* szKey = pCipherKey.getKey( );
170
171         double nCharsPerSlot = (double) pCipherKey.getKeyLength( ) /

```

```

172         ( sMessage.length( ) + 1 );
173     unsigned long nCurrentKey = 0;
174
175     /* Do first key pass */
176
177     for ( unsigned long i=nCurrentKey; i < nCharsPerSlot; i++, nCurrentKey++ )
178     {
179         sReturn += szKey[ nCurrentKey ];
180     }
181
182     /* Write all characters */
183
184     for ( unsigned long nChar=0; nChar < sMessage.length( ); nChar++ )
185     {
186         sReturn += sEncrypted[nChar];
187
188         /* Write keys after all message characters */
189
190         for ( ; nCurrentKey < static_cast<unsigned long>( nCharsPerSlot * (
191             nChar + 2 ) ); nCurrentKey++ )
192         {
193             sReturn += szKey[ nCurrentKey ];
194         }
195
196         /* Write any leftover keys */
197
198         for ( ; nCurrentKey < pCipherKey.getKeyLength( ); nCurrentKey++ )
199         {
200             sReturn += szKey[ nCurrentKey ];
201         }
202
203         return sReturn;
204     }
205
206     std::string decryptWithKey( std::string sEncrypted )
207     {
208         std::string sMsg, sKey;
209
210         unsigned long nChars = sEncrypted.length( ) - static_cast<unsigned long>(
211             pCipherKey.getKeyLength( ) );
212         double nCharsPerSlot = (double) pCipherKey.getKeyLength( ) /
213             ( nChars + 1 );
214
215         /* nCurrent is position in overall string, nCurrentKey is
216            * current part of the key */
217
218         unsigned long nCurrent=0, nCurrentKey = 0;
219
220         /* Do first key pass */
221
222         for ( ; nCurrentKey < nCharsPerSlot; nCurrentKey++ )
223         {
224             sKey += sEncrypted[nCurrent++];
225         }
226
227         /* Look at all characters */
228
229         for ( size_t nMsg = 0; nMsg < nChars; nMsg++ )

```

```

229     {
230         sMsg += sEncrypted[nCurrent++];
231
232         for ( ; nCurrentKey < static_cast<unsigned long>( nCharsPerSlot * ( nMsg
                + 2 ) ); nCurrentKey++ )
233         {
234             sKey += sEncrypted[nCurrent++];
235         }
236     }
237
238     /* Check any leftover keys */
239
240     for ( ; nCurrent < sEncrypted.length( ); nCurrent++ )
241     {
242         sKey += sEncrypted[nCurrent];
243     }
244
245     pCipherKey.setKey( sKey.c_str( ) );
246     sMessage = decrypt( sMsg );
247
248     return sMessage;
249 }
250
251 friend std::ostream& operator<<( std::ostream& pOutput, const FileCipher&
    pCipher )
252 {
253     pOutput << pCipher.encryptWithKey( ) << std::endl;
254
255     return pOutput;
256 }
257
258 friend std::istream& operator>>( std::istream& pInput, FileCipher& pCipher )
259 {
260     std::string sLine;
261     std::getline( pInput, sLine );
262
263     pCipher.decryptWithKey( sLine );
264
265     return pInput;
266 }
267 };
268
269 void printUsage( char* arg0 )
270 {
271     std::cout << "USAGE: " << arg0 << " -f <filename> [options]" << std::endl << std
        ::endl;
272     std::cout << "OPTIONS: " << std::endl;
273     std::cout << "    -f, --file\t\t\tFile to do operations on." << std::endl;
274     std::cout << "    -e, --encrypt <msg>\t\tEncrypts <msg> and saves it in file."
        << std::endl;
275     std::cout << "    -d, --decrypt\t\tDecrypts the message loaded from file." <<
        std::endl << std::endl;
276 }
277
278 enum ProgramStatus
279 {
280     STATUS_UNKNOWN,
281     STATUS_ENCRYPT,
282     STATUS_DECRYPT

```

```

283 };
284
285 int main( int argc , char** argv )
286 {
287     std::string sFile;
288     std::string sInputMsg;
289     ProgramStatus nStatus = STATUS_UNKNOWN;
290
291     if ( argc < 2 )
292     {
293         printUsage( argv[0] );
294         return 1;
295     }
296     else
297     {
298         bool bArgsGood = true;
299         int i = 1;
300
301         while ( i < argc && bArgsGood )
302         {
303             char* szArg = argv[i];
304
305             if ( szArg[0] != '-' )
306             {
307                 bArgsGood = false;
308             }
309             else
310             {
311                 if ( szArg[1] == 'f' || std::strcmp( szArg, "--file" ) == 0 )
312                 {
313                     sFile = argv[i+1];
314                     i += 2;
315                 }
316                 if ( szArg[1] == 'e' || std::strcmp( szArg, "--encrypt" ) == 0 )
317                 {
318                     nStatus = STATUS_ENCRYPT;
319                     sInputMsg = argv[i+1];
320
321                     i += 2;
322                 }
323                 if ( szArg[1] == 'd' || std::strcmp( szArg, "--decrypt" ) == 0 )
324                 {
325                     nStatus = STATUS_DECRYPT;
326                     i++;
327                 }
328             }
329         }
330
331         if ( !bArgsGood )
332         {
333             printUsage( argv[0] );
334             return 1;
335         }
336     }
337
338     FileCipher pCipher;
339
340     if ( nStatus == STATUS_ENCRYPT )
341     {

```

```

342         std::ofstream fOutput;
343
344         pCipher.setMessage( sInputMsg );
345         fOutput.open( sFile , std::ofstream::out );
346
347         fOutput << pCipher;
348
349         fOutput.close( );
350     }
351     else if ( nStatus == STATUS_DECRYPT )
352     {
353         std::ifstream fInput;
354
355         fInput.open( sFile , std::ifstream::in );
356         fInput >> pCipher;
357
358         std::cout << pCipher.getMessage( ) << std::endl;
359     }
360
361     return 0;
362 }

```

2.1.3 Compiler Output

Listing 7: ../project/cipher/compilerout

```

1     cipher git:(master)    make CC=harper.cpp
2 harper.cpp -std=c++14 main.cpp -o cipher.out
3 main.cpp***

```

2.1.4 Program Output

Listing 8: ../project/cipher/progout

```

1     cipher git:(master)    ./cipher.out
2 USAGE: ./cipher.out -f <filename> [options]
3
4 OPTIONS:
5     -f, --file           File to do operations on.
6     -e, --encrypt <msg>   Encrypts <msg> and saves it in file.
7     -d, --decrypt         Decrypts the message loaded from file.
8
9     cipher git:(master)    ./cipher.out -f file -e helloworld
10    cipher git:(master)    ./cipher.out -f file -d
11 HELLOWORLD
12    cipher git:(master)    ./cipher.out -f file -e goodmorningjasonjames
13    cipher git:(master)    ./cipher.out -f file -d
14 GOODMORNINGJASONJAMES

```

3 Labs

3.1 Game Highscores

Name: Nicolas Nytko

Course: CSC216

Activity: Game Highscores

Level: 4

Description: P-3.4. Store 10 game highscores in a doubly-linked list.

3.1.1 Compiler Environment

Listing 9: environment

```
1 tex git:(master) pwd
2 /Users/nicolas/Git/portfolio1/tex
3 tex git:(master) uname -a
4 Darwin Nicolass-MacBook-Pro.local 16.0.0 Darwin Kernel Version 16.0.0: Mon Aug 29
   17:56:20 PDT 2016; root:xnu-3789.1.32~3/RELEASE_ARM64_T8020 x86_64
5 tex git:(master) clang --version
6 Apple LLVM version 8.0.0 (clang-800.0.38)
7 Target: x86_64-apple-darwin16.0.0
8 Thread model: posix
9 InstalledDir: /Library/Developer/CommandLineTools/usr/bin
10 ~ harper_cpp --version
11 This is harper_cpp version 1.221 executing under perl v5.18.2 and compiling with:
12
13 Configured with: --prefix=/Library/Developer/CommandLineTools/usr --with-gxx-include
   -dir=/usr/include/c++/4.2.1
14 Apple LLVM version 8.0.0 (clang-800.0.38)
15 Target: x86_64-apple-darwin16.1.0
16 Thread model: posix
17 InstalledDir: /Library/Developer/CommandLineTools/usr/bin
```

3.1.2 Source

Listing 10: ../lab/highscores/main.cpp

```
1 #include <iostream>
2
3 /* P-3.4
4  * Write a class that maintains the top 10 scores for a game application,
5  * implementing the add and remove functions of Section 3.1.1, but use a
6  * doubly linked list. Your implementation of remove(i) should make the
7  * fewest number of pointer hops to get to the game entry at index i.
8  */
9
10 /**
11  * High score entry containing name and score.
12  */
13
14 class GameEntry
15 {
16 private:
17     std::string name;
18     int score;
19 }
```

```

20 public:
21     GameEntry( const std::string& setName="", int setScore=0 ): name( setName ),
        score( setScore ) { }
22     GameEntry( const GameEntry& pOther ): name( pOther.name ), score( pOther.score )
        { }
23
24     GameEntry& operator=( const GameEntry& pOther )
25     {
26         name = pOther.name;
27         score = pOther.score;
28
29         return *this;
30     }
31
32     std::string getName( ) const
33     {
34         return name;
35     }
36
37     int getScore( ) const
38     {
39         return score;
40     }
41
42     void setName( const std::string& sNewName )
43     {
44         name = sNewName;
45     }
46
47     void setScore( int nNewScore )
48     {
49         score = nNewScore;
50     }
51 };
52
53 /**
54  * Linked-list node.
55  */
56
57 class ListNode
58 {
59 private:
60     GameEntry pData;
61     class ListNode* pPrev, *pNext;
62
63 public:
64     ListNode( ): pPrev( NULL ), pNext( NULL ) { }
65
66     ListNode( const GameEntry& pSetData ): pData( pSetData ),
67         pPrev( NULL ),
68         pNext( NULL ) { }
69
70     ListNode( const ListNode& pOther ): pData( pOther.pData ),
71         pPrev( pOther.pPrev ),
72         pNext( pOther.pNext ) { }
73
74     ListNode& operator=( const ListNode& pOther )
75     {
76         pData = pOther.pData;

```



```

77         pPrev = pOther.pPrev;
78         pNext = pOther.pNext;
79
80         return *this;
81     }
82
83     GameEntry& getData( )
84     {
85         return pData;
86     }
87
88     GameEntry getData( ) const
89     {
90         return pData;
91     }
92
93     friend class List;
94 };
95
96 /**
97  * Linked-list implementation class.
98  */
99
100 class List
101 {
102 private:
103     ListNode* pFirst, *pLast;
104     size_t nLength;
105
106     ListNode* getNode( size_t nIndex )
107     {
108         if ( nLength == 0 )
109             return NULL;
110
111         ListNode* pReturn;
112
113         if ( nIndex < nLength/2 )
114         {
115             pReturn = pFirst;
116
117             for ( size_t i=0; i < nIndex; i++ )
118             {
119                 pReturn = pReturn->pNext;
120             }
121         }
122         else
123         {
124             pReturn = pLast;
125
126             for ( size_t i=nLength-1; i > nIndex; i-- )
127             {
128                 pReturn = pReturn->pPrev;
129             }
130         }
131
132         return pReturn;
133     }
134
135 public:

```

```

136 List( ): pFirst( NULL ), pLast( NULL ), nLength( 0 )
137 {
138     pFirst = new ListNode;
139     pLast = pFirst;
140 }
141
142 List( const List& pOther ): pFirst( pOther.pFirst ),
143                             pLast( pOther.pLast ),
144                             nLength( pOther.nLength ) { }
145
146 List& operator=( const List& pOther )
147 {
148     pFirst = pOther.pFirst;
149     pLast = pOther.pLast;
150     nLength = pOther.nLength;
151
152     return *this;
153 }
154
155 ~List( )
156 {
157     if ( nLength != 0 )
158     {
159         for ( ListNode* pCurrent = pFirst;
160              pCurrent != NULL;
161              pCurrent = pCurrent->pNext )
162         {
163             delete pCurrent;
164         }
165     }
166 }
167
168 size_t getLength( ) { return nLength; }
169
170 GameEntry& get( size_t nIndex )
171 {
172     return getNode( nIndex )->getData( );
173 }
174
175 GameEntry& operator [] ( const size_t nIndex )
176 {
177     return getNode( nIndex )->getData( );
178 }
179
180 void push_back( const GameEntry& pData )
181 {
182     if ( nLength == 0 )
183     {
184         pFirst = new ListNode( pData );
185         pLast = pFirst;
186     }
187     else
188     {
189         ListNode* pTempNode = new ListNode( pData );
190         pLast->pNext = pTempNode;
191         pTempNode->pPrev = pLast;
192         pLast = pTempNode;
193     }
194 }

```

```

195         nLength++;
196     }
197
198     bool insert( size_t nIndex, const GameEntry& pData )
199     {
200         if ( nLength == 0 )
201         {
202             if ( nIndex != 0 )
203                 return false;
204
205             /* If theres no other nodes, call our push_back function */
206
207             push_back( pData );
208
209             return true;
210         }
211         else
212         {
213             if ( nIndex > nLength )
214                 return false; /* Fail if last node slot + 1 */
215
216             if ( nIndex == nLength )
217             {
218                 /* If we're trying to place at the last slot then call push_back */
219
220                 push_back( pData );
221                 return true;
222             }
223             else if ( nIndex == 0 )
224             {
225                 /* If we're trying to place at the beginning */
226
227                 ListNode* pSecond = pFirst;
228                 ListNode* pNewTemp = new ListNode( pData );
229
230                 pNewTemp->pNext = pSecond;
231                 pFirst = pNewTemp;
232
233                 nLength++;
234
235                 return true;
236             }
237             else
238             {
239                 /* Placing at an arbitrary point in the list */
240
241                 ListNode* pAt = getNode( nIndex );
242                 ListNode* pPrev = pAt->pPrev;
243                 ListNode* pNewTemp = new ListNode( pData );
244
245                 pNewTemp->pPrev = pPrev;
246                 pNewTemp->pNext = pAt;
247                 pAt->pPrev = pNewTemp;
248                 pPrev->pNext = pNewTemp;
249
250                 nLength++;
251
252                 return true;
253             }

```

```

254     }
255
256     return false;
257 }
258
259 bool remove( size_t nIndex )
260 {
261     if ( nLength == 0 )
262     {
263         /* Can't remove when there's already nothing */
264
265         return true;
266     }
267     else if ( nLength == 1 )
268     {
269         delete pFirst;
270         pFirst = NULL;
271         pLast = NULL;
272
273         return true;
274     }
275     else
276     {
277         if ( nIndex >= nLength )
278             return false;
279
280         /* If last node, remove and update the new last node */
281
282         if ( nIndex == nLength - 1 )
283         {
284             ListNode* pNewEnd = pLast->pPrev;
285             delete pLast;
286
287             pLast = pNewEnd;
288             pNewEnd->pNext = NULL;
289
290             return true;
291         }
292         else
293         {
294             /* Else, remove node and update next and previous nodes to point
295              * to each other */
296
297             ListNode* pPrev, *pNext, *pCurrent;
298             pCurrent = getNode( nIndex );
299             pPrev = pCurrent->pPrev;
300             pNext = pCurrent->pNext;
301
302             delete pCurrent;
303             pPrev->pNext = pNext;
304             pNext->pPrev = pPrev;
305
306             return true;
307         }
308     }
309 }
310 };
311
312 int main( )

```

```

313 {
314     List scores;
315
316     scores.push_back( GameEntry( "BOB", 50000 ) );
317     scores.push_back( GameEntry( "NIK", 42000 ) );
318     scores.push_back( GameEntry( "ASK", 36900 ) );
319     scores.push_back( GameEntry( "TUT", 31000 ) );
320     scores.push_back( GameEntry( "DAN", 20000 ) );
321
322     scores.insert( 0, GameEntry( "LOL", 65000 ) );
323     scores.insert( 6, GameEntry( "SUX", 100 ) );
324     scores.insert( 6, GameEntry( "BWA", 500 ) );
325     scores.insert( 6, GameEntry( "ASD", 1000 ) );
326     scores.insert( 6, GameEntry( "DSF", 2000 ) );
327
328     for ( size_t i=0; i < scores.getLength( ); i++ )
329     {
330         std::cout << i << ": " << scores[i].getName( ) << ": " << scores[i].getScore
331             ( ) << std::endl;
332     }
333     return 0;
334 }

```

3.1.3 Compiler Output

Listing 11: ../lab/highscores/compilerout

```

1      highscores git:(master)      make CC=harper_cpp
2 harper_cpp -std=c++14 main.cpp -o highscores.out
3 main.cpp***

```

3.1.4 Program Output

Listing 12: ../lab/highscores/progout

```

1      highscores git:(master)      ./highscores.out
2 0: LOL: 65000
3 1: BOB: 50000
4 2: NIK: 42000
5 3: ASK: 36900
6 4: TUT: 31000
7 5: DAN: 20000
8 6: DSF: 2000
9 7: ASD: 1000
10 8: BWA: 500
11 9: SUX: 100

```

3.2 Matrix Class

Name: Nicolas Nytko

Course: CSC216

Activity: Matrix Class

Level: 3

Description: P-3.2. Matrix class with multiplication and addition operators.

3.2.1 Compiler Environment

Listing 13: environment

```
1      tex git:(master)      pwd
2  /Users/nicolas/Git/portfolio1/tex
3      tex git:(master)      uname -a
4  Darwin Nicolass-MacBook-Pro.local 16.0.0 Darwin Kernel Version 16.0.0: Mon Aug 29
    17:56:20 PDT 2016; root:xnu-3789.1.32~3/RELEASE_ARM64_T8020 x86_64
5      tex git:(master)      clang --version
6  Apple LLVM version 8.0.0 (clang-800.0.38)
7  Target: x86_64-apple-darwin16.0.0
8  Thread model: posix
9  InstalledDir: /Library/Developer/CommandLineTools/usr/bin
10     ~ harper.cpp --version
11  This is harper.cpp version 1.221 executing under perl v5.18.2 and compiling with:
12
13  Configured with: --prefix=/Library/Developer/CommandLineTools/usr --with-gxx-include
    -dir=/usr/include/c++/4.2.1
14  Apple LLVM version 8.0.0 (clang-800.0.38)
15  Target: x86_64-apple-darwin16.1.0
16  Thread model: posix
17  InstalledDir: /Library/Developer/CommandLineTools/usr/bin
```

3.2.2 Source

Listing 14: ../lab/matrix/main.cpp

```
1  #include <iostream>
2  #include "matrix.hpp"
3
4  int main( )
5  {
6      Matrix<3,2> a = { 1, 2, 3, 4, 5, 6 };
7      Matrix<2,3> b = { 7, 8, 9, 10, 11, 12, 13 };
8      Matrix<2,3> c = { 14, 15, 16, 17, 18, 19 };
9
10     std::cout << "Matrices: " << std::endl;
11     std::cout << "a: " << a << std::endl << "b: " << b << std::endl << "c: "
        << c << std::endl << std::endl;
12
13     auto product = a * b;
14     auto sum = b + c;
15
16     std::cout << "a*b: " << product << std::endl;
17     std::cout << "b+c: " << sum << std::endl;
18
19     return 0;
20 }
```

Listing 15: ../lab/matrix/matrix.hpp

```
1  #ifndef LIB_MATRIX_HPP
2  #define LIB_MATRIX_HPP
3
4  #include <fstream>
5
6  /**
```

```

7  * Template class for an nRows by nCols matrix.
8  */
9
10 template <short nRows, short nCols>
11 class Matrix
12 {
13 private:
14     double dData[nRows*nCols];
15
16 public:
17     Matrix( )
18     {
19         for ( size_t i=0; i < nRows*nCols; i++ )
20         {
21             dData[i] = 0.0;
22         }
23     }
24
25     Matrix( std::initializer_list<double> dList )
26     {
27         for ( size_t i=0; i < dList.size( ) && i < nRows*nCols; i++ )
28         {
29             dData[i] = *( dList.begin( ) + i );
30         }
31     }
32
33     constexpr unsigned long getArea( ) const { return nRows*nCols; }
34     constexpr short getRows( ) const { return nRows; }
35     constexpr short getCols( ) const { return nCols; }
36     constexpr short getHeight( ) const { return nRows; }
37     constexpr short getWidth( ) const { return nCols; }
38
39     double& operator[]( const size_t nIndex )
40     {
41         if ( nIndex >= getArea( ) )
42             return dData[ getArea( ) - 1 ];
43
44         return dData[ nIndex ];
45     }
46
47     double& get( const size_t x, const size_t y )
48     {
49         return dData[ ( y * nCols ) + x ];
50     }
51
52     double get( const size_t x, const size_t y ) const
53     {
54         return dData[ ( y * nCols ) + x ];
55     }
56
57     Matrix<nRows,nCols> add( const Matrix<nRows,nCols>& mOther )
58     {
59         Matrix<nRows,nCols> mReturn;
60
61         for ( size_t i=0; i < getArea( ); i++ )
62         {
63             mReturn.dData[i] = dData[i] + mOther.dData[i];
64         }
65

```

```

66         return mReturn;
67     }
68
69     Matrix<nRows,nCols> operator+( const Matrix<nRows,nCols> & mOther )
70     {
71         return add( mOther );
72     }
73
74     template<short nCols2>
75     Matrix<nRows,nCols2> multiply( const Matrix<nCols,nCols2>& mOther )
76     {
77         /* Adapted from pseudocode on https://en.wikipedia.org/wiki/
78            Matrix_multiplication_algorithm */
79
80         Matrix<nRows,nCols2> mReturn;
81
82         for ( size_t i=0; i < nRows; i++ )
83         {
84             for ( size_t j=0; j < nCols2; j++ )
85             {
86                 double dSum = 0;
87
88                 for ( size_t k=0; k < nCols; k++ )
89                 {
90                     dSum += get( k, i ) * mOther.get( j, k );
91                 }
92
93                 mReturn.get( j, i ) = dSum;
94             }
95
96             return mReturn;
97         }
98
99         template<short nCols2>
100         Matrix<nRows,nCols2> operator*( const Matrix<nCols,nCols2>& mOther )
101         {
102             return multiply( mOther );
103         }
104
105         friend std::ostream& operator<<( std::ostream& stream, const Matrix& mMatrix )
106         {
107             stream << "(" << nRows << "x" << nCols << ")[";
108
109             for ( size_t i=0; i < mMatrix.getArea( ); i++ )
110             {
111                 stream << ' ' << mMatrix.dData[ i ];
112
113                 if ( ( i + 1 ) % nCols == 0 && i != mMatrix.getArea( )-1 )
114                     stream << ',';
115                 else
116                     stream << ' ';
117             }
118
119             stream << "];";
120
121             return stream;
122         }
123     };

```



```
124
125 #endif
```

3.2.3 Compiler Output

Listing 16: ../lab/matrix/compilerout

```
1      matrix git:(master)      make CC=harper.cpp
2 harper.cpp -std=c++14 main.cpp -o matrix.out
3 main.cpp***
```

3.2.4 Program Output

Listing 17: ../lab/matrix/progout

```
1      matrix git:(master)      ./matrix.out
2 Matrices:
3 a:   (3x2)[ 1  2, 3  4, 5  6 ]
4 b:   (2x3)[ 7  8  9, 10 11 12 ]
5 c:   (2x3)[ 14 15 16, 17 18 19 ]
6
7 a*b: (3x3)[ 27  30  33, 61  68  75, 95 106 117 ]
8 b+c: (2x3)[ 21  23  25, 27  29  31 ]
```

3.3 Sort Int Array

Name: Nicolas Nytko

Course: CSC216

Activity: Sort Int Array

Level: 3

Description: C-3.18. Write a short recursive C++ function that will rearrange an array of int values so that all the even values appear before the odd values.

3.3.1 Compiler Environment

Listing 18: environment

```
1      tex git:(master)      pwd
2 /Users/nicolas/Git/portfolio1/tex
3      tex git:(master)      uname -a
4 Darwin Nicolass-MacBook-Pro.local 16.0.0 Darwin Kernel Version 16.0.0: Mon Aug 29
   17:56:20 PDT 2016; root:xnu-3789.1.32~3/RELEASE_X86_64 x86_64
5      tex git:(master)      clang --version
6 Apple LLVM version 8.0.0 (clang-800.0.38)
7 Target: x86_64-apple-darwin16.0.0
8 Thread model: posix
9 InstalledDir: /Library/Developer/CommandLineTools/usr/bin
10     ~ harper.cpp --version
11 This is harper.cpp version 1.221 executing under perl v5.18.2 and compiling with:
12
13 Configured with: --prefix=/Library/Developer/CommandLineTools/usr --with-gxx-include
   -dir=/usr/include/c++/4.2.1
14 Apple LLVM version 8.0.0 (clang-800.0.38)
15 Target: x86_64-apple-darwin16.1.0
16 Thread model: posix
17 InstalledDir: /Library/Developer/CommandLineTools/usr/bin
```

3.3.2 Source

Listing 19: ../lab/sortint/main.cpp

```
1  #include <iostream>
2  #include <utility>
3
4  /* Recursively rearrange an array so that all even numbers
5   * will appear before odd ones. Rearranged array will not
6   * be sorted and is not stable */
7
8  void sort( int* pArray, size_t nLength )
9  {
10     long nEven = -1, nOdd = -1;
11
12     for ( long i=0; i < static_cast<long>( nLength ) && ( nEven == -1 || nOdd == -1 ); i++ )
13     {
14         if ( nEven == -1 && pArray[i] % 2 == 0 )
15             nEven = i;
16
17         if ( nOdd == -1 && pArray[i] % 2 == 1 )
18             nOdd = i;
19     }
20
21     if ( nEven != -1 && nOdd != -1 )
22     {
23         std::swap( pArray[nEven], pArray[nOdd] );
24     }
25
26     if ( nLength > 1 )
27     {
28         sort( pArray + 1, nLength - 1 );
29     }
30 }
31
32 template<typename T>
33 void printArray( T* pArray, size_t nLength )
34 {
35     for ( size_t i=0; i < nLength; i++ )
36     {
37         std::cout << pArray[i] << ' ';
38     }
39
40     std::cout << std::endl;
41 }
42
43 int main( )
44 {
45     const int LENGTH = 20;
46     int example[LENGTH] = { 1, 2, 3, 4, 5, 6, 7, 8, 9, 10,
47                             11, 12, 13, 14, 15, 16, 17, 18, 19, 20};
48
49     std::cout << "Array pre sorting:" << std::endl;
50     printArray( example, LENGTH );
51
52     sort( example, LENGTH );
53
54     std::cout << "Array post sorting:" << std::endl;
```

```
55     printArray( example, LENGTH );
56
57     return 0;
58 }
```

3.3.3 Compiler Output

Listing 20: ../lab/sortint/compilerout

```
1      sortint git:(master)      make CC=harper.cpp
2 harper.cpp -std=c++14 main.cpp -o sort.out
3 main.cpp***
```

3.3.4 Program Output

Listing 21: ../lab/sortint/progout

```
1      sortint git:(master)      ./sort.out
2 Array pre sorting:
3 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20
4 Array post sorting:
5 2 4 6 8 10 12 14 16 18 20 11 3 13 7 15 1 17 9 19 5
```