

Class 10: Comparative analysis of structures

Nicolò (PID: A18109144)

We need some new packages, these include `bio3d` and `msa`.

The `msa` package is from BioConductor. These packages focus on genomics type work and are managed by the `BioConductor` package.

Install `install.packages("BiocManager")` and then `BiocManager::install("msa")` all entered in the R “brain” console.

```
library(bio3d)

aa <- get.seq("lake_A")
```

Warning in `get.seq("lake_A")`: Removing existing file: `seqs.fasta`

Fetching... Please wait. Done.

```
aa
```

```

      1      .      .      .      .      .      60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLAAVKSGSELGKQAKDIMDAGKLV
      1      .      .      .      .      .      60

      61      .      .      .      .      .      120
pdb|1AKE|A  DELVIALVKERIAQEDCRNGFLLDGFPRTIPQADAMKEAGINVVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      120

     121      .      .      .      .      .      180
pdb|1AKE|A  VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG
     121      .      .      .      .      .      180

     181      .      .      .      214
```

```

pdb|1AKE|A    YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
          181          .          .          .    214

```

```

Call:
  read.fasta(file = outfile)

```

```

Class:
  fasta

```

```

Alignment dimensions:
  1 sequence rows; 214 position columns (214 non-gap, 0 gap)

```

```

+ attr: id, ali, call

```

Now I can search the PDB database for related sequences:

```

#b <- blast.pdb(aa)
#hits <- plot(b)

```

```

#attributes(b)
#head(b$hit.tbl)

```

These are the related structures in the PDB database that we found via a BLAST search...

```

hits <- NULL
hits$ pdb.id <- c('1AKE_A', '6S36_A', '6RZE_A', '3HPR_A', '1E4V_A', '5EJE_A', '1E4Y_A', '3X2S_A', '
hits$ pdb.id

```

```

[1] "1AKE_A" "6S36_A" "6RZE_A" "3HPR_A" "1E4V_A" "5EJE_A" "1E4Y_A" "3X2S_A"
[9] "6HAP_A" "6HAM_A" "4K46_A" "3GMT_A" "4PZL_A"

```

Side-note: let's annotate the structures (in other words find out what they are, what species they are from, stuff about the experiment they were solved in etc.)

For this we can use the `pdb.annotate()`

```

anno <- pdb.annotate(hits$ pdb.id)

```

```

# attributes(anno)
head(anno)

```

	structureId	chainId	macromoleculeType	chainLength	experimentalTechnique
1AKE_A	1AKE	A	Protein	214	X-ray
6S36_A	6S36	A	Protein	214	X-ray
6RZE_A	6RZE	A	Protein	214	X-ray
3HPR_A	3HPR	A	Protein	214	X-ray
1E4V_A	1E4V	A	Protein	214	X-ray
5EJE_A	5EJE	A	Protein	214	X-ray

	resolution	scopDomain	pfam	ligandId
1AKE_A	2.00	Adenylate kinase	Adenylate kinase (ADK)	AP5
6S36_A	1.60	<NA> Adenylate kinase	(ADK) CL (3),NA,MG (2)	
6RZE_A	1.69	<NA> Adenylate kinase	(ADK) NA (3),CL (2)	
3HPR_A	2.00	<NA> Adenylate kinase	(ADK)	AP5
1E4V_A	1.85	Adenylate kinase	Adenylate kinase (ADK)	AP5
5EJE_A	1.90	<NA> Adenylate kinase	(ADK)	AP5,CO

	ligandName
1AKE_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
6S36_A	CHLORIDE ION (3),SODIUM ION,MAGNESIUM ION (2)
6RZE_A	SODIUM ION (3),CHLORIDE ION (2)
3HPR_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
1E4V_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
5EJE_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE,COBALT (II) ION

	source
1AKE_A	Escherichia coli
6S36_A	Escherichia coli
6RZE_A	Escherichia coli
3HPR_A	Escherichia coli K-12
1E4V_A	Escherichia coli
5EJE_A	Escherichia coli 0139:H28 str. E24377A

1AKE_A STRUCTURE OF THE COMPLEX BETWEEN ADENYLATE KINASE FROM ESCHERICHIA COLI AND THE INHIBITORS

6S36_A

6RZE_A

3HPR_A

1E4V_A

5EJE_A

	citation	rObserved	rFree
1AKE_A	Muller, C.W., et al. J Mol Biol (1992)	0.1960	NA
6S36_A	Rogne, P., et al. Biochemistry (2019)	0.1632	0.2356
6RZE_A	Rogne, P., et al. Biochemistry (2019)	0.1865	0.2350
3HPR_A	Schrank, T.P., et al. Proc Natl Acad Sci U S A (2009)	0.2100	0.2432
1E4V_A	Muller, C.W., et al. Proteins (1993)	0.1960	NA
5EJE_A	Kovermann, M., et al. Proc Natl Acad Sci U S A (2017)	0.1889	0.2358

rWork spaceGroup

Cryst

```
1AKE_A 0.1960 P 21 2 21
6S36_A 0.1594 C 1 2 1
6RZE_A 0.1819 C 1 2 1
3HPR_A 0.2062 P 21 21 2
1E4V_A 0.1960 P 21 2 21
5EJE_A 0.1863 P 21 2 21
```

Now we can download all these structures for further analysis.

```
# Download related PDB files
files <- get.pdb(hits$pdb.id, path="pdbs", split=TRUE, gzip=TRUE)
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1AKE.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6S36.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6RZE.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3HPR.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb exists. Skipping download
```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb exists. Skipping download

	0%
=====	8%
=====	15%
=====	23%
=====	31%
=====	38%
=====	46%
=====	54%
=====	62%
=====	69%
=====	77%
=====	85%
=====	92%
=====	100%

Now we have all these structures we can Align and Supperpose...

```
# Align releated PDBs
pdbbs <- pdbaln(files, fit = TRUE, exefile="msa")
```

Reading PDB files:

```
pdbbs/split_chain/1AKE_A.pdb
pdbbs/split_chain/6S36_A.pdb
pdbbs/split_chain/6RZE_A.pdb
pdbbs/split_chain/3HPR_A.pdb
pdbbs/split_chain/1E4V_A.pdb
pdbbs/split_chain/5EJE_A.pdb
pdbbs/split_chain/1E4Y_A.pdb
pdbbs/split_chain/3X2S_A.pdb
pdbbs/split_chain/6HAP_A.pdb
pdbbs/split_chain/6HAM_A.pdb
pdbbs/split_chain/4K46_A.pdb
pdbbs/split_chain/3GMT_A.pdb
pdbbs/split_chain/4PZL_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
...
```

Extracting sequences

```
pdb/seq: 1   name: pdbbs/split_chain/1AKE_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbbs/split_chain/6S36_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbbs/split_chain/6RZE_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 4   name: pdbbs/split_chain/3HPR_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbbs/split_chain/1E4V_A.pdb
pdb/seq: 6   name: pdbbs/split_chain/5EJE_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbbs/split_chain/1E4Y_A.pdb
```

```

pdb/seq: 8   name: pdb/split_chain/3X2S_A.pdb
pdb/seq: 9   name: pdb/split_chain/6HAP_A.pdb
pdb/seq: 10  name: pdb/split_chain/6HAM_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 11  name: pdb/split_chain/4K46_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdb/split_chain/3GMT_A.pdb
pdb/seq: 13  name: pdb/split_chain/4PZL_A.pdb

```

pdb

```

1 . . . 40
[Truncated_Name:1] 1AKE_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:2] 6S36_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:3] 6RZE_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:4] 3HPR_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:5] 1E4V_A.pdb -----MRIILLGAPVAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:6] 5EJE_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:7] 1E4Y_A.pdb -----MRIILLGALVAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:8] 3X2S_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:9] 6HAP_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:10] 6HAM_A.pdb -----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:11] 4K46_A.pdb -----MRIILLGAPGAGKGTQAQFIMAKFGIPQIS
[Truncated_Name:12] 3GMT_A.pdb -----MRLILLGAPGAGKGTQANFIKEKFGIPQIS
[Truncated_Name:13] 4PZL_A.pdb TENLYFQSNAMRIILLGAPGAGKGTQAKIIEQKYNIAHIS
                        **~*****  *****  *  *~ *  **
1 . . . 40

41 . . . 80
[Truncated_Name:1] 1AKE_A.pdb TGDMLRAAVKSGSELGKQAKDIMDAGKLVDELVIALVKE
[Truncated_Name:2] 6S36_A.pdb TGDMLRAAVKSGSELGKQAKDIMDAGKLVDELVIALVKE
[Truncated_Name:3] 6RZE_A.pdb TGDMLRAAVKSGSELGKQAKDIMDAGKLVDELVIALVKE
[Truncated_Name:4] 3HPR_A.pdb TGDMLRAAVKSGSELGKQAKDIMDAGKLVDELVIALVKE
[Truncated_Name:5] 1E4V_A.pdb TGDMLRAAVKSGSELGKQAKDIMDAGKLVDELVIALVKE
[Truncated_Name:6] 5EJE_A.pdb TGDMLRAAVKSGSELGKQAKDIMDACKLVDELVIALVKE
[Truncated_Name:7] 1E4Y_A.pdb TGDMLRAAVKSGSELGKQAKDIMDAGKLVDELVIALVKE
[Truncated_Name:8] 3X2S_A.pdb TGDMLRAAVKSGSELGKQAKDIMDCGKLVDELVIALVKE
[Truncated_Name:9] 6HAP_A.pdb TGDMLRAAVKSGSELGKQAKDIMDAGKLVDELVIALVRE
[Truncated_Name:10] 6HAM_A.pdb TGDMLRAAIKSGSELGKQAKDIMDAGKLVDEIIIALVKE
[Truncated_Name:11] 4K46_A.pdb TGDMLRAAIKAGTELGKQAKSVIDAGQLVSDDIILGLVKE
[Truncated_Name:12] 3GMT_A.pdb TGDMLRAAVKAGTPLGVEAKTYMDEGKLVPSLIIGLVKE

```

[Truncated_Name:13] 4PZL_A.pdb	TGDMIRETIKSGSALGQELKKVLDAGELVSDEFI IKIVKD	
	****~* ~* *~ ** * ~* ** * ^^ ~*^^	
	41 . . . 80	
	81 . . . 120	
[Truncated_Name:1] 1AKE_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:2] 6S36_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:3] 6RZE_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:4] 3HPR_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:5] 1E4V_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:6] 5EJE_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:7] 1E4Y_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:8] 3X2S_A.pdb	RIAQEDSRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:9] 6HAP_A.pdb	RICQEDSRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:10] 6HAM_A.pdb	RICQEDSRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD	
[Truncated_Name:11] 4K46_A.pdb	RIAQDDCAKGFLLDGFPR TIPQADGLKEVGVVVVDYVIEFD	
[Truncated_Name:12] 3GMT_A.pdb	RLKEADCANGYLFDFGPR TIAQADAMKEAGVAIDYVLEID	
[Truncated_Name:13] 4PZL_A.pdb	RISKNDCNNGFLLDGVPR TIPQAQELDKLGVNIDYIVEVD	
	*~ * ~* ** ***** ** ^ ~* ~**~* *	
	81 . . . 120	
	121 . . . 160	
[Truncated_Name:1] 1AKE_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:2] 6S36_A.pdb	VPDELIVDKIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:3] 6RZE_A.pdb	VPDELIVDAIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:4] 3HPR_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDGTG	
[Truncated_Name:5] 1E4V_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:6] 5EJE_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:7] 1E4Y_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:8] 3X2S_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:9] 6HAP_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:10] 6HAM_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG	
[Truncated_Name:11] 4K46_A.pdb	VADSVIVERMAGRRAHLASGR TYHNVYNPPKVEGKDDVTG	
[Truncated_Name:12] 3GMT_A.pdb	VPFSEIIERMSGRRTHPASGR TYHV KFNPPKVEGKDDVTG	
[Truncated_Name:13] 4PZL_A.pdb	VADNLLIERITGRRIH PASGR TYHTKFNPPKVADKDDVTG	
	* ~~~ ^ *** * *** ** ^***** *** **	
	121 . . . 160	
	161 . . . 200	
[Truncated_Name:1] 1AKE_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN	
[Truncated_Name:2] 6S36_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN	
[Truncated_Name:3] 6RZE_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN	
[Truncated_Name:4] 3HPR_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN	


```

[Truncated_Name:5] 1E4V_A.pdb      EELTTRKDDQEETVRKRLVEYHQM TAPLIGYYSKEAEAGN
[Truncated_Name:6] 5EJE_A.pdb      EELTTRKDDQEECVRKRLVEYHQM TAPLIGYYSKEAEAGN
[Truncated_Name:7] 1E4Y_A.pdb      EELTTRKDDQEETVRKRLVEYHQM TAPLIGYYSKEAEAGN
[Truncated_Name:8] 3X2S_A.pdb      EELTTRKDDQEETVRKRLCEYHQM TAPLIGYYSKEAEAGN
[Truncated_Name:9] 6HAP_A.pdb      EELTTRKDDQEETVRKRLVEYHQM TAPLIGYYSKEAEAGN
[Truncated_Name:10] 6HAM_A.pdb      EELTTRKDDQEETVRKRLVEYHQM TAPLIGYYSKEAEAGN
[Truncated_Name:11] 4K46_A.pdb      EDLVIREDDKEETV LARLG VYHNQTAPLIAYYGKEAEAGN
[Truncated_Name:12] 3GMT_A.pdb      EPLVQRDDDK EETVKKRLDVYEAQTKPLITYYGDWARRGA
[Truncated_Name:13] 4PZL_A.pdb      EPLITRTDDNEDTVKQRLSVYHAQTAKLIDFYRNFSSNTNT
                                     * * * ** * ^ * ** * * ** ^*
161                               .           .           .           200

201                               .           .           227
[Truncated_Name:1] 1AKE_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:2] 6S36_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:3] 6RZE_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:4] 3HPR_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:5] 1E4V_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:6] 5EJE_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:7] 1E4Y_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:8] 3X2S_A.pdb      T--KYAKVDG TKPVAEVRADLEKILG-
[Truncated_Name:9] 6HAP_A.pdb      T--KYAKVDG TKPVCEVRADLEKILG-
[Truncated_Name:10] 6HAM_A.pdb      T--KYAKVDG TKPVCEVRADLEKILG-
[Truncated_Name:11] 4K46_A.pdb      T--QYLKFDG TKAVEVSAELEKALA-
[Truncated_Name:12] 3GMT_A.pdb      E-----NGLKAPA-----YRKISG-
[Truncated_Name:13] 4PZL_A.pdb      KIPKYIKINGDQAVEKVSQDIFDQLNK
                                     *
201                               .           .           227

```

Call:

```
pdbaln(files = files, fit = TRUE, exefile = "msa")
```

Class:

```
pdbs, fasta
```


Alignment dimensions:

```
13 sequence rows; 227 position columns (204 non-gap, 23 gap)
```

```
+ attr: xyz, resno, b, chain, id, ali, resid, sse, call
```

Principal Component analysis

```
# Perform PCA
pc.xray <- pca(pdbx)
plot(pc.xray)
```



```
# Visualize first principal component
pc1 <- mktrj(pc.xray, pc=1, file="pc_1.pdb")
```

AlphaFold

Querying the AlphaFold database

1. Use the following sequence to search AFDB:

```
> HIV-Pr
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQY
DQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
```

The top hit is Peptidase A2 domain-containing protein from *Thalassobius mangrovi*, which is not an HIV protein.

Making predictions

We used AlphaFold's Colab Notebook to predict the structure of the HIV protease as a monomer and as an homodimer.

Interpreting results

Visualization of the models and their estimated reliability

HIV protease monomer colored for uncertainty/disorder



Custom analysis of resulting models

Setting the directory

```
results_dir <- "HIVpr_dimer_23119/"
```

```
# File names for all PDB models
pdb_files <- list.files(path=results_dir,
                        pattern="*.pdb",
                        full.names = TRUE)

pdb_files
```

```
[1] "HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_001_alphafold2_multimer_v3_model_1_seed_001.pdb"
[2] "HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_002_alphafold2_multimer_v3_model_5_seed_001.pdb"
[3] "HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_003_alphafold2_multimer_v3_model_4_seed_001.pdb"
[4] "HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_004_alphafold2_multimer_v3_model_2_seed_001.pdb"
[5] "HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_005_alphafold2_multimer_v3_model_3_seed_001.pdb"
```

```
library(bio3d)
```

```
# Read all data from Models
# and superpose/fit coords
pdbs <- pdbaln(pdb_files, fit=TRUE, exefile="msa")
```

Reading PDB files:

```
HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_001_alphafold2_multimer_v3_model_1_seed_001.pdb
HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_002_alphafold2_multimer_v3_model_5_seed_001.pdb
HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_003_alphafold2_multimer_v3_model_4_seed_001.pdb
HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_004_alphafold2_multimer_v3_model_2_seed_001.pdb
HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_005_alphafold2_multimer_v3_model_3_seed_001.pdb
.....
```

Extracting sequences

```
pdb/seq: 1    name: HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_001_alphafold2_multimer_v3_model_1_seed_001.pdb
pdb/seq: 2    name: HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_002_alphafold2_multimer_v3_model_5_seed_001.pdb
pdb/seq: 3    name: HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_003_alphafold2_multimer_v3_model_4_seed_001.pdb
pdb/seq: 4    name: HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_004_alphafold2_multimer_v3_model_2_seed_001.pdb
pdb/seq: 5    name: HIVpr_dimer_23119/HIVpr_dimer_23119_unrelaxed_rank_005_alphafold2_multimer_v3_model_3_seed_001.pdb
```

Let's see the alignments

```
pdbs
```

```

1 . . . . 50
[Truncated_Name:1]HIVpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGI
[Truncated_Name:2]HIVpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGI
[Truncated_Name:3]HIVpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGI
[Truncated_Name:4]HIVpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGI
[Truncated_Name:5]HIVpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGI
*****
1 . . . . 50

51 . . . . 100
[Truncated_Name:1]HIVpr_dime GGFIVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:2]HIVpr_dime GGFIVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:3]HIVpr_dime GGFIVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:4]HIVpr_dime GGFIVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:5]HIVpr_dime GGFIVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
*****
51 . . . . 100

101 . . . . 150
[Truncated_Name:1]HIVpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:2]HIVpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:3]HIVpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:4]HIVpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:5]HIVpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
*****
101 . . . . 150

151 . . . . 198
[Truncated_Name:1]HIVpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:2]HIVpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:3]HIVpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:4]HIVpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:5]HIVpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
*****
151 . . . . 198

```

Call:

```
pdbaln(files = pdb_files, fit = TRUE, exefile = "msa")
```

Class:

```
pdbs, fasta
```

Alignment dimensions:

```
5 sequence rows; 198 position columns (198 non-gap, 0 gap)
+ attr: xyz, resno, b, chain, id, ali, resid, sse, call
```

Calculate the RMSD between all models

```
rd <- rmsd(pdbbs)
```

Warning in rmsd(pdbbs): No indices provided, using the 198 non NA positions

```
range(rd)
```


```
[1] 0.000 20.431
```

Draw a heatmap of RMSD matrix values

```
library(pheatmap)
```

Warning: package 'pheatmap' was built under R version 4.3.2

```
colnames(rd) <- paste0("m",1:5)
rownames(rd) <- paste0("m",1:5)
pheatmap(rd)
```




And a plot pLDDT values across all models

```
# Read a reference PDB structure
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
plotb3(pdb$b, typ="l", lwd=2, sse=pdb)
points(pdb$b[2,], typ="l", col="red")
points(pdb$b[3,], typ="l", col="blue")
points(pdb$b[4,], typ="l", col="darkgreen")
points(pdb$b[5,], typ="l", col="orange")
abline(v=100, col="gray")
```

We can improve the superposition/fitting of our models by finding the most consistent “rigid core” common across all the models. For this we will use the `core.find()` function:

```
core <- core.find(pdbbs)
```

```
core size 197 of 198 vol = 6154.839
core size 196 of 198 vol = 5399.676
core size 195 of 198 vol = 5074.795
core size 194 of 198 vol = 4802.518
core size 193 of 198 vol = 4520.256
core size 192 of 198 vol = 4305.362
core size 191 of 198 vol = 4089.792
core size 190 of 198 vol = 3886.145
core size 189 of 198 vol = 3758.321
core size 188 of 198 vol = 3620.18
core size 187 of 198 vol = 3496.698
core size 186 of 198 vol = 3389.985
core size 185 of 198 vol = 3320.114
core size 184 of 198 vol = 3258.683
core size 183 of 198 vol = 3208.591
core size 182 of 198 vol = 3156.736
core size 181 of 198 vol = 3141.668
```

core size 180 of 198	vol = 3136.574
core size 179 of 198	vol = 3155.52
core size 178 of 198	vol = 3185.362
core size 177 of 198	vol = 3204.487
core size 176 of 198	vol = 3211.978
core size 175 of 198	vol = 3234.993
core size 174 of 198	vol = 3244.062
core size 173 of 198	vol = 3237.845
core size 172 of 198	vol = 3218.77
core size 171 of 198	vol = 3180.743
core size 170 of 198	vol = 3130.369
core size 169 of 198	vol = 3067.881
core size 168 of 198	vol = 2989.546
core size 167 of 198	vol = 2928.272
core size 166 of 198	vol = 2851.193
core size 165 of 198	vol = 2780.877
core size 164 of 198	vol = 2708.433
core size 163 of 198	vol = 2636.516
core size 162 of 198	vol = 2563.25
core size 161 of 198	vol = 2478.024
core size 160 of 198	vol = 2404.793
core size 159 of 198	vol = 2330.997
core size 158 of 198	vol = 2250.477
core size 157 of 198	vol = 2159.432
core size 156 of 198	vol = 2070.759
core size 155 of 198	vol = 1983.579
core size 154 of 198	vol = 1917.913
core size 153 of 198	vol = 1842.556
core size 152 of 198	vol = 1775.398
core size 151 of 198	vol = 1695.133
core size 150 of 198	vol = 1632.173
core size 149 of 198	vol = 1570.391
core size 148 of 198	vol = 1497.238
core size 147 of 198	vol = 1434.802
core size 146 of 198	vol = 1367.706
core size 145 of 198	vol = 1302.596
core size 144 of 198	vol = 1251.985
core size 143 of 198	vol = 1207.976
core size 142 of 198	vol = 1167.112
core size 141 of 198	vol = 1118.27
core size 140 of 198	vol = 1081.664
core size 139 of 198	vol = 1029.75
core size 138 of 198	vol = 981.766

core size 137 of 198 vol = 944.446
core size 136 of 198 vol = 899.224
core size 135 of 198 vol = 859.402
core size 134 of 198 vol = 814.694
core size 133 of 198 vol = 771.862
core size 132 of 198 vol = 733.807
core size 131 of 198 vol = 702.053
core size 130 of 198 vol = 658.757
core size 129 of 198 vol = 622.574
core size 128 of 198 vol = 578.29
core size 127 of 198 vol = 543.07
core size 126 of 198 vol = 510.934
core size 125 of 198 vol = 481.595
core size 124 of 198 vol = 464.672
core size 123 of 198 vol = 451.721
core size 122 of 198 vol = 430.417
core size 121 of 198 vol = 409.141
core size 120 of 198 vol = 378.942
core size 119 of 198 vol = 348.325
core size 118 of 198 vol = 324.738
core size 117 of 198 vol = 312.394
core size 116 of 198 vol = 300.89
core size 115 of 198 vol = 279.976
core size 114 of 198 vol = 263.434
core size 113 of 198 vol = 250.263
core size 112 of 198 vol = 229.592
core size 111 of 198 vol = 209.929
core size 110 of 198 vol = 196.379
core size 109 of 198 vol = 180.628
core size 108 of 198 vol = 167.088
core size 107 of 198 vol = 155.875
core size 106 of 198 vol = 142.595
core size 105 of 198 vol = 128.924
core size 104 of 198 vol = 114.054
core size 103 of 198 vol = 100.936
core size 102 of 198 vol = 90.431
core size 101 of 198 vol = 81.972
core size 100 of 198 vol = 74.017
core size 99 of 198 vol = 66.855
core size 98 of 198 vol = 59.525
core size 97 of 198 vol = 52.263
core size 96 of 198 vol = 43.699
core size 95 of 198 vol = 35.813

```

core size 94 of 198  vol = 28.888
core size 93 of 198  vol = 20.692
core size 92 of 198  vol = 14.975
core size 91 of 198  vol = 9.146
core size 90 of 198  vol = 5.232
core size 89 of 198  vol = 3.53
core size 88 of 198  vol = 2.657
core size 87 of 198  vol = 1.998
core size 86 of 198  vol = 1.333
core size 85 of 198  vol = 1.141
core size 84 of 198  vol = 1.012
core size 83 of 198  vol = 0.891
core size 82 of 198  vol = 0.749
core size 81 of 198  vol = 0.618
core size 80 of 198  vol = 0.538
core size 79 of 198  vol = 0.479
FINISHED: Min vol ( 0.5 ) reached

```

We can use the identified core atom positions as a basis for a more suitable superposition:

```


core.inds <- print(core, vol=0.5)

# 80 positions (cumulative volume <= 0.5 Angstrom^3)
  start end length
1    10  25     16
2    27  48     22
3    53  94     42

xyz <- pdbfit(pdb, core.inds, outpath="corefit_structures")

```

HIV protease dimer colored for uncertainty/disorder




Now we can update our RMSD analysis and examine the RMSF between positions of the structure:

```
rd <- rmsd(xyz)
```


Warning in rmsd(xyz): No indices provided, using the 198 non NA positions

```
# Change the names for easy reference
colnames(rd) <- paste0("m",1:5)
rownames(rd) <- paste0("m",1:5)
pheatmap(rd)
```



```
rf <- rmsf(xyz)

plotb3(rf, sse=pdb)
abline(v=100, col="gray", ylab="RMSF")
```



Predicted Alignment Error for domains

Independent of the 3D structure, AlphaFold produces an output called Predicted Aligned Error (PAE). This is detailed in the JSON format files, one for each model structure.

Below we read these files and see that AlphaFold produces a useful inter-domain prediction for model 1 but not for model 5:

```
library(jsonlite)

# Listing of all PAE JSON files
pae_files <- list.files(path=results_dir,
                        pattern=".*model.*\\.json",
                        full.names = TRUE)

pae1 <- read_json(pae_files[1],simplifyVector = TRUE)
pae5 <- read_json(pae_files[5],simplifyVector = TRUE)

attributes(pae1)
```

```
$names
[1] "plddt"    "max_pae" "pae"      "ptm"      "iptm"
```

```
# Per-residue pLDDT scores
# same as B-factor of PDB..
head(pae1$plddt)
```

```
[1] 92.50 96.56 96.94 96.62 97.69 96.00
```

The maximum PAE values - we can see that model 5 is much worse than model 1. The lower the better.

```
pae1$max_pae
```


```
[1] 15.54688
```

```
pae5$max_pae
```


```
[1] 29.29688
```

We can plot these with ggplot or with functions from the Bio3D package:

```
plot.dmat(pae1$pae,
          xlab="Residue Position (i)",
          ylab="Residue Position (j)")
```





```
plot.dmat(pae5$pae,
          xlab="Residue Position (i)",
          ylab="Residue Position (j)",
          grid.col = "black",
          zlim=c(0,30))
```



We should really plot all of these using the same z range. Here is the model 1 plot again but this time using the same data range as the plot for model 5:

```
plot.dmat(pae1$pae,
  xlab="Residue Position (i)",
  ylab="Residue Position (j)",
  grid.col = "black",
  zlim=c(0,30))
```



Residue conservation from alignment file

```
aln_file <- list.files(path=results_dir,
                       pattern=".a3m$",
                       full.names = TRUE)
aln_file
```

```
[1] "HIVpr_dimer_23119/HIVpr_dimer_23119.a3m"
```

```
aln <- read.fasta(aln_file[1], to.upper = TRUE)
```


```
[1] " ** Duplicated sequence id's: 101 **"
```

```
[2] " ** Duplicated sequence id's: 101 **"
```

```
dim(aln$ali)
```

```
[1] 5378 132
```

```
sim <- conserv(aln)
plotb3(sim[1:99], sse=trim.pdb(pdb, chain="A"))
```



```
con <- consensus(aln, cutoff = 0.9)
con$seq
```

```
[1] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[19] "-" "-" "-" "-" "-" "-" "D" "T" "G" "A" "-" "-" "-" "-" "-" "-" "-"
[37] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[55] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[73] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[91] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[109] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[127] "-" "-" "-" "-" "-" "-"
```

```
m1.pdb <- read.pdb(pdb_files[1])
occ <- vec2resno(c(sim[1:99], sim[1:99]), m1.pdb$atom$resno)
write.pdb(m1.pdb, o=occ, file="m1_conserv.pdb")
```

HIV protease colored for occupancy

