

Class 06: R Functions

Nicolò (PID: A18109144)

All about functions in R

Functions are the way we get stuff done in R. We call a function to read data, compute stuff, plot stuff, etc. etc.

R makes writing functions accessible but we should always start by trying to get a working snippet of code first before we write our function.

Today's lab

We will grade a whole class of student assignments. We will always try to start with a simplified version of the problem.

```
# Example input vectors to start with
student1 <- c(100, 100, 100, 100, 100, 100, 100, 90)
student2 <- c(100, NA, 90, 90, 90, 90, 97, 80)
student3 <- c(90, NA, NA, NA, NA, NA, NA, NA)
```

```
mean(student1)
```

```
[1] 98.75
```

Let's be nice instructors and drop the lowest score so the answer here should be 100

```
min(student1)
```

```
[1] 90
```

I found the `which.min()` function that may be useful here. How does it work? Let's just try it:

```
student1
```

```
[1] 100 100 100 100 100 100 100 90
```

```
which.min(student1)
```

```
[1] 8
```

I can use the minus syntax trick to get everything but the element with the min value

```
student1[-which.min(student1)]
```

```
[1] 100 100 100 100 100 100 100
```

I have my first working snippet of code

```
mean(student1[-which.min(student1)])
```

```
[1] 100
```

Let's test on the other students

```
mean(student2[-which.min(student2)])
```

```
[1] NA
```

```
mean(student3[-which.min(student3)])
```

```
[1] NA
```

Where is the problem? It's the NA value, let's ignore it

```
mean(student2, na.rm=TRUE)
```

```
[1] 91
```

No bueno. We need to fix this!

I want to stop working with `student1`, `student2` etc. and typing it out every time so let's instead work with an input called `x`.

```
x <- student2
x
```

```
[1] 100 NA 90 90 90 90 97 80
```

We want to overwrite the NA values with zero - if you miss a homework you score zero on this homework.

Google and Claude told me about the `is.na()` function, let's use it.

```
is.na(x)
```

```
[1] FALSE TRUE FALSE FALSE FALSE FALSE FALSE
```

We can use logicals to index a vector

```
x[is.na(x)] <- 0
x
```

```
[1] 100 0 90 90 90 90 97 80
```

```
mean(x[-which.min(x)])
```

```
[1] 91
```

This is my working snippet of code that solves the problem for all my example student inputs

```
x <- student2
#Mask NA values to 0
x[is.na(x)] <- 0
#Drop lowest score and get the mean
mean(x[-which.min(x)])
```

```
[1] 91
```

Q1. Write a function `grade()` to determine an overall grade from a vector of student homework assignment scores dropping the lowest single score. If a student misses a homework (i.e. has an NA value) this can be used as a score to be potentially dropped. Your final function should be adequately explained with code comments and be able to work on an example class gradebook such as this one in CSV format: "<https://tinyurl.com/gradeinput>" [3pts]

```

grade <- function(x) {
  #Mask NA values to 0
  x[is.na(x)] <- 0
  #Drop lowest score and get the mean
  mean(x[-which.min(x)])
}

```

Use this function:

```
grade(student1)
```

```
[1] 100
```

```
grade(student2)
```

```
[1] 91
```

```
grade(student3)
```

```
[1] 12.85714
```

We need to read the gradebook

```

gradebook <- read.csv("https://tinyurl.com/gradeinput", row.names = 1)
gradebook

```

	hw1	hw2	hw3	hw4	hw5
student-1	100	73	100	88	79
student-2	85	64	78	89	78
student-3	83	69	77	100	77
student-4	88	NA	73	100	76
student-5	88	100	75	86	79
student-6	89	78	100	89	77
student-7	89	100	74	87	100
student-8	89	100	76	86	100
student-9	86	100	77	88	77
student-10	89	72	79	NA	76
student-11	82	66	78	84	100

```

student-12 100 70 75 92 100
student-13 89 100 76 100 80
student-14 85 100 77 89 76
student-15 85 65 76 89 NA
student-16 92 100 74 89 77
student-17 88 63 100 86 78
student-18 91 NA 100 87 100
student-19 91 68 75 86 79
student-20 91 68 76 88 76

```

Calculate the averages for every student in the gradebook:

```

avg_scores <- apply(gradebook, 1, grade)
avg_scores

```

```

student-1 student-2 student-3 student-4 student-5 student-6 student-7
  91.75    82.50    84.25    84.25    88.25    89.00    94.00
student-8 student-9 student-10 student-11 student-12 student-13 student-14
  93.75    87.75    79.00    86.00    91.75    92.25    87.75
student-15 student-16 student-17 student-18 student-19 student-20
  78.75    89.50    88.00    94.50    82.75    82.75

```

Q2. Using your `grade()` function and the supplied gradebook, Who is the top scoring student overall in the gradebook? [3pts]

```

which.max(apply(gradebook, 1, grade))

```

```

student-18
  18

```

Q3. From your analysis of the gradebook, which homework was toughest on students (i.e. obtained the lowest scores overall)? [2pts]

```

mask <- gradebook

mask[is.na(mask)] <- 0
hw.ave <- apply(mask, 2, mean)
hw.ave

```

```

hw1 hw2 hw3 hw4 hw5
89.00 72.80 80.80 85.15 79.25

```

```
which.min(hw.ave)
```

hw2

2

Q4. Optional Extension: From your analysis of the gradebook, which homework was most predictive of overall score (i.e. highest correlation with average grade score)? [1pt]

```
highest_cor <- apply(mask, 2, cor, y=avg_scores)
highest_cor
```

	hw1	hw2	hw3	hw4	hw5
	0.4250204	0.1767780	0.3042561	0.3810884	0.6325982

```
which.max(highest_cor)
```

hw5

5