

ROOM A EVIDENCE PACK v1

Purpose: Human-reviewed transcription of the Room A laser survey for a provisional Codex reconstruction.

Status: Ready for first-pass Room A reconstruction, subject to the explicit cautions and unresolved items below.

Units: millimetres unless stated otherwise.

1. Survey conventions

- Existing finished floor level is the floor/height datum.
- Supplemental horizontal measurements were taken at approximately **1350 mm above finished floor level (AFFL)** unless stated otherwise.
- Blu Tack nodes represent points on the **finished wall plane**.
- Where door or window casing projects in front of the wall, the wall-plane node remains behind that projection.
- Decorative casing-face dimensions and casing projections are separate from wall-plane node positions.
- Raw readings are preserved even where repeat measurements differ.
- A missing or blocked reading must not be inferred unless Codex derives it from other stated constraints and labels it as derived.
- Photographs and this typed evidence pack should be used together where handwritten source sheets are ambiguous.

2. Room A baseline boundary chain

ID	From	To	Reading	Status / note
BASE-A-01	A0	A1	1316	Measured
BASE-A-02	A1	A2	284	Measured
BASE-A-03	A2	A3	1955	Measured
BASE-A-04	A3	A4	268	Measured
BASE-A-05	A4	A5	1293	Measured
BASE-A-06	A5	W1-AL	1410	Measured to wall-plane node
BASE-A-07	W1-AR	A6	-	Not measured / physically blocked. W1-AR and A6 are Blu Tack reference nodes located on the finished wall plane, behind the projecting window and door casing faces. The casing is a separate object layer that projects forward from those wall-plane nodes. A straight laser line between the nodes would therefore have to pass through the projecting casing, making this direct measurement physically impossible. Do not invent or substitute a casingface measurement for this wall-plane span.
BASE-A-08	A6	D1-AL	529	Measured
BASE-A-09	D1-AR	A7	2825	Confirmed
BASE-A-10	A7	D2-AL	550	Measured
BASE-A-11	D2-AR	A0	2664	Measured

3. Room A supplemental measurements - page 1

All readings below were taken at approximately **1350 mm AFFL**.

ID	From	To	Reading	Note
SUP-001	A2	A0	1338	Confirmed
SUP-002	A2	D2-AR	2696	
SUP-003	A2	A7	4215	
SUP-004	A2	D1-AR	4287	
SUP-005	A2	A6	5155	
SUP-006	A2	W1-AL	3430	

4. Supplemental measurements - page 13

All readings below were taken at approximately **1350 mm AFFL** unless stated otherwise.

ID	From	To	Reading	Note
SUP-025	A3	A5	1318	
SUP-026	A3	W1-AL	1721	
SUP-027	A3	A6	4206	
SUP-028	A3	D1-AL	4082	
SUP-029	A3	D1-AR	4029	
SUP-030	A3	A7	5157	
SUP-031	A3	D2-AR	4017	Approximate mark shown on source sheet
SUP-032	A4	W1-AL	1900	
SUP-033	A4	A6	4458	
SUP-034	A4	D1-AL	4342	
SUP-035	A0	A2	1333	Repeat/check against SUP-001
SUP-036	A0	W1-AL	4760	
SUP-037	A0	A6	6251	
SUP-038	A0	D1-AR	5133	

SUP-039	A1	D2-AR	2945	
SUP-040	A1	A7	4485	
SUP-041	A5	D1-AL	4298	
SUP-042	A5	A7	6225	
SUP-043	A5	D2-AR	5237	
SUP-044	W1-AR	D1-AL	1514	

5. Supplemental measurements - page 14

5.1 Horizontal constraints

All readings below were taken at approximately **1350 mm AFFL**.

ID	From	To / landing area	Reading	Interpretation
SUP-045	W1-AR	A7 area	4760	Approximate / obstructed note on source
SUP-046	A6	D2-AR area	4838	Approximate; note mentions reflection and casing
SUP-061	Wall area between W1-AR and A6	Wall area between A7 and D2-AL	4558	Wall-to-wall span between two general wall segments, not node-to-node. May be omitted if it creates ambiguity.
SUP-062	W1-AL	Wall area between D2-AR and A0	4547	Start is an exact node; endpoint is a wall-face landing area within the named segment.
ID	From	To / landing area	Reading	Interpretation
SUP-063	A1	Wall area between D1-AR and A7	4297	Start is an exact node; endpoint is a wall-face landing area within the named segment.
SUP-064	D1-AL	Wall area between A5 and A6	4268	Start is an exact node; endpoint is a wall-face landing area within the named segment.

5.2 Ceiling heights

These are vertical measurements from the **existing finished floor directly below the named area to the ceiling**.

ID	Area	Height
SUP-047	A0 area	3125
SUP-048	A1 area	3124
SUP-049	A2 area	3122
SUP-050	A3 area	3142
SUP-051	A4 area	3143
SUP-052	A5 area	3147
SUP-053	W1-AL area	3160
SUP-054	W1-AR area	3167

SUP-055	A6 area	3169
SUP-056	D1-AL area	3165
SUP-057	D1-AR area	3151
SUP-058	A7 area	3146
SUP-059	D2-AL area	3140
SUP-060	D2-AR area	3137

Do not replace these with one averaged ceiling height. Preserve them as local observations.

6. Door D1 - Room A face

6.1 Raw evidence

Measurement	Reading	Meaning
Clear opening width	781	Clear lining edge to opposite clear lining edge
Clear opening height	2030	Finished floor/threshold to underside of clear opening head
Front-face casing width	1204	Measured across the visible front face of the casing; this is not D1-AL to D1-AR
Casing projection	31	Perpendicular distance from the finished wall-plane nodes at D1-AL / D1-AR out to the casing front face
Outer casing height	2321	Lower casing datum to top of outer casing
Left casing trim width	206	Visible left trim
Right casing trim width	206	Visible right trim
Top of clear opening to top of casing	294	Vertical difference
Top of outer casing to ceiling	833	Vertical clearance

6.2 Interpretation

- D1-AL and D1-AR are wall-plane nodes.
- The 1204 mm width is across the casing's front face.
- The casing front face projects approximately 31 mm forward from the node/wall plane.
- Therefore the front-face width must not be substituted automatically for the wall-plane node-to-node distance.

7. Door D2 - Room A face

Measurement	Reading	Note
Clear opening width	767	
Clear opening height	1971	
Lining depth	-	Source entry crossed / not reliable; do not use
Outer casing width	1096	Front-face casing width
Outer casing height	2140	

Left trim width	158	
Right trim width	161	
Maximum casing projection	37	Wall plane to casing face
Top casing to ceiling	996	
Lower casing/frame to floor	-	Not recorded

8. Window W1 - Room A face

8.1 Raw evidence

Measurement	Reading	Meaning
W1 front-face width	1430	Width across the visible front face of the outer casing
W1-AL wall-plane node to outer left casing face	157	Projection/offset from node position to casing face/edge
W1-AR wall-plane node to outer right casing face	151	Projection/offset from node position to casing face/edge
Outer left casing edge to inner left casing edge	200	Left casing-face width
Outer right casing edge to inner right casing edge	201	Right casing-face width
Window width	1026	Recorded as window width; preserve this label for first pass
Casing height	2873	Outer casing height
Window height	1887	Recorded as window height
Top casing to ceiling	approximately 294	Approximate source reading

8.2 Interpretation

- W1-AL and W1-AR are wall-plane nodes behind the casing projection.
- The 1430 mm dimension is the casing **front-face width**, not automatically the wall-plane node-to-node width.
- The left and right casing projections/offsets are asymmetrical: 157 mm left and 151 mm right.
- The visible side casing widths are 200 mm left and 201 mm right.
- The 1026 mm and 1887 mm readings are preserved as the recorded window width and window height. They should be used as secondary object evidence unless photographs establish the exact frame/glazing layer.
- For the first Room A visual, model the opening and casing layers separately and do not collapse them into one rectangle.

9. Evidence hierarchy for Codex

Use evidence in this order:

1. Baseline wall-chain measurements and exact wall-plane nodes.
2. Supplemental node-to-node triangulation.
3. Supplemental node-to-wall and wall-to-wall constraints.
4. Door and window object measurements.
5. Photographs for interpreting casing layers, projections and endpoint meaning.

Where evidence conflicts:

- retain every raw reading;
- report the residual or mismatch;

- do not silently average;
 - identify the smallest set of readings that cannot coexist geometrically;
 - prefer a provisional best-fit reconstruction over rejecting the entire room.
-

10. Instructions for first-pass reconstruction

The first reconstruction should include:

- Room A finished-wall shell;
- node labels A0-A7;
- opening/node positions for W1, D1 and D2;
- a separate casing/front-face layer for W1, D1 and D2; • measurement residuals or contradictions;
- a simple 2D SVG or equivalent visual.

The first reconstruction should **not** attempt to finalise:

- structural wall cores;
 - concealed construction;
 - decorative moulding profiles;
 - perfect 3D ceiling surfaces;
 - inferred dimensions for BASE-A-07.
-

11. Explicit cautions

- **BASE-A-07 has no measurement.** W1-AR and A6 are wall-plane nodes behind projecting casing object layers. A direct wall-plane laser path is physically blocked by those projections, so the value must remain missing and must not be replaced with a front-face casing span.
- **SUP-061 is lower-confidence as a geometric constraint** because neither endpoint is an exact node. It can be excluded from the first solver pass.
- The handwritten source sheets reused some row headings for measurements that were physically different. The typed meanings in this document take precedence for interpretation, while the numeric readings remain raw evidence.
- D1 and W1 front-face widths are not equivalent by definition to the associated wall-plane node spans.