

Read about automatic differentiation in "Machine Learning Defined" appendix B. You can find that online here https://jermwatt.github.io/machine_learning_refined/notes/3_First_order_methods/3_5_Automatic.html To make the module autograd available we use the following commands:

```
In [15]: # import statement for autograd wrapped numpy
import autograd.numpy as np
# import statment for gradient calculator
from autograd import grad
import seaborn as sns
```

Then we can use the following generic code for doing the gradient descent:

```
In [3]: # import automatic differentiator to compute gradient module
from autograd import grad

# gradient descent function - inputs: g (input function), alpha (steplength parameter), max_its (maximum number of iterations)
def gradient_descent(g,alpha,max_its,w):
    # compute gradient module using autograd
    gradient = grad(g)

    # run the gradient descent loop
    weight_history = [w] # container for weight history
    cost_history = [g(w)] # container for corresponding cost function history
    for k in range(max_its):
        # evaluate the gradient, store current weights and cost function value
        grad_eval = gradient(w)

        # take gradient descent step
        w = w - alpha*grad_eval

        # record weight and cost
        weight_history.append(w)
        cost_history.append(g(w))
    return cost_history
```

We now want to find the minimum of

$$g(w) = \frac{1}{50}(w^4 + w^2 + 10w)$$


using the above gradient descent. Make three separate runs using a step length of $\alpha=1, 0.01$ and 0.01 starting from $w^0 = 2$. Plot the resulting cost histories. Which step length works best for this particular function and initial point ?

```
In [11]: g = lambda w: (1/50)*(w**4+w**2+10*w)
w0=2.0
```


```
In [12]: cost_history=gradient_descent(g,1,100,w0)
```

```
In [19]: sns.set_theme()
sns.set(rc = {'figure.figsize':(15,8)})
```


```
In [20]: alpha_choice=1;
max_its=100
cost_history=gradient_descent(g,alpha_choice,max_its,w0)
p=sns.lineplot(y=cost_history,x=[i for i in range(max_its+1)])
_p.set(title="Cost function for Alpha="+str(alpha_choice),ylabel="Value of Function",xlabel="Iteration no.",xticks=range(0,100,5))
```



```
In [21]: alpha_choice=0.1;
max_its=100
cost_history=gradient_descent(g,alpha_choice,max_its,w0)
p=sns.lineplot(y=cost_history,x=[i for i in range(max_its+1)])
_p.set(title="Cost function for Alpha="+str(alpha_choice),ylabel="Value of Function",xlabel="Iteration no.",xticks=range(0,100,5))
```



```
In [22]: alpha_choice=0.01;
max_its=100
cost_history=gradient_descent(g,alpha_choice,max_its,w0)
p=sns.lineplot(y=cost_history,x=[i for i in range(max_its+1)])
_p.set(title="Cost function for Alpha="+str(alpha_choice),ylabel="Value of Function",xlabel="Iteration no.",xticks=range(0,100,5))
```



The most appropriate step size is when alpha is equal to 1, as it reaches the lowest minimum of the 3 tested step sizes, as well as reaching it in the least number of steps.

```
In [ ]:
```

