# An Optimal Deterministic Adversary for Sorting

Nicholas Nash
ORCID: 0009-0003-0475-7852

8 November 2026

**Abstract**

This paper describes an optimal *deterministic*, polynomial-time adversary for ordinary sorting. For any correct sorting algorithm, the adversary forces that algorithm to make $(1 - o(1))n \log_2 n$ comparisons. The best previously known adversary forced $\frac{37}{64} n \log_2 n$ comparisons. The adversary represents the evolving partial order by a hierarchical family of directed acyclic graphs. Bounds on vertex degrees and directed path lengths allow comparison answers to be chosen through deterministic calculations on small graph neighborhoods.

## Methodological disclosure

All novel ideas in this paper were generated by GPT 6 Astra. The human author is revising this manuscript into a clear human-readable exposition. This is currently complete until the end of Section 3.

## 1 Introduction

We consider comparison sorting of $n$ distinct labelled keys.[1] A sorting algorithm (or *sorter*, for short) chooses each pair using the answers to its earlier comparisons and must be correct for every strict total order on the labels. A sorting adversary supplies those answers as the comparisons arrive. The sorting adversary is *legal* if every finite sequence of its answers is consistent with at least one total order. The adversary knows $n$ and sees the comparisons, but it need not inspect the sorter that generates them.

The classical *information-theoretic lower bound* (ITLB) shows that any sorter must perform $\lceil \log(n!) \rceil = n \log n - O(n)$ comparisons in the worst case [1, Section 5.3.1]. This bound guarantees the existence of a hard input for every correct sorter. Here the problem is to produce hard answers by one *deterministic, polynomial-time* adversary algorithm.

Kaplan, Zamir, and Zwick [7, Section 7] ask whether an efficient deterministic adversary can force $(1-\varepsilon)n \log n$ comparisons for every $\varepsilon > 0$ and all sufficiently large $n$. The following theorem answers their question.

**Theorem 1.1.** *There is a deterministic legal adversary, initialized using only $n$, that uses polynomially many bit operations per query and forces every correct sorter to make at least $(1 - o(1))n \log n$ comparisons.*

We refer to an adversary satisfying Theorem 1.1 as an *optimal* adversary. Without the restriction to polynomial-time, a deterministic optimal adversary is immediate. With randomness, simple, polynomial-time adversaries achieve optimality in both expectation and with high probability, just by generating random permutations.

[1] Throughout, log denotes $\log_2$, and ln the natural logarithm. We assume $n \geq 2$.

**Deterministic adversaries without the polynomial-time restriction** If an adversary need not operate in polynomial-time, an optimal deterministic adversary is a simple book-keeping exercise. The adversary must simply keep all total orders consistent with the answers so far. Each comparison partitions them into two classes. The adversary answers so as to retain a larger class. After $q$ comparisons, at least $n!/2^q$ orders remain, forcing $q \geq \log(n!)$. This rule is deterministic, but enumerating its classes may require factorial work. A consistent total order is a *linear extension* of the partial order given by the answered comparisons; counting these extensions exactly is #P-complete [10].

**Deterministic adversaries in polynomial-time** Kahn and Kim [12] already give a deterministic polynomial-time adversary for sorting with partial information. Starting from any given partial order $P$, it answers comparisons online and forces $\frac{1}{2}\log e(P)$ comparisons, where $e(P)$ is the number of linear extensions of $P$, and thus $\frac{1}{2}n\log n$ for ordinary sorting. We note that, for ordinary sorting, the much simpler adversary of Brodal et al [6] achieves the same guarantee.

**With randomness** If randomness is allowed, an optimal, polynomial-time adversary is a simple matter of generating a single uniformly random permutation. After choosing such a permutation the adversary simply answers from the ranks in that permutation. For every fixed correct sorter, the usual comparison-tree argument gives at least $\log(n!)$ comparisons in expectation and $\log(n!) - O(\log n)$ comparisons with probability $1 - o(1)$.

**Randomized approximation of the number of linear extensions.** Randomization also makes it possible to estimate how many linear extensions remain after each possible answer. Given the current partial order $P$, assign each label a real coordinate in $(0, 1)$ and form the region

$$K(P) = \{X \in (0,1)^n : X_i < X_j \text{ whenever } i <_P j\}.$$

Each allowed total order occupies volume $1/n!$ in the unit cube. Hence $\mathrm{vol}(K(P)) = e(P)/n!$ [9]. The two possible answers to a comparison cut this region into two parts, and their volumes are proportional to their counts of allowed orders. Dyer, Frieze, and Kannan [11] approximate these volumes in randomized polynomial time, so randomness also lets the adversary estimate which answer retains more orders.

**Organization of this paper.** To motivate our adversary, we describe the earlier adversaries of Brodal et al. [6], and Kaplan et al [8] in Section 2. Section 3 describes the data structure and the comparison procedure, then states the mathematical guarantees on which the adversary relies. This gives an operational account with the proofs deferred. Section 4 proves the comparison lower bound using the local guarantees stated in Section 3. The appendices prove the properties of order-restriction DAGs and the consistency of the tree updates, and give the deterministic local calculations. Section 5 then spells out how to choose graph bounds as a function of $n$ to obtain polynomial running time.

Lastly, Section 6 states some immediate corollaries for sorting under partial information, as well as for efficient partial order production.

## 2 Related Work

### 2.1 Sorting with partial information

Fredman [2] studied how closely sorting can approach the information-theoretic lower bound when some orders have already been excluded. For any nonempty family $\Gamma$ of permutations of $n$ items,

he showed that the unknown order can be identified using at most $\log|\Gamma| + 2n$ comparisons. In particular, if the available information is a partial order $P$, this gives $\log e(P) + 2n$ comparisons, where $e(P)$ counts its linear extensions. The comparison bound is within an additive $2n$ of the ITLB, but constructing the strategy requires enumerative information about the possible orders and does not give a polynomial-time algorithm for general partial orders [12, p. 390].

Kahn and Kim [12] later gave a deterministic polynomial-time sorting algorithm using $O(\log e(P))$ comparisons. They also constructed a deterministic polynomial-time adversary forcing $\Omega(\log e(P))$ comparisons. This history highlights the distinction between comparison complexity and the computation needed to choose comparisons. Our adversary faces the corresponding task of choosing answers efficiently while forcing asymptotically the full ITLB for ordinary sorting.

## 2.2 Binary-tree adversaries

Atallah and Kosaraju [3] gave an efficient sorting adversary with a lower bound of $\frac{1}{2}n\log n$ comparisons. Related adversaries occur in the work of Borodin, Guibas, Lynch, and Yao [4] on searching after partial sorting, Richards and Vaidya [5] on the distribution of comparisons among keys, and Brodal, Chaudhuri, and Radhakrishnan [6] on maintaining the minimum. The binary-tree rule of Borodin et al. and Brodal et al. provides the starting point for our construction.

Place every item at the root of an ordered binary tree. Items in disjoint subtrees have the left-to-right order of those subtrees. A comparison changes the placement as follows.

- If both items occupy the same node, move one to its left child and the other to its right child, and answer accordingly.
- If one item is at an ancestor of the other, move the higher item to the child whose subtree does not contain the lower item.
- If their nodes are unrelated by ancestry, answer from their left-to-right order, without moving either item.

For a concrete example, start with $A, B, C, D$ at the root. Answering $A < B$ moves $A$ to the left child and $B$ to the right, while $C, D$ remain at the root. If the sorter next compares $A$ and $C$, the ancestor rule moves $C$ to the right child and gives $A < C$. Comparing $D$ and $B$ then moves $D$ to the left child and gives $D < B$. The two children now contain $\{A, D\}$ and $\{B, C\}$. A subsequent comparison of $D$ with $C$ is answered $D < C$ without moving either item. The orders within $\{A, D\}$ and within $\{B, C\}$ remain unresolved. Figure 1 shows the placements.





**Figure 1:** The binary-tree adversary. The first comparison separates two items at the same node. The next two comparisons each move an item from an ancestor into the opposite child. In the final state, comparing $D$ with $C$ requires no movement.

Each comparison increases the sum of item depths by at most two. At completion, occupied nodes must be distinct and unrelated by ancestry: otherwise two represented items can occur in either relative order, leaving an unresolved comparison. Associate the root with $(0, 1)$, and associate each child with the corresponding half of its parent's interval. A node of depth $d_i$

therefore represents an interval of length $2^{-d_i}$. At completion these intervals are disjoint, giving

$$\sum_i 2^{-d_i} \le 1, \qquad 2^{-\frac{1}{n}\sum_i d_i} \le \frac{1}{n}\sum_i 2^{-d_i} \le \frac{1}{n}.$$

Convexity gives the bound on $2^{-\frac{1}{n}\sum_i d_i}$. Hence $\sum_i d_i \ge n \log n$, and at least $\frac{1}{2} n \log n$ comparisons are necessary [6, Section 4.1].

The tree representation can settle relations that have never been queried. For example, start again with four items at the root and answer $A < B$ and $C < D$. Placing $A, C$ in the left child and $B, D$ in the right child also commits the adversary to $A < D$ and $C < B$. Neither relation follows from those two answers alone.

### 2.3 The adversary of Kaplan, Zamir, and Zwick

Kaplan, Zamir, and Zwick [8] use a four-child tree. Intermediate states correspond to consecutive ranges of children, so an item can narrow its range before entering a particular child. See Figure 2.

A key idea of this adversary is that a comparison between two items need not immediately cause them to descend in the tree structure. Instead, pairs of items whose relative order are fixed can remain in the same node. We extend this idea to sufficiently structured DAGs in our adversary of Section 3.





**Figure 2:** One step of the four-child tree in the adversary of Kaplan, Zamir, and Zwick [8, Section 5]. An intermediate node records a range of possible children. An item at $[1, 3]$ can still enter any of children 1, 2, or 3.

Their analysis measures the sorters progress in terms of a suitably defined potential, our analysis is similar, although more involved. The resulting lower bound of this adversary is $\frac{37}{64} n \log n$ comparisons, improving the earlier $\frac{1}{2} n \log n$ bound.

## 3 The new optimal adversary

Kaplan, Zamir, and Zwick [8] keep a comparison between two items at a node as an ordered pair. However, in their adversary, an item can only belong to at most one pair.

A key ingredient of our adversary is to simply relax this requirement, and allow DAGs of items to form at each node. The adversary then periodically simplifies these DAGs in order to bound the degree of nodes in these DAGs, as well as their path lengths. This in turn allows the adversary to answer comparisons using only small neighborhoods of nodes in these in-node DAGs.

### 3.1 Order-restriction DAGs

An *order-restriction DAG* $D$ consists of a directed acyclic graph on a finite set $V$, together with an open interval $(\ell_x, r_x) \subseteq (0, 1)$ for each vertex $x$. Its *feasible assignments* are the points in

$$K(D) = \{X \in \mathbb{R}^V : \ell_x < X_x < r_x \text{ for every } x, \quad X_x < X_y \text{ for every arc } x \to y\}. \tag{1}$$

Assignments with distinct coordinates determine relative orders of the vertices. For example, the arcs $a \to b$ and $a \to c$, with all three intervals equal to $(0, 1)$, allow both $a < b < c$ and $a < c < b$. Write $V(D) = \operatorname{vol} K(D)$, taking $V(D) = 1$ when $V$ is empty.

We call the intervals *canonical* when each is the full range of its coordinate in feasible assignments. The routine `Normalize`$(D)$ propagates lower bounds forward along arcs and upper bounds backward. Two topological passes suffice, as shown in Algorithm 4.

### 3.2 A tree of order-restriction DAGs

The core data structure of our adversary is a rooted tree. Each node $v$ stores an order-restriction DAG $D_v$, whose vertices are the items recorded there. Figure 3 shows an example.

Each item has a record $(x, \ell_x, r_x)$ stored at exactly one node. The label $x$ identifies the key. The variable $X_x$ describes its position among the items and child anchors at that node. We call the item *free* there while this position remains variable. The interval endpoints are *dyadic rationals*, meaning that their denominators are powers of two. We keep the intervals canonical by calling `Normalize` after each change.

An arc $x \to y$ in $D_v$ records a comparison answered $x < y$ between items stored at $v$. A comparison between two free items contributes at most one arc.

Initially the tree consists of just the root, containing all records with bounds $\ell_x = 0$ and $r_x = 1$. The position variables $X_x$ are unassigned, and the root's graph has no arcs. Thus every assignment in $(0, 1)^n$ is feasible, and every total order can be obtained by assigning distinct positions.

Each child is attached to a fixed position $c \in (0, 1)$ in its parent, called its *anchor*. A node has at most one child at each anchor. For any feasible assignment at the parent, an item with position below $c$ precedes every item in that child's subtree; an item with position above $c$ follows every item in it. Subtrees of different children are ordered by their anchors. All items of each child subtree therefore occur consecutively in the resulting total order. The child's order-restriction DAG describes the possible orders within this block, using position variables in $(0, 1)$.





**Figure 3:** A state of the adversary. Each large box is a tree node, containing an order-restriction DAG, drawn as its arcs and allowed intervals.

In the root of Figure 3, the in-node DAG records $a < b$ and $a < c$. To read an order from this

state, choose feasible positions at each node, avoiding ties with other items or child anchors. List the items and anchors from left to right, and recursively replace each anchor by its child's order. For example, root positions $(X_a, X_b, X_c) = (1/3, 1/2, 7/8)$ give

$$p < q < a < b < r < s < c.$$

Other feasible choices give other orders. The *transcript* $\mathcal{T}$ is the sequence of answers so far. Our invariant is that every represented order satisfies the transcript.

### 3.3 Answering a comparison

Algorithm 1 descends from the root while one child subtree contains both queried items. At the node where it stops, each item is represented by its free coordinate or its child's anchor. Two distinct anchors determine the answer directly. Otherwise, `Select` returns either an answer or a pair $(x, c)$: move the queried item $x$ into the child anchored at $c$, then retry. After recording the answer, `Repair` restores the degree and path-length bounds.

The adversary uses this recursive state for at most

$$Q(n) = n \lceil \log n \rceil \tag{2}$$

answers, then answers from fixed ranks consistent with the transcript. By then the required comparison lower bound has already been reached.

**Algorithm 1:** `Compare`$(A, B)$: answer a comparison query.

**Input:** Distinct item labels $A, B$ and the current adversary state.
**Output:** An answer $A < B$ or $B < A$, with the state updated.
**if** *fixed ranks have been chosen* **then**
  **return** their order of $A, B$
**if** $|\mathcal{T}| = Q(n)$ **then**
  Form the DAG of answers in $\mathcal{T}$ and choose a topological order, breaking ties by label
  Store its ranks and **return** their order of $A, B$
**while** *true* **do**
  $v \leftarrow$ the root
  **while** *$A$ and $B$ lie in the same child subtree of $v$* **do**
    $v \leftarrow$ that child
  **if** *$A$ and $B$ lie in different child subtrees of $v$* **then**
    *answer* $\leftarrow$ the left-to-right order of their child anchors
    **break**
  $\alpha, \beta \leftarrow$ the coordinates or child anchors representing $A, B$ at $v$
  $r \leftarrow$ `Select`$(D_v, \alpha, \beta)$
  **if** *$r$ is an answer* **then**
    *answer* $\leftarrow$ the corresponding order of $A, B$
    **break**
  $(x, c) \leftarrow r$
  `RefineAt`$(x, c)$
**if** *at least one queried item is stored at $v$* **then**
  Store *answer* as an arc in the graph at $v$ or as an interval bound
  `Normalize`$(D_v)$
Append *answer* to $\mathcal{T}$
`Repair`$(v)$
**return** *answer*

The routine `Select` examines the order-restriction DAG at the node handling the comparison. Each possible answer selects a part of its feasible region. A deterministic local calculation tries to certify an answer retaining roughly half the region's volume or more. If it cannot do so, it returns an interior position $c$ for one of the queried items, so that `RefineAt` can move that item into a child.

An answer between two free items adds an arc to the in-node DAG. An answer between a free item and an anchor tightens the item's interval. We now describe how `RefineAt` moves an item and how `Repair` uses these moves to keep the graphs small.

### 3.3.1 Moving an item into a child

For a canonical $D$ and $c \in (\ell_x, r_x)$, the operation $\texttt{Restrict}(D, x, c)$ fixes $X_x = c$ and removes its coordinate. For each arc $y \to x$, it sets $r_y \leftarrow \min(r_y, c)$, and for each arc $x \to z$, it sets $\ell_z \leftarrow \max(\ell_z, c)$. It then deletes $x$ and its incident arcs and normalizes the remaining bounds. Algorithm 5 gives the procedure.

The operation $\texttt{RefineAt}(x, c)$ moves $x$ from its current node $v$ into the child anchored at $c \in (\ell_x, r_x)$. It first replaces $D_v$ by $\texttt{Restrict}(D_v, x, c)$. It then inserts $x$ into the child's order-restriction DAG as an isolated vertex with interval $(0, 1)$, creating the child if needed. Figure 4 illustrates reuse of an existing child.

**Algorithm 2:** $\texttt{RefineAt}(x, c)$: move an item into a child.

**Input:** A free item $x$, an interior anchor $c$, and the current adversary state.
**Output:** The updated state, with $x$ stored in a child of its former node.
$v \leftarrow$ the node storing $x$
$D_v \leftarrow \texttt{Restrict}(D_v, x, c)$
**if** *$v$ has no child anchored at $c$* **then**
  Create a child of $v$ at $c$, with an empty order-restriction DAG
$u \leftarrow$ the child of $v$ anchored at $c$
Insert $x$ into $D_u$ as an isolated vertex with record $(x, 0, 1)$





**Figure 4:** The two arc inequalities become bounds on the remaining parent coordinates. The new coordinate of $x$ orders it within the child, where both $x < z$ and $z < x$ remain possible. The anchor $c$ locates the child block among the parent items; the child's constraints determine the orders within that block.

### 3.3.2 Keeping the in-node DAGs small

Fix an integer degree threshold $k \geq 64$. We also bound directed paths by $H = 2^k$ vertices; degree counts neighbors in either direction. Between queries, every in-node DAG has degree below $k$ and directed paths with fewer than $H$ vertices. Recording an answer adds at most one arc, and `Repair` restores these bounds.

If there is a path on $H$ vertices, refine every item on the selected path in path order, including those whose arcs have already been removed. Otherwise, if a vertex has degree $k$, refine that

vertex. Each move uses `ChooseAnchor` to select an interior position and `RefineAt` to move the item into the corresponding child. Only isolated vertices are inserted into children.

For determinism, choose the lexicographically first eligible path and the smallest eligible label for a degree repair. When `Select` can return either queried item for refinement, use the smaller label.

**Algorithm 3:** `Repair`$(v)$: restore the graph bounds after an answer.

**Input:** The node $v$ at which the answer was determined.
**if** *the graph at $v$ has a directed path on $H$ vertices* **then**
  $L \leftarrow$ the selected path's list of labels, in path order
  **foreach** $x \in L$ *in path order* **do**
    $c \leftarrow$ `ChooseAnchor`$(D_v, x)$
    `RefineAt`$(x, c)$
**else if** *a vertex at $v$ has degree $k$* **then**
  $x \leftarrow$ the selected such vertex
  $c \leftarrow$ `ChooseAnchor`$(D_v, x)$
  `RefineAt`$(x, c)$

### 3.4 Properties of the operations

We now state the guarantees used in the analysis. The first concerns normalization and restriction of a single order-restriction DAG. The others describe the effect of refinement, the choices made by the local routines, and consistency of the whole tree with the transcript.

**Lemma 3.1** (Canonical intervals and coordinate restriction)**.** *Normalization preserves $K(D)$. This region has positive volume exactly when all the resulting intervals have positive width. In that case the intervals are canonical. For any $c \in (\ell_x, r_x)$, the feasible region of* `Restrict`$(D, x, c)$ *is exactly the section of $K(D)$ with $X_x = c$, measured in the remaining coordinates, and has positive volume.*

Appendix A proves the lemma.

To measure the effect of restriction, suppose $V(D) > 0$ and choose $X$ uniformly from $K(D)$. The density $f_x(c)$ of coordinate $X_x$ is the volume of the section at $c$ divided by $V(D)$. Thus the lemma gives

$$V(\mathrm{Restrict}(D, x, c)) = V(D) f_x(c). \tag{3}$$

This defines the density at every interior $c$ and gives $\mathbb{P}(a < X_x < b) = \int_a^b f_x(t)\, dt$.

**The effect of refinement.** Write $K_v = K(D_v)$ and $V_v = V(D_v)$. To measure the effect of a refinement on the whole state, take the product of the node volumes,

$$Z = \prod_v V_v. \tag{4}$$

Each item has a position variable at exactly one node, so the product region has dimension $n$. A node with no free items contributes volume one. Initially $Z = 1$; whenever every node has positive volume, $0 < Z \leq 1$.

Refinement fixes an item's position in its parent and gives it a fresh unit coordinate in a child. Write

$$g = \log \frac{Z_{\text{after}}}{Z_{\text{before}}} \tag{5}$$

for the resulting change in $\log Z$. We call $g$ the refinement's *volume gain*; it can be negative.

The restriction identity (3) now gives the change in this product. Here $f_x$ is the coordinate density in $D_v$ before the move.

**Lemma 3.2** (Refinement identity)**.** *Suppose every node region has positive volume. Refining $x$ at an interior anchor $c$ satisfies*

$$\frac{Z_{\text{after}}}{Z_{\text{before}}} = f_x(c). \tag{6}$$

Appendix E proves the identity.

Thus the refinement's volume gain is $g = \log f_x(c)$.

**Choosing answers and anchors.** The next lemma makes the guarantee of `Select` precise and specifies the anchors returned by both local routines. Put

$$\eta = \frac{1}{100k}. \tag{7}$$

The temporary bounds $k$ and $2H$ allow for the arc inserted by a comparison before `Repair` runs. The final inequality ensures that anchors requiring many binary digits produce a correspondingly large volume gain.

**Lemma 3.3** (Local selection)**.** *Let $D$ be an order-restriction DAG with canonical dyadic intervals, $V(D) > 0$, degree at most $k$, and directed paths of at most $2H$ vertices.*

1. *For a comparison $X_a < X_b$ with $a \neq b$, or between $X_a$ and a dyadic constant,* `Select` *returns either an answer retaining at least $1/2 - \eta$ of $V(D)$ or a queried coordinate $x$ and a dyadic $c \in (\ell_x, r_x)$ with $\log f_x(c) > k$.*
2. *Given a coordinate $x$,* `ChooseAnchor`$(D, x)$ *returns a dyadic $c \in (\ell_x, r_x)$.*

*Every returned position $c = (2i+1)/2^{m+1}$ in reduced form satisfies*

$$\log f_x(c) \geq (1 - 1/k)m - 4. \tag{8}$$

*The routines are deterministic and use only the graph and interval bounds in a neighborhood of the queried coordinates whose radius depends on $k$.*

Appendix B constructs the local calculations, and Appendix E proves the lemma. Thus `Select` either answers while losing at most about one bit of $\log Z$, or requests a refinement that gains more than $k$ bits. Every repair anchor also satisfies (8). Section 5 states the running-time guarantee.

**Consistency and termination.** The following proposition ensures that these local choices fit together into a legal adversary. Its proof uses the fact that an item can enter an existing child only when the transcript leaves its order relative to the items there unrestricted.

**Proposition 3.4** (Consistency and termination)**.** *Throughout the recursive phase the state has positive feasible volume, and every represented order satisfies the transcript. Each call terminates with at most $n + 2$ refinements. The strict degree and path bounds hold between calls.*

Appendix E gives the induction over the state updates.

**The comparison guarantee.** Let $T_q$ be the number of total orders consistent with the first $q$ answers. The preceding guarantees lead to the following bound.

**Theorem 3.5** (Comparison prefixes)**.** *For every integer $k \geq 64$, the adversary with parameter $k$ is deterministic and legal. There is a nonnegative $\delta_k = O(\log k/k)$, independent of $n$ and the query sequence, such that after any $q$ answers*

$$\log T_q \geq \log(n!) - (1 + \delta_k)q. \tag{9}$$

Section 4 proves the theorem by first showing that only $O(q/k)$ refinements occur in $q$ comparisons. When a correct sorter stops, $T_q = 1$, so the theorem forces at least $\log(n!)/(1+\delta_k)$ comparisons. Section 5 chooses $k$ as a function of $n$ to obtain the optimal asymptotic bound in polynomial time.

# 4 Counting the orders that remain

We prove Theorem 3.5 in two steps. First, the gain bounds limit the number of refinements. We then count orders consistent with the transcript using the volumes and the anchors in the stored tree.

## 4.1 Refinements are rare

Recording an answer between two anchors leaves $Z$ unchanged. Every other answer retains at least $1/2 - \eta$ of its node's volume, so its loss in $\log Z$ is at most

$$a_\eta = -\log(1/2 - \eta) = 1 + O(1/k). \tag{10}$$

Let $G$ be the sum of the refinement gains through $q$ completed calls. Since $Z$ starts at one and never exceeds one,

$$G \le \log Z + a_\eta q \le a_\eta q. \tag{11}$$

**Lemma 4.1** (Refinement count)**.** *After $q$ completed recursive calls, the total number $P$ of refinements is at most $Cq/k$ for an absolute constant $C$.*

*Proof.* Let $D$ count degree repairs. Each removes $k$ arcs, and each call inserts at most one arc. Thus $D \le q/k$. By (8), each such move gains at least $-4$. A move after a failed comparison test gains more than $k$.

In a path repair, refining $x_i$ at $c_i$ changes the arc to $x_{i+1}$ into the bound $X_{x_{i+1}} > c_i$. The next anchor therefore satisfies $c_{i+1} > c_i$. These $H = 2^k$ anchors are distinct. For reduced denominator $2^{m+1}$ there are $2^m$ anchors, so fewer than $H/2$ have $m < k-1$. The batch gains at least

$$(1 - 1/k)\frac{H}{2}(k-1) - 4H = H\left(\frac{k}{2} - 5 + \frac{1}{2k}\right) \ge \frac{kH}{4}.$$

Every counted batch is complete. Summing the gains gives

$$\frac{k}{4}(P - D) - 4D \le G \le a_\eta q, \qquad D \le q/k.$$

Rearranging proves the claim, for example with $C = 8$ since $k \ge 64$. □

## 4.2 Counting with the queried labels

The state can represent fewer orders than the $T_q$ orders consistent with the transcript. For example, if $a < b$ lie in the same child block and $z$ is at the root, the state cannot place $z$ between $a$ and $b$. If the sole recorded relation among them is $a < b$, the transcript permits $a < z < b$ as well.

Let $s$ be the number of labels that have appeared in queries. Every other label is still an isolated root coordinate on $(0, 1)$. Moves before answering select queried labels, and every item moved in a repair is incident to an arc of the graph before that repair starts. All those arcs were created by comparisons. Normalization leaves an isolated root coordinate unchanged. Temporarily discard the unqueried labels. Their independent unit intervals contribute a factor of one to $Z$, so the product volume is the same for the remaining $s$ labels.

We assign a weight to a child at the reduced dyadic anchor $c = (2i+1)/2^{m+1}$ by

$$w(c) = \frac{1}{k^2}\left(\frac{1-1/k}{2}\right)^m. \tag{12}$$

The sum over all possible anchors is $1/k$ because there are $2^m$ anchors for each $m$. For each label, multiply the weights along the path to its storage node. Let $\mathcal{W}$ be the product over all labels. A label stored at the root contributes one, so discarding the unqueried labels also leaves $\mathcal{W}$ unchanged.

**Lemma 4.2** (Orders consistent with the transcript)**.** *After a completed recursive call,*

$$T_q \geq n!(1-1/k)^s Z\mathcal{W}.$$

*The same inequality holds before the first call.*

*Proof.* For each of the $s$ labels independently, draw a position in the state tree. Start at the root. At each node, enter a child with probability equal to its weight, or stop with the remaining probability and draw a uniform coordinate in $(0,1)$ there. The stopping probability is at least $1-1/k$. Order the resulting positions by the tree and its anchors. Ties have probability zero. Since the labels have the same distribution, each of their $s!$ relative orders has probability $1/s!$.

The event that the labels follow their stored paths, stop at their storage nodes, and satisfy all node constraints has probability at least $(1-1/k)^s Z\mathcal{W}$. Its orders respect the transcript by Proposition 3.4. Each such order extends to $n!/s!$ full orders by inserting the other labels, whose positions the transcript does not constrain. Multiplying gives the bound. □

### 4.3 The prefix bound

*Proof of Theorem 3.5.* In the recursive phase, legality and termination follow from Proposition 3.4. After the horizon, the fixed ranks respect the recorded answers. For $q \geq Q(n) \geq \log(n!)$, the right side of (9) is nonpositive and $T_q \geq 1$.

For an earlier prefix put $d_k = -\log(1-1/k)$. Each refinement multiplies $\mathcal{W}$ by the weight of the child it enters. Its cost $\ell(c) = -\log w(c)$ satisfies

$$\ell(c) = (1+d_k)m + 2\log k \leq ag + b, \qquad a = \frac{1+d_k}{1-1/k}, \quad b = 4a + 2\log k$$

by (8). Thus $a \geq 1$, $a = 1 + O(1/k)$ and $b = O(\log k)$. Taking logarithms in Lemma 4.2, then using (11), gives

$$\begin{aligned}\log T_q &\geq \log(n!) - sd_k + \log Z - \sum_r \ell(c_r) \\ &\geq \log(n!) - sd_k + (1-a)\log Z - aa_\eta q - bP.\end{aligned}$$

Here $s \leq 2q$, $(1-a)\log Z \geq 0$, and $P \leq Cq/k$ by Lemma 4.1. We can therefore take $\delta_k = aa_\eta - 1 + 2d_k + Cb/k$. □

The same prefix bound applies when an algorithm can stop with several orders still possible.

## 5 Polynomial running time

The local routines inspect a bounded neighborhood. Their cost also depends on the precision of the interval endpoints. The following bound makes both dependencies explicit.

**Lemma 5.1** (Cost of the local routines)**.** *For the routines in Lemma 3.3, there is a computable budget $E_k$, depending only on $k$, such that each call enumerates at most $E_k$ digit assignments. If the stored interval bounds have at most $\Lambda$ fractional binary digits, every returned anchor has at most $\Lambda + \log E_k$ such digits.*

Theorem B.1 gives the enumeration bound; Appendix F proves the precision bound and accounts for the associated exact arithmetic.

Choose $k = k(n) \to \infty$ slowly enough that the enumeration bound $E_k$ in Lemma 5.1 satisfies $E_k \le n$. Appendix F gives a polynomial-time rule for this choice and verifies that the stored state and exact arithmetic have polynomial cost. This yields a fixed polynomial bound on bit operations per query, independent of the length of the interaction.

*Proof of Theorem 1.1.* The adversary is deterministic and polynomial-time. By Theorem 3.5 it is legal, and a correct sorter can stop only when $T_q = 1$, which requires

$$q \ge \frac{\log(n!)}{1 + \delta_{k(n)}} = (1 - o(1))n \log n,$$

since $\delta_k = O(\log k/k)$ and $k(n) \to \infty$. □

# 6 Consequences and further questions

The counting argument also applies when the algorithm starts or finishes with a partial order. The two settings have different information bounds: initial relations reduce what remains to be learned, whereas a target partial order specifies what the algorithm must establish. We state the consequences here and give their proofs in Appendix H.

## 6.1 Producing a prescribed partial order

Let $R$ be a partial order on $n$ slots. In *partial-order production*, the input consists of $n$ keys with no known relations. The algorithm must assign one key to each slot so that the key in slot $u$ is smaller than the key in slot $v$ whenever $u <_R v$. Sorting is the case where $R$ is a chain; a slot required to precede every other slot asks for the minimum.

A fixed assignment is valid for exactly $e(R)$ total orders of the keys. The information-theoretic lower bound is therefore

$$I(R) = \log(n!) - \log e(R).$$

Cardinal et al. [14] give a deterministic polynomial-time algorithm using $I(R) + o(I(R)) + O(n)$ comparisons.

**Corollary 6.1** (Partial-order production)**.** *There is a nonnegative sequence $\varepsilon_n \to 0$, independent of the target, such that the adversary of Theorem 1.1 forces every correct comparison algorithm producing an $n$-element partial order $R$ to make at least*

$$(1 - \varepsilon_n)I(R)$$

*comparisons. The adversary is initialized using only $n$ and works for every target $R$.*

Its leading term matches Cardinal et al.'s upper bound when $I(R) = \omega(n)$. The information bound can be smaller than the task's comparison complexity. For example, producing a minimum has $I(R) = \log n$ and requires $n - 1$ comparisons.

### 6.2 Sorting from supplied partial information

Now let $P$ describe relations already known between the input keys, supplied as a DAG. The sorter must identify one of its $e(P)$ linear extensions, so the information bound is $\log e(P)$.

**Corollary 6.2** (Supplied partial information)**.** *There is a deterministic adversary that can be initialized from any $n$-element partial order $P$ in polynomial time, gives legal answers in polynomial time per comparison, and forces every correct sorter to make at least*

$$(1 - o(1)) \log e(P) - O(n \log \log n)$$

*additional comparisons. Both error terms are uniform over $P$.*

The construction uses Cardinal et al.'s polynomial-time procedure [14] to extend $P$ to a *weak order*: a sequence of antichain layers, with every key in an earlier layer preceding every key in a later one. The additional relations reduce $\log e(P)$ by at most $O(n \log \log n)$. Run an independent copy of our adversary within each layer and answer between layers from their fixed order. All copies use the same parameters, chosen from the total size $n$, so the guarantee also covers small layers.

The comparison bound approaches $\log e(P)$ when $\log e(P) = \omega(n \log \log n)$. Kahn and Kim's adversary already forces $\Omega(\log e(P))$ for every $P$. The improvement here is the coefficient approaching one in this regime.

### 6.3 Preserving small amounts of remaining uncertainty

Can a deterministic polynomial-time adversary force $(1 - o(1)) \log e(P)$ further comparisons for every supplied partial order $P$? The additive loss in Corollary 6.2 can overwhelm the information that remains. Two disjoint chains of length $n/2$ have $\log e(P) = \Theta(n)$; a chain on $n - 1$ items and one unrelated item have $e(P) = n$.

Reducing the additive loss to $O(n)$ would already extend the useful range. Cardinal et al. [14, Section 4] exhibit partial orders $P$ for which every weak-order extension $W$ satisfies $\log e(W) \leq \log e(P) - \Omega(n \log \log n)$. A sharper construction must therefore preserve more of the possible interleavings between layers.

Initial partial information also arises when sorting points whose locations are known only to lie in specified intervals [15, 16]. Extending our adversary to those models would require answers compatible with realizable coordinates and with the permitted geometric operations. Another direction is the amortized minimum-maintenance problem linked to sorting adversaries by Kaplan, Zamir, and Zwick [7, Section 7]: handling insertions and deletions would require controlling how they change the represented orders.

## A Canonical intervals and densities

We prove Lemma 3.1 for order-restriction DAGs. We then establish the density bounds used to choose anchors and analyse probability certificates.

## A.1 Normalization and restriction

**Algorithm 4:** `Normalize`$(D)$: propagate the interval bounds.

**Input:** An order-restriction DAG $D$.
**foreach** *vertex $x$ in topological order* **do**
  $\ell_x \leftarrow \max(\{\ell_x\} \cup \{\ell_y : y \to x\})$
**foreach** *vertex $x$ in reverse topological order* **do**
  $r_x \leftarrow \min(\{r_x\} \cup \{r_y : x \to y\})$

**Algorithm 5:** `Restrict`$(D, x, c)$: fix and remove a coordinate.

**Input:** A canonical order-restriction DAG $D$ with $V(D) > 0$, a vertex $x$, and $c \in (\ell_x, r_x)$.
**foreach** *arc $y \to x$* **do**
  $r_y \leftarrow \min(r_y, c)$
**foreach** *arc $x \to z$* **do**
  $\ell_z \leftarrow \max(\ell_z, c)$
Delete $x$ and its incident arcs
`Normalize`$(D)$
**return** $D$

*Proof of Lemma 3.1.* Every propagated bound is already implied by an arc and an interval bound. A forward topological pass propagates every lower bound to all its successors; the reverse pass propagates every upper bound to all its predecessors. Thus normalization preserves the region and gives $\ell_x \le \ell_y$ and $r_x \le r_y$ along every arc $x \to y$.

Positive volume requires positive widths. Conversely, suppose all widths are positive. Choose numbers $0 < \theta_x < 1$ increasing in a topological order, and set

$$X_x = (1 - \theta_x)\ell_x + \theta_x r_x.$$

Along an arc $x \to y$, increasing $\theta_x$ to $\theta_y$ strictly increases this value, because $r_x > \ell_x$. Replacing the endpoints by $\ell_y, r_y$ cannot decrease it. Thus $X_x < X_y$, all interval bounds hold strictly, and a small open neighborhood is feasible.

Now fix $X_x = c$ in the normalized interval and delete its coordinate. Every incident inequality becomes exactly the bound imposed by `Restrict`, while all other inequalities persist. This proves that the resulting region is the section at $c$. Lower bounds propagate forward and upper bounds backward. Any earlier lower bound that reached a successor through $x$ is superseded by $c > \ell_x$; any earlier upper bound that reached a predecessor through $x$ is superseded by $c < r_x$. The normalized intervals of the remaining coordinates are therefore

$$\begin{cases} (\ell_y, \min(r_y, c)), & y \text{ precedes } x, \\ (\max(\ell_y, c), r_y), & y \text{ succeeds } x, \\ (\ell_y, r_y), & y \text{ is incomparable with } x. \end{cases} \tag{13}$$

A predecessor retains positive width because $r_y > \ell_y$ and $c > \ell_x \ge \ell_y$. A successor does too because $r_y > \ell_y$ and $c < r_x \le r_y$. Other widths are unchanged. The criterion just proved shows that the section has positive volume. Since this holds for every $c \in (\ell_x, r_x)$, that interval is exactly the coordinate projection. □

## A.2 Bounds from convex sections

Let $V$ be the set of coordinates, let $N = |V|$, and let $K \subseteq \mathbb{R}^V$ be their feasible region. For a coordinate $x$ and a real number $t$, write

$$K_x(t) = \{(z_i)_{i \ne x} : z \in K,\ z_x = t\}, \qquad S_x(t) = \mathrm{vol}_{N-1} K_x(t).$$

Here $K_x(t)$ is the $(N-1)$-dimensional section obtained by fixing coordinate $x$ at $t$. The uniform distribution on $K$ therefore gives $x$ the density

$$f_x(t) = \frac{S_x(t)}{\operatorname{vol}_N K}.$$

These formulas define $f_x$ pointwise, and we use this definition throughout. If some coordinates have already been fixed, we use the same definitions in the remaining free coordinates. In dimension zero, the volume of the singleton consisting of the empty assignment is one.

**Lemma A.1** (Density of a linear projection)**.** *Let $C \subseteq \mathbb{R}^d$ be a bounded open convex region of positive volume, and let $\varphi$ be a nonzero linear functional with $\varphi(C) = (\ell, r)$ of width $W$. For $X$ uniform on $C$, the density $g$ of $\varphi(X)$ satisfies*

$$g(t) \le \frac{d}{W}, \qquad g(t) \ge \frac{4^{-(d-1)}}{W} \quad (\ell + W/4 \le t \le r - W/4).$$

*Proof.* An invertible linear change of coordinates makes $\varphi$ the first coordinate. Its constant Jacobian preserves uniformity on the transformed region, so it suffices to prove the bounds for a coordinate projection. Write $S(t)$ for the section volume at that coordinate's value $t$; then $g(t) = S(t)/\operatorname{vol} C$.

Choose points in $\overline{C}$ whose first coordinates are $\ell$ and $r$. Such points exist because $C$ is bounded. For $\ell < t < s < r$, join every point of the section at $t$ to the point at $r$. Since $C$ is open and convex, the image with first coordinate $s$ lies in the section of $C$ there. Each of its $d-1$ directions is scaled by $(r-s)/(r-t)$, so

$$S(s) \ge \left(\frac{r-s}{r-t}\right)^{d-1} S(t) \qquad (t < s). \tag{14}$$

Joining instead to the point at $\ell$ gives

$$S(s) \ge \left(\frac{s-\ell}{t-\ell}\right)^{d-1} S(t) \qquad (s < t). \tag{15}$$

Normalize these inequalities and integrate over $s$ on both sides of $t$:

$$1 \ge g(t)\left(\int_\ell^t \left(\frac{s-\ell}{t-\ell}\right)^{d-1} ds + \int_t^r \left(\frac{r-s}{r-t}\right)^{d-1} ds\right) = \frac{W g(t)}{d}.$$

Thus $g(t) \le d/W$.

For the lower bound, choose $t_0$ with $g(t_0) \ge 1/W$, which exists because $g$ integrates to one over an interval of length $W$. For any $s \in [\ell + W/4, r - W/4]$, the appropriate ratio in (14) or (15) is at least $1/4$. Consequently

$$g(s) \ge 4^{-(d-1)} g(t_0) \ge \frac{4^{-(d-1)}}{W}.$$

The case $s = t_0$ satisfies the same bound directly. □

**Lemma A.2** (Coordinate density bounds)**.** *Let $D$ be a canonical order-restriction DAG with $V(D) > 0$, and suppose $x$ has at most $B$ other comparable coordinates and canonical interval $(\ell, r)$ of width $W$. Its density satisfies*

$$f_x(t) \le \frac{B+1}{W}, \tag{16}$$

$$f_x(t) \ge \frac{4^{-B}}{W} \qquad (\ell + W/4 \le t \le r - W/4). \tag{17}$$

*Proof.* Fix all coordinates incomparable with $x$, at values leaving a nonempty region. By the section formula in Lemma 3.1, each such fixing leaves $x$'s canonical interval unchanged. The remaining region $C$ is open and convex, has dimension $d \le B+1$, and still projects onto $(\ell, r)$ in coordinate $x$. Lemma A.1 therefore gives both required bounds for the density of $x$ in $C$.

Average over the fixed coordinates. If $\omega$ denotes their values, $C_\omega$ the remaining region, and $g_\omega$ its coordinate density, integration of each section gives the pointwise identity

$$f_x(t) = \frac{\int \operatorname{vol}(C_\omega) g_\omega(t)\, d\omega}{\int \operatorname{vol}(C_\omega)\, d\omega}.$$

Empty slices contribute zero. The bounds on $g_\omega$ are uniform in $\omega$, so they also hold for $f_x$. □

**Lemma A.3** (A bound for small differences)**.** *Let $X$ be uniform on $K(D)$ for a canonical order-restriction DAG $D$ with $V(D) > 0$, and suppose $x$ has at most $B$ other comparable coordinates and canonical interval of width $W$. Let $Y$ be a fixed number or $X_y$ for any distinct free coordinate $y$. For every interval $I$ of length $a$,*

$$\mathbb{P}(X_x - Y \in I) \le \frac{(B+1)a}{W}. \tag{18}$$

*Proof.* For a fixed number $Y$, integrate the coordinate-density upper bound over $I + Y$. Now let $Y = X_y$ for any free coordinate $y \neq x$. As above, fix all coordinates incomparable with $x$. The remaining convex region $C$ has dimension $d \le B+1$, and $x$ retains its width $W$. We show that the projection $X_x - X_y$ has width at least $W$ in each such region.

If $y$ is incomparable with $x$, it is now fixed, so the projection is a translate of $X_x$ and has width $W$. Otherwise $y$ remains free. Write $(\ell_z, r_z)$ for canonical intervals in $C$; $x$'s endpoints are unchanged. If a directed path goes from $x$ to $y$, then $r_y \ge r_x$. Fixing $X_y = t \in (\ell_y, r_y)$ leaves $x$ the interval $(\ell_x, \min(r_x, t))$, by Lemma 3.1. As $t$ approaches $r_y$, its width tends to $W$. On that section the difference $X_x - t$ varies over an interval of the same width. Thus the projection of the whole region $C$ has width at least $W$. If a directed path goes from $y$ to $x$, let $t$ approach $\ell_y$ instead. Here $\ell_y \le \ell_x$, and the remaining interval $(\max(\ell_x, t), r_x)$ again has width tending to $W$.

Lemma A.1 bounds the conditional density of the difference by $d/W \le (B+1)/W$. Integrating over $I$ and averaging over the fixed coordinates proves (18). If both coordinates have at most $B$ comparable coordinates, exchanging $x$ and $y$ gives the same bound with $\max(W_x, W_y)$ in the denominator. □

## A.3 Density in a central interval

A density is *log-concave* if its positive support is convex and its logarithm is concave there. The coordinate densities above are log-concave pointwise: the uniform density on $K$ is log-concave, and integrating out the other coordinates preserves this property by Prékopa's marginal theorem [13, Theorem 8]. We finish with the density bound used for positions having substantial probability on each side.

**Lemma A.4** (Density at central positions)**.** *Let $X$ have a log-concave density $f$. If $\mathbb{P}(X \le c) \ge p$ and $\mathbb{P}(X \ge c) \ge p$ for some $0 < p \le 1/2$, then*

$$f(c) \ge p \sup_t f(t).$$

*Proof.* For $s \le c \le t$, log-concavity gives

$$f(s) f(t) \le f(c) f(s + t - c).$$

Indeed, $c$ and $s+t-c$ are complementary convex combinations of $s,t$; multiply the two log-concavity inequalities. Fixing $t \geq c$ and integrating over $s \leq c$ gives

$$pf(t) \leq f(c) \int_{-\infty}^{c} f(s+t-c)\, ds \leq f(c).$$

Here the first inequality uses the mass at least $p$ to the left of $c$, and the last uses that a density integrates to one. Fixing $s \leq c$ and integrating over $t \geq c$ instead uses the right-hand mass and gives $pf(s) \leq f(c)$. Taking the supremum over both sides of $c$ proves the claim. □

**Lemma A.5** (Density in a central interval)**.** *Let $X$ be uniform on $K(D)$ for an order-restriction DAG $D$ with $V(D) > 0$. Suppose $J = [u, v] \subset (\ell_x, r_x)$ satisfies*

$$\mathbb{P}(X_x \leq u) \geq \tfrac{1}{4}, \qquad \mathbb{P}(X_x \in J) \geq \tfrac{1}{4}, \qquad \mathbb{P}(X_x \geq v) \geq \tfrac{1}{4}.$$

*Then, for every $c \in J$,*

$$f_x(c) \geq \frac{1}{16|J|}.$$

*Proof of Lemma A.5.* Put $M = \sup_t f_x(t)$. The inside-mass condition gives $M|J| \geq 1/4$. Every $c \in J$ has probability at least $1/4$ on each side, so Lemma A.4 gives $f_x(c) \geq M/4 \geq 1/(16|J|)$. □

# B Local calculations on order-restriction DAGs

We construct the routines in Lemma 3.3 for a single order-restriction DAG. Both use lists of intervals enclosing the queried coordinates. A pair of disjoint intervals certifies an order, and a list of intervals can certify how much probability lies on each side of a candidate anchor interval.

## B.1 A coordinate update with finitely many choices

Let $D$ be an order-restriction DAG with canonical interval endpoints $\ell_z, r_z$. Write $G$ for its underlying graph. For a current assignment $Y$, the interval permitted at coordinate $z$ has endpoints

$$L_z = \max(\{\ell_z\} \cup \{Y_u : u \to z\}), \qquad U_z = \min(\{r_z\} \cup \{Y_u : z \to u\}).$$

Fix a power of two $S$. For a digit $j \in \{0, \ldots, S-1\}$, update

$$Y_z \leftarrow \frac{Y_z + (S-1-j)L_z + jU_z}{S}. \tag{19}$$

The coefficients are nonnegative and sum to one. Thus an assignment satisfying the interval bounds and arc inequalities weakly continues to do so after an update, including when $L_z = U_z$.

Choosing the digit uniformly preserves the uniform distribution on the feasible region. Start from a uniform feasible assignment and condition on all coordinates other than $z$. Then $Y_z$ is uniform on $(L_z, U_z)$. Its normalized position $r = (Y_z - L_z)/(U_z - L_z)$ is sent to

$$r' = \frac{r+j}{S}.$$

For a fixed digit, this is uniform on the corresponding one of the $S$ equal subintervals. Averaging over the digits makes $r'$ uniform on $(0,1)$ again.

For $S = 2$, the two updates are $r \mapsto r/2$ and $r \mapsto (r+1)/2$. Each sends a uniform coordinate to one half of its interval. With no neighbors, enumerating the two digits in each of two sweeps gives the four quarter intervals.

### B.2 Enclosing intervals from two calculations

Let $T$ be the set of queried coordinates. Retain every vertex within undirected distance $\rho$ of $T$, together with all arcs between retained vertices. Retain their stored interval endpoints. Vertices at distance exactly $\rho$ form the boundary; those at smaller distance form the interior.

Run two calculations using the same digits. The lower calculation starts at $A_z = \ell_z$, and the upper calculation starts at $B_z = r_z$. Keep the boundary values fixed throughout both calculations. A *sweep* updates each interior coordinate once in topological order. All neighbors of an updated vertex are retained.

Enumerate every assignment of digits to $t$ sweeps. If there are $b'$ interior vertices, this gives

$$N = S^{b't} \tag{20}$$

computations. Each contributes the intervals $[A_x, B_x]$, $x \in T$, to the list, including repeated entries.

**Algorithm 6:** `Enclose`: compute a finite list of enclosing intervals.

**Input:** The retained subgraph of $D$ and its interval bounds, its interior vertices, a topological order, queried coordinates $T$, and integers $S, t$.
**Output:** A list of enclosing intervals $([A_x, B_x])_{x \in T}$, one per digit assignment.
$\mathcal{L} \leftarrow$ the empty list
**foreach** *assignment of digits* $j_{z,s} \in \{0, \dots, S-1\}$ *to the* $b't$ *interior visits* **do**
  $A_z \leftarrow \ell_z$ and $B_z \leftarrow r_z$ for every retained vertex $z$
  **for** $s = 1, \dots, t$ **do**
    **foreach** *interior vertex* $z$ *in the supplied order* **do**
      Apply (19) to $A_z$, using the current $A$ values and digit $j_{z,s}$
      Apply (19) to $B_z$, using the current $B$ values and the same digit
  Append $([A_x, B_x])_{x \in T}$ to $\mathcal{L}$
**return** $\mathcal{L}$

**Theorem B.1** (Local enclosing intervals)**.** *Let $d, h \geq 1$ be integers and let $\delta, \alpha \in (0,1)$ be rational. There are computable parameters $S, t, \rho$ and a bound $E$, depending only on $d, h, \delta, \alpha$, with the following property.*

*Suppose $D$ is an order-restriction DAG with canonical dyadic intervals, degree at most $d$, directed paths of at most $h$ vertices, and $V(D) > 0$. Write $K = K(D)$. For any nonempty set $T$ of one or two coordinates, Algorithm 6 returns a list satisfying two guarantees:*

1. *A uniformly selected entry and a uniform feasible assignment $X$ can be drawn jointly so that $A_x \leq X_x \leq B_x$ for every $x \in T$.*
2. *At most a fraction $\alpha$ of its entries have $\max_{x \in T}(B_x - A_x) > \delta$.*

*The calculation enumerates at most $E$ digit assignments. If the stored bounds have at most $\Lambda$ fractional binary digits, every computed endpoint has at most $\Lambda + \log E$ fractional digits.*

The enclosure guarantee holds for every finite number of sweeps and every choice of radius $\rho \geq 1$. Start a full assignment uniformly on $K$ and update the entire graph with independent uniform digits. Share its digits with the two endpoint calculations at interior vertices. The update is increasing in every coordinate, since maxima, minima, and the nonnegative linear combination in (19) are increasing. Thus it preserves the inequalities $A_z \leq X_z \leq B_z$ at an interior update. At a boundary vertex the full position always remains between its fixed interval endpoints, even as it changes during the full calculation. The full assignment remains uniform, and every interior digit sequence has probability $1/N$. This proves the first guarantee.

### B.3 How far a sweep can reach

For the width estimate, consider lower and upper sweeps that update the full graph. In either calculation, the update of a coordinate uses the new values of its predecessors, the old values of its successors, and its own old value. The resulting values are independent of the choice of topological order because these dependencies specify every update.

To trace a dependency backwards through one sweep, follow new values along incoming arcs. This follows a directed path with at most $h-1$ arcs. Moving from that path to an old value crosses at most one more arc. A value after $t$ sweeps thus depends only on digits, bounds and initial values within distance $ht$. With $\rho = ht+1$, every update in this dependency calculation is in the retained interior. Its initial values, stored bounds, and digits are the same in the local and full calculations. Consequently the queried endpoints agree exactly for every assignment of the digits, with arbitrary digits outside the retained region.

Appendix C bounds the widths on the full graph. Exact agreement transfers that estimate to the local lists.

### B.4 From intervals to answers and anchors

For two queried positions, count the entries with $B_x < A_y$ and those with $B_y < A_x$. For a threshold use $[c, c]$ as its interval. Each count divided by $N$ is a lower bound on the corresponding probability because the enclosed positions obey the certified order. `Select` uses the answer with the larger bound if that bound is at least $1/2 - \eta$. Otherwise it chooses a queried coordinate and rounds in the middle half of its range.

The routine `ChooseAnchor` uses a one-coordinate list. It tests whether a proposed interval contains at least a quarter of the mass, with at least a quarter on either side. The test counts entries lying wholly in each of these three regions. On success it rounds within the tested interval. On failure it rounds in the middle half of the coordinate's range. Appendix D gives the endpoint selection and shows that a failed test identifies a short coordinate interval. The gain and precision estimates in Appendix E complete the proof of Lemma 3.3.

**Algorithm 7:** `ChooseAnchor`$(D, x)$: choose an interior position.

**Input:** A canonical order-restriction DAG $D$ and a coordinate $x$ with interval $(\ell_x, r_x)$.
**Output:** A dyadic position $c \in (\ell_x, r_x)$.
$J \leftarrow$ `CentralInterval`$(D, x)$
**if** $J$ *is* `FAIL` **then**
  $W_x \leftarrow r_x - \ell_x$
  $J \leftarrow [\ell_x + W_x/4,\ r_x - W_x/4]$
**return** `RoundUp`$(J)$

## C Why the enclosing intervals become narrow

We analyse lower and upper calculations on the full graph, with a fresh independent uniform digit at every vertex in every sweep. By Appendix B.3, the queried endpoints have the same distribution as those in the finite local list.

### C.1 The decrease after one sweep

Write $\Delta_z = B_z - A_z$. Superscripts old and new refer to the start of a sweep and the value after a coordinate's update. For a vertex $z$, the shared digit $j_z$ gives

$$\Delta_z^{\text{new}} \le \frac{1}{S}\Delta_z^{\text{old}} + \frac{S-1-j_z}{S}\max_{u\to z}\Delta_u^{\text{new}} + \frac{j_z}{S}\max_{z\to u}\Delta_u^{\text{old}}, \tag{21}$$

with an empty maximum equal to zero. The stored interval bounds in the two calculations are identical.

Let $B_h(z)$ be the vertices at undirected distance at most $h$ from $z$. Put $D = \max_{u \in B_h(z)} \Delta_u^{\text{old}}$ and $a_u = (S - 1 - j_u)/S$. At $z$, (21) gives

$$\Delta_z^{\text{new}} \le (1 - a_z)D + a_z \max_{u \to z} \Delta_u^{\text{new}}.$$

Follow a predecessor attaining the maximum, and continue backwards to a source. This path has at most $h$ vertices; all its vertices and their successors lie in $B_h(z)$. At the source the predecessor term is zero. Substitution along the path bounds the new width by $(1 - \prod_u a_u)D$.

Write $\Delta_z(s)$ for the width after $s$ sweeps. Call the pair $(z, s)$ *bad* if, during sweep $s$, the digit at $z$ or any vertex preceding $z$ on a directed path equals $S - 1$. Otherwise all factors $a_u$ in the preceding expansion are at least $1/S$, and there are at most $h$ of them. Put $\beta = 1 - S^{-h}$. Consequently,

$$\Delta_z(s) \le \kappa_z(s) \max_{u \in B_h(z)} \Delta_u(s-1), \qquad \kappa_z(s) = \begin{cases} 1, & (z,s) \text{ is bad,} \\ \beta, & \text{otherwise.} \end{cases} \tag{22}$$

## C.2 Choosing the parameters

Write $r = 2$ for the bound on the number of queried coordinates. Both $B_h(z)$ and the set consisting of $z$ and its directed-path predecessors have at most $M$ vertices. Choose

$$M = (d+1)^{h+1}, \qquad S = \text{the least power of two at least } 4M^2. \tag{23}$$

The bad event in (22) involves only fresh digits from the current sweep. Its conditional probability is at most $M/S \le 1/(4M)$. With $\beta = 1 - S^{-h}$, choose the smallest positive integer $p$ satisfying the rational test

$$\beta^p \le \frac{1}{4M}. \tag{24}$$

Consequently,

$$\mathbb{E}\big[\kappa_z(s)^p \mid \text{earlier sweeps}\big] \le \frac{1}{4M} + \beta^p \le \frac{1}{2M}.$$

This estimate uses all directed-path predecessors in defining the bad event, so it also covers the predecessor choices made in the one-sweep expansion. No independence between vertices within a sweep is required.

Choose the smallest positive integer $t$ satisfying

$$2^{-t} \le \frac{\alpha \delta^p}{r}, \qquad \rho = ht + 1. \tag{25}$$

These choices are computable: $0 < \beta < 1$, and both tests compare rational numbers. Retain radius $\rho$ around the queried set $T$, freezing the outer boundary as in Algorithm 6.

The widths before sweep $s$ are fixed when we condition on earlier sweeps. Raising (22) to the power $p$, bounding the maximum by a sum, and taking expectations gives

$$\mathbb{E}\Delta_z(s)^p \le \frac{1}{2M} \sum_{u \in B_h(z)} \mathbb{E}\Delta_u(s-1)^p.$$

All initial widths are at most one and $|B_h(z)| \le M$. Induction gives $\mathbb{E}\Delta_z(s)^p \le 2^{-s}$ for every vertex. At sweep $t$, Markov's inequality gives $\mathbb{P}(\Delta_z(t) > \delta) \le 2^{-t}\delta^{-p} \le \alpha/r$. A union bound over the at most $r$ queried positions proves the width guarantee.

Each radius-$\rho$ neighborhood has at most $1 + d + \cdots + d^\rho \le (d+1)^{\rho+1}$ vertices. We may therefore use

$$b = r(d+1)^{\rho+1}, \qquad E = S^{bt} \tag{26}$$

as bounds on the retained vertices and enumerated digit assignments. All these choices depend only on $d, h, \delta, \alpha$.

# D Calibration of the finite certificates

We verify the central-interval routine and choose the finite calculation's parameters. The purpose of the calibration is to ensure that a failed certificate identifies a coordinate whose short interval gives a high density throughout its middle half.

## D.1 The central-interval test

For the one-coordinate list $[A_i, B_i]$, $1 \le i \le N$, take $u$ to be the $N/4$-th upper endpoint in sorted order and $v$ to be the $3N/4$-th lower endpoint. The alphabet size $S$ is divisible by four, and the queried coordinate is interior, so $N/4$ is an integer. Return `FAIL` if $u \ge v$ or fewer than $N/4$ list intervals lie wholly in $[u, v]$. Otherwise return $[u, v]$.

At least $N/4$ intervals end at or below $u$, and at least $N/4$ begin at or above $v$. On success, at least $N/4$ intervals also lie wholly inside $[u, v]$. Enclosure certifies mass at least $1/4$ in each of the three regions. The true distribution is continuous and supported on $(\ell_x, r_x)$, so these masses imply $\ell_x < u < v < r_x$. The endpoints are dyadic, and sorting and counting finite lists are deterministic.

## D.2 The width at which certificates succeed

The graph bounds limit how many coordinates can be comparable with a queried coordinate. Define

$$B = (k+1)^{2H+1}. \tag{27}$$

In an order-restriction DAG of degree at most $k$ and directed paths of at most $2H$ vertices, every comparable coordinate lies within undirected distance $2H$. Thus $B$ bounds the number of other comparable coordinates. Set

$$w_* = 2^{-2kB}. \tag{28}$$

This width calibrates the finite calculations. The algorithms test the computed certificates directly.

**Lemma D.1** (When certification succeeds)**.** *Let $D$ be a canonical order-restriction DAG with dyadic interval bounds, $V(D) > 0$, degree at most $k$, and directed paths of at most $2H$ vertices. If any coordinate involved in a comparison has interval width at least $w_*$, comparison certification succeeds. If $W_x \ge w_*$, then* `CentralInterval`$(D, x)$ *succeeds.*

*Proof of Lemma D.1.* Calibrate both routines using Theorem B.1 with

$$d = k, \qquad h = 2H, \qquad \alpha = \frac{\eta}{2}, \qquad \delta = \frac{\eta w_*}{8(B+1)}. \tag{29}$$

These parameters are fixed for the interaction. They do not depend on the queried widths.

Suppose one queried coordinate $x$ has $W_x \ge w_*$. If the computed intervals overlap and both have width at most $\delta$, the enclosed positions differ by at most $2\delta$. Lemma A.3 therefore bounds the unresolved fraction by

$$1 - p - q \le \alpha + \mathbb{P}(|X_x - X_y| \le 2\delta) \le \alpha + \frac{4(B+1)\delta}{w_*} = \eta.$$

Thus $\max(p, q) \ge (1-\eta)/2 > 1/2 - \eta$, so comparison certification succeeds. For a threshold $c$, an unresolved interval contains $c$. If its width is at most $\delta$, its enclosed position is within $\delta$ of $c$, giving the stronger bound

$$\alpha + \frac{2(B+1)\delta}{w_*} = \frac{3\eta}{4}. \tag{30}$$

It remains to show that `CentralInterval` succeeds when $W_x \geq w_*$. By (30), at most a fraction $\tau = 3\eta/4$ of its intervals contain any fixed real number. This bound applies in particular to the selected endpoints $u$ and $v$. An interval extending below $u$ either ends strictly below $u$ or contains $u$. By the rank defining $u$, fewer than $N/4$ intervals end strictly below it. Thus at most $(1/4 + \tau)N$ intervals extend below $u$. Similarly, at most $N/4$ intervals begin strictly above $v$, so at most $(1/4 + \tau)N$ extend above $v$.

At least $(1/2 - 2\tau)N \geq N/4$ intervals therefore lie wholly inside $[u, v]$, since $\eta < 1/32$. Enclosure gives this interval mass at least $1/4$. Continuity forces $u < v$, so both success tests pass. □

# E Selection guarantees and state updates

## E.1 Rounding an anchor

For a nondegenerate closed interval $J = [u, v] \subset (0, 1)$, choose the largest power-of-two spacing $h$ no greater than its length. The routine `RoundUp` rounds $u$ up to a multiple of $h$:

$$h = 2^{-r}, \qquad h \leq |J| < 2h, \qquad c = h \lceil u/h \rceil . \tag{31}$$

**Lemma E.1** (Rounding to a binary fraction)**.** *The value $c$ returned by* `RoundUp`$(J)$ *belongs to $J$. Writing $c = (2i + 1)/2^{m+1}$ in reduced form, it satisfies*

$$|J| < 2^{-m}. \tag{32}$$

*Proof.* The rounded value obeys $u \leq c < u + h \leq v$, so $c \in J$. The choice of spacing gives $h \leq |J| < 2h$. Reduction of the fraction cannot increase its denominator, so $m + 1 \leq r$ and $|J| < 2h \leq 2^{-m}$. □

*Proof of Lemma 3.3.* The interval comparisons in Appendix B certify lower probability bounds. If the larger bound is at least $1/2 - \eta$, `Select` returns its answer, breaking a tie in favor of the first queried label. On failure it rounds in the middle half of a queried coordinate's interval. For `ChooseAnchor`, a successful central test supplies the interval to round. On failure it too rounds in the middle half.

For a successful central test, Lemma A.5 gives $f_x(c) \geq 1/(16|J|)$. By Lemma E.1, $\log f_x(c) > m-4$. For either type of failed test, Lemma D.1 gives $W_x < w_* = 2^{-2kB}$ for the selected coordinate. Write $L = \log(1/W_x) > 2kB$. The density estimate (17) gives $\log f_x(c) \geq L - 2B > k$ throughout the middle half. That interval has length $W_x/2$, so $m < L + 1$ by Lemma E.1. Thus

$$\log f_x(c) \geq L - 2B > (1 - 1/k)L > (1 - 1/k)m - 4.$$

Both intervals used for rounding lie strictly inside the coordinate's range. □

## E.2 Refinement and child admission

*Proof of Lemma 3.2.* By (3), restriction multiplies the parent volume by $f_x(c)$. Inserting the isolated vertex into the child replaces $K_u$ by $K_u \times (0, 1)$, which has the same volume. The ratio of the products is therefore $f_x(c)$. □

For example, the parent region $0 < X_A < X_B < 1$ has area $1/2$. Fixing $X_A = 1/4$ leaves the interval $X_B \in (1/4, 1)$ of length $3/4$. The new child coordinate $U_A \in (0, 1)$ turns this into a rectangle of area $3/4$, so refinement multiplies $Z$ by $3/2$; see Figure 5. Both regions represent the order $A < B$. Replacing the fixed parent coordinate by a fresh child coordinate gives the larger area.





**Figure 5:** The highlighted section of the triangle has length 3/4. Replacing the fixed parent coordinate by a fresh unit coordinate in the child gives the rectangle on the right. Its area is 3/2 times the original area.

**Lemma E.2** (Refinement and child admission)**.** *Suppose the state represents only orders consistent with the transcript and every node has positive feasible volume. An interior refinement preserves both properties.*

*Proof.* Take feasible positions representing any order after the move. Remove the fresh coordinate of $x$ from the child and restore $X_x = c$ in the parent. The parent positions satisfy the old inequalities by construction. Keeping the other coordinates fixed, we can perturb $X_x$ slightly to either side of $c$, since its inequalities are strict. These two old orders place $x$ immediately before and immediately after the child block. Both respect the transcript, so it contains no comparison between $x$ and an item in the block. In the new order, $x$ can occur anywhere inside that block, with its order relative to all outside items preserved. For a new child the block was empty, and the same argument places $x$ at its former parent position. Positivity follows from Lemma 3.1 and the refinement identity. □

A refinement can change which orders the state represents. For instance, a move into an existing child allows interleavings inside that child that were previously excluded. The invariant concerns consistency with the transcript.

## E.3 Restoring the graph bounds

**Lemma E.3** (One-arc repair)**.** *Suppose all node graphs have degree below $k$ and directed paths with fewer than $H$ vertices before an answer is recorded. Recording the answer and executing* `Repair` *restores these bounds. During this operation, degrees are at most $k$ and directed paths have fewer than $2H$ vertices.*

*Proof.* An answer involving an anchor adds only an interval bound. An answer between free items adds at most one arc, say $x \to y$. Its certified positive probability ensures that the resulting region is nonempty, so the arc cannot create a directed cycle. Only $x$ and $y$ can reach degree $k$. Every new path consists of two old paths joined by this arc, so it has fewer than $2H$ vertices.

If an $H$-vertex path now exists, it must contain $x \to y$. Refining its entire vertex set removes both endpoints. Otherwise a degree repair removes an endpoint that has reached degree $k$. Either repair deletes the new arc; the remaining parent DAG is a subgraph of the previously valid DAG. Each child receives only isolated vertices, so its bounds remain valid too. If neither violation occurs, no repair is needed. □

### E.4 Consistency and termination

*Proof of Proposition 3.4.* Initially every node has positive volume, every order is represented, and the strict node graph bounds hold. We induct over completed calls and, within each call, over its changes to the state.

Before answering, a refinement deletes one vertex and adds an isolated vertex to a child, so the strict DAG bounds continue to hold. The anchor routine returns an interior position, as proved in Lemma 3.3. Lemma E.2 preserves positive node volumes and consistency with the transcript. Normalization preserves the represented region by Lemma 3.1.

If the queried labels lie in different child subtrees, their anchors determine the answer in every represented order. Otherwise, the answer guarantee in Lemma 3.3 ensures that the chosen answer retains at least $1/2 - \eta > 0$ of its node's volume. Recording its arc or interval bound therefore preserves positive volume and makes the answer true in every represented order. A new arc cannot create a cycle, since that would make the region empty. Normalization preserves this updated region. The transcript is then extended by the chosen answer.

During the subsequent repair, the temporary DAG bounds follow from Lemma E.3. Each move again preserves positive volume and the transcript by Lemma E.2. This applies to every vertex of a selected path, including those whose incident arcs were removed earlier in the batch. The full batch is completed, and Lemma E.3 restores the strict bounds for the next call.

The finite certificate calculations and the explicit rounding rule terminate. Before answering, only queried labels can move. After a move, the label has an isolated coordinate with interval $(0, 1)$. Further refinements leave it isolated with the same interval, so its density remains one. A second move would therefore have gain zero, contradicting the failed-certification gain guarantee. Thus there are at most two such moves. A repair makes at most $n$ further moves, so every call terminates with at most $n + 2$ refinements. All analytic guarantees used here apply to arbitrary positive-volume regions with the stated DAG bounds, independently of the interaction history. □

## F Exact arithmetic and the stored state

The budget $E_k \le n$ bounds the number of digit assignments and their length. We verify that it also bounds their bit cost, and that the recursive state remains of polynomial size up to the comparison horizon. Computation is measured on a fixed deterministic multitape Turing machine, with integers represented in binary.

Write $S_k$ for the number of digit choices, $t_k$ for the number of sweeps, and $b_k$ for the bound on retained vertices in (26), with the parameters chosen in Appendix D. The enumeration bound is

$$E_k = S_k^{b_k t_k}. \tag{33}$$

### F.1 Choosing the parameter

A fixed program generates the parameters and $E_k$ for $k = 64, 128, \ldots$, writing each completed tuple in binary. On input size $n$, run this program for $n$ steps and choose the largest completed $k$ with $E_k \le n$. If none qualifies, answer from the fixed label order. The simulation writes at most $n$ bits, so parsing its output and selecting a tuple also take polynomial time.

For every fixed $k$, both its generation time and $E_k$ are finite. That tuple therefore qualifies for all sufficiently large $n$, proving $k(n) \to \infty$.

### F.2 Precision in the interval calculation

Suppose the stored endpoints have at most $\Lambda$ fractional binary digits. An update takes maxima and minima, forms an integer linear combination, and divides by the power of two $S$. It therefore adds at most $\log S$ fractional digits. If there are $b'$ interior vertices, each endpoint calculation makes $b't$ updates. The two calculations share digits but use their own values, so the precision in either is at most

$$\Lambda + b't \log S \le \Lambda + \log E. \tag{34}$$

This proves the precision claim of Theorem B.1. All computed positions remain in $[0, 1]$, so their integer numerators need at most one additional bit. Digits and counts have at most $\log S$ and $\log E + 1$ bits, respectively.

### F.3 Precision of new anchors

If a nondegenerate interval has dyadic endpoints with at most $F$ fractional digits, its length is at least $2^{-F}$. The rounding rule of Lemma E.1 therefore uses a grid exponent at most $F$, and its anchor has at most $F$ fractional digits.

For a certified central interval, (34) gives $F \le \Lambda + \log E_k$. Forming the middle half of a stored interval gives endpoints with at most $\Lambda + 2$ digits. Since $E_k \ge 4$, both choices produce anchors with at most $\Lambda + \log E_k$ digits. This also covers the direct middle-half choice after a failed comparison certificate. The update of neighboring bounds and `Normalize` take maxima and minima of existing endpoints and the chosen anchor, adding no precision.

All initial endpoints are 0 or 1. After $P$ refinements, induction therefore gives $\Lambda \le P \log E_k$. By Lemma 4.1, completed calls before the horizon account for $O(Q(n)/k)$ refinements. An unfinished call adds at most $n + 2$ by Proposition 3.4. Thus, throughout the recursive phase,

$$P = O(Q(n)/k + n), \tag{35}$$

and consequently

$$\Lambda \le P \log E_k = O(n \log^2 n). \tag{36}$$

Temporary endpoints in the next calculation add at most another $\log E_k$ digits.

### F.4 Inventory and work per call

Each refinement creates at most one recursive-tree node. There are thus at most $P + 1$ nodes, $n$ item records, and at most $P$ stored child anchors. An item belongs to exactly one node graph, so their total numbers of vertices and arcs are at most $n$ and $n^2$, respectively. The recorded prefix contains at most $Q(n)$ comparisons. Labels, pointers, depths, and counters have polynomial length, as do all dyadic endpoints by (36).

For one certificate, the algorithm enumerates at most $E_k \le n$ digit assignments. Each assignment uses two endpoint calculations, each with at most $b_k t_k \le \log E_k \le \log n$ updates. The boundary vertices remain fixed. Maxima, minima, integer multiplication, and division by powers of two operate on polynomially many bits. Central certification sorts at most $n$ lower and upper endpoints and counts the intervals inside its candidate. Rounding computes a grid exponent and a ceiling using the same bounded-precision integers. Standard binary arithmetic therefore gives a fixed polynomial bound for each operation.

Before selecting an answer, a call makes at most two failure refinements and three calls to `Select`. Failure refinements use the middle half directly. After recording the answer, the single structural repair makes at most $n$ refinements and hence at most $n$ calls to `ChooseAnchor`.

The remaining work is polynomial in the stored graph size. Topological passes normalize intervals and compute directed-path lengths. A finite graph search finds each retained neighborhood; it stops when either the prescribed radius or all available vertices have been reached. Routing uses the recursive tree, and deterministic choices can be made by scanning labels. At the horizon, topologically sorting the bounded transcript DAG produces the fixed ranks for all later answers. Thus the bit-operation bound has a fixed exponent, independent of $k$ and of the number of queries already answered.

# G Parameter reference

Table 1 collects the parameters of the adversary and its analysis. The last two columns distinguish where a parameter's role is introduced from where its value is chosen and explained. All choices are fixed before the first query. Appendix C gives explicit choices for the digit alphabet, number of sweeps, and neighborhood radius in the local enclosure theorem.

**Table 1:** Parameters and their roles. References lead to the explanations in the text.

| Symbol | Value | Role | Introduced | Choice |
|---|---|---|---|---|
| $k$ | Integer, $k \geq 64$ | Repair a vertex that reaches this degree after an answer. | §3.3 | §4 |
| $H$ | $2^k$ | Number of vertices refined in a selected directed path. | §3.3 | §3.3 |
| $B$ | $(k+1)^{2H+1}$ | Bounds the number of other vertices comparable with one vertex in its node graph. | App. D | App. D |
| $w_*$ | $2^{-2kB}$ | Calibrates the finite calculations: a coordinate of at least this width guarantees certification. | App. D | App. D |
| $\eta$ | $1/(100k)$ | Accept an answer whose certified probability is at least $1/2 - \eta$. | §3.3 | §3.3 |
| $Q(n)$ | $n \lceil \log n \rceil$ | Number of answers before switching to a fixed consistent order. | §3.3 | §3.3 |

# H Proofs of the consequences

## H.1 Producing a target order

*Proof of Corollary 6.1.* A successful output assigns each key to one slot of $R$. Every total order satisfying the transcript must respect this assignment, so $T_q \leq e(R)$. Apply Theorem 3.5 with the parameter $k = k(n)$ selected in Section 5. It gives $q \geq I(R)/(1+\delta_{k(n)})$. Take $\varepsilon_n = \delta_{k(n)}/(1+\delta_{k(n)})$ when a parameter qualifies and $\varepsilon_n = 1$ otherwise. Since $k(n) \to \infty$, $\varepsilon_n \to 0$, uniformly over targets. □

## H.2 A compatible partition into layers

The reduction for an initial partial order needs an ordered partition whose layers retain many permutations. Cardinal et al.'s construction gives such a partition.

**Lemma H.1** (Weak-order extension)**.** *Given a partial order $P$ on $n$ elements, one can deterministically construct in polynomial time a weak order $W$ extending $P$ such that*

$$\log e(W) \geq \log e(P) - C_0 n \log\log n$$

*for an absolute constant $C_0$.*

*Proof.* Cardinal et al. [14, Section 3, Lemmas 1 and 3] construct $W$ in polynomial time with

$$I(W) \leq I(P) + 2n \log(I(P)/n + 1) + O(n).$$

Since $I(P) \leq \log(n!) \leq n \log n$, the extra term is $O(n \log\log n)$. Substitute $I(W) - I(P) = \log e(P) - \log e(W)$. For two elements, take $W = P$. □

An arbitrary partition into antichains need not admit a compatible layer order. For example, the relations $a < b$ and $c < d$ permit the antichains $\{a, d\}$ and $\{b, c\}$, but require opposite orders between them. Lemma H.1 supplies both the partition and a layer order respecting all initial relations.

*Proof of Corollary 6.2.* Construct $W$ using Lemma H.1, and let its layers have sizes $m_1, \ldots, m_t$. Choose $k = k(n)$ once, using the full input size. Within every layer of size at least two, run a copy of the ordinary adversary with these parameters and its local horizon $Q(m_i) = m_i \lceil \log m_i \rceil$. A singleton needs no comparisons. Answer comparisons between layers from their fixed order.

Each local transcript has a consistent total order. Concatenating these orders gives a linear extension of $W$ and hence of $P$, proving legality. At termination, each layer must have a unique possible order: two possible orders in one layer, combined with the same orders in the others, would give two global orders consistent with the full transcript.

Let $q_i$ count comparisons within layer $i$. Theorem 3.5 applies to the local transcript with $T_{q_i} = 1$ and gives

$$q_i \geq \frac{\log(m_i!)}{1 + \delta_k}.$$

The inequality also holds for a singleton. Since $\sum_i m_i = n$ and $e(W) = \prod_i m_i!$, summing gives

$$\begin{aligned} q \geq \sum_i q_i &\geq \frac{\log e(W)}{1 + \delta_k} \\ &\geq \frac{\log e(P) - C_0 n \log\log n}{1 + \delta_k}. \end{aligned}$$

As $k(n) \to \infty$, this implies the stated bound, uniformly over $P$.

The common choice of $k(n)$ is essential to this estimate: each layer has the same $\delta_k$, even when its size stays small. It also preserves polynomial time in $n$. Each finite calculation enumerates at most $E_k \leq n$ assignments. Across all layers, the horizons sum to at most $n \lceil \log n \rceil$, and the refinement and precision bounds of Section 5 apply with the ambient size $n$. The construction of $W$ is polynomial-time as well. For the finitely many sizes at which no tuple qualifies, use a fixed topological order of $P$. □

## References


[1] Donald E. Knuth. *The Art of Computer Programming, Volume 3: Sorting and Searching.* Second edition, Addison-Wesley, 1998. Publisher's page.

[2] Michael L. Fredman. *How good is the information theory bound in sorting?* Theoretical Computer Science 1(4), 355–361, 1976. doi:10.1016/0304-3975(76)90078-5.

[3] Mikhail J. Atallah and S. Rao Kosaraju. *An adversary-based lower bound for sorting.* Information Processing Letters 13(2), 55–57, 1981.

[4] Allan Borodin, Leonidas J. Guibas, Nancy A. Lynch, and Andrew C. Yao. *Efficient searching using partial ordering.* Information Processing Letters 12(2), 71–75, 1981. doi:10.1016/0020-0190(81)90005-3.

[5] Dana Richards and Pravin M. Vaidya. *On the distribution of comparisons in sorting algorithms.* BIT 28, 764–774, 1988. Authors' paper.

[6] Gerth Stølting Brodal, Shiva Chaudhuri, and Jaikumar Radhakrishnan. *The randomized complexity of maintaining the minimum.* Nordic Journal of Computing 3(4), 337–351, 1996. Authors' report, BRICS RS-96-40.

[7] Haim Kaplan, Or Zamir, and Uri Zwick. *The amortized cost of finding the minimum.* Proceedings of the Twenty-Sixth Annual ACM–SIAM Symposium on Discrete Algorithms (SODA), 757–768, 2015. Published online 22 December 2014. doi:10.1137/1.9781611973730.51. Authors' paper.

[8] Haim Kaplan, Or Zamir, and Uri Zwick. *A sort of an adversary.* Proceedings of the Thirtieth Annual ACM–SIAM Symposium on Discrete Algorithms (SODA), 1291–1310, 2019. doi:10.1137/1.9781611975482.79.

[9] Richard P. Stanley. *Two poset polytopes.* Discrete & Computational Geometry 1, 9–23, 1986. doi:10.1007/BF02187680. Author's copy.

[10] Graham Brightwell and Peter Winkler. *Counting linear extensions.* Order 8(3), 225–242, 1991. doi:10.1007/BF00383444.

[11] Martin Dyer, Alan Frieze, and Ravi Kannan. *A random polynomial-time algorithm for approximating the volume of convex bodies.* Journal of the ACM 38(1), 1–17, 1991. doi:10.1145/102782.102783. Authors' manuscript.

[12] Jeff Kahn and Jeong Han Kim. *Entropy and sorting.* Journal of Computer and System Sciences 51(3), 390–399, 1995. doi:10.1006/jcss.1995.1077.

[13] András Prékopa. *On logarithmic concave measures and functions.* Acta Scientiarum Mathematicarum 34, 335–343, 1973. Publisher's paper.

[14] Jean Cardinal, Samuel Fiorini, Gwenaël Joret, Raphaël M. Jungers, and J. Ian Munro. *An efficient algorithm for partial order production.* SIAM Journal on Computing 39(7), 2927–2940, 2010. doi:10.1137/090759860. Authors' manuscript.

[15] Ivor van der Hoog, Irina Kostitsyna, Maarten Löffler, and Bettina Speckmann. *Preprocessing ambiguous imprecise points.* 35th International Symposium on Computational Geometry (SoCG), LIPIcs 129, 42:1–42:16, 2019. doi:10.4230/LIPIcs.SoCG.2019.42.

[16] Ivor van der Hoog, Irina Kostitsyna, Maarten Löffler, and Bettina Speckmann. *Sorting under partial (interval order) information.* Journal of Computational Geometry 15(1), 143–171, 2024. doi:10.20382/jocg.v15i1a6.