

Vox Populi: Collecting High-Quality Labels from a Crowd

Authors: Ofer Dekel, Ohad Shamir (COLT 2009)

Presenter: Haofan Zhang

David R. Cheriton School of Computer Science,
University of Waterloo,
Waterloo, Canada

October 20, 2014

Agenda



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Introduction

Background

Settings and Notations

Algorithms and Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned Dataset

Experiments

Experiment Settings

Experiment Results

Q & A



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

3

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ Traditional machine learning focuses on the **single-teacher setting**

Introduction

Learning from Crowd



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

3

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ Traditional machine learning focuses on the **single-teacher setting**
- ▶ We are faced with the problem of **learning from crowd**



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

3

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ Traditional machine learning focuses on the **single-teacher setting**
- ▶ We are faced with the problem of **learning from crowd**
- ▶ Therefore, we are interested in identifying and removing low-quality teachers

Introduction

Learning from Crowd



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

4

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Several challenges:



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

4

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Several challenges:

- ▶ No prior knowledge on the identity or the quality of the teacher



Several challenges:

- ▶ No prior knowledge on the identity or the quality of the teacher
- ▶ No access to gold-set of perfectly labeled examples

4

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A



Several challenges:

- ▶ No prior knowledge on the identity or the quality of the teacher
- ▶ No access to gold-set of perfectly labeled examples
 - ▶ Moreover, a typical teacher only labels a handful set of examples

Introduction

4

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A



Several challenges:

- ▶ No prior knowledge on the identity or the quality of the teacher
- ▶ No access to gold-set of perfectly labeled examples
 - ▶ Moreover, a typical teacher only labels a handful set of examples
- ▶ No control on assignment of examples

4

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A



Several challenges:

- ▶ No prior knowledge on the identity or the quality of the teacher
- ▶ No access to gold-set of perfectly labeled examples
 - ▶ Moreover, a typical teacher only labels a handful set of examples
- ▶ No control on assignment of examples
 - ▶ Prevent us from applying **repeated labeling**.
 - ▶ Even applicable, should be avoided because of the cost.

4

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Introduction

Our Goal



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

5

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Ultimately, our problem is to:

- ▶ Work with raw labeled data, with **single noisy label per example**
- ▶ Detect and eliminate low-quality teaches in a **principled** and **effective** manner

Introduction

Vox Populi



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

6

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Vox populi, vox Dei
–The voice of the people [is] the voice of God.

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Suppose we have **multiple labels** for each example

7

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

28

David R. Cheriton School of
Computer Science,
University of Waterloo

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Suppose we have **multiple labels** for each example

- If most of teaches are good, we can simply take the **average** or **majority** over repeated labels

7

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Suppose we have **multiple labels** for each example

- ▶ If most of teaches are good, we can simply take the **average** or **majority** over repeated labels
- ▶ Then we treat this **aggregated label** as ground truth and count incorrect label provided by each teacher

7

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Suppose we have **multiple labels** for each example

- ▶ If most of teaches are good, we can simply take the **average** or **majority** over repeated labels
- ▶ Then we treat this **aggregated label** as ground truth and count incorrect label provided by each teacher
- ▶ Once we identify low-quality teachers, we can ignore them in the future.

7

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Suppose we have **multiple labels** for each example

- ▶ If most of teaches are good, we can simply take the **average** or **majority** over repeated labels
- ▶ Then we treat this **aggregated label** as ground truth and count incorrect label provided by each teacher
- ▶ Once we identify low-quality teachers, we can ignore them in the future.

However, we don't have aggregated labels...

7

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Suppose we have **multiple labels** for each example

- ▶ If most of teaches are good, we can simply take the **average** or **majority** over repeated labels
- ▶ Then we treat this **aggregated label** as ground truth and count incorrect label provided by each teacher
- ▶ Once we identify low-quality teachers, we can ignore them in the future.

However, we don't have aggregated labels...

We want to **simulate** them!

7

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

8

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Simulating aggregated labels:

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

8

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Simulating aggregated labels:

- Specifically, we train a hypothesis(classifier) on the entire unfiltered dataset

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

8

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Simulating aggregated labels:

- ▶ Specifically, we train a hypothesis(classifier) on the entire unfiltered dataset
- ▶ Then we regard the predictions of this hypothesis as the ground truth.

Introduction

A Simple Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

8

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Simulating aggregated labels:

- ▶ Specifically, we train a hypothesis(classifier) on the entire unfiltered dataset
- ▶ Then we regard the predictions of this hypothesis as the ground truth.
- ▶ We **pretend** that we can rely on it, and eliminate low-quality teachers!

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

We focus on **binary classification** setting:

- ▶ Instance space: $\mathcal{X} \subseteq \mathbb{R}^n$

Introduction

Background

9

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

We focus on **binary classification** setting:

- ▶ Instance space: $\mathcal{X} \subseteq \mathbb{R}^n$
- ▶ Test Probability Distribution: $\mathcal{D} : \mathcal{X} \times \{-1, +1\}$

9

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

We focus on **binary classification** setting:

- ▶ Instance space: $\mathcal{X} \subseteq \mathbb{R}^n$
- ▶ Test Probability Distribution: $\mathcal{D} : \mathcal{X} \times \{-1, +1\}$
- ▶ Given dataset: $S = \{\mathbf{x}_i, y_i\}_{i=1}^m$

9

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

We focus on **binary classification** setting:

- ▶ Instance space: $\mathcal{X} \subseteq \mathbb{R}^n$
- ▶ Test Probability Distribution: $\mathcal{D} : \mathcal{X} \times \{-1, +1\}$
- ▶ Given dataset: $S = \{\mathbf{x}_i, y_i\}_{i=1}^m$
- ▶ The ML algorithm minimizes:

$$\hat{F}_\lambda(\mathbf{w}, S) = \lambda \|\mathbf{w}\|^2 + \frac{1}{m} \sum_{i=1}^m \ell(f(\mathbf{w}, \mathbf{x}_i), y_i)$$

- ▶ Additionally,

$$f(\mathbf{w}, \mathbf{x}_i) = \langle \mathbf{w}, \phi(\mathbf{x}_i) \rangle$$

represents application of classifier \mathbf{w} to the instance \mathbf{x}_i

Introduction

Background

9

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

In typical supervised learning setting:

- ▶ we assume that a training set S is sampled i.i.d from \mathcal{D}

Introduction

Background

10

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

In typical supervised learning setting:

- ▶ we assume that a training set S is sampled i.i.d from \mathcal{D}

Here, we introduce an **extra stage** where data is labeled by a set of k teachers:

10

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

10

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

In typical supervised learning setting:

- ▶ we assume that a training set S is sampled i.i.d from \mathcal{D}

Here, we introduce an **extra stage** where data is labeled by a set of k teachers:

- ▶ There exists k classifiers

$$\{h_1(\mathbf{x}), h_2(\mathbf{x}), \dots, h_k(\mathbf{x})\} : \mathcal{X} \rightarrow \{-1, +1\}$$

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

10

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

In typical supervised learning setting:

- ▶ we assume that a training set S is sampled i.i.d from \mathcal{D}

Here, we introduce an **extra stage** where data is labeled by a set of k teachers:

- ▶ There exists k classifiers
 $\{h_1(\mathbf{x}), h_2(\mathbf{x}), \dots, h_k(\mathbf{x})\} : \mathcal{X} \rightarrow \{-1, +1\}$
- ▶ For each unlabeled instance \mathbf{x} , we choose a teacher
 $t \in \{1, \dots, k\}$ at random (uniformly here for simplicity)

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

10 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

In typical supervised learning setting:

- ▶ we assume that a training set S is sampled i.i.d from \mathcal{D}

Here, we introduce an **extra stage** where data is labeled by a set of k teachers:

- ▶ There exists k classifiers
 $\{h_1(\mathbf{x}), h_2(\mathbf{x}), \dots, h_k(\mathbf{x})\} : \mathcal{X} \rightarrow \{-1, +1\}$
- ▶ For each unlabeled instance \mathbf{x} , we choose a teacher
 $t \in \{1, \dots, k\}$ at random (uniformly here for simplicity)
- ▶ This results in splitting the sample into k subsets, S_1, \dots, S_k

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

11 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- This process can be viewed as sampling an unlabeled dataset and labeling it using $\bar{h}(\mathbf{x})$,

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

11 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- This process can be viewed as sampling an unlabeled dataset and labeling it using $\bar{h}(\mathbf{x})$, where $\bar{h}(\mathbf{x})$ is the random classifier defined by randomly choosing a hypothesis from h_1, \dots, h_k

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

11 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ This process can be viewed as sampling an unlabeled dataset and labeling it using $\bar{h}(\mathbf{x})$, where $\bar{h}(\mathbf{x})$ is the random classifier defined by randomly choosing a hypothesis from h_1, \dots, h_k
- ▶ Remember we want to minimize $\hat{F}_\lambda(\mathbf{w}, S)$:

$$\hat{F}_\lambda(\mathbf{w}, S) = \lambda \|\mathbf{w}\|^2 + \frac{1}{m} \sum_{i=1}^m \ell(f(\mathbf{w}, \mathbf{x}_i), y_i)$$

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

11 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

David R. Cheriton School of
Computer Science,
University of Waterloo

- ▶ This process can be viewed as sampling an unlabeled dataset and labeling it using $\bar{h}(\mathbf{x})$, where $\bar{h}(\mathbf{x})$ is the random classifier defined by randomly choosing a hypothesis from h_1, \dots, h_k
- ▶ Remember we want to minimize $\hat{F}_\lambda(\mathbf{w}, S)$:

$$\hat{F}_\lambda(\mathbf{w}, S) = \lambda \|\mathbf{w}\|^2 + \frac{1}{m} \sum_{i=1}^m \ell(f(\mathbf{w}, \mathbf{x}_i), y_i)$$

- ▶ Then, it can be seen as the empirical counterpart of minimizing

$$F_\lambda(\mathbf{w}) = \lambda \|\mathbf{w}\|^2 + \mathbb{E} [\ell(f(\mathbf{w}, \mathbf{x}), \bar{h}(\mathbf{x}))]$$

- ▶ We denote \mathbf{w}^* as the minimizer of $F_\lambda(\mathbf{w})$

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

12 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- Remember that, our goal is to identify and prune away low-quality teachers.

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

12 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ Remember that, our goal is to identify and prune away low-quality teachers.
- ▶ After pruning, only a set of high-quality teachers are left

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

12 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ Remember that, our goal is to identify and prune away low-quality teachers.
- ▶ After pruning, only a set of high-quality teachers are left
- ▶ We denote $\bar{h}_T(\cdot)$ as randomly pick one classifier from high-quality teachers

Settings and Notations



- Error rate of teacher t :

$$e_t = \Pr_{(\mathbf{x}, y) \sim D} (yh_t(\mathbf{x}) < 0)$$

Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

13 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

13

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- Error rate of teacher t :

$$e_t = \Pr_{(\mathbf{x}, y) \sim D} (yh_t(\mathbf{x}) < 0)$$

- Error rate of entire crowd before pruning:

$$\bar{e} = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}(\mathbf{x}) < 0)$$

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

13

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- Error rate of teacher t :

$$e_t = \Pr_{(\mathbf{x}, y) \sim D} (yh_t(\mathbf{x}) < 0)$$

- Error rate of entire crowd before pruning:

$$\bar{e} = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}(\mathbf{x}) < 0)$$

- Error rate of entire crowd after pruning:

$$\bar{e}_T = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}_T(\mathbf{x}) < 0 | \mathcal{S})$$

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

13 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- Error rate of teacher t :

$$e_t = \Pr_{(\mathbf{x}, y) \sim D} (yh_t(\mathbf{x}) < 0)$$

- Error rate of entire crowd before pruning:

$$\bar{e} = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}(\mathbf{x}) < 0)$$

- Error rate of entire crowd after pruning:

$$\bar{e}_T = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}_T(\mathbf{x}) < 0 | \mathcal{S})$$

However, we don't know \mathcal{D} nor h_t , we cannot calculate e_t directly!

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

13 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- Error rate of teacher t :

$$e_t = \Pr_{(\mathbf{x}, y) \sim D} (yh_t(\mathbf{x}) < 0)$$

- Error rate of entire crowd before pruning:

$$\bar{e} = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}(\mathbf{x}) < 0)$$

- Error rate of entire crowd after pruning:

$$\bar{e}_T = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}_T(\mathbf{x}) < 0 | \mathcal{S})$$

However, we don't know \mathcal{D} nor h_t , we cannot calculate e_t directly!
We need to look at something different!

Settings and Notations



The true “error-rate” according to \mathcal{D} :

$$e_t = \Pr_{(\mathbf{x}, y) \sim D} (yh_t(\mathbf{x}) < 0)$$

$$\bar{e} = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}(\mathbf{x}) < 0)$$

$$\bar{e}_T = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}_T(\mathbf{x}) < 0 | S)$$

Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

14 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

14 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

The true “error-rate” according to \mathcal{D} :

$$e_t = \Pr_{(\mathbf{x}, y) \sim D} (yh_t(\mathbf{x}) < 0)$$

$$\bar{e} = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}(\mathbf{x}) < 0)$$

$$\bar{e}_T = \Pr_{(\mathbf{x}, y) \sim D} (y\bar{h}_T(\mathbf{x}) < 0 | S)$$

The idea is to look at the “error-rate” with respect to \mathbf{w}^* :

$$\epsilon_t = \Pr(h_t(\mathbf{x})f(\mathbf{w}^*, \mathbf{x}) < 0)$$

$$\bar{\epsilon} = \Pr(\bar{h}(\mathbf{x})f(\mathbf{w}^*, \mathbf{x}) < 0)$$

$$\bar{\epsilon}_T = \Pr(\bar{h}_T f(\mathbf{w}^*, \mathbf{x}) < 0 | S)$$

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

15 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

The idea is to look at the “error-rate” with respect to \mathbf{w}^* :

$$\epsilon_t = \Pr(h_t(\mathbf{x})f(\mathbf{w}^*, \mathbf{x}) < 0)$$

$$\bar{\epsilon} = \Pr(\bar{h}(\mathbf{x})f(\mathbf{w}^*, \mathbf{x}) < 0)$$

$$\bar{\epsilon}_T = \Pr(\bar{h}_T f(\mathbf{w}^*, \mathbf{x}) < 0 | S)$$

Also, it is easy to see:

$$\bar{\epsilon} = \frac{\sum_{t=1}^k \epsilon_t}{k}, \quad \bar{\epsilon}_T = \frac{\sum_{t=1}^k \mathbf{1}(t \text{ not pruned}) \epsilon_t}{|\{t : t \text{ not pruned}\}|}$$

Settings and Notations



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

15 Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

The idea is to look at the “error-rate” with respect to \mathbf{w}^* :

$$\epsilon_t = \Pr(h_t(\mathbf{x})f(\mathbf{w}^*, \mathbf{x}) < 0)$$

$$\bar{\epsilon} = \Pr(\bar{h}(\mathbf{x})f(\mathbf{w}^*, \mathbf{x}) < 0)$$

$$\bar{\epsilon}_T = \Pr(\bar{h}_T f(\mathbf{w}^*, \mathbf{x}) < 0 | S)$$

Also, it is easy to see:

$$\bar{\epsilon} = \frac{\sum_{t=1}^k \epsilon_t}{k}, \quad \bar{\epsilon}_T = \frac{\sum_{t=1}^k \mathbf{1}(t \text{ not pruned}) \epsilon_t}{|\{t : t \text{ not pruned}\}|}$$

So, what is the relationship between $\bar{\epsilon}_T$ and classification error?

Algorithms and Theoretical Foundations

Relating $\bar{\epsilon}_T$ and Classification Error



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

16 Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Theorem 1

Assuming $p_D(y|\mathbf{x}) \in \{0, 1\}$, it holds for any teacher t that

$$\epsilon_t = \Pr_{(\mathbf{x}, y) \sim D}(yf(\mathbf{w}^*, \mathbf{x}) < 0) + \mathbb{E}_{(\mathbf{x}, y)}[e_t(\mathbf{x})\text{sign}(yf(\mathbf{w}^*, \mathbf{x}))]$$



Corollary 2

Assume that for any teacher t , $e_t(\mathbf{x}) \equiv e_t$ is a constant independent of \mathbf{x} . If $\Pr(\text{sign}(f(\mathbf{w}^*, \mathbf{x})) \neq y) < 1/2$, then $\{\epsilon_t\}, \bar{\epsilon}, \bar{\epsilon}_T$ are equivalent to $\{e_t\}, \bar{e}, \bar{e}_T$ respectively, up to a uniform, monotonically increasing linear transformation.



Corollary 2

Assume that for any teacher t , $e_t(\mathbf{x}) \equiv e_t$ is a constant independent of \mathbf{x} . If $\Pr(\text{sign}(f(\mathbf{w}^*, \mathbf{x})) \neq y) < 1/2$, then $\{\epsilon_t\}, \bar{\epsilon}, \bar{\epsilon}_T$ are equivalent to $\{e_t\}, \bar{e}, \bar{e}_T$ respectively, up to a uniform, monotonically increasing linear transformation.

- This means, \mathbf{w}^* does not have to be particularly good, an error-rate smaller than $1/2$ suffices.

Pruning Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

18 Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Motivated by Theorem 1, we consider the following simple algorithm to prune teachers:

Pruning Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

18 Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Motivated by Theorem 1, we consider the following simple algorithm to prune teachers:

- ▶ Train a classifier \mathbf{w}' on the entire dataset and prune away any teacher for which

$$\frac{\sum_{i \in S_t} \mathbf{1}(h_t(\mathbf{x}_i)f(\mathbf{w}', \mathbf{x}_i) < 0)}{|S_t|} > T$$

for some threshold $T \in (0, 1)$

Pruning Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

18 Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Motivated by Theorem 1, we consider the following simple algorithm to prune teachers:

- ▶ Train a classifier \mathbf{w}' on the entire dataset and prune away any teacher for which

$$\frac{\sum_{i \in S_t} \mathbf{1}(h_t(\mathbf{x}_i)f(\mathbf{w}', \mathbf{x}_i) < 0)}{|S_t|} > T$$

for some threshold $T \in (0, 1)$

- ▶ Essentially, this calculates a rough empirical estimate of ϵ_t , and removes all teachers where this estimate exceeds the threshold T

Pruning Algorithm



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

18 Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Motivated by Theorem 1, we consider the following simple algorithm to prune teachers:

- ▶ Train a classifier \mathbf{w}' on the entire dataset and prune away any teacher for which

$$\frac{\sum_{i \in S_t} \mathbf{1}(h_t(\mathbf{x}_i)f(\mathbf{w}', \mathbf{x}_i) < 0)}{|S_t|} > T$$

for some threshold $T \in (0, 1)$

- ▶ Essentially, this calculates a rough empirical estimate of ϵ_t , and removes all teachers where this estimate exceeds the threshold T
- ▶ The question is: Can this actually help???

Pruning Can Help



Theorem 3

Assume we use the pruning procedure described previously. Also, let $F : [0, 1] \rightarrow [0, 1]$ be a cumulative distribution function, such that $F(a) = \frac{1}{k} \sum_{t=1}^k \mathbf{1}(\epsilon_t \leq a)$. Let $P \sim F(\cdot)$, and let $N \sim \text{Poi}(m/k)$ be a Poisson random variable with parameter m/k . If we assume $m/k = \Theta(1)$ as m, k increase, it holds that

$$\bar{\epsilon} = \mathbb{E}_P[P]$$

and with probability at least $1 - \delta$ over the training sample

$$\bar{\epsilon}_T \leq \frac{\mathbb{E}_{P,N}[\Pr(X_N^P \leq NT)P] + r(m, \delta)}{\mathbb{E}_{P,N}[\Pr(X_N^P \leq NT)] - r(m, \delta)}$$

where X_N^P is a binomial random variable, representing sum of N independent Bernoulli random variables with parameter P , and

$$r(m, \delta) = O\left(\sqrt{\frac{\log(6/\delta)}{m}}\right)$$

Vox Populi: Collecting High-Quality Labels from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and Theories

19 Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

David R. Cheriton School of Computer Science,
University of Waterloo

Pruning Can Help



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

20 Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Pruning Can't Hurt



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

21 **Pruning Can't Hurt**

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Another question is:

Can we guarantee that $\bar{\epsilon}_T$ is never considerably larger than $\bar{\epsilon}$?

Pruning Can't Hurt



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

21 Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Another question is:

Can we guarantee that $\bar{\epsilon}_T$ is never considerably larger than $\bar{\epsilon}$?

Theorem 4

In the setting of Theorem 3, it holds for any $\{\epsilon_t\}$ that

$$\bar{\epsilon}_T \leq \bar{\epsilon} + \frac{2r(m, \delta)}{\mathbb{E}_{P,N}[\Pr(X_N^P \leq NT)] - r(m, \delta)}$$

where

$$r(m, \delta) = O\left(\sqrt{\frac{\log(6/\delta)}{m}}\right)$$

Setting the Threshold T



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

22 Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

One final question is, how to choose the threshold T ?

Setting the Threshold T



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

22 Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

One final question is, how to choose the threshold T ?

Corollary 5

In the setting of Theorem 1, a sufficient condition for $e_t > \bar{e}$ is

$$\epsilon_t > \Pr_{(\mathbf{x}, y) \sim D} (yf(\mathbf{w}^*, \mathbf{x}) < 0) + \bar{e}$$

Setting the Threshold T



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

22 Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

One final question is, how to choose the threshold T ?

Corollary 5

In the setting of Theorem 1, a sufficient condition for $e_t > \bar{e}$ is

$$\epsilon_t > \Pr_{(\mathbf{x}, y) \sim D} (yf(\mathbf{w}^*, \mathbf{x}) < 0) + \bar{e}$$

- ▶ This corollary implies that, if ϵ_t is larger than a certain quantity, it is definitely worse than average
- ▶ This suggests a reasonable choice for T is:

$$\Pr_{(\mathbf{x}, y) \sim D} (yf(\mathbf{w}', \mathbf{x}) < 0) + \bar{e}$$

Reusing the Cleaned Dataset



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

23

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- If pruning is successful, we expect to have a cleaner dataset

28

Reusing the Cleaned Dataset



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

23

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ If pruning is successful, we expect to have a cleaner dataset
- ▶ A more accurate classifier is thereby obtainable

28

Reusing the Cleaned Dataset



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

23

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

- ▶ If pruning is successful, we expect to have a cleaner dataset
- ▶ A more accurate classifier is thereby obtainable
- ▶ However, the pruning is data-dependent, therefore generalization will be an issue!

28

Reusing the Cleaned Dataset



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

24

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Fortunately, we can address this easily:

- First, randomly split S into S_1 and S_2

28

Reusing the Cleaned Dataset



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

24

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Fortunately, we can address this easily:

- ▶ First, randomly split S into S_1 and S_2
- ▶ Second, we get low-quality teacher set B_1 and B_2 according to S_1 and S_2

28

Reusing the Cleaned Dataset



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

24

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Fortunately, we can address this easily:

- ▶ First, randomly split S into S_1 and S_2
- ▶ Second, we get low-quality teacher set B_1 and B_2 according to S_1 and S_2
- ▶ Third, use B_1 clean S_2 to get S'_2 and use B_2 clean S_1 to get S'_1

Reusing the Cleaned Dataset



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

24

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Q & A

Fortunately, we can address this easily:

- ▶ First, randomly split S into S_1 and S_2
- ▶ Second, we get low-quality teacher set B_1 and B_2 according to S_1 and S_2
- ▶ Third, use B_1 clean S_2 to get S'_2 and use B_2 clean S_1 to get S'_1
- ▶ Finally, train a classifier on S' , where

$$S' = S'_1 \cup S'_2$$

28

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

25

Experiment Settings

Experiment Results

Q & A

28

David R. Cheriton School of
Computer Science,
University of Waterloo

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

25

Experiment Settings

Experiment Results

Q & A

- The data-pruning approach is tested using *Amazon.com's Mechanical Turk*

28

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

25

Experiment Settings

Experiment Results

Q & A

- ▶ The data-pruning approach is tested using *Amazon.com's Mechanical Turk*
- ▶ We create an unlabeled set of over 8,000 examples, each consists
 - ▶ A search engine query
 - ▶ An Internet URL

28

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

25

Experiment Settings

Experiment Results

Q & A

- ▶ The data-pruning approach is tested using *Amazon.com's Mechanical Turk*
- ▶ We create an unlabeled set of over 8,000 examples, each consists
 - ▶ A search engine query
 - ▶ An Internet URL
- ▶ Task was to determine if they are relevant match or not

28

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

25

Experiment Settings

Experiment Results

Q & A

- ▶ The data-pruning approach is tested using *Amazon.com's Mechanical Turk*
- ▶ We create an unlabeled set of over 8,000 examples, each consists
 - ▶ A search engine query
 - ▶ An Internet URL
- ▶ Task was to determine if they are relevant match or not
- ▶ Each example was labeled by 15 different teachers

28

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

25

Experiment Settings

Experiment Results

Q & A

- ▶ The data-pruning approach is tested using *Amazon.com's Mechanical Turk*
- ▶ We create an unlabeled set of over 8,000 examples, each consists
 - ▶ A search engine query
 - ▶ An Internet URL
- ▶ Task was to determine if they are relevant match or not
- ▶ Each example was labeled by 15 different teachers
- ▶ A total of 375 individual teachers contributed to the dataset

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

26 Experiment Settings

Experiment Results

Q & A

μ	$\mu = \infty(\text{original})$	$\mu = 200$	$\mu = 50$
No. of Teachers	375	881	2509
Typical Label / Teacher	NA	14	4

Table: Description of 3 Datasets

- Parameter μ : each teacher labels at most μ examples

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

26

Experiment Settings

Experiment Results

Q & A

μ	$\mu = \infty(\text{original})$	$\mu = 200$	$\mu = 50$
No. of Teachers	375	881	2509
Typical Label / Teacher	NA	14	4

Table: Description of 3 Datasets

- ▶ Parameter μ : each teacher labels at most μ examples
- ▶ The average of 15 labels are treated as ground truth

Experiments



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

26 Experiment Settings

Experiment Results

Q & A

μ	$\mu = \infty(\text{original})$	$\mu = 200$	$\mu = 50$
No. of Teachers	375	881	2509
Typical Label / Teacher	NA	14	4

Table: Description of 3 Datasets

- ▶ Parameter μ : each teacher labels at most μ examples
- ▶ The average of 15 labels are treated as ground truth
- ▶ The training algorithm is **well-tuned linear SVM**

Experiments



Vox Populi: Collecting High-Quality Labels from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned Dataset

Experiments

Experiment Settings

27

Experiment Results

Q & A

28



Vox Populi: Collecting
High-Quality Labels
from a Crowd

Dekel & Shamir

Introduction

Background

Settings and Notations

Algorithms and
Theories

Pruning Can Help

Pruning Can't Hurt

Setting the Threshold T

Reusing the Cleaned
Dataset

Experiments

Experiment Settings

Experiment Results

Thank you very much!
Any Questions?