

---

# A TEMPLATE FOR THE *arxiv* STYLE

---

A PREPRINT

**David S. Hippocampus\***  
Department of Computer Science  
Cranberry-Lemon University  
Pittsburgh, PA 15213  
hippo@cs.cranberry-lemon.edu

**Elias D. Striatum**  
Department of Electrical Engineering  
Mount-Sheikh University  
Santa Narimana, Levand  
stariate@ee.mount-sheikh.edu

February 8, 2022

## ABSTRACT

Diabetic retinopathy is an eye disease that can affect people suffering diabetes. It causes damage to the blood vessels of the eyes, deteriorates the eyesight and can lead in the worst case to blindness of the patient. It is important to detect the disease in an early stage to mitigate it as good as possible with an early treatment. Analyzing images of eyes and classify the severity of diabetic retinopathy is a challenging task that requires expert knowledge. To assist doctors and medical personnel, a classification model shall be trained to classify the severity automatically.

## 1 Introduction

Text about why diabetic retinopathy Detection

Dataset

## 2 Object Classification

### 2.1 Problem analysis

Einordnung als supervised learning problem

To tackle the problem of diabetic retinopathy detection, several methods are possible. Because the dataset consists of ordinally scaled data of 5 classes, regression could be used to estimate the serverity of a case. In addition, a the problem can be handled as a classification problem after one-hot-encoding the labels. As a third option, one can define a threshold to define problematic diabetic retinopathy and non-problematic diabetic retinopathy and can handle the problem as a binary classification. Further, only binary and multiclass classification are anlyzed.

A binary classification has the advantage of higher accuracy, but lacks details, because the network only outputs 0 or 1 and no information about the exact serverity of the disease. Metrics are also easy to implement, because precision, recall and f1-score are standard implementations and nicely interpretable.

A multiclass classification has typically a lower accuracy, because the network needs to pick the right class among several classes. It provides the benefit of receiving richer information, i.e. the exact serverity of the disease. Evaluating a multiclass classification problem becomes harder, because missclassifications can vary in their error. Classifying a class 1 as class 2 is for example less problematic than classifying class 1 as class 5.

### 2.2 Architecture

VGG, Resnet, Weight freeeze / unfreeze, GAP, Flatten, Dense Layers

---

\*Use footnote for providing further information about author (webpage, alternative address)—*not* for acknowledging funding agencies.

## 2.3 Weight initialization

## 2.4 Augmentation

## 2.5 Dataset Balancing

## 2.6 Training

Adam, SGD, Momentum, Learning rate decay

## 2.7 Metrics

incl. QWC

# 3 Experiments

## 3.1 Procedure

The training of the deep neural network classifier requires the selection of suitable hyperparameters that differ from problem to problem. A useful strategy to find a good set of hyperparameters are parameter sweeps. Weights&Biases is a python library that enables the easy implementation of sweeps.

Hyperparameter optimization requires besides training and test dataset a third, the validation dataset, to evaluate the model after hyperparameter tuning and to avoid overfitting on the hyperparameters. Because the given dataset only contains training and test data, the original training dataset was split into 80% training data and 20% validation data.

In total, x sweeps consisting of x runs and x epochs were performed during the project.

## 3.2 Hyperparameter selection

The following parameters show a big effect on the performance of the neural network on the validation data, why they are selected for the final classifier.

Balancing

...

## 3.3 Grad cam

# 4 Results

best binary + multiclass performance; color coded confusion matrix

# 5 Headings: first level

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. See Section 5.

## 5.1 Headings: second level

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla

egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

$$\xi_{ij}(t) = P(x_t = i, x_{t+1} = j | y, v, w; \theta) = \frac{\alpha_i(t) a_{ij}^{w_t} \beta_j(t+1) b_j^{v_{t+1}}(y_{t+1})}{\sum_{i=1}^N \sum_{j=1}^N \alpha_i(t) a_{ij}^{w_t} \beta_j(t+1) b_j^{v_{t+1}}(y_{t+1})} \quad (1)$$

### 5.1.1 Headings: third level

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

**Paragraph** Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

## 6 Examples of citations, figures, tables, references

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui. [1, 2] and see [3].

The documentation for natbib may be found at

<http://mirrors.ctan.org/macros/latex/contrib/natbib/natnotes.pdf>

Of note is the command `\citet`, which produces citations appropriate for use in inline text. For example,

```
\citet{hasselmo} investigated\dots
```

produces

Hasselmo, et al. (1995) investigated...

<https://www.ctan.org/pkg/booktabs>

### 6.1 Figures

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi. See Figure 1. Here is how you add footnotes.<sup>2</sup> Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

### 6.2 Tables

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien

---

<sup>2</sup>Sample of the first footnote.



Figure 1: Sample figure caption.

Table 1: Sample table title

Part		
Name	Description	Size ( $\mu\text{m}$ )
Dendrite	Input terminal	$\sim 100$
Axon	Output terminal	$\sim 10$
Soma	Cell body	up to $10^6$

facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo. See awesome Table 1.

### 6.3 Lists

- Lorem ipsum dolor sit amet
- consectetur adipiscing elit.
- Aliquam dignissim blandit est, in dictum tortor gravida eget. In ac rutrum magna.

### References

- [1] George Kour and Raid Saabne. Real-time segmentation of on-line handwritten arabic script. In *Frontiers in Handwriting Recognition (ICFHR), 2014 14th International Conference on*, pages 417–422. IEEE, 2014.
- [2] George Kour and Raid Saabne. Fast classification of handwritten on-line arabic characters. In *Soft Computing and Pattern Recognition (SoCPaR), 2014 6th International Conference of*, pages 312–318. IEEE, 2014.
- [3] Guy Hadash, Einat Kermany, Boaz Carmeli, Ofer Lavi, George Kour, and Alon Jacovi. Estimate and replace: A novel approach to integrating deep neural networks with existing applications. *arXiv preprint arXiv:1804.09028*, 2018.