

L^AT_EX: from beginner to T_EXpert

John Gardner

March 2008

Contents

1	Introduction	2
2	What is L^AT_EX?	2
3	How does L^AT_EX work?	3
4	Getting L^AT_EX	4
4.1	On Windows	4
4.2	On Mac OS X	4
4.3	On Linux	5
5	L^AT_EX basics	5
5.1	L ^A T _E X commands	5
5.2	The preamble	5
5.3	The document body	6
5.4	Document structure	6
6	Environments	7
7	Modifying text styles	8
8	Packages	8
8.1	The graphicx package	9
8.2	The geometry package	10
8.3	Other packages	10
9	Figures and tables	10
9.1	Figures	10
9.2	Tables	11

10 Annotations	12
10.1 Footnotes and endnotes	12
10.2 Cross references	13
10.3 Table of contents	13
10.4 Bibliography	13
11 Inserting mathematics	13
11.1 Inline	13
11.2 Display math	14
11.3 Equation	14
11.4 Align	14
11.5 Mathematical notation	14
12 For further reference	16

1 Introduction

This document introduces the L^AT_EX typesetting system. After digesting the information below, you’ll be able to:

- Download and install L^AT_EX on your PC or Mac
- Create basic documents using L^AT_EX
- Install new L^AT_EX packages
- Insert tables and figures into a L^AT_EX document
- Use L^AT_EX’s cross-referencing, footnote and basic bibliography features
- Insert equations into a L^AT_EX document

These topics cover the majority of tasks that most people need to do when writing a document. However, please note that while the L^AT_EX system makes it very easy to create professional-looking documents, it is both comprehensive and extensible. There are many topics that are not covered by this basic tutorial. Fortunately, L^AT_EX is very well documented. If you come across something that you can’t figure out how to do, ask your old friend Google for help.

2 What is L^AT_EX?

At its core, L^AT_EX is a typesetting system that allows authors to create highly polished documents without having to worry about formatting, page breaks, object positioning, or any other style concerns that distract them from focusing on writing. L^AT_EX is pronounced “lay-tech,” as it is an extension of T_EX (“tech”), the original typesetting system. You can read all about the history of T_EX and L^AT_EX on Wikipedia.

L^AT_EX is used widely in a variety of professions. Mathematicians, physicists, economists, statisticians and other academics and professionals that regularly use mathematical notation in their documents often use L^AT_EX because of the ease with which it handles such notation. Many publishers use T_EX-based systems for typesetting documents.

3 How does L^AT_EX work?

L^AT_EX differs from traditional word processors in two fundamental ways:

1. Generally, L^AT_EX documents are written using the easy-to-learn L^AT_EX markup language, rather than by using a graphical interface to apply styles¹
2. L^AT_EX processes your document after you have entered your text. So unlike word processors, it can use information about the total length of your document, number of tables, etc. to find the optimal places for tables, figures, page breaks, etc. to format your text

The following is an example of a very basic L^AT_EX document:

```
\documentclass{article}
\author{Your Name}
\title{Test Document}
\begin{document}
\maketitle
This is a test document
\end{document}
```

With any L^AT_EX distribution, saving the above text as a TEX (.tex file and running L^AT_EX on that file would produce the following:

Test Document

Your Name

April 21, 2006

This is a test document.

¹Graphical editors, such as Scientific Word (a commercial application) and LyX (an open-source application), are available; these applications are easier to use if you know how L^AT_EX works, so it's a good idea to learn it even if you don't plan to write L^AT_EX markup by hand.

L^AT_EX is designed to create the same output on any system. As a result, if you distributed the above text to anyone with a working L^AT_EX distribution, regardless of their particular system, they would get the exact same result. L^AT_EX outputs compiled documents in several formats, but the most popular is PDF.

4 Getting L^AT_EX

All you technically need to create L^AT_EX documents is a L^AT_EX engine – the binary files and libraries that will convert plain text TEX files to polished PDF files. L^AT_EX can be run from the command line, so *nix and DOS aficionados will feel right at home. However, using a frontend for L^AT_EX can make things much easier. Most frontends are essentially text editors with functions to

- Compile documents with L^AT_EX without using the command line
- Facilitate writing in the L^AT_EX language (wizards for table creation, code completion, etc.)

In this document, I assume that you'll use both a L^AT_EX engine and a frontend. There are many engines and frontends to choose from on every operating system. I'm going to describe how to install the most popular (and easy to install) open-source tools for Windows and Mac OS X. Other L^AT_EX tools have different configuration requirements and operating instructions, but almost every working environment involves (i) editing raw TEX files using a frontend and (ii) compiling the L^AT_EX document to a PDF, generally using buttons or menu commands in the frontend rather than the command line.

4.1 On Windows

Engine MikTeX is a popular open-source distribution. To install, visit www.miktex.org, download the executable, and follow the dialog. Additional installation instructions are on the download page.

Frontend TeXnic Center, available from toolscenter.org, is an open-source frontend with many helpful features. Installation is standard, just download and open the executable, which opens a wizard.

TeXnic center is automatically configured to work with MikTeX. To test out your setup, save the sample document above as a .tex file using TeXnic Center and select Build ⇒ Current file. If everything is set up properly, a new PDF file (along with a log file) will be created in the directory where your document is saved.

4.2 On Mac OS X

Engine gwTeX is a free and open-source L^AT_EX distribution for OS X that comes with a graphical installer. To install, download the i-Installer application,

select a mirror, then select the TeX package. Additional installation instructions are available ii2.sourceforge.net/tex-index.html. Once installation is complete, all you need is a frontend.

Frontend TeXShop (www.uoregon.edu/~koch/texshop/) is a very popular L^AT_EX frontend for OS X. Installation requires a simple drag and drop to the ~/Applications folder. TeXShop is automatically configured to work with gw-TeX, so if that's the engine that you're using, you're set.

To test out your distribution, try saving the sample document above as a TEX file and running L^AT_EX on your document by pressing command-t. If everything is configured properly, a window will appear similar to the example output above, and a new PDF file (as well as a log file) will appear in the directory where your file is saved.

4.3 On Linux

Different Linux systems have their own application management utilities (apt-get or rpm, for example), and installation will depend on your particular Linux distribution. Ubuntu users can use the Synaptic Package Manager. Kile is a popular and easy-to-use frontend that works with both KDE and Gnome.

5 L^AT_EX basics

5.1 L^AT_EX commands

L^AT_EX commands generally begin with a backslash and take the form:

```
\command[options]{argument}
```

For example,

```
\section{Introduction}
```

would define a new section, named “Introduction.” The “%” character defines a comment, and everything from that character to the end of the line is commented out and will be ignored by L^AT_EX. To insert the “%” character into a document, escape it with a backslash: \%. To insert a backslash, use `\backslash$`.

Quotes work a bit differently in L^AT_EX. To insert quote marks, use the form ‘‘text’’. That is, the ‘ character (top left of the keyboard) twice, followed by the single quote character, ’, twice.

5.2 The preamble

Everything before the line `\begin{document}` is part of the preamble. A typical preamble might look like this:

```

\documentclass{article}
\usepackage{graphicx}
\usepackage{amsmath,amsthm,amsfonts}
\title{Test}
\author{Test}
\date{}

```

In the example above:

- `\documentclass{article}` tells L^AT_EX that the document is an article. Other classes include book, letter and slides
- `\usepackage{graphicx}` tells L^AT_EX to use the graphicx package, which allows users to include many types of graphics in their documents. Packages are covered later on. The `\usepackage{amsmath,...}` command invokes packages from the American Mathematical Society that extend the functionality of L^AT_EX
- `\title{}` and `\author{}` obviously define the title and author
- `\date{}` tells L^AT_EX to leave the data blank. `\date{April 2006}` would print “April 2006” as the date. Leaving the `\date{}` line out would cause L^AT_EX to use today’s date

The `\documentclass{}` command has options. For example,

```

\documentclass[11pt,twocolumn]{article}

```

would organize body of the document into two columns. Note that options are separated by a comma. Other options include:

- **oneside** or **twoside**: change margins for a one or two-sided document
- **landscape**: change the document from portrait to landscape
- **titlepage** or **notitlepage**: define whether there is a separate title page, or if the title, author and date info are presented at the top of the article

5.3 The document body

Everything after the preamble and between `\begin{document}` and `\end{document}` is part of the document body. Most of a L^AT_EX document is simply plain text. To start a new paragraph, insert two carriage returns (blank lines). L^AT_EX will ignore one blank line. To force a line break, use `\\`.

5.4 Document structure

A document’s structure is defined using `\section{}` commands. L^AT_EX is strongly based on well-structured documents. The structure tags include:

- `\section{Name}`
- `\subsection{Name}`
- `\subsubsection{Name}`
- `\paragraph{Name}`

To insert an unnumbered section, use the command `\section*{Name}`. The section numbering will continue as normal with the next section, subsection, etc.

The `\paragraph{}` command doesn't need to be included unless you want to insert a heading for a paragraph. The image below shows the different structure commands in use:

1 Section command

Section star command

This section is not numbered.

2 Section command

Text here. The numbering continues normally.

2.1 Subsection command

Text here.

2.1.1 Subsubsection

Paragraph command This paragraph has a title.

6 Environments

Environments are special blocks of text. For example, the `itemize` and `enumerate` environments create bulleted and numbered lists, respectively. The following markup:

```
\begin{itemize}
\item First thing
\item Second thing
\item Third thing
\end{itemize}

\begin{enumerate}
```

```

\item First numbered thing
\item Second numbered thing
\end{enumerate}

```

would produce a bulleted list followed by a numbered list.

Note that environments always begin with `\begin{environmentname}` and end with `\end{environmentname}`. They can be nested, so one item of a bulleted list might contain another bulleted list, or a numbered list, etc.

Other frequently used environments include:

Quote `\begin{quote}...\end{quote}` creates a section of indented, quoted text.

Verbatim `\begin{verbatim} ... \end{verbatim}` is similar to `<pre>` in HTML.

In the verbatim environment, text is printed in a monospace font and special characters (such as `\` and `%`) are ignored. Verbatim is useful for typing code tips.

Description Description lists are similar to bulleted lists, with a bold item name followed by a description:

```

\begin{description}
\item[First item] Description of item
\item[Second item] Description of item
\end{description}

```

This list is presented using the verbatim environment.

7 Modifying text styles

The basic idea behind \LaTeX is to absolve the author of formatting duties. Nevertheless, it's still occasionally necessary to manually format certain text styles.

- To insert bold text, use `\textbf{text here}`
- To insert italic text, use `\emph{text here}`
- To insert monospace text, use `\texttt{text here}`
- To use verbatim text within a sentence, use `\verb|your text here|`. Note that any delimiter can be used, for example `\verb+your text here+` will produce the same result

8 Packages

Packages extend \LaTeX 's functionality. Package installation essentially consists of two steps:

1. Running \LaTeX on the INS file to produce STY or CLS files
2. Copying the newly created files to an appropriate directory and updating the \LaTeX database

However, there are exceptions. The filetypes STY and CLS stand for style and class, respectively. If a package does not come as an INS file, but rather a STY or CLS file, it does not need to be processed with \LaTeX , and you can skip directly to step two. Also, running \LaTeX on an INS file usually produces a DTX file. This file can be processed with \LaTeX to create a manual for the package.

Note To process a package file (ins or dtx) with \LaTeX , just open that file with your frontend and process it like you would a normal TEX file.

Windows The easiest way to install a package on a PC using MikTeX is to use the MikTeX package manager, which is available through the Start Menu. Just open the package manager, select a mirror, and navigate to the package that you want to install. MikTeX will take care of the rest. Another nice feature of MikTeX is that if you are processing a TEX file that requires a package that isn't installed on your machine, it will prompt you to download it.

OS X To install a new package on your Mac using gwTeX , process the files as described above, and move the STY, CLS and other files to $\sim/\text{Library}/\text{texmf}$. If this directory does not exist, create it.

Next, I discuss two popular packages: `graphicx` and `geometry`. These packages are already installed with gwTeX and MikTeX, so there is no need to download and install them.

8.1 The `graphicx` package

The `graphicx` package allows you to insert images into a \LaTeX document. To use it, first use the command `\usepackage{graphicx}` in your document preamble. Then, to insert a graphic, use the command:

```
\includegraphics[options]{filename.png}
```

The `graphicx` package supports many filetypes, including PDF, PNG and JPG. The options include:

- `width=Xin`
- `height=Xin`
- `scale=X` (where x is between 0 and 1)

8.2 The geometry package

While formatting documents using L^AT_EX is easy, changing those default formats can be fairly difficult. The geometry package can make changing certain aspects of your document, including the margins, much easier. To change the margins to 1" all around, for example, use:

```
\usepackage[margin=1in]{geometry}
```

in your document's preamble.

8.3 Other packages

For just about every modification that you might want to make to a standard L^AT_EX document, there is a pre-made package to help you do so. To learn more about the packages described, or to download new packages, visit the Comprehensive TeX Archive Network (CTAN).

9 Figures and tables

Figures and tables are L^AT_EX environments, however they have special attributes, such as the `\caption{}` command, which gives them titles within the document. They are called float elements, because their position in the final compiled document depends on L^AT_EX's style algorithm.

9.1 Figures

To insert a figure, use

```
\begin{figure}[hbt]  
  \caption{Figure name}  
  \begin{center}  
    \includegraphics{filename.pdf}  
  \end{center}  
  \label{your-reference-key}  
\end{figure}
```

In the above markup,

- `\begin{figure}` simply tells L^AT_EX that there is a figure environment
- `[hbt]` determines how L^AT_EX will place the figure (here (h), bottom (b), top(t), page(p)). L^AT_EX will first attempt to insert the figure at its insertion point in the TEX file. If this is not possible due to space or other aesthetic considerations, it will try to place it at the bottom of the page, then at the top of the page, then on a special page reserved just for float elements. The order in which h, b, t and p are specified determines where L^AT_EX tries to place the float first. To force the graphic to appear in its

original place, for example, you could put `\begin{figure}[h]`, omitting `b`, `p` and `t`

- `\caption{Figure name}` specifies the name of the figure
- `\begin{center}` simply tells \LaTeX to center the figure on the page. Don't forget to end the centering environment before you end the figure environment
- `\includegraphics{...}` specifies the location of the file that is being inserted as a figure
- `\label{your-reference-key}` is a label that you can use to refer to the figure in the text. For example, if you label your figure "fig1" then you can reference it later on by typing `\ref{fig1}`

9.2 Tables

A floated table in \LaTeX consists of two environments: "table," the actual floated entity in the text, and "tabular," the data contained in the table. For example,

```
\begin{table}[hbt]
\caption{This table is an example}
\begin{center}
\begin{tabular}{c|cc}
First row, first column &
  First row second column &
  First row, third column \\ \hline
Second row, first column &
  Second row, second column &
  Second row, third column \\
Third row, first column &
  Third row, second column &
  Third row, third column \\
\multicolumn{3}{c}{...}
\end{tabular}
\end{center}
\label{exampletable}
\end{table}
```

would produce Table 1.

Everything except the code between `\begin{tabular}` ... `\end{tabular}` is the same as the figure environment described above. Here's how the tabular environment works:

- `\begin{tabular}{c|cc}` tells \LaTeX to start a new tabular environment with three centered columns. The bar ("`|`") after the first "`c`", tells \LaTeX that the first column has a vertical border. Using `{lcr}` would create

Table 1: This table is an example

First row, first column	First row second column	First row, third column
Second row, first column	Second row, second column	Second row, third column
Third row, first column	Third row, second column	Third row, third column
...		

four columns, the first left aligned, the second centered, and the third and fourth right aligned

- Table cells are separated by “&” and table rows are separated by “\”
- `\hline` creates a horizontal line
- `\multicolumn{3}{c}{Text here}` creates a row that spans all three columns, is centered, and contains the text “Text here”

There are more complicated options for creating and inserting tables, but the rules above cover the commands needed to create most basic to intermediate tables.²

10 Annotations

L^AT_EX is capable of automatically creating important annotations, such as footnotes, cross references, tables of contents and bibliographies. Note that, since the following commands require L^AT_EX to automatically number text elements, L^AT_EX must be run on your document twice for proper display.

10.1 Footnotes and endnotes

To insert a footnote, simply type `\footnote{text here}`. L^AT_EX will automatically insert the footnote number and text.³

To use endnotes, first invoke the endnotes package in the preamble:

```
\usepackage{endnote}
```

and use the command `\endnote{Text}` to create new endnotes. At the point in your document where you want the endnotes to appear, simply type `\theendnotes`.

²OpenOffice users can use Calc2L^AT_EX to convert between Calc spreadsheets and L^AT_EX tables. MS Office users can try Excel2L^AT_EX, which does the same thing using Excel spreadsheets. Both utilities are cross-platform.

³To create an “attribution” footnote, where the first footnote is marked by an asterisk, use the `\thanks{text here}` command.

10.2 Cross references

To reference a labeled Table or Figure, use `\ref{your-reference-key}` where “your-reference-key” is the argument to the `\label{your-reference-key}` command in the table or figure environments.

10.3 Table of contents

To insert a table of contents, simply put `\tableofcontents` at the beginning of your document.

10.4 Bibliography

To create a bibliography, insert a list of the citations at the end of your document, using the form:

```
\begin{thebibliography}{99}
...
\bibitem{key1} Gardner, John. 2006.
‘‘\LaTeX{}: from beginner to \TeX pert.’’
\emph{Dataninja}. Available online at
\texttt{http://generaldisarray.wordpress.com}.
...
\end{thebibliography}
```

You must manually type the bibliography entries. To refer to an item within the text, use `\cite{key}[1]`. The `{99}` tells \LaTeX that there a maximum of 99 entries in the bibliography. \LaTeX needs to know this so it can correctly justify the bibliography entries with their numbering on the left.

A more efficient way to create bibliographies is to use BibTeX, which allows you to maintain a database of citations and call them as needed in your bibliography. There are also graphical tools for managing your reference databases, so you don’t have to hard code the citations, and can easily change them to different formats. However, BibTeX is too complicated to explain in this document. For an introduction, see this page.

11 Inserting mathematics

There are several ways to include mathematical notation in \LaTeX documents. The most common are inline notation and the `displaymath` environment.

11.1 Inline

To include some mathematical notation within a paragraph, without offsetting from the rest of the text, enclose the notation between dollar signs. For example, $a^2+b^2=c^2$ is our favorite theorem.

11.2 Display math

The `displaymath` environment lets you offset some mathematical notation from the rest of the document. The code

```
\[
a^2+b^2=c^2
\]
```

would create a paragraph break and center the equation on the page.

11.3 Equation

The `equation` environment can be used to place numbered equations in the text. For example,

```
\begin{equation}
a^2+b^2=c^2
\label{pythag}
\end{equation}
```

would offset the equation just like the `displaymath` version did, but it would have a number in parenthesis on the right, and you would be able to call it in the text by typing, for example, “as we see in equation `\ref{pythag}`...”

11.4 Align

The `align` environment allows you to align parts of equations at the equal sign. For example,

```
\begin{align}
a &= b+c \\
d &= e+f
\end{align}
```

would produce

$$a = b + c \tag{1}$$

$$d = e + f \tag{2}$$

Note You must have invoked the `amsmath` package in order to use the `align` environment. Also, it is possible to suppress the numbering by using the commands `\begin{align*}` and `\end{align*}`.

11.5 Mathematical notation

There are many commands for inserting specific mathematical operators and symbols into equations. They can all be found online, and as always, use Google if you can't figure out a specific command. The following are some common operators and commands

Greek letters Generally, just use the spelled-out letter. For example, `\beta` produces β and `\epsilon` produces ϵ . For upper case, capitalize the letter: `\Gamma` produces Γ while `\gamma` produces γ .

Misc. symbols L^AT_EX can produce almost any symbol; the following are just a few examples. `\leftarrow`: \leftarrow . Use `\Leftarrow` for a double arrow: \Leftarrow . Similarly, `\rightarrow`: \rightarrow and `\Leftrightarrow`: \Leftrightarrow . For $<$, $>$, use `\leq` (less than or equal to), `\geq` (greater than or equal to).

Indexing and exponents Subscripts are denoted using the underscore (`xi`) and superscripts use the `^` key (`a2`). To type “ $i_{j,k}$ ” you need to write `i_{j,k}` to tell L^AT_EX that the “j,k” comprises the entire subscript. The bracket characters are generic grouping operators in L^AT_EX, and they won’t appear in your document.

Some operators `\sum{1/x}` ($\sum 1/x$) or `\sum_{i=1}^{\infty}{x_i}`, `\prod` (the product), `\coprod` (the coproduct), `\sin`, `\log`, `\max`, `\lim`, `\sqrt`, etc.

Decorations `\hat{x}` (\hat{x}), `\tilde{x}` (\tilde{x}), `\bar{x}` (\bar{x}), `\underline{x}` (\underline{x}), etc.

Fractions `\frac{a}{b}` ($\frac{a}{b}$)

Brackets For brackets use “(”, “[” or `\{` and `\}` for “{” and “}”. However, if you need stretched brackets, use `\left(...\right)` or `\left\{ <math here> \right\}`. For example,

```
\left[ \frac{1}{2} \right]
```

produces

$$\left[\frac{1}{2} \right].$$

Matrices To insert a matrix with square brackets, use

```
\begin{bmatrix}
a & b & c \\
d & e & f
\end{bmatrix}
```

Once again, you must invoke the `amsthm` package. The code shown above would produce:

$$\begin{bmatrix} a & b & c \\ d & e & f \end{bmatrix}.$$

Other matrix types include `pmatrix` for a matrix with parenthetical brackets and `cases` to define, for example, a piecewise function.

Other tips To insert a space within an equation, use `\quad` or `\qquad`. To put some ordinary text within a math environment, use `\text{}`. For example:

```
y=\alpha+\beta x+\varepsilon \qquad e \sim N(0,\sigma^2)
\quad \text{A basic line}
```

would produce:

$$y = a + bx + e \qquad e \sim N(0, \sigma^2) \quad \text{A basic line}$$

For help with other symbols and operators, see this page.

12 For further reference

The instructions above cover many of the basic functions of \LaTeX , but there are many more. A good, thorough introduction is *The \LaTeX Primer* (PDF). I have other tools and references on my data analysis weblog *Dataninja*.

References

- [1] Gardner, John. 2006. “ \LaTeX : from beginner to \TeX pert.” *Dataninja*. Available online at <http://dataninja.wordpress.com>.