Speaker Walk Around Self Test

Before you begin

For compatible Sync 3 systems with the physical controls described below. Park safely. If the engine is running, keep the vehicle outdoors. **Test tones can be loud or high-pitched.**

This procedure requires the radio to turn on and FM to be selected. If Audio will not open, FM cannot be selected, or the controls do not match, stop and contact us. An unavailable test is not a failed speaker test.

Run the test

1. Turn on the radio and select an FM station. Exit CarPlay or Android Auto so you are testing the vehicle radio.

2. Hold the **right seek / next track** button on the steering wheel and the **right seek / next track** button on the dashboard/HVAC panel together for about five seconds.

3. When the test starts, listen to each tone and record the named speaker position shown on the display. Use the diagnostic menu to exit or rerun the speaker test if needed. Do not change other diagnostic settings.

4. If the test will not start or you are unsure how to read the result, record that and ask for help.

What to record

Some positions silent: record each silent position. The speaker, wiring, or amplifier output may be responsible. The test alone does not identify which component failed.

No tones heard: report that result. It does not prove that all speakers, the ACM, or the amplifier have failed. Power, connections, and correct test operation need review.

All tested positions played: record whether normal AM/FM, phone playback, or calls still have a problem. Working tones do not prove that the normal playback path is working.

Send us your results

Include the vehicle year/model, audio package (standard, Sony, B&O, THX, Revel, or aftermarket), affected sources, and the speaker positions you recorded.

simplymichigan.co/contact-us | nick@simplymichigan.co