MULTI-AGENT DELIBERATION

RUST · CARGO

CONVERGED

Think Tank

Four agents debate. An Arbiter decides when they have converged — measured, not guessed.

ENGINEERING REPORT · RENDERED FROM REPOSITORY DATA

HOW IT WORKS

A strictly sequential debate loop

- Researcher claims, Skeptic challenges, Visionary improvises, Synthesizer merges — then the Arbiter scores.
- The Arbiter weighs semantic stabilisation at 0.80 and the opposition ratio at 0.20.
- Rounds repeat until the alignment score clears the target, or the round budget runs out.

4	0.80	6
AGENTS PER ROUND	SEMANTIC WEIGHT	ROUND CEILING

PROVEN ON ITS OWN OUTPUT

This deck is the measurement

- Rendered by deckgen: a headless egui harness painting ArtCraft's tokens onto A4.
- One binary, no browser, no network — any repo's data can produce this deck.



0

BROWSERS IN THE LOOP

ENGINEERING

Boring on purpose

ONE RUST CRATE, NO REDUCERS

every node clones state and appends, so history is never lost.

All providers speak the OpenAI protocol; adding one is a row in a table.

Tests drive a local stub server — the suite makes zero network calls.

5	3	0
NODES PER ROUND	STRUCTURED-OUTPUT RETRIES	NETWORK CALLS IN TESTS

THE HONEST NUMBERS

What the arbiter actually saw

1.00

CONVERGED SCORE - AGAINST A 0.65 TARGET, IN 2 OF 6 ROUNDS

THE FORCED RUN

The same loop scored 0.1536 against an impossible 1.01 target.

A benchmark that only shows wins is marketing — this one shows both.

0.15	392
FORCED SCORE	TOKENS SPENT

WHERE THIS GOES

Decks as a build artifact

Any repo that emits JSON can emit a deck

Reports, benchmarks and architecture reviews render from the same file. A coding agent regenerates this PDF from repository data — no browser, no network, no layout code.

1
DESIGN SYSTEM

3
OFL TYPEFACES

6
PAGES FROM ONE FILE