



JX1 v0.4 - JX1_Pelvis
MATERIAL: 6061-T6
PROCESS: laser 6/4 mm plates + tapped 8x8 corner bars
QTY/ROBOT: 1 (+ mirrored R part where listed)
ALL DIMENSIONS mm. GENERAL TOLERANCE ISO 2768-m. BREAK SHARP EDGES 0.3.
Actuator bolt patterns ASSUMED (open issue OI-1): confirm against RobStride STEP before release.
ENVELOPE: 310 x 150 x 46 mm MASS: 1326 g
CYLINDRICAL FEATURES (holes / bores / bosses): D3.4 x18, D24 x2, D30 x1, D40 x1, D94 x2
DIMENSIONS: from the STEP model (master geometry).
This sheet: material, process, quantity, inspection.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: LINEAR: ANGULAR:						FINISH:						DEBURR AND BREAK SHARP EDGES						DO NOT SCALE DRAWING						REVISION																													
	NAME				SIGNATURE				DATE												TITLE: Pelvis																																
DRAWN																																																					
CHK'D																																																					
APPV'D																																																					
MFG																																																					
Q.A																		MATERIAL: 6061-T6 (SS)												DWG NO. JX1_Pelvis												A3											
																		WEIGHT: 1326.05												SCALE:1:5												SHEET 1 OF 1											