



JX1 v0.4 - JX1_High_L
MATERIAL: 6061-T6
PROCESS: CNC 2 setups from 30 mm plate (or 10 mm plate + bolted flange bars)
QTY/ROBOT: 1 (+ mirrored R part where listed)
ALL DIMENSIONS mm. GENERAL TOLERANCE ISO 2768-m. BREAK SHARP EDGES 0.3.
Actuator bolt patterns ASSUMED (open issue OI-1): confirm against RobStride STEP before release.
ENVELOPE: 364.9 x 109.8 x 30 mm MASS: 867.2 g
CYLINDRICAL FEATURES (holes / bores / bosses): D5.5 x16, D12 x1, D20 x1, D22 x2, D26 x1, D50.3 x1
DIMENSIONS: from the STEP model (master geometry).
This sheet: material, process, quantity, inspection.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: LINEAR: ANGULAR:						FINISH:		DEBURR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION		
	NAME		SIGNATURE		DATE				TITLE: Thigh L					
DRAWN														
CHK'D														
APPV'D														
MFG														
Q.A					MATERIAL: 6061-T6 (SS)				DWG NO.		JX1_Thigh_L		A3	
					WEIGHT: 867.20				SCALE:1:5		SHEET 1 OF 1			